

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised March 25, 1999

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.
30-015-34330

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.
VB0158

7. Lease Name or Unit Agreement
Name:

Marlin 32 State

8. Well No.
#1

9. Pool name or Wildcat
Undes Winchester Morrow

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other ☐

2. Name of Operator

Mewbourne Oil Company 14744

3. Address of Operator

PO Box 5270 Hobbs, NM 88241

4. Well Location

Unit Letter L : 1650 feet from the South line and 990 feet from the West line

Section 32 Township 19S Range 29E NMPM Eddy County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)
3282' GL

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: TD well and TOC ☒

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

12/14/05...TD'ed 8 3/4" hole @ 11550'. Ran 11550' 5 1/2" 17# HCP110/N80 LT&C Csg. Cemented 1st stage with 450 sks (61:15:11) Super H modified with additives. Mixed @ 13.2 /g w/1.64 yd. Tail with 650 sks Class "H" with additives. Mixed @ 15.1 #/g w/ 1.28 yd. Drop bomb & open DV tool with 900#. Circ 142 sks off DV tool. Cemented 2nd stage with 850 sks (35:65:6) BJ Lite"H" modified with additives. Mixed @ 12.5 /g w/1.94 yd. Tail with 400 sks Class "H" with additives. Mixed @ 15.6 #/g w/ 1.18 yd. Slow rate lift pressure at 1671# at 3 BPM. At 9:30 am 12/21/05, tested 5 1/2" casing to 3280# for 30 minutes, held OK. Set 100k on slips.

12/21/05...Released rig at 3:00 pm 12/21/05.

12/30/05...Ran CBL and found TOC at 1360'.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Kristi Green TITLE Hobbs Regulatory DATE 01/03/06

Type or print name Kristi Green Telephone No. 505-393-5905

(This space for State use)

FOR RECORDS ONLY

APPROVED BY _____ TITLE _____ DATE JAN 12 2006

Conditions of approval, if any: