

Submit 3 Copies To Appropriate District Office

District I

1625 N. French Dr., Hobbs, NM 87240

District II

811 South First, Artesia, NM 87210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION

2040 South Pacheco

Santa Fe, NM 87505

Form C-103

Revised March 25, 1999

WELL API NO.

30-015-28905

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name
Todd "2" State

8. Well No. 4

9. Pool name or Wildcat
Ingle Wells; Delaware

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☒ Gas Well ☐ Other

2. Name of Operator Ricks Exploration, Inc.

3. Address of Operator 550 W. Texas Ave., Suite 1300
Midland, Texas 79701

4. Well Location

Unit Letter I : 1980 feet from the South line and 660 feet from the East line

Section 2 Township 24 Range 31 NMPM County Eddy

10. Elevation (Show whether DR, RKB, RT, GR, etc.)
3524' KB (19' AGL)

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: Add Delaware Sand Pay ☒

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOBS ☐

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and proposed work). SEE RULE 1103. For Multiple Completions: Attach diagram of proposed completion or recompletion.

Ricks Exploration, respectfully requests your approval, as follows:

Proposed Perfs: 7220 - 7252'

1. POOH w/rods and pump. NU BOP. Pull tbg. OOH.

2. MIRU ELU. Perf w/4" csg. gun 2 spf: 7220 - 7252'.

3. Pick up BP and pkr. Test tbg in hole to 6000#.

4. Set RBP @ 7300'. Set pkr @ 7150'.

5. Frac as designed.

6. Clean out sand and return to production.

7. Place SN @ 7150'. Run 1 1/2" pump w/10 of largest diameter rods in string on btm. Finish out w/standard taper with existing rods.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Brenda Coffman TITLE Regulatory Analyst DATE 07/09/2003

Type or print name Brenda Coffman

Telephone No. (432) 685-437

(This space for State use)

APPROVED BY Jim W. Beum TITLE District Supervisor DATE JUL 11 2003

Conditions of approval, if any: