

15-43443

WELL NAME: CEDAR LAKE FEDERAL CA 646H

API: 30-015-43443

SPUD DATE: 12/9/2015

PRODUCING FORMATION: YESO PADDOCK

FIELD: CEDAR LAKE (BP)

COUNTY: EDDY

STATE: NEW MEXICO

WORKING INTEREST: 59.92%

SURFACE LOC: 1980' FNL & 330' FWL

SECTION: 6

TOWNSHIP: 17-S

RANGE: 31-E

SURVEY: RONALD J. EIDSON

BOTTOM HOLE LOC: 1998.9' FNL & 547.9' FWL

SECTION: 5

TOWNSHIP: 17-S

RANGE: 31-E

SURVEY: RONALD J. EIDSON

DRILL RIG: CAPSTAR 119

RIG RELEASE: 1/22/2015

KB (ft): 3,770.00

GL (ft): 3,759.00

KBGL DIF (ft): 11.00

TMD (ft): 9,827.00

TD OF PILOT HOLE (ft): N/A

FC DEPTH (ft): 9,788.00

PBMD (ft): 9,827.00

RDV DEPTH (ft): N/A

ORIG VALVE (ft): N/A

DEEPEST TVD (ft): 4,870.00

TAPERED CASING STRING:

7" 29# L-80 TO X-OVER @ 4,290'

TAPERING TO 5.5" 20# L-80 SET @ 9,797'

KOP (ft): 4,251
LATERAL LENGTH (ft): 4,732
TD OF PILOT HOLE (ft): N/A

PACKERS & SLEEVES
TOP PERF (MD): 5,095
BOTTOM PERF (MD): 9,788

TMD (ft): 9,827
FC DEPTH (ft): 9,788
PBMD (ft): 9,827
RDV DEPTH (ft): N/A
ORIG VALVE (ft): N/A

COMPLETION:

STIMULATION:

STATUS:

COMMENTS:

LAST UPDATED BY: HILLARI GOULD
LAST UPDATED: 8/30/2016

CROSSOVER SUB @ 4,290'

PACKERS & SLEEVES - 17 STAGES			
TOTAL ACID (bb)	TOTAL LTR (bb)	TOTAL PROPANT (lbs)	MAX WH RATE (bpm)
3,055	83,029	4,811,640	94.00
PRODUCTION METHOD	LIFT TYPE	SETTING DEPTH	MAX WH PRESSURE (psi)
Pumping	ESP	4219	6,479

