Form 3160-5 (September 2001)

DEPARTMENT OF THE INTERIOR OCD-ARTESIA **BUREAU OF LAND MANAGEMENT**

FORM APPROVED OMB No. 1004-0135 Expires: January 31, 2004

5. Lease Serial No.

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

NM 93460 6. If Indian, Allottee or Tribe Name

THE CONTROL WORKS TOWN BEST TOWN TO THE RESERVENCE OF THE SECTION	and the property of the state o	V 55 YOU'S LEVY VALUE FASSIVE WE'L A LE	and the first of the control of the	7 1611-14	CA/A	
SUBMIT IN TRIPLICATE - Other instructions on reverse side				7. It Unit of	r CA/Agreement, Name and/or No.	
1. Type of Well Oil Well Gas Well 2. Name of Operator	RECEIVED			8. Well Name and No. Josey Federal #3		
NADEL AND GUSSMAN PERI	0 4 51 37/ 31 37					
3a. Address		3b. Phone No. (include greg code) 2006		30-015-34	30-015-34513	
601 N. MARIENFELD MIDLA!	(432) 682-4429	AANIMITEO	10. Field and Pool, or Exploratory Area			
4. Location of Well (Footage, Sec Surface: UL N Sec. 30 T20S R23 BH: UL N Sec. 30 T20S R23E 6			Chester 11. County	Chester 11. County or Parish, State		
				Eddy Cou		
12. CHECK AP	PROPRIATE BOX(ES) TO	INDICATE NAT	URE OF NOTICE,	REPORT, OI	R OTHER DATA	
TYPE OF SUBMISSION	TYPE OF ACTION					
_	Acidize	Deepen	Production (St	art/Resume)	■ Water Shut-Off	
Notice of Intent	Alter Casing	Fracture Treat	Reclamation		Well Integrity	
Subsequent Report	Casing Repair	New Construction	Recomplete		Other CMT PROD. CSG	
	Change Plans	Plug and Abandor	Temporarily A	bandon		
Final Abandonment Notice	Convert to Injection	Plug Back	Water Disposa			
determined that the site is ready 02/17/06 RU Casing Crew / Safe 02/18/06 Depth 8670' TD Run Circulate twice the csg capacity [10% D20, 3% D44 (BWOW), 0.3 w/ 2% D44 (bwow), 0.2% D65, 0 check float OK. Circulated 3 Bb test casing 1500 psi. high and 250	ety Meeting. Run 83 jts 5 ½" 17 17 17 18 N80 LTC Casing, To 405 Bbls]. RU Schlumberger / 2% D65, 0.2% D167, 0.25 pps D2% D167, 0.2% D46, 0.4% D1 ls [8 sks] cmt to surface. ND B6	otal 190 jts, FC @ 8 Safety Meeting. Pur 025, 0.1% D134, 0.2 3 @ 13.0 ppg / 1.41	574' set @ 8668' Instanped 20 Bbl Mud was 19% d46 @ 11.8 ppg 2. cuft/sk yield. Displace 5,000# tension. Cut cs	h, Lead: 773 s 48 cuft/sk yiel ed w/ 199 Bbl g & install 11"	iks [341 Bbls] 50 / 50 POZ / C w/d. Tail: 766 sks [192 Bbls] PVL ls FW. Bumped Plug w/ 1810 psi	
14. I hereby certify that the foregoin Name (PrintedlTyped)	ng is true and correct					
JOSH FERNAU	Title S	Title STAFF ENGINEER				
Signature & Fin			02/21/06			
	THIS SPACE FO	Commence of the second second second	STATE OFFICE US	E		
Approved by (Signature)	and the second s	Name (Printed Typed)		Title		
Conditions of approval, if any, are certify that the applicant holds leg which would entitle the applicant to	does not warrant or in the subject lease	Office		Date		
Title 18 U.S.C. Section 1001 and Ti States any false, fictitious or fraudul	itle 43 U.S.C. Section 1212, make it ent statements or representations as	t a crime for any perso to any matter within it	on knowingly and willful s jurisdiction.	ly to make to an	y department or agency of the United	