

Office

Revised July 18, 2013

District I - (575) 393-6161

1625 N. French Dr., Hobbs, NM 88240

District II - (575) 748-1283

811 S. First St., Artesia, NM 88210

District III - (505) 334-6178

1000 Rio Brazos Rd., Aztec, NM 87410

District IV - (505) 476-3460

1220 S. St. Francis Dr., Santa Fe, NM

87505

Energy, Minerals and Natural Resources

ARTESIA DISTRICT

JAN 13 2017

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

RECEIVED

WELL API NO.

30-015-43319

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil &amp; Gas Lease No.

7. Lease Name or Unit Agreement Name

Wild Turkey 36/35 B2AB St Com

8. Well Number 1H

9. OGRID Number 14744

10. Pool name or Wildcat

Palmillo; Bone Spring, East 49553

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Mewbourne Oil Company

3. Address of Operator

PO Box 5270, Hobbs NM 88241

4. Well Location

Unit Letter A: 500 feet from the North line and 185 feet from the East lineSection 36 Township 18S Range 28E NMPM Eddy County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

3426' GL

## 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

## NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐TEMPORARILY ABANDON ☐ CHANGE PLANS ☐PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐DOWNHOLE COMMINGLE ☐CLOSED-LOOP SYSTEM ☐OTHER: ☐

## SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐COMMENCE DRILLING OPNS. ☐ P AND A ☐CASING/CEMENT JOB ☒OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

12/22/16 TD 8 3/4" hole @ 8239'. Ran 7850' of 7" 26# P110 LT&C csg. Cmt w/500 sks Lite Class H (50:50:10) w/additives. Mixed @ 11.9#/g w/2.47 yd. Tail w/400 sks Class H w/additives. Mixed @ 15.6#/g w/1.18 yd. Plug down @ 11:15 A.M. 12/22/16. Circ 80 sks of cmt. Tested csg to 7500#. Set wellhead slips through BOPE w/230k#. FIT test EMW of 10.0 PPG. Pump 20 bbls FW spacer. At 10:15 P.M. 12/22/16, tested csg to 2500# for 30 min, held OK. Drilled out with 6 1/8" bit.

Spud Date: 12/13/16

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Ruby Caballero TITLE Regulatory DATE 01/03/2017Type or print name Ruby Caballero E-mail address: rojeda@mewbourne.com PHONE: 575-393-5905

For State Use Only

APPROVED BY: Raymond H. Rodney TITLE Geologist DATE 2-16-2017

Conditions of Approval (if any):