## **NM OIL CONSERVATION**

ARTESIA DISTRICT

District I
1625 N. French Dr., Hobbs, NM 88240
District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

FEB **09** 2017

Form C-141 Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Submit 1 Copy to appropriate District Office in RECEIVEL2ccordance with 19.15.29 NMAC.

Santa Fe, NM 87505 Release Notification and Corrective Action

DABI	105	32141				OPERATOR			X Initial Report Final Report		
		Burnett Oil C		<i>3080</i>		Contact: Johnny Titsworth					
				ort Worth, TX 76102		Telephone No. (432) 425-2891					
Facility Name: Jackson B 004WIW						Facility Type: Injection Well					
Surface Ow	ner: BLM	<u> </u>		Mineral C	)wner:	BLM API No				. 30-015-0403	6
				LOCA	ATIO	N OF RE	LEASE				
Unit Letter D	Section 1	Township 17S	Range 30E	Feet from the 660		South Line	Feet from the 660	East/West Line FWL		County Eddy	
	<del> </del>	I,		Latitude: 3	2.86162	2 Longitud	e: -103.92887				
				NAT	URE	OF REL	EASE				
Type of Rele								Volume Recovered 145 BBLS			
Source of Re				<del></del>	Date and Hour of Occurrence: 2/8/17			Date and Hour of Discovery 9:00 am 2/8/17			
Was Immediate Notice Given?  X Yes  No Not Required						If YES, To Whom? OCD – M. Bratcher BLM – S. Tucker					
By Whom? Johnny Titsworth						Date and Hour:					
Was a Watercourse Reached?						If YES, Volume Impacting the Watercourse.					
If a Waterco	urse was Im	pacted, Descr	ribe Fully.	*	************************	<u></u>		<del></del>			
		·······									
N/A											
		lem and Reme oded and relea			ig fluid l	nas been pick	ed up and hauled t	to dispo	sal. Area v	vill be remediate	ed to regulatory
Describe Are	a Affected	and Cleanup	Action Ta	ken.*		***************************************		<del></del>	<del></del>		
					acility lo	ocation, as we	ell as an 2'x30' are	ea in pa	sture.		
regulations a public health should their or or the enviro	all operators or the envi operations l nment. In a	are required in the ironment. The have failed to	to report a e acceptan adequately OCD acce	nd/or file certain in ce of a C-141 rep investigate and i	release n ort by th remediat	otifications a e NMOCD m e contaminat	knowledge and und perform correct tarked as "Final Right to that pose a three the operator of the correct tarket as "Final Right tarket as "Final Right" tarket as "Final Righ	tive act eport" of eat to g	ions for rele loes not rele round water	eases which may ieve the operator, surface water,	y endanger r of liability human health
	1	1 =	$\sim$				OIL CON	SERV	ATION	DIVISION	
Signature:						Sell 2					
Printed Name: Johnny Titsworth						Approved by Ensignanichial Specialists Sugarifica					
Title: HSE Coordinator						Approval Da	te: 2 20 1	1	Expiration	Date: N/A	
E-mail Address: jtitsworth@burnettoil.com						Conditions of Approval:			]		
Date:		Phone	: (432) 42	5-2891		1	See afto	achi	2al		_
	itional She	ets If Neces								0.	20 1100

2KP-412/

Operator/Responsible Party,

It is the Division's obligation under both the Oil & Gas Act and Water Quality Act to provide for the protection of public health and the environment. Our regulations (19.15.29.11 NMAC) state the following,

The responsible person shall complete <u>division-approved corrective action</u> for releases that endanger public health or the environment. The responsible person shall address releases in accordance with a remediation plan submitted to and approved by the division or with an abatement plan submitted in accordance with 19.15.30 NMAC. [emphasis added]

Release characterization is the first phase of corrective action unless the release is ongoing or is of limited volume and all impacts can be immediately addressed. Proper and cost-effective remediation typically cannot occur without adequate characterization of the impacts of any release. Furthermore, the Division has the ability to impose reasonable conditions upon the efforts it oversees. As such, the Division is requiring a workplan for the characterization of impacts associated with this release be submitted to the OCD District  $\frac{2}{\sqrt{2}}$  office in  $\frac{4}{\sqrt{2}}$  on or before  $\frac{4}{\sqrt{2}}$ . If and when the release characterization workplan is approved, there will be an associated deadline for submittal of the resultant investigation report. Modest extensions of time to these deadlines may be granted, but only with acceptable justification.

The goals of a characterization effort are: 1) determination of the lateral and vertical extents along with the magnitude of soil contamination. 2) determine if groundwater or surface waters have been impacted. 3) If groundwater or surface waters have been impacted, what are the extents and magnitude of that impact. 4) The characterization of any other adverse impacts that may have occurred (examples: impacts on vegetation, impacts on wildlife, air quality, loss of use of property, etc.). To meet these goals as quickly as possible, the following items must, at a minimum, be addressed in the release characterization workplan and subsequent reporting:

- Horizontal delineation of soil impacts in each of the four cardinal compass directions. Adsorbed soil contamination must be characterized for the following constituents using the associated laboratory methods: benzene, toluene, ethylbenzene, and total xylenes by either Method 8260 or 8021, total petroleum hydrocarbons by Method 8015 extended range (GRO+DRO+MRO; C<sub>6</sub> thru C<sub>36</sub>), and for chloride by Method 300. This is not an exclusive list of potential contaminants. Analyzed parameters should be modified based on the nature of the released substance(s). Soil sampling must be both within the impacted area and beyond.
- Vertical delineation of soil impacts. Adsorbed soil contamination must be characterized for the following constituents using the associated laboratory methods: benzene, toluene, ethylbenzene, and total xylenes by either Method 8260 or 8021, total petroleum hydrocarbons by Method 8015 extended range (GRO+DRO+MRO; C<sub>6</sub> thru C<sub>36</sub>), and for chloride by Method 300. As above, this is not an exclusive list of potential contaminants and can be modified. Vertical characterization samples should be taken at depth intervals no greater than five feet apart. Lithologic description of encountered soils must also be provided. At least ten vertical feet of soils with contaminant concentrations at or below these values must be demonstrated as existing above the water table.
- Nominal detection limits for field and laboratory analyses must be provided.
- Composite sampling is not generally allowed.
- Field screening and assessment techniques are acceptable (headspace, titration, EC [include algorithm for validation purposes], EM, etc.), but the sampling and assay procedures must be clearly defined. Copies of field notes are highly desirable. A statistically significant set of split samples must be submitted for confirmatory laboratory analysis, including the laterally farthest and vertically deepest sets of soil samples. Make sure there are at least two soil samples submitted

for laboratory analysis from each borehole or test pit (highest observed contamination and deepest depth investigated). Copies of the actual laboratory results must be provided including chain of custody documentation.

- •Probable depth to shallowest protectable groundwater and lateral distance to nearest surface water. If there is an estimate of groundwater depth, the information used to arrive at that estimate must be provided. If there is a reasonable assumption that the depth to protectable water is 50 feet or less, the responsible party should anticipate the need for at least one groundwater monitoring well to be installed in the area of likely maximum contamination.
- If groundwater contamination is encountered, an additional investigation workplan may be required to determine the extents of that contamination. Groundwater and/or surface water samples, if any, must be analyzed by a competent laboratory for volatile organic hydrocarbons (typically Method 8260 full list), total dissolved solids, pH, major anions and cations including chloride and sulfate, dissolved iron, and dissolved manganese. The investigation workplan must provide the groundwater sampling method(s) and sample handling protocols. To the fullest extent possible, aqueous analyses must be undertaken using nominal method detection limits. As with the soil analyses, copies of the actual laboratory results must be provided including chain of custody documentation.
- Accurately scaled and well-drafted site maps must be provided providing the location of borings, test pits, monitoring wells, potentially impacted areas, and significant surface features including roads and site infrastructure that might limit either the release characterization or remedial efforts. Field sketches may be included in subsequent reporting, but should not be considered stand-alone documentation of the site's layout. Digital photographic documentation of the location and fieldwork is recommended, especially if unusual circumstances are encountered.

Nothing herein should be interpreted to preclude emergency response actions or to imply immediate remediation by removal cannot proceed as warranted. Nonetheless, characterization of impacts and confirmation of the effectiveness of remedial efforts must still be provided to the OCD before any release incident will be closed.

Jim Griswold

OCD Environmental Bureau Chief 1220 South St. Francis Drive Santa Fe, New Mexico 87505 505-476-3465 jim.griswold@state.nm.us