

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENTFORM APPROVED  
OMB NO. 1004-0137  
Expires: January 31, 2018**SUNDRY NOTICES AND REPORTS ON WELLS**  
*Do not use this form for proposals to drill or to re-open an abandoned well. Use form 3160-3 (APD) for such proposals.*Please Serial No.  
090161

6. If Indian, Allottee or Tribe Name

**SUBMIT IN TRIPLICATE - Other instructions on page 2**7. If Unit or CA/Agreement, Name and/or No.  
NMNM120042X

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other8. Well Name and No.  
WEST BLINEBRY DRINKARD UNIT 1922. Name of Operator  
APACHE CORPORATIONContact: SORINA FLORES  
E-Mail: sorina.flores@apachecorp.com9. API Well No.  
30-025-42494-00-X13a. Address  
303 VETERANS AIRPARK LANE SUITE 3000  
MIDLAND, TX 797053b. Phone No. (include area code)  
Ph: 432-818-116710. Field and Pool or Exploratory Area  
EUNICE

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Sec 8 T21S R37E NENE 1865FSL 1985FEL  
32.491191 N Lat, 103.182544 W Lon11. County or Parish, State  
LEA COUNTY, NM**12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA**

TYPE OF SUBMISSION	TYPE OF ACTION			
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Hydraulic Fracturing	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input checked="" type="checkbox"/> Other
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	Change to Original A
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	PD

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.

BLM-CO-1463 NATIONWIDE; NMB000736

APACHE IS PROPOSING A 2-STAGE PROD CMT JOB CONTINGENCY IF SEVERE LOSSES ARE ENCOUNTERED. A DVT ABOVE LOSS ZONE MAY BE IMPLEMENTED.

1st stage

Lead: 230sx 65/35/6 Class C, 6% gel, 5% salt  
(12.6 ppg, 2.06 ft3/sk, 11.04 gal/sk)Tail: 275sx 50/50 POZ w Class C, 2% gel, 5% salt  
(14.2 ppg, 1.31 ft3/sk, 5.54 gal/sk)NM OIL CONSERVATION  
ARTESIA DISTRICTSEE ATTACHED FOR  
CONDITIONS OF APPROVAL

FEB 24 2017

RECEIVED

14. I hereby certify that the foregoing is true and correct.

Electronic Submission #365260 verified by the BLM Well Information System  
For APACHE CORPORATION, sent to the Hobbs  
Committed to AFMSS for processing by PRISCILLA PEREZ on 02/06/2017 (17PP0192SE)

Name (Printed/Typed) SORINA FLORES

Title SUBMITTING CONTACT

Signature (Electronic Submission)

Date 01/30/2017

**THIS SPACE FOR FEDERAL OR STATE OFFICE USE**

Approved By MUSTAFA HAQUE

Title PETROLEUM ENGINEER

Date 02/22/2017

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office Hobbs

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

\*\* BLM REVISED \*\* BLM REVISED \*\* BLM REVISED \*\* BLM REVISED \*\* BLM REVISED \*\*

Accepted for record - NMOC

RNF 36-

**Additional data for EC transaction #365260 that would not fit on the form**

**32. Additional remarks, continued**

DVT above loss zone

2nd stage

Lead: 400sx 65/35/6 Class C, 6% gel, 5% salt  
(12.6 ppg, 2.06 ft<sup>3</sup>/sk, 11.04 gal/sk)

Tail: 95sx Class C  
(14.8 ppg, 1.32 ft<sup>3</sup>/sk, 6.31 gal/sk)

**PECOS DISTRICT  
CONDITIONS OF APPROVAL**

<b>OPERATOR'S NAME:</b>	<b>Apache Corporation</b>
<b>LEASE NO.:</b>	<b>NMNM-90161</b>
<b>WELL NAME &amp; NO.:</b>	<b>West Blinebry Drinkard Unit 192W</b>
<b>SURFACE HOLE FOOTAGE:</b>	<b>1865' FSL &amp; 1985' FEL</b>
<b>LOCATION:</b>	<b>Section 17, T. 21 S., R 37 E., NMPM</b>
<b>COUNTY:</b>	<b>Lea County, New Mexico</b>

See below for the changes in the Conditions of Approval for the Drilling Section.

**DRILLING**

**All previous COAs still apply except the following:**

1. The minimum required fill of cement behind the 5-1/2 inch production casing is:

**Operator has proposed DV tool at depth of 3900', but will adjust cement proportionately if moved. DV tool shall be set a minimum of 50' below previous shoe and a minimum of 200' above current shoe. Operator shall submit sundry if DV tool depth cannot be set in this range. If an ECP is used, it is to be set a minimum of 50' below the shoe to provide cement across the shoe. If it cannot be set below the shoe, a CBL shall be run to verify cement coverage.**

- a. First stage to DV tool:

☒ Cement to circulate. If cement does not circulate, contact the appropriate BLM office before proceeding with second stage cement job. Operator should have plans as to how they will achieve circulation on the next stage.

- b. Second stage above DV tool:

☒ Cement to surface. Operator shall provide method of verification.

**MHH 02222017**



Haque, Mustafa <mhaque@blm.gov>

## West Blinebry Drinakrd Unit Sundry

2 messages

Haque, Mustafa <mhaque@blm.gov>

Wed, Feb 22, 2017 at 1:31 PM

To: Sorina.Flores@apachecorp.com

Hello Sorina,

Chris Walls forwarded me the DV tool sundries to work on. Can you please let me know the DV tool depth for -

**West Blinbery Drinkard Unit 192**

**West Blinbery Drinkard Unit 130**

**West Blinbery Drinkard Unit 221**

**West Blinbery Drinkard Unit 185**

Thank you-  
Haque

Regards,

*Mustafa Haque*

Petroleum Engineer  
Bureau of Land Management  
620 E Greene St.  
Carlsbad, NM-88220  
Office : (575)-234-5971

Flores, Sorina <Sorina.Flores@apachecorp.com>

Wed, Feb 22, 2017 at 1:33 PM

To: "Haque, Mustafa" <mhaque@blm.gov>

Yes.. DVT will be 3900' on all Thank you!!!

**SORINA FLORES**

Permian Drilling

direct 432-818-1167

**From:** Haque, Mustafa [mailto:mhaque@blm.gov]

**Sent:** Wednesday, February 22, 2017 2:32 PM

**To:** Flores, Sorina <Sorina.Flores@apachecorp.com>

**Subject:** West Blinebry Drinakrd Unit Sundry

[Quoted text hidden]