Form 3160-5 (June 2015)

UNITED STATES DEPARTMENT OF THE INTERIOR OPERATOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB NO. 1004-0137 Expires: January 31, 2018

SUNDRY NOTICES AND REPORTS ON WELLS

5. Lease Serial No. NMNM81586

Do not use thi abandoned we	6. If Indian, Allottee	6. If Indian, Allottee or Tribe Name			
SUBMIT IN	7. If Unit or CA/Agre	7. If Unit or CA/Agreement, Name and/or No.			
Type of Well ☐ Gas Well ☐ Oth		8. Well Name and No. CEDAR CANYON 22 FEDERAL 21H			
Name of Operator Contact: JANA MENDIOLA OXY USA INCORPORATED E-Mail: janalyn_mendiola@oxy.com			9. API Well No. 30-015-43642-0	9. API Well No. 30-015-43642-00-X1	
3a. Address 5 GREENWAY PLAZA SUITE 110 HOUSTON, TX 77046-0521 3b. Phone No. (include area code) Ph: 432-685-5936				10. Field and Pool or Exploratory Area PIERCE CROSSING	
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)			11. County or Parish,	11. County or Parish, State	
Sec 22 T24S R29E NESE 254 32.202504 N Lat, 103.964108	EDDY COUNT	EDDY COUNTY, NM			
12. CHECK THE AI	PPROPRIATE BOX(ES) TO) INDICATE NATURE O	F NOTICE, REPORT, OR OT	HER DATA	
TYPE OF SUBMISSION	TYPE OF ACTION				
☐ Notice of Intent	☐ Acidize	□ Deepen	☐ Production (Start/Resume)	■ Water Shut-Off	
_	☐ Alter Casing	☐ Hydraulic Fracturing	☐ Reclamation	□ Well Integrity	
Subsequent Report	□ Casing Repair	☐ New Construction	☐ Recomplete	Other	
☐ Final Abandonment Notice	Change Plans	□ Plug and Abandon	☐ Temporarily Abandon	· ·	
	Convert to Injection	☐ Plug Back	☐ Water Disposal		
following completion of the involved testing has been completed. Final Abdetermined that the site is ready for f. 11/3/16 Skid rig back to Ceda 10-3/4" casing to 1500# for 30 perform FIT test to EMW=23p & set 7-5/8" 29.7# L80 BTC cs 1430sx (662bbl) PPC w/ addit 13.2ppg 1.61 yield, no cmt to no cmt or spacer at surface, p additives 12.9ppg 1.65 yield for cancellation plug, pressure up be near surface, talked to BLN WOC. Install pack-off, test to rig for skid to Cedar Canyon 2	operations. If the operation results bandonment Notices must be filed of final inspection. The Canyon 22 Federal 21H. Rowing and page 330ps; good test. 11/4/16 and page 330ps; good test. 11/4/16 and page 330ps; pool test. 11/4/16 and page 340ps; pool test. 11/	s in a multiple completion or recomby after all requirements, including the second of	ation to 500', 11/7/16. RIH N spacer then cmt w/ C w/ additives od circulation, Dsx (262bbl) PPC w/ 33 yield, drop ow cement should tinue operations,	50-4 must be filed once	
14. I hereby certify that the foregoing is	Electronic Submission #360	918 verified by the BLM We	Information System	/ ^	
For OXY USA INCORPORATEĎ, sent to thé Carlsbad Committed to AFMSS for processing by JENNIFER SANCHEZ on 12/20/20				/ //	
Name (Printed Typed) DAVID ST	TEWART		ATORY ADVISOR	4 11	
Signature (Electronic S	Submission)	Date 12 12	GEPTED FOR RECOF	KD //	
	THIS SPACE FOR	FEDERAL OR STATE	OFFICE USE	Alalhi	
Approved By Conditions of approval, if any, are attache	d. Approval of this notice does not	Title warrant or	DEC 71 2016	MpdeM	
certify that the applicant holds legal or equivalent would entitle the applicant to condi-	uitable title to those rights in the sub uct operations thereon.	Office	BUREAU OF LAND MANAGEMENT CARLSBAD FIELD OFFICE	4	
Title 18 U.S.C. Section 1001 and Title 43 States any false, fictitious or fraudulent	U.S.C. Section 1212, make it a crin statements or representations as to a	ne for any person knowingly ard any matter within its jurisdiction	i willfully to make to any department or	r agency of the United	
(Instructions on page 2) ** BLM REV	ISED ** BLM REVISED **	BLM REVISED BLI	M REVISED ** BLM REVISE	D** V	

Additional data for EC transaction #360918 that would not fit on the form

32. Additional remarks, continued

11/24/16 Skid rig from Cedar Canyon 23 Federal 3H to Cedar Canyon 22 Federal 21H. RU BOP, test @ 250# low 5000# high. RIM & tag DVT, drill out DVT, test 7-5/8" casing to 3880# for 30 min, good test. Drill new formation to 8325', perform FIT test EMW=12.5ppg, good test. 11/25/16 Drill 6-3/4" hole to 13620'M 8718'V 12/5/16. RIH & set tapered csytring w/ 4-1/2" 13.5# P110 @ 13610-8782' and 5-1/2" 20# P110 csg @ 8782-0'. Pump 40 EW-spacer then cmt w/ 830sx (162bbl) PPC w/ additives @ 13.2ppg 1.63 yield, full returns throughout job (no cmt to surface, WOC. ND BOP, Install pack off & test to 5000# for 15min, good test. RD Ref Rig 12/7/16.