⁴ Form 3160-5 (June 2015)


UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT


NMOCD Artesia


FORM APPROVED OMB NO. 1004-0137 Expires: January 31, 2018


Lease Serial No.


SUNDRY NOTICES AND REPORTS ON WELLS			NMNM134867		
Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.				6. If Indian, Allottee or Tribe Name	
SUBMIT IN TRIPLICATE - Other instructions on page 2 1. Type of Well Oil Well Gas Well Other				7. If Unit or CA/Agreement, Name and/or No. 8. Well Name and No. HOSS 2/11 B2BO FED COM 2H	
3a. Address PO BOX 5270 HOBBS, NM 88241 4. Location of Well (Footage, Sec., T., R., M., or Survey Description)				Field and Pool or Exploratory Area SAN LORENZO NORTH BONE SP County or Parish, State	
12. CHECK THE APPROPRIATE	BOX(ES) TO INDIC	ATE NATURE O	F NOTICE,	REPORT, OR OTI	HER DATA
TYPE OF SUBMISSION	OF SUBMISSION TYPE OF ACTION				
☐ Notice of Intent ☐ Acidize	D Do	eepen	☐ Product	ion (Start/Resume)	☐ Water Shut-Off
☐ Alter Cas	sing H	ydraulic Fracturing	☐ Reclama	ation	■ Well Integrity
☑ Subsequent Report ☐ Casing R	epair	ew Construction	☐ Recomp	lete	Other
☐ Final Abandonment Notice ☐ Change F	Plans	ug and Abandon	☐ Temporarily Abandon		Well Spud
		☐ Water Disposal			
B. Describe Proposed or Completed Operation: Clearly star If the proposal is to deepen directionally or recomplete Attach the Bond under which the work will be perform following completion of the involved operations. If the testing has been completed. Final Abandonment Notice determined that the site is ready for final inspection.	horizontally, give subsurfaced or provide the Bond No. coperation results in a mult es must be filed only after a	ce locations and measure on file with BLM/BIA iple completion or recoult requirements, includ	red and true ve Required sub impletion in a r ing reclamation	rtical depths of all pertin sequent reports must be new interval, a Form 316 n, have been completed a	nent markers and zones. e filed within 30 days 50-4 must be filed once
Describe Proposed or Completed Operation: Clearly stars If the proposal is to deepen directionally or recomplete Attach the Bond under which the work will be performed following completion of the involved operations. If the testing has been completed. Final Abandonment Notice determined that the site is ready for final inspection. 05/15/2017 MI & spud 17?" hole. TD @ 46 w/500 sks Class C w/2% CaCl2. Mixed @ 1. FW. Plug down @ 8:15 P.M. 05/15/2017. Cir Annular to 3500#. Tested standpipe & mud li 8:00 P.M. 05/16/2017, tested csg to 1500# for	horizontally, give subsurfaced or provide the Bond No. e operation results in a mult es must be filed only after a 4'. Ran 449' of 13 &## 4.8#/g w/1.34 yd. Pum to 105 sks of cmt to the ines to the pumps to 5	ce locations and measure on file with BLM/BIA in pile completion or recompletion or recomplete in the pile completion of recomplete in the pile in the	red and true ve Required sub impletion in a r ing reclamation GT&C csg. (Displaced w/ E to 5000# & 0.5 PPG EM	rtical depths of all perting sequent reports must be new interval, a Form 316 n, have been completed and the complete and the compl	nent markers and zones. If filed within 30 days 50-4 must be filed once and the operator has
Describe Proposed or Completed Operation: Clearly star If the proposal is to deepen directionally or recomplete Attach the Bond under which the work will be perform following completion of the involved operations. If the testing has been completed. Final Abandonment Notice determined that the site is ready for final inspection. 05/15/2017 MI & spud 17 ?" hole. TD @ 46 w/500 sks Class C w/2% CaCl2. Mixed @ 1 FW. Plug down @ 8:15 P.M. 05/15/2017. Cir Annular to 3500#. Tested standpipe & mud li	horizontally, give subsurfared or provide the Bond No. e operation results in a mult es must be filed only after a 4'. Ran 449' of 13 &## 4.8#/g w/1.34 yd. Purr c 105 sks of cmt to the ines to the pumps to 5 or 30 minutes, held Ok</td><td>ce locations and measu on file with BLM/BIA jiple completion or reco ill requirements, includ 8540;" \$4.5# J55 S nped 20 bbls FW. De e pit. Tested BOPE 000#. FIT test to 19 6. Drilled out with</td><td>red and true ve Required sub impletion in a r ing reclamation ST&C csg. (Displaced w/ E to 5000# & 0.5 PPG EM 12 ?" bit.</td><td>rtical depths of all perting sequent reports must be usew interval, a Form 316 a, have been completed at 63 bbls at M. At</td><td>nent markers and zones. Filed within 30 days 50-4 must be filed once and the operator has MOIL CONSERVAT ARTESIA DISTRICT</td></tr><tr><td>B. Describe Proposed or Completed Operation: Clearly star If the proposal is to deepen directionally or recomplete Attach the Bond under which the work will be perform following completion of the involved operations. If the testing has been completed. Final Abandonment Notice determined that the site is ready for final inspection. 05/15/2017 MI & spud 17?" hole. TD @ 46 w/500 sks Class C w/2% CaCl2. Mixed @ 1. FW. Plug down @ 8:15 P.M. 05/15/2017. Cir Annular to 3500#. Tested standpipe & mud li 8:00 P.M. 05/16/2017, tested csg to 1500# for</td><td>horizontally, give subsurfared or provide the Bond No. e operation results in a mult es must be filed only after a 4'. Ran 449' of 13 &## 4.8#/g w/1.34 yd. Purr c 105 sks of cmt to the ines to the pumps to 5 or 30 minutes, held Ok</td><td>ce locations and measure on file with BLM/BIA in pile completion or recompletion or recomplete in the pile completion of recomplete in the pile in the</td><td>red and true ve Required sub impletion in a r ing reclamation ST&C csg. (Displaced w/ E to 5000# & 0.5 PPG EM 12 ?" bit.</td><td>rtical depths of all perting sequent reports must be usew interval, a Form 316 a, have been completed at 63 bbls at M. At</td><td>nent markers and zones. If filed within 30 days 50-4 must be filed once and the operator has</td></tr><tr><td>B. Describe Proposed or Completed Operation: Clearly star If the proposal is to deepen directionally or recomplete Attach the Bond under which the work will be performed following completion of the involved operations. If the testing has been completed. Final Abandonment Notice determined that the site is ready for final inspection. 05/15/2017 MI & spud 17?" hole. TD @ 46 w/500 sks Class C w/2% CaCl2. Mixed @ 1 FW. Plug down @ 8:15 P.M. 05/15/2017. Cir Annular to 3500#. Tested standpipe & mud li 8:00 P.M. 05/16/2017, tested csg to 1500# fc Chart & Schematic Attached.</td><td>horizontally, give subsurfared or provide the Bond No. e operation results in a mult es must be filed only after a 4'. Ran 449' of 13 &## 4.8#/g w/1.34 yd. Purr c 105 sks of cmt to the ines to the pumps to 5 or 30 minutes, held Ok</td><td>ce locations and measu on file with BLM/BIA jiple completion or reco ill requirements, includ 8540;" \$4.5# J55 S nped 20 bbls FW. De e pit. Tested BOPE 000#. FIT test to 19 6. Drilled out with</td><td>red and true ve Required sub impletion in a r ing reclamation ST&C csg. (Displaced w/ E to 5000# & 0.5 PPG EM 12 ?" bit.</td><td>rtical depths of all perting sequent reports must be usew interval, a Form 316 a, have been completed at 63 bbls at M. At</td><td>nent markers and zones. Filed within 30 days 50-4 must be filed once and the operator has MOIL CONSERVAT ARTESIA DISTRICT</td></tr><tr><td>In the proposed or Completed Operation: Clearly stars of the proposal is to deepen directionally or recomplete Attach the Bond under which the work will be performed following completion of the involved operations. If the testing has been completed. Final Abandonment Notice determined that the site is ready for final inspection. 05/15/2017 MI & spud 17?" hole. TD @ 46 w/500 sks Class C w/2% CaCl2. Mixed @ 1. FW. Plug down @ 8:15 P.M. 05/15/2017. Cir Annular to 3500#. Tested standpipe & mud li 8:00 P.M. 05/16/2017, tested csg to 1500# for Chart & Schematic Attached. Bond on file: NM1693 nationwide & NMB000 and the correct. Electronic Suitable Complete Suitable Correct.</td><td>horizontally, give subsurfared or provide the Bond No. e operation results in a mult es must be filed only after a 4'. Ran 449' of 13 &## 4.8#/g w/1.34 yd. Purr c 105 sks of cmt to the ines to the pumps to 5 or 30 minutes, held Ok</td><td>ce locations and measu on file with BLM/BIA iple completion or recoil requirements, includ 8540;" 54.5# J55 S sped 20 bbls FW. De pit. Tested BOPE 000#. FIT test to 10. Drilled out with</td><td>red and true ve Required sub- impletion in a r ing reclamation Table C csg. (College College College Table C csg. (College College College Table C csg. (College Table C csg.</td><td>rtical depths of all pertinsequent reports must be new interval, a Form 316 n, have been completed at 63 bbls. W. At NI</td><td>nent markers and zones. Filed within 30 days 50-4 must be filed once and the operator has MOIL CONSERVAT ARTESIA DISTRICT JUL 19 2017</td></tr><tr><td>Describe Proposed or Completed Operation: Clearly star If the proposal is to deepen directionally or recomplete Attach the Bond under which the work will be perform following completion of the involved operations. If the testing has been completed. Final Abandonment Notice determined that the site is ready for final inspection. 05/15/2017 MI & spud 17?" hole. TD @ 46 w/500 sks Class C w/2% CaCl2. Mixed @ 1. FW. Plug down @ 8:15 P.M. 05/15/2017. Cir Annular to 3500#. Tested standpipe & mud li 8:00 P.M. 05/16/2017, tested csg to 1500# for Chart & Schematic Attached. Bond on file: NM1693 nationwide & NMB000 and the correct. Electronic Su</td><td>horizontally, give subsurfaced or provide the Bond No. coperation results in a multics must be filed only after a 4'. Ran 449' of 13 .8#/g w/1.34 yd. Purrice 105 sks of cmt to the ines to the pumps to 5 or 30 minutes, held Ok</td><td>ce locations and measu on file with BLM/BIA iple completion or record ill requirements, includ 8540;" 54.5# J55 Saped 20 bbls FW. De pit. Tested BOPE 000#. FIT test to 10. Drilled out with a complete of the pit. Tested BOPE out with a complete ou</td><td>red and true ve Required sub- impletion in a r- ing reclamation ST&C csg. (C) Displaced w/ E to 5000# & 0.5 PPG EM 12 ?" bit. 20 -) 7 d - NMOC</td><td>rtical depths of all pertinsequent reports must be new interval, a Form 316 a, have been completed at 63 bbls at W. At NI</td><td>ment markers and zones. If filed within 30 days 30-4 must be filed once and the operator has MOIL CONSERVAT ARTESIA DISTRICT JUL 19 2017 RECEIVED</td></tr><tr><td>Describe Proposed or Completed Operation: Clearly star If the proposal is to deepen directionally or recomplete Attach the Bond under which the work will be perform following completion of the involved operations. If the testing has been completed. Final Abandonment Notice determined that the site is ready for final inspection. 05/15/2017 MI & spud 17?" hole. TD @ 46 w/500 sks Class C w/2% CaCl2. Mixed @ 1. FW. Plug down @ 8:15 P.M. 05/15/2017. Cir Annular to 3500#. Tested standpipe & mud li 8:00 P.M. 05/16/2017, tested csg to 1500# for Chart & Schematic Attached. Bond on file: NM1693 nationwide & NMB000 multiple in the correct. Electronic Sul For</td><td>horizontally, give subsurfaced or provide the Bond No. coperation results in a multics must be filed only after a 4'. Ran 449' of 13 .8#/g w/1.34 yd. Purrice 105 sks of cmt to the ines to the pumps to 5 or 30 minutes, held Ok</td><td>ce locations and measu on file with BLM/BIA iple completion or record ill requirements, includ 8540;" 54.5# J55 Saped 20 bbls FW. De pit. Tested BOPE 000#. FIT test to 10. Drilled out with a complete of the pit. Tested BOPE out with a complete ou</td><td>red and true ve Required sub- impletion in a r- ing reclamation ST&C csg. (C) Displaced w/ E to 5000# & 0.5 PPG EM 12 ?" bit. 20 -) 7 d - NMOC</td><td>rtical depths of all pertinsequent reports must be new interval, a Form 316 n, have been completed at 63 bbls. W. At NI</td><td>ment markers and zones. If filed within 30 days 30-4 must be filed once and the operator has MOIL CONSERVAT ARTESIA DISTRICT JUL 19 2017 RECEIVED</td></tr><tr><td>Describe Proposed or Completed Operation: Clearly star If the proposal is to deepen directionally or recomplete Attach the Bond under which the work will be performed following completion of the involved operations. If the testing has been completed. Final Abandonment Notice determined that the site is ready for final inspection. 05/15/2017 MI & spud 17 ?" hole. TD @ 46 w/500 sks Class C w/2% CaCl2. Mixed @ 1 FW. Plug down @ 8:15 P.M. 05/15/2017. Cir Annular to 3500#. Tested standpipe & mud li 8:00 P.M. 05/16/2017, tested csg to 1500# for Chart & Schematic Attached. Bond on file: NM1693 nationwide & NMB000 NM</td><td>horizontally, give subsurfared or provide the Bond No. coperation results in a multies must be filed only after a 4'. Ran 449' of 13 4.8#/g w/1.34 yd. Purror 105 sks of cmt to the ines to the pumps to 5 or 30 minutes, held Ok</td><td>ce locations and measure on file with BLM/BIA iple completion or record ill requirements, includ 8540;" 34.5# J55 Suped 20 bbls FW. Example of the political form of the politic</td><td>red and true ve Required sub- impletion in a ring reclamation Table C csg. (Displaced w/ E to 5000# & 0.5 PPG EM 12 ?" bit. The complete of the complete</td><td>rtical depths of all pertinsequent reports must be new interval, a Form 316 a, have been completed at 63 bbls W. At NI System</td><td>ment markers and zones. If filed within 30 days 50-4 must be filed once and the operator has MOIL CONSERVAT ARTESIA DISTRICT JUL 19 2017 RECEIVED</td></tr><tr><td>Describe Proposed or Completed Operation: Clearly star If the proposal is to deepen directionally or recomplete Attach the Bond under which the work will be perform following completion of the involved operations. If the testing has been completed. Final Abandonment Notice determined that the site is ready for final inspection. 05/15/2017 MI & spud 17 ?" hole. TD @ 46 w/500 sks Class C w/2% CaCl2. Mixed @ 1 FW. Plug down @ 8:15 P.M. 05/15/2017. Cir Annular to 3500#. Tested standpipe & mud li 8:00 P.M. 05/16/2017, tested csg to 1500# for Chart & Schematic Attached. Bond on file: NM1693 nationwide & NMB000 NMB0</td><td>horizontally, give subsurfaced or provide the Bond No. coperation results in a multics must be filed only after a 4'. Ran 449' of 13 .8#/g w/1.34 yd. Purrice 105 sks of cmt to the ines to the pumps to 5 or 30 minutes, held Ok</td><td>ce locations and measure on file with BLM/BIA iple completion or record ill requirements, includ 8540;" 34.5# J55 Suped 20 bbls FW. Example of the political form of the politic</td><td>red and true ve Required sub- impletion in a ring reclamation Table C csg. (Displaced w/ E to 5000# & 0.5 PPG EM 12 ?" bit. The complete of the complete</td><td>rtical depths of all pertinsequent reports must be new interval, a Form 316 a, have been completed at 63 bbls W. At NI System</td><td>ment markers and zones. Filed within 30 days 50-4 must be filed once and the operator has M OIL CONSERVAT ARTESIA DISTRICT JUL 19 2017 RECEIVED</td></tr><tr><td>3. Describe Proposed or Completed Operation: Clearly sta If the proposal is to deepen directionally or recomplete Attach the Bond under which the work will be perform following completion of the involved operations. If the testing has been completed. Final Abandonment Notice determined that the site is ready for final inspection. 05/15/2017 MI & spud 17 ?" hole. TD @ 46 w/500 sks Class C w/2% CaCl2. Mixed @ 1. FW. Plug down @ 8:15 P.M. 05/15/2017. Clar Annular to 3500#. Tested standpipe & mud li 8:00 P.M. 05/16/2017, tested csg to 1500# for Chart & Schematic Attached. Bond on file: NM1693 nationwide & NMB000 NMB000</td><td>horizontally, give subsurfared or provide the Bond No. coperation results in a multies must be filed only after a 4'. Ran 449' of 13 4.8#/g w/1.34 yd. Purror 105 sks of cmt to the ines to the pumps to 5 or 30 minutes, held Ok</td><td>ce locations and measu on file with BLM/BIA iple completion or recoil requirements, includ 8540;" 34.5# J55 Sped 20 bbls FW. Dept. Tested BOPE 000#. FIT test to 10. Drilled out with a complete for recording the by the BLM Wel MPANY, sent to the Title AUTHO Date 05/22/20</td><td>red and true ve Required sub- impletion in a ring reclamation Table C csg. (Displaced w/ to 5000# & 0.5 PPG EM 12 ?" bit. The complete of the complete of the carlsbad RIZED REP 017 OFFICE US</td><td>rtical depths of all pertinsequent reports must be new interval, a Form 316 n, have been completed at 63 bbls W. At NI System System System RESENTATIVE PROPERTY AND AD System</td><td>ment markers and zones. Filed within 30 days 50-4 must be filed once and the operator has M OIL CONSERVAT ARTESIA DISTRICT JUL 19 2017 RECEIVED</td></tr><tr><td>B. Describe Proposed or Completed Operation: Clearly star If the proposal is to deepen directionally or recomplete Attach the Bond under which the work will be perform following completion of the involved operations. If the testing has been completed. Final Abandonment Notice determined that the site is ready for final inspection. 05/15/2017 MI & spud 17 ?" hole. TD @ 46 w/500 sks Class C w/2% CaCl2. Mixed @ 1 FW. Plug down @ 8:15 P.M. 05/15/2017. Cir Annular to 3500#. Tested standpipe & mud li 8:00 P.M. 05/16/2017, tested csg to 1500# fc Chart & Schematic Attached. Bond on file: NM1693 nationwide & NMB000 on file: NM1693 nationwide & NMB000 on Schematic Sulfaction (Printed/Typed) JACKIE LATHAN</td><td>horizontally, give subsurfaced or provide the Bond No. coperation results in a multices must be filed only after a 4'. Ran 449' of 13 .8#/g w/1.34 yd. Purror 105 sks of cmt to the ines to the pumps to 5 or 30 minutes, held Ok</td><td>ce locations and measu on file with BLM/BIA iple completion or recoil requirements, includ 8540;" 34.5# J55 Sped 20 bbls FW. De pit. Tested BOPE 000#. FIT test to 10. Drilled out with a complete for record filed by the BLM Well MPANY, sent to the Title AUTHO Date 05/22/20</td><td>red and true ve Required sub- impletion in a ring reclamation ST&C csg. (Cosplaced w/E to 5000# & 0.5 PPG EM 12 ?" bit. 1 Information c Carlsbad RIZED REP</td><td>rtical depths of all pertir issequent reports must be sew interval, a Form 316 n, have been completed and the sew interval, a Form 316 n, have been completed and the sew interval, a Form 316 n, have been completed and the sew interval, a Form 316 n, have been completed and the sew interval. A Form 316 n, have been completed and the sew interval. A Form 316 n, have been completed and the sew interval. A Form 316 n, have been completed and the sew interval. A Form 316 n, have been completed and the sew interval.</td><td>ment markers and zones. Filed within 30 days 30.4 must be filed once and the operator has MOIL CONSERVAT ARTESIA DISTRICT JUL 19 2017 RECEIVED</td></tr></tbody></table>				














WELDING • BOP TESTING NIPPLE UP SERVICE • BOP LIFTS • TANDEM MUD AND GAS SEPARATORS

Company: 148 Whow Ca &	Lovington, NM • 575-396-4540	Pg.
Lease: Fire 2111 FOFO FALL	Date:	oī
Plug Size & Type:	Drilling Contractor:	Invoice #
Required BOP:	Drill Pipe Size	Rig # 2/3
Appropriate Casing Valve Must Be Open During BOP Test *	Installed BOP:	- I - Ster:
		Check Valve Must Be Occurry



TEMS TESTED	TEST LENGTH	LOW PSI	THOU	<u>·</u>	
3 1500	10 110	1	HIGH PSI	REM	AFIKS
1		1.50	· 200 2	77,000	440
13	(2.2)	Lar 1	xx 8 9		
	18 110	3.7			
			200 8		
5 77 26 4 79		75:0	Sec P		
6 126	13/16	250 -			· · · · · · · · · · · · · · · · · · ·
	1	. 1			
1/41 K 1/2			100 P		
8 436	Berger	5	000 8		
9 5,60 11 250	101.0	1	Cer. P		
	Later				
			2000 1		
415. 3 7		20 0	mores of		
may to the same	11/10	į.	00 F		
	like I				
- 12 10 E		50/0	00 6		
4 13 11 11 2 1	mlio .	7 100			
	10/100 100				
7 19 70	161				
	1300	- 10c	0 0		
	+				
	1.				
A Commence of the Commence of					
				the state of the s	

Chevron Use Only

DSM Signed:
Rig Manager Signed

MAN WELDING SERVICES, INC.

DSM & Rig manager must be present

	•		
Company Marshound		Date 5 - 16 - 1	
Lease 1/1 2/11 62 50	Talecore C	County /	
Drilling Contractor			
Accumulator Pressure:			
Accun To Check - USABLE FLUID I		ion Test - OO&(BOTTLES (III.A.2.c.i.	
Make sure all rams and aEnsure accumulator is put	nnular are open and if mped up to working p	f applicable HCR is closed oressure! (Shut off all pur	nps)
 Open HCR Valve. (If Close annular. Close all pipe rams. Open one set of the pi 		osing the blind ram	
<u> </u>	· · · · · · · · · · · · · · · · · · ·	i. Test Fails if pressere is lo	war than raquired
6. If annular is closed, oper			e. {1500 psi for a 3000 system}
To Check - PRECHARGE ON	BOTTLES OR SPH	ERICAL (III.A.2.d.)	
		mum acceptable pre-charge {1100 psi for 2000 and 30	
 Close bleed line. Bare Record pressure drop 	ly bump electric pum psi. Test fa	needle will drop at the lop and see what pressure the ails if pressure drops below. {900 psi for a 2000 &	e needle jumps up to. ow minimum.
To Check - THE CAPACITY O	F THE ACCUMULA	ATOR PUMPS (III.A.2.f.)
Isolate the accumulator bo	ttles or enherical from	n the numns & manifold	
		psi should go to 0 psi } clo	ose bleed valve.
 Open the HCR valve, Close annular 	if applicable}		
3. With pumps only, time		regain the required manifol	
4. Record elapsed time_ a. {950 psi for a 1:	7 (Test fails 00 psi system) b.	if it takes over 2 minutes {1200 psi for a 2000 & 300	00 psi system)