Submit 1 Copy To Appropriate District Office <u>District 1</u> – (575) 393-6161	rict II – (575) 393-6161 S. First St., Artesia, NM 88210 rict III – (505) 334-6178 Energy, Minerals and Natural Resources OIL CONSERVATION DIVISION 1220 South St. Francis Dr.		Form C-103 Revised July 18, 2013
1625 N. French Dr., Hobbs, NM 88240 <u>District II</u> – (575) 748-1283 811 S. First St., Artesia, NM 88210			WELL API NO. 30-015-40978 5. Indicate Type of Lease
District III - (505) 334-6178			STATE FEE
1000 Rio Brazos Rd., Aztec, NM 87410 <u>District IV</u> – (505) 476-3460	Santa Fe, N	M 87505	6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM			
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)			7. Lease Name or Unit Agreement Name BRAINARD 11 P
1. Type of Well: Oil Well Gas Well Other			8. Well Number #4
2. Name of Operator			9. OGRID Number 277558
LIME ROCK RESOURCES II-A, L.P.			7. OGRED Number 277556
3. Address of Operator			10. Pool name or Wildcat
c/o Mike Pippin LLC, 3104 N. Sullivan, Farmington, NM 87401			Red Lake, Glorieta-Yeso (51120)
4. Well Location			
Unit Letter P: 825 feet from the South line and 330 feet from the East line			
Section 11 Township 18-S Range 26-E NMPM Eddy County			
11. Elevation (Show whether DR, RKB, RT, GR, etc.)			
	3304' GL		
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:			
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. P AND A			
TEMPORARILY ABANDON DULL OR ALTER CASING	CHANGE PLANS ⊠ MULTIPLE COMPL □		
DOWNHOLE COMMINGLE		CASING/CLIVIEN	1308
CLOSED-LOOP SYSTEM			
OTHER: Change Surface C		OTHER:	
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.			
Lime Rock proposes to set the surface protection casing at a minimum of 1230', which is at least 50' below the base of the Artesian aquifer porosity that develops from 1160 to 1170' on the Lime Rock - Terry 14C #2 Neutron-Density log dated September 8, 2016. Historically there are at least 20 nearby Atoka field San Andres wells as identified in the IHS Energy database. Eleven wells have the surface casing protection string set at 1100' or deeper, with the deepest string at 1209'.			
hereby certify that the information above is true and complete to the best of my knowledge and belief.			
SIGNATURE Mike	Pippin TITLE	Petroleum Engineer - Ag	gent DATE <u>8/7/17</u>
Гуре or print name <u>Mike Pir</u>	pin E-mail a	ddress: <u>mike@pipp</u>	inllc.com PHONE: 505-327-4573
For State Use Only		_	
APPROVED BY Saymon Conditions of Approval (if any):	St. Juday TITLE_	Greologist.	DATE <u>\$-\$-/7</u>
Conditions of Approval (II any):	V	-	NM OIL CONSERVATION

ARTESIA DISTRICT

AUG 08 2017