

District I - (575) 393-6161  
1625 N. French Dr., Hobbs, NM 88240  
District II - (575) 748-1283  
811 S. First St., Artesia, NM 88210  
District III - (505) 334-6178  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV - (505) 476-3460  
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

<b>SUNDRY NOTICES AND REPORTS ON WELLS</b> (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-015- <del>40485</del> <b>44188</b>
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>		5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
2. Name of Operator <b>LIME ROCK RESOURCES II-A, L.P.</b>		6. State Oil & Gas Lease No.
3. Address of Operator c/o Mike Pippin LLC, 3104 N. Sullivan, Farmington, NM 87401		7. Lease Name or Unit Agreement Name <b>LEAVITT 14 A</b>
4. Well Location Unit Letter <u>A</u> : <u>1305</u> feet from the <u>NORTH</u> line and <u>330</u> feet from the <u>EAST</u> line Section <u>14</u> Township <u>18-S</u> Range <u>26-E</u> NMPM <u>Eddy</u> County		8. Well Number <b>#2</b>
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3304' GL		9. OGRID Number <b>277558</b>
10. Pool name or Wildcat Atoka, Glorieta-Yeso (0)		

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input checked="" type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	P AND A <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	MULTIPLE COMPL <input type="checkbox"/>	CASING/CEMENT JOB <input type="checkbox"/>	
DOWNHOLE COMMINGLE <input type="checkbox"/>			
CLOSED-LOOP SYSTEM <input checked="" type="checkbox"/>			
OTHER: <u>Change Surface Casing to 1230'</u> <input checked="" type="checkbox"/>		OTHER: <input type="checkbox"/>	

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work).  
SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Lime Rock proposes to set the 8-5/8" surface protection casing at a minimum of 1230', which is at least 50' below the base of the Artesian aquifer porosity that develops from 1160 to 1170' on the Lime Rock - Terry 14C #2 Neutron-Density log dated September 8, 2016. Historically there are at least 20 nearby Atoka field San Andres wells as identified in the IHS Energy database. Eleven wells have the surface casing protection string set at 1100' or deeper, with the deepest string at 1209'.

Spud Date:

Drilling Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Mike Pippin TITLE Petroleum Engineer - Agent DATE 8/7/17

Type or print name Mike Pippin E-mail address: mike@pippinllc.com PHONE: 505-327-4573

**For State Use Only**

APPROVED BY: Raymond D. Rodary TITLE Geologist DATE 8-8-17

Conditions of Approval (if any):

NM OIL CONSERVATION  
ARTESIA DISTRICT

AUG 08 2017

RECEIVED