

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
May 27, 2004

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other ☐	2. Name of Operator PARALLEL PETROLEUM CORPORATION	3. Address of Operator 1004 N BIG SPRING, SUITE 400, MIDLAND, TX 79701	4. Well Location Unit Letter <u>D</u> : <u>400</u> feet from the <u>N</u> line and <u>1880</u> feet from the <u>E</u> line Section <u>4</u> Township <u>15S</u> Range <u>26E</u> NMPM <u>CHAVES</u> County	5. Indicate Type of Lease STATE ☒ FEE ☐	6. State Oil & Gas Lease No.	7. Lease Name or Unit Agreement Name: DASH FOR CASH	8. Well Number 1	9. OGRID Number 230387	10. Pool name or Wildcat WILDCAT
11. Elevation (Show whether DR, RKB, RT, GR, etc.) GR 3446									
Pit or Below-grade Tank Application ☐ or Closure ☐ Pit type _____ Depth to Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water _____ Pit Liner Thickness: _____ mil Below-Grade Tank: Volume _____ bbls; Construction Material _____									

12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐

OTHER: SURVEY REPORTS (8 PAGES) ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

INRUN SURVEY 0 - 5314.74 (4 PAGES)

PATHFINDER SURVEY REPORT 4800 - 9295 (4 PAGES)

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed/closed according to NM OCD guidelines ☐ , a general permit ☐ or an (attached) alternative OCD-approved plan ☐

SIGNATURE Kaye McCormick TITLE SR PROD & REG TECH DATE 04-20-2006

Type or print name KAYE MC CORMICK

E-mail address: kmccormick@plll.com

Telephone No. 432-685-6563

For State Use Only

FOR RECORDS ONLY

APR 24 2006

APPROVED BY _____ TITLE _____ DATE _____

Conditions of Approval, if any:

0.05							
	1500.00	1499.89	13.57	0.74	165.38	-13.57	-0.55
0.05	1600.00	1599.88	14.74	0.67	161.03	-14.74	-0.20
0.09	1700.00	1699.88	15.96	0.77	169.54	-15.96	0.11
0.15	1800.00	1799.87	17.16	0.62	175.71	-17.16	0.28
0.17	1900.00	1899.86	18.25	0.63	179.24	-18.25	0.32
0.04							
	2000.00	1999.86	19.30	0.58	180.25	-19.30	0.33
0.05	2100.00	2099.85	20.27	0.53	180.30	-20.27	0.33
0.05	2200.00	2199.85	21.13	0.46	192.15	-21.13	0.24
0.12	2300.00	2299.84	21.84	0.40	201.76	-21.84	0.02
0.09	2400.00	2399.84	22.33	0.24	218.42	-22.33	-0.23
0.18							
	2500.00	2499.84	22.48	0.07	284.93	-22.48	-0.42
0.22	2600.00	2599.84	22.49	0.07	245.71	-22.49	-0.54
0.05	2700.00	2699.84	22.52	0.07	266.91	-22.52	-0.66
0.03	2800.00	2799.84	22.42	0.12	346.98	-22.42	-0.74
0.13	2900.00	2899.84	22.31	0.07	276.62	-22.31	-0.82
0.12							
	3000.00	2999.84	22.19	0.13	4.79	-22.19	-0.88
0.15	3100.00	3099.84	21.99	0.15	311.43	-21.99	-0.96
0.13	3200.00	3199.84	21.84	0.08	20.03	-21.84	-1.04
0.14	3300.00	3299.84	21.55	0.26	350.71	-21.55	-1.05
0.19	3400.00	3399.84	21.21	0.13	345.07	-21.21	-1.12
0.13							
	3500.00	3499.84	20.96	0.20	35.77	-20.96	-1.04
0.15	3600.00	3599.84	20.66	0.34	56.05	-20.66	-0.70
0.17	3700.00	3699.84	20.38	0.38	69.82	-20.38	-0.14
0.10	3800.00	3799.83	20.22	0.33	82.08	-20.22	0.46

0.12	5300.00	5299.74	20.46	0.68	94.63	-20.46	16.88
0.02	5315.00	5314.74	20.46	0.71	88.94	-20.46	17.06
0.50							

The Horizontal Displacement (in Feet) at
Measured Depth 5315.00 is 26.64 in a Direction of 140.18
Degrees

□

Pathfinder

Survey Report

Page 1
Job No: JWT-0603-0062-WTWT
Date: 3/23/2006
Time: 5:12 am
Wellpath ID: 06030062
Date Created: 3/6/2006
Last Revision: 3/23/2006

Calculated using the Minimum Curvature Method
Computed using PDS VER2.2.6
Vertical Section Plane: 180.12 deg.

Survey Reference: WELLHEAD
Vertical Section Reference: WELLHEAD
Closure Reference: WELLHEAD
TVD Reference: WELLHEAD

Parallel Petroleum
Dash For Cash #1
JW Rig #4
Chaves County, NM
06030062

Measured Depth (ft)	Incl (deg.)	Drift Dir. (deg.)	Course Length (ft)	TVD (ft)	Vertical Section (ft)	T O T A L		Closure		DLS (dg/100ft)
						Rectangular (ft)	Offsets (ft)	Dist. (ft)	Dir. (deg.)	
Tie In From Scientific Gyro Survey										
4800.00	0.57	85.36	0.00	4799.78	20.30	20.32 S	10.75 E	22.95	@152.12	0.00
First Pathfinder MWD Survey										
4830.00	3.96	173.77	30.00	4829.76	21.32	21.34 S	11.01 E	24.01	@152.70	13.28
4862.00	8.79	177.81	32.00	4861.55	24.86	24.88 S	11.22 E	27.30	@155.72	15.15
4894.00	13.54	178.52	32.00	4892.93	31.05	31.07 S	11.42 E	33.10	@159.83	14.85
4926.00	16.36	179.83	32.00	4923.85	39.30	39.33 S	11.53 E	40.98	@163.67	8.88
4958.00	18.64	182.82	32.00	4954.36	48.92	48.94 S	11.29 E	50.23	@167.01	7.66
4989.00	20.75	182.29	31.00	4983.55	59.36	59.38 S	10.82 E	60.36	@169.67	6.83
5021.00	23.57	183.09	32.00	5013.18	71.41	71.43 S	10.25 E	72.17	@171.83	8.86
5053.00	27.00	183.88	32.00	5042.11	85.05	85.07 S	9.42 E	85.55	@173.68	10.77
5085.00	31.48	182.47	32.00	5070.03	100.66	100.68 S	8.56 E	101.04	@175.14	14.16
5117.00	34.38	182.12	32.00	5096.89	118.04	118.06 S	7.87 E	118.32	@176.19	9.08
5146.00	36.93	181.33	29.00	5120.45	134.94	134.95 S	7.36 E	135.15	@176.88	8.94
5178.00	40.80	182.03	32.00	5145.36	155.00	155.02 S	6.77 E	155.17	@177.50	12.17
5209.00	44.14	182.12	31.00	5168.22	175.92	175.93 S	6.01 E	176.04	@178.04	10.78
5241.00	47.75	182.03	32.00	5190.47	198.90	198.91 S	5.18 E	198.98	@178.51	11.28
5273.00	50.83	182.47	32.00	5211.34	223.14	223.15 S	4.23 E	223.15	@178.92	9.68
5305.00	53.99	182.38	32.00	5230.86	248.47	248.48 S	3.15 E	248.50	@179.27	9.88
5337.00	57.24	182.65	32.00	5248.93	274.85	274.86 S	1.99 E	274.86	@179.58	10.18
5369.00	60.15	182.12	32.00	5265.55	302.17	302.17 S	0.86 E	302.17	@179.84	9.20
5400.00	62.96	182.29	31.00	5280.32	329.41	329.41 S	0.19W	329.41	@180.03	9.08
5434.00	66.48	181.77	34.00	5294.83	360.13	360.13 S	1.28W	360.13	@180.20	10.44
5466.00	70.87	181.42	32.00	5306.47	389.92	389.92 S	2.11W	389.92	@180.31	13.76
5498.00	75.53	180.89	32.00	5315.71	420.54	420.53 S	2.72W	420.54	@180.37	14.65
5529.00	80.02	180.62	31.00	5322.28	450.83	450.82 S	3.12W	450.83	@180.40	14.51
5560.00	83.45	180.89	31.00	5326.73	481.50	481.49 S	3.53W	481.51	@180.42	11.10
5592.00	87.05	180.80	32.00	5329.38	513.38	513.37 S	4.00W	513.38	@180.45	11.25
5624.00	86.61	180.98	32.00	5331.15	545.33	545.32 S	4.49W	545.34	@180.47	1.49
5656.00	88.55	180.62	32.00	5332.50	577.30	577.29 S	4.94W	577.31	@180.49	6.17
5689.00	91.54	180.62	33.00	5332.48	610.29	610.28 S	5.29W	610.30	@180.50	9.06
5721.00	91.98	180.45	32.00	5331.49	642.28	642.27 S	5.59W	642.29	@180.50	1.47
5752.00	90.75	179.66	31.00	5330.75	673.27	673.26 S	5.62W	673.28	@180.48	4.72
5784.00	88.11	178.87	32.00	5331.07	705.26	705.25 S	5.21W	705.27	@180.42	8.61
5815.00	86.79	177.64	31.00	5332.45	736.21	736.20 S	4.27W	736.21	@180.33	5.82

Pathfinder Survey Report

Page 2
Date: 3/23/2006
Wellpath ID: 06030062

Measured Depth (ft)	Incl (deg.)	Drift Dir. (deg.)	Course Length (ft)	TVD (ft)	Vertical Section (ft)	T O T A L		Closure		DLS (dg/100ft)
						Rectangular Offsets (ft)	(ft)	Dist. (ft)	Dir. (deg.)	
5847.00	86.79	177.81	32.00	5334.24	768.13	768.13 S	3.00W	768.13	@180.22	0.53
5879.00	87.49	177.28	32.00	5335.84	800.06	800.06 S	1.63W	800.06	@180.12	2.74
5911.00	88.20	177.90	32.00	5337.04	832.00	832.01 S	0.29W	832.01	@180.02	2.94
5943.00	89.16	177.90	32.00	5337.78	863.97	863.98 S	0.88 E	863.98	@179.94	3.00
5974.00	89.43	177.72	31.00	5338.16	894.94	894.95 S	2.07 E	894.95	@179.87	1.05
6006.00	89.52	177.81	32.00	5338.46	926.92	926.92 S	3.32 E	926.93	@179.79	0.40
6038.00	89.78	178.16	32.00	5338.65	958.89	958.90 S	4.44 E	958.91	@179.73	1.36
6070.00	89.96	178.16	32.00	5338.72	990.87	990.89 S	5.47 E	990.90	@179.68	0.56
6103.00	90.13	178.25	33.00	5338.70	1023.86	1023.87 S	6.50 E	1023.85	@179.64	0.58
6135.00	91.01	178.78	32.00	5338.38	1055.84	1055.86 S	7.33 E	1055.88	@179.60	3.21
6166.00	91.54	180.01	31.00	5337.69	1086.83	1086.85 S	7.66 E	1086.88	@179.60	4.32
6197.00	91.10	179.92	31.00	5336.98	1117.82	1117.84 S	7.68 E	1117.87	@179.61	1.45
6229.00	89.69	179.39	32.00	5336.75	1149.82	1149.84 S	7.87 E	1149.86	@179.61	4.71
6261.00	89.08	179.31	32.00	5337.10	1181.81	1181.83 S	8.23 E	1181.86	@179.60	1.92
6293.00	88.55	178.78	32.00	5337.76	1213.80	1213.82 S	8.77 E	1213.85	@179.59	2.34
6325.00	88.64	178.60	32.00	5338.54	1245.78	1245.80 S	9.50 E	1245.84	@179.56	0.63
6357.00	89.87	179.39	32.00	5338.96	1277.77	1277.80 S	10.06 E	1277.84	@179.55	4.57
6389.00	89.87	179.66	32.00	5339.03	1309.77	1309.79 S	10.33 E	1309.84	@179.55	0.84
6421.00	89.52	179.39	32.00	5339.20	1341.77	1341.79 S	10.59 E	1341.83	@179.55	1.38
6453.00	89.60	179.83	32.00	5339.45	1373.77	1373.79 S	10.81 E	1373.83	@179.55	1.40
6485.00	88.81	179.22	32.00	5339.89	1405.76	1405.79 S	11.07 E	1405.83	@179.55	3.12
6517.00	88.81	179.04	32.00	5340.56	1437.75	1437.78 S	11.56 E	1437.82	@179.54	0.56
6549.00	88.72	178.95	32.00	5341.25	1469.74	1469.76 S	12.12 E	1469.81	@179.53	0.40
6581.00	88.29	178.60	32.00	5342.08	1501.72	1501.75 S	12.80 E	1501.80	@179.51	1.73
6613.00	88.37	178.69	32.00	5343.02	1533.69	1533.72 S	13.56 E	1533.78	@179.49	0.38
6644.00	88.72	179.13	31.00	5343.80	1564.67	1564.71 S	14.15 E	1564.77	@179.48	1.81
6676.00	88.99	179.04	32.00	5344.44	1596.66	1596.70 S	14.66 E	1596.76	@179.47	0.89
6708.00	88.90	179.13	32.00	5345.03	1628.65	1628.69 S	15.17 E	1628.76	@179.47	0.40
6740.00	89.08	179.48	32.00	5345.60	1660.64	1660.68 S	15.56 E	1660.75	@179.46	1.23
6772.00	89.16	179.39	32.00	5346.09	1692.64	1692.67 S	15.88 E	1692.75	@179.46	0.38
6804.00	89.16	179.75	32.00	5346.56	1724.63	1724.67 S	16.12 E	1724.75	@179.46	1.12
6836.00	89.25	180.01	32.00	5347.00	1756.63	1756.67 S	16.18 E	1756.74	@179.47	0.86
6867.00	89.43	179.92	31.00	5347.36	1787.63	1787.66 S	16.20 E	1787.74	@179.48	0.65
6898.00	89.78	179.75	31.00	5347.57	1818.63	1818.66 S	16.29 E	1818.74	@179.49	1.26
6930.00	90.52	180.89	32.00	5347.49	1850.62	1850.66 S	16.11 E	1850.73	@179.50	4.25
6961.00	92.07	181.42	31.00	5346.79	1881.61	1881.65 S	15.49 E	1881.71	@179.53	5.28
6993.00	92.59	182.12	32.00	5345.49	1913.57	1913.60 S	14.50 E	1913.66	@179.57	2.72
7025.00	92.77	181.68	32.00	5343.99	1945.52	1945.55 S	13.44 E	1945.60	@179.60	1.48
7057.00	91.36	181.50	32.00	5342.84	1977.49	1977.52 S	12.55 E	1977.56	@179.64	4.44
7089.00	90.84	181.24	32.00	5342.22	2009.47	2009.50 S	11.79 E	2009.54	@179.66	1.82
7121.00	90.40	180.71	32.00	5341.88	2041.47	2041.50 S	11.24 E	2041.53	@179.68	2.15
7153.00	89.69	179.66	32.00	5341.85	2073.47	2073.50 S	11.14 E	2073.53	@179.69	3.96
7184.00	89.52	179.39	31.00	5342.06	2104.47	2104.49 S	11.40 E	2104.52	@179.69	1.03
7216.00	89.16	179.04	32.00	5342.43	2136.46	2136.49 S	11.84 E	2136.52	@179.68	1.57
7248.00	88.46	179.39	32.00	5343.10	2168.45	2168.48 S	12.27 E	2168.51	@179.68	2.45
7280.00	88.02	178.69	32.00	5344.08	2200.43	2200.46 S	12.81 E	2200.50	@179.67	2.58
7312.00	87.76	178.43	32.00	5345.26	2232.39	2232.43 S	13.61 E	2232.47	@179.65	1.15
7343.00	88.81	178.78	31.00	5346.19	2263.37	2263.40 S	14.37 E	2263.45	@179.64	3.57

Pathfinder Survey Report

Page 3
Date: 3/23/2006
Wellpath ID: 06030062

Measured Depth (ft)	Incl (deg.)	Drift Dir. (deg.)	Course Length (ft)	TVD (ft)	Vertical Section (ft)	T O T A L		Closure		DLS (dg/100ft)
						Rectangular Offsets (ft)	(ft)	Dist. (ft)	Dir. (deg.)	
7375.00	89.43	179.13	32.00	5346.68	2295.36	2295.39 S	14.95 E	2295.44@179.63	2.22	
7406.00	91.28	179.83	31.00	5346.49	2326.35	2326.39 S	15.23 E	2326.44@179.62	6.38	
7437.00	91.28	179.04	31.00	5345.79	2357.34	2357.38 S	15.54 E	2357.43@179.62	2.55	
7469.00	91.28	179.31	32.00	5345.08	2389.33	2389.37 S	16.00 E	2389.42@179.62	0.84	
7501.00	91.19	179.22	32.00	5344.39	2421.32	2421.36 S	16.41 E	2421.42@179.61	0.40	
7533.00	91.28	178.78	32.00	5343.70	2453.31	2453.35 S	16.97 E	2453.41@179.60	1.40	
7565.00	90.92	179.04	32.00	5343.09	2485.29	2485.34 S	17.58 E	2485.40@179.59	1.39	
7596.00	90.75	178.95	31.00	5342.63	2516.28	2516.33 S	18.12 E	2516.35@179.59	0.62	
7628.00	90.48	178.87	32.00	5342.29	2548.28	2548.32 S	18.73 E	2548.35@179.58	0.88	
7659.00	90.40	178.69	31.00	5342.05	2579.27	2579.31 S	19.39 E	2579.35@179.57	0.64	
7691.00	90.75	178.52	32.00	5341.73	2611.25	2611.30 S	20.17 E	2611.38@179.56	1.22	
7723.00	91.28	179.22	32.00	5341.16	2643.24	2643.29 S	20.80 E	2643.37@179.55	2.74	
7754.00	91.19	179.66	31.00	5340.50	2674.23	2674.28 S	21.10 E	2674.36@179.55	1.45	
7786.00	89.96	180.01	32.00	5340.17	2706.23	2706.28 S	21.19 E	2706.36@179.55	4.00	
7817.00	89.87	180.54	31.00	5340.22	2737.23	2737.28 S	21.04 E	2737.36@179.56	1.73	
7850.00	89.69	180.10	33.00	5340.35	2770.23	2770.28 S	20.86 E	2770.36@179.57	1.44	
7881.00	89.87	180.54	31.00	5340.47	2801.23	2801.28 S	20.69 E	2801.35@179.58	1.53	
7912.00	89.87	181.15	31.00	5340.54	2832.22	2832.27 S	20.23 E	2832.34@179.59	1.97	
7944.00	90.13	180.89	32.00	5340.54	2864.22	2864.27 S	19.66 E	2864.33@179.61	1.15	
7976.00	89.60	180.80	32.00	5340.61	2896.22	2896.26 S	19.19 E	2896.33@179.62	1.68	
8007.00	89.08	181.24	31.00	5340.97	2927.21	2927.26 S	18.64 E	2927.32@179.64	2.20	
8039.00	88.81	181.68	32.00	5341.56	2959.20	2959.24 S	17.82 E	2959.25@179.65	1.61	
8071.00	89.16	181.77	32.00	5342.13	2991.18	2991.22 S	16.86 E	2991.27@179.68	1.13	
8102.00	89.52	181.77	31.00	5342.48	3022.16	3022.20 S	15.90 E	3022.25@179.70	1.16	
8135.00	89.69	182.12	33.00	5342.71	3055.15	3055.18 S	14.78 E	3055.22@179.72	1.18	
8165.00	89.69	181.85	30.00	5342.87	3085.13	3085.17 S	13.74 E	3085.20@179.74	0.90	
8197.00	89.78	182.03	32.00	5343.02	3117.11	3117.15 S	12.66 E	3117.17@179.77	0.63	
8228.00	88.55	181.24	31.00	5343.47	3148.10	3148.13 S	11.77 E	3148.15@179.79	4.72	
8260.00	87.76	180.18	32.00	5344.50	3180.08	3180.11 S	11.38 E	3180.13@179.80	4.13	
8291.00	87.93	180.89	31.00	5345.67	3211.06	3211.09 S	11.09 E	3211.11@179.80	2.35	
8322.00	88.20	181.33	31.00	5346.71	3242.03	3242.06 S	10.49 E	3242.08@179.81	1.66	
8354.00	88.46	181.42	32.00	5347.65	3274.01	3274.04 S	9.72 E	3274.06@179.83	0.86	
8385.00	89.08	181.42	31.00	5348.31	3305.00	3305.02 S	8.95 E	3305.04@179.84	2.00	
8417.00	89.60	181.33	32.00	5348.68	3336.99	3337.01 S	8.18 E	3337.02@179.86	1.65	
8449.00	90.13	181.15	32.00	5348.76	3368.98	3369.00 S	7.49 E	3369.01@179.87	1.75	
8480.00	90.22	181.42	31.00	5348.66	3399.97	3400.00 S	6.80 E	3400.00@179.89	0.92	
8512.00	90.40	181.33	32.00	5348.49	3431.97	3431.99 S	6.03 E	3431.95@179.90	0.63	
8543.00	90.13	181.50	31.00	5348.34	3462.96	3462.98 S	5.26 E	3462.98@179.91	1.03	
8574.00	88.64	180.45	31.00	5348.68	3493.95	3493.97 S	4.74 E	3493.97@179.92	5.88	
8607.00	87.58	178.07	33.00	5349.77	3526.93	3526.95 S	5.16 E	3526.95@179.92	7.89	
8637.00	87.23	178.60	30.00	5351.12	3556.88	3556.90 S	6.03 E	3556.91@179.90	2.12	
8669.00	87.67	178.52	32.00	5352.55	3588.84	3588.86 S	6.84 E	3588.87@179.89	1.40	
8701.00	87.93	178.25	32.00	5353.78	3620.80	3620.82 S	7.74 E	3620.83@179.88	1.17	
8732.00	88.20	178.60	31.00	5354.82	3651.77	3651.79 S	8.59 E	3651.80@179.87	1.43	
8764.00	88.29	178.34	32.00	5355.80	3683.74	3683.77 S	9.44 E	3683.78@179.85	0.86	
8795.00	88.55	178.52	31.00	5356.66	3714.72	3714.75 S	10.29 E	3714.76@179.84	1.02	
8826.00	88.46	178.25	31.00	5357.47	3745.69	3745.72 S	11.17 E	3745.74@179.83	0.92	
8858.00	88.37	177.81	32.00	5358.35	3777.66	3777.69 S	12.27 E	3777.71@179.81	1.40	

Pathfinder **Survey Report**

Page 4
Date: 3/23/2006
Wellpath ID: 06030062

Measured Depth (ft)	Incl (deg.)	Drift Dir. (deg.)	Course Length (ft)	TVD (ft)	Vertical Section (ft)	TOTAL Rectangular Offsets (ft)	Closure Dist. Dir. (ft) (deg.)	DLS (dg/100ft)
8889.00	88.64	178.43	31.00	5359.16	3808.63	3808.66 S 13.28 E	3808.66@179.80	2.18
8921.00	88.20	178.60	32.00	5360.04	3840.60	3840.64 S 14.11 E	3840.67@179.79	1.47
8954.00	87.58	178.25	33.00	5361.26	3873.57	3873.61 S 15.02 E	3873.63@179.78	2.16
8985.00	86.97	177.90	31.00	5362.73	3904.51	3904.55 S 16.06 E	3904.59@179.76	2.27
9017.00	87.93	177.72	32.00	5364.16	3936.45	3936.50 S 17.28 E	3936.54@179.75	3.05
9048.00	87.99	177.55	31.00	5365.26	3967.40	3967.45 S 18.56 E	3967.49@179.73	0.58
9079.00	88.05	177.55	31.00	5366.33	3998.35	3998.40 S 19.88 E	3998.45@179.72	0.19
9111.00	88.10	177.81	32.00	5367.40	4030.31	4030.36 S 21.18 E	4030.42@179.70	0.83
9142.00	87.97	177.99	31.00	5368.47	4061.27	4061.32 S 22.31 E	4061.38@179.69	0.72
9174.00	87.53	177.81	32.00	5369.72	4093.22	4093.27 S 23.48 E	4093.34@179.67	1.49
9206.00	87.35	177.64	32.00	5371.15	4125.16	4125.22 S 24.75 E	4125.29@179.66	0.77
9237.00	88.01	179.66	31.00	5372.41	4156.12	4156.18 S 25.48 E	4156.26@179.65	6.85
Straight line Projection To Bit @ 9295 MD/5374 TVD								
9295.00	88.01	179.66	58.00	5374.42	4214.08	4214.15 S 25.83 E	4214.23@179.65	0.00