District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy, Minerals and Natural Resources Department

Submit Original to Appropriate District Office

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

NM OIL CONSERVATION ARTESIA DISTRICT

	GAS CAPTURE PLAN				N	IAY 15 2018
Date: 5-15-18						RECEIVED
□ Original	Operator & OGRID No.: Mewbourne Oil Company - 14744					
☐ Amended - Reason for	Amendment					
new completion (new dril	l, recomplete	to new zone, re-fra	ac) activity.			facility flaring/venting for
Note: Form C-129 must be su Well(s)/Production Facil			eding 60 days o	allowed by Ru	le (Subsection 2	1 of 19.15.18.12 NMAC).
The well(s) that will be lo	cated at the p	roduction facility a	are shown in	the table be	low.	
Well Name	API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments
South Loving 2/11 WOCF State #1H		3-2-24S-27E	360'FNL & 2030' FWL	0		Online after frac
30.	013-44	1947				
Gathering System and P	ipeline Notif	<u>fication</u>				
Well(s) will be connected	to a producti	ion facility after fl	owback ope	rations are c	omplete, if g	gas transporter system is in
place. The gas produced	from produ	iction facility is de	edicated to	Cresty	vood	and will be connected to
Crestwood low/	nigh pressur	e gathering system	n located in	Eddy	County, New	Mexico. It will require
(namiadically) to	connect the	facility to low/high	n pressure ga	thering syst	em. Mewbo	urne Oil Company provides
he drilled in the foreseed	olo futuro I	n addition Mowh	on and estima	ted first prod	uction date ic	or wells that are scheduled to a have periodic
conference calls to discus	s changes to	o drilling and com	npletion sche	edules. Gas	from these	wells will be processed at

Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on Crestwood system at that time. Based on current information, it is Operator's belief the system can take this gas upon completion of the well(s).

The actual flow of the gas will be based on compression operating parameters and gathering system pressures.

Processing Plant located in Sec. 29 , Twn. 24S , Rng. 28E , Eddy County, New Mexico.

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease
 - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
 - o Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
 - Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines