

**NM OIL CONSERVATION
ARTESIA DISTRICT**

Intent ☒ As Drilled ☐

OCT 18 2018

API #
30-015- 45360

Operator Name: EOG Resources, Inc.	Property Name: Torpedo 11 State	Well Number 702H
---------------------------------------	------------------------------------	---------------------

RECEIVED

Kick Off Point (KOP)

UL D	Section 11	Township 25S	Range 27E	Lot	Feet 51	From N/S North	Feet 972	From E/W West	County Eddy
Latitude 32.1517941					Longitude -104.1665727			NAD 83	

First Take Point (FTP)

UL D	Section 11	Township 25S	Range 27E	Lot	Feet 330	From N/S North	Feet 972	From E/W West	County Eddy
Latitude N 32.1510255					Longitude W -104.1665755			NAD 83	

Last Take Point (LTP)

UL M	Section 14	Township 25S	Range 27E	Lot	Feet 330	From N/S South	Feet 975	From E/W West	County Eddy
Latitude N 32.1236424					Longitude W -104.1663862			NAD 83	

Is this well the defining well for the Horizontal Spacing Unit? ☐ No

Is this well an infill well? ☐ Yes

If infill is yes please provide API if available, Operator Name and well number for Defining well for Horizontal Spacing Unit.

API # 30-015-	Operator Name: EOG Resources, Inc.	Property Name: Torpedo 11 State Com	Well Number 722H
------------------	---------------------------------------	--	---------------------

KZ 06/29/2018

Permit Information:

Well Name: Torpedo 11 State Com No. 702H

Location:

SHL: 342' FNL & 948' FWL, Section 11, T-25-S, R-27-E, Eddy Co., N.M.

BHL: 230' FSL & 975' FWL, Section 14, T-25-S, R-27-E, Eddy Co., N.M.

Design A**Casing Program:**

Hole Size	Interval	Csg OD	Weight	Grade	Conn	DF _{min} Collapse	DF _{min} Burst	DF _{min} Tension
12.25"	0' – 740'	9.625"	40#	J-55	LTC	1.125	1.25	1.60
8.75"	0' – 7,845'	7.625"	29.7#	HCP-110	FXL	1.125	1.25	1.60
6.75"	0' – 19,212'	5.5"	17#	HCP-110	LTC	1.125	1.25	1.60

Cement Program:

Depth	No. Sacks	Wt. ppg	Yld Ft ³ /sk	Slurry Description
740'	400	13.5	1.73	Class C + 4.0% Bentonite + 0.6% CD-32 + 0.5% CaCl ₂ + 0.25 lb/sk Cello-Flake (TOC @ Surface)
	300	14.8	1.34	Class C + 0.6% FL-62 + 0.25 lb/sk Cello-Flake + 0.2% Sodium Metasilicate
7,845'	300	9.0	3.5	Class C + 5% Gypsum + 3% CaCl ₂ (TOC @ Surface)
	550	14.4	1.20	50:50 Class H:Poz + 0.25% CPT20A + 0.40% CPT49 + 0.20% CPT35 + 0.80% CPT16A + 0.25% CPT503P
19,212'	800	14.2	1.31	Class H + 0.1% C-20 + 0.05% CSA-1000 + 0.20% C-49 + 0.40% C-17 (TOC @ 7,345)

Mud Program:

Depth	Type	Weight (ppg)	Viscosity	Water Loss
0 – 740'	Fresh - Gel	8.6-8.8	28-34	N/c
740' – 7,845'	Brine	8.8-10.0	28-34	N/c
7,845' – 8,598'	Oil Base	10.0-11.5	58-68	3 - 6
8,598' – 19,212' Lateral	Oil Base	10.0-11.5	58-68	3 - 6

Design B

Casing Program:

Hole Size	Interval	Csg OD	Weight	Grade	Conn	DF _{min} Collapse	DF _{min} Burst	DF _{min} Tension
17.5"	0' – 740'	13.375"	54.5#	J-55	STC	1.125	1.25	1.60
12.25"	0' – 2,220'	9.625"	40#	J-55	LTC	1.125	1.25	1.60
8.75"	0' – 7,845'	7.625"	29.7#	HCP-110	FXL	1.125	1.25	1.60
6.75"	0' – 19,212'	5.5"	17#	HCP-110	LTC	1.125	1.25	1.60

Cement Program:

Depth	No. Sacks	Wt. lb/gal	Yld Ft ³ /sk	Slurry Description
740'	697	13.5	1.74	Lead: Class 'C' + 4.00% Bentonite + 2.00% CaCl ₂ (TOC @ Surface)
	333	14.8	1.35	Tail: Class 'C' + 0.6% FL-62 + 0.25 lb/sk Cello-Flake + 0.2% Sodium Metasilicate + 2.0% KCl (1.06 lb/sk)
2,220'	692	12.7	2.22	Lead: Class C + 0.15% C-20 + 11.63 pps Salt + 0.1% C-51 + 0.75% C-41P (TOC @ Surface)
	303	14.8	1.32	Tail: Class C + 0.13% C-20
7,845'	375	10.8	3.67	Lead: Class C + 0.40% D013 + 0.20% D046 + 0.10% D065 + 0.20% D167 (TOC @ 1,720')
	400	14.8	2.38	Tail: Class H + 94.0 pps D909 + 0.25% D065 + 0.30% D167 + 0.02% D208 + 0.15% D800
19,212'	950	14.8	1.31	Class H + 0.1% C-20 + 0.05% CSA-1000 + 0.20% C-49 + 0.40% C-17 (TOC @ 7,345')

Mud Program:

Depth	Type	Weight (ppg)	Viscosity	Water Loss
0 – 740'	Fresh - Gel	8.6-8.8	28-34	N/c
740' – 2,220'	Brine	10.0-10.2	28-34	N/c
2,220' – 7,845'	Oil Base	8.7-9.4	58-68	N/c - 6
7,845' – 19,212' Lateral	Oil Base	10.0-11.5	58-68	3 - 6

EOG RESOURCES, INC.
TORPEDO 11 STATE COM #702H

Hydrogen Sulfide Plan Summary

- A. All personnel shall receive proper H₂S training in accordance with Onshore Order III.C.3.a.
- B. Briefing Area: two perpendicular areas will be designated by signs and readily accessible.
- C. Required Emergency Equipment:
- Well control equipment
 - a. Flare line 150' from wellhead to be ignited by flare gun.
 - b. Choke manifold with a remotely operated choke.
 - c. Mud/gas separator
 - Protective equipment for essential personnel.

Breathing apparatus:

 - a. Rescue Packs (SCBA) — 1 unit shall be placed at each breathing area, 2 shall be stored in the safety trailer.
 - b. Work/Escapes packs — 4 packs shall be stored on the rig floor with sufficient air hose not to restrict work activity.
 - c. Emergency Escape Packs — 4 packs shall be stored in the doghouse for emergency evacuation.

Auxiliary Rescue Equipment:

 - a. Stretcher
 - b. Two OSHA full body harness
 - c. 100 ft 5/8 inch OSHA approved rope
 - d. 1-20# class ABC fire extinguisher
 - H₂S detection and monitoring equipment:

The stationary detector with three sensors will be placed in the upper dog house if equipped, set to visually alarm @ 10 ppm and audible @ 14 ppm. Calibrate a minimum of every 30 days or as needed. The sensors will be placed in the following places: Rig floor / Bell nipple / End of flow line or where well bore fluid is being discharged.
(Gas sample tubes will be stored in the safety trailer)
 - Visual warning systems.
 - a. One color code condition sign will be placed at the entrance to the site reflecting the possible conditions at the site.
 - b. A colored condition flag will be on display, reflecting the current condition at the site at the time.
 - c. Two wind socks will be placed in strategic locations, visible from all angles.

EOG RESOURCES, INC.
TORPEDO 11 STATE COM #702H

- **Mud program:**
The mud program has been designed to minimize the volume of H₂S circulated to surface. The operator will have the necessary mud products to minimize hazards while drilling in H₂S bearing zones.
- **Metallurgy:**
All drill strings, casings, tubing, wellhead, blowout preventer, drilling spool, kill lines, choke manifold and lines, and valves shall be suitable for H₂S service.
- **Communication:**
Communication will be via cell phones and land lines where available.

**EOG RESOURCES, INC.
TORPEDO 11 STATE COM #702H**

Emergency Assistance Telephone List

PUBLIC SAFETY: **911 or**

Lea County Sheriff's Department	(575) 396-3611
Rod Coffman	
Fire Department:	
Carlsbad	(575) 885-3125
Artesia	(575) 746-5050
Hospitals:	
Carlsbad	(575) 887-4121
Artesia	(575) 748-3333
Hobbs	(575) 392-1979
Dept. of Public Safety/Carlsbad	(575) 748-9718
Highway Department	(575) 885-3281
New Mexico Oil Conservation	(575) 476-3440
U.S. Dept. of Labor	(575) 887-1174

EOG Resources, Inc.

EOG / Midland	Office (432) 686-3600
---------------	-----------------------

Company Drilling Consultants:

David Dominique	Cell (985) 518-5839
Mike Vann	Cell (817) 980-5507

Drilling Engineer

Steve Munsell	Office (432) 686-3609
	Cell (432) 894-1256

Drilling Manager

Aj Dach	(432) 686-3751
	(817) 480-1167

Drilling Superintendent

Todd Hamilton	(432) 848-9029
	(210) 413-9569

H&P Drilling

H&P Drilling	Office (432) 563-5757
H&P 651 Drilling Rig	Rig (903) 509-7131

Tool Pusher:

Johnathan Craig	Cell (817) 760-6374
Brad Garrett	

Safety

Brian Chandler (HSE Manager)	Office (432) 686-3695
	Cell (817) 239-0251


**Torpedo 11 State Com #702H
Eddy County, New Mexico**

**342' FNL
948' FWL
Section 11
T-25-S, R-27-E**

Proposed Wellbore Design A

API: 30-025-*****

**KB: 3,197'
GL: 3,172'**



Lateral: 19,212' MD, 9,068' TVD

**BH Location: 230' FSL & 975' FWL
Section 14
T-25-S, R-27-E**

**Torpedo 11 State Com #702H
Eddy County, New Mexico**

Proposed Wellbore Design B

**342' FNL
948' FWL
Section 11
T-25-S, R-27-E**

API: 30-025-*****

**KB: 3,197'
GL: 3,172'**

