Submit 3 Copies To Appropriate District Office	State of New Mexico		Form C-103
District I	Energy, Minerals and Natural Resources		WELL API NO.
1625 N. French Dr., Hobbs, NM 88240 District II	OT CONSERVATION DUVISION		30-015-34600
1301 W. Grand Ave., Artesia, NM 88210			5. Indicate Type of Lease
<u>District III</u> 1000 Rio Brazos Rd., Aztec, NM 87410	1220 South St. Francis Dr.		STATE FEE
District IV	Santa Fe, NM 8/303		6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM 87505			
SUNDRY NOTICES AND REPORTS ON WELLS			7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)			Hannibal Fee Com
	Gas Well 🛛 Other	BECEIVED	8. Well Number #1
2. Name of Operator		MAY 0 1 2006	9. OGRID Number
Nadel and Gussman Permian, LLC		4 60 11 12 12	155615
3. Address of Operator	1 577 50501	- CONTROLLEDIN	10. Pool name or Wildcat
601 N. Marienfeld Suite 508 Midla	nd, TX 79701		Dublin Ranch; Morrow
4. Well Location			
Unit Letter B :660' _ feet from theNorth line and1,980' feet from theEast line			
Section 31		Range 28E	NMPM County Eddy
	11. Elevation (Show whether	DR, RKB, RT, GR, etc.,	
3,050' Pit or Below-grade Tank Application or Closure			
Pit type Reserve Depth to Groundwater _ 25' Distance from nearest fresh water well _ Less than 200' Distance from nearest surface water 200'			
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:			
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK			
TEMPORARILY ABANDON			LLING OPNS. P AND A
PULL OR ALTER CASING			
OTHER:	П	OTHER:	П
			d give pertinent dates, including estimated date
	ork). SEE RULE 1103. For Mu	ltiple Completions: At	tach wellbore diagram of proposed completion
or recompletion.			
04/13/05 MI & RU Patterson Rig 511 (04/13/05), Pull up BHA, weld conductor and mix spud mud.			
04/14/06 Spud @ 6:30am 04/14/05. Drilling 17 ½" hole from 40' to 415' w/ all WOB and 80-90 RPM Survey @ 168' 1.00 deg and @			
345' 0.50 deg. Circ and POOH to run CSG. Run 10 jts 13 3/8" 48# csg and circ. Cement w/ Lead 192 sks (66 bbls) 35/65 Poz Tail w/ 200			
345' 0.50 deg. Circ and POOH to ru	Drilling 17 ½" hole from 40' to CSG. Run 10 its 13 3/8" 48# 6	o 415' w/ all WOB and	80-90 RPM Survey @ 168' 1.00 deg and @
345' 0.50 deg. Circ and POOH to ru	n CSG. Run 10 jts 13 3/8" 48# c	esg and circ. Cement w	v/ Lead 192 sks (66 bbls) 35/65 Poz Tail w/ 200
345' 0.50 deg. Circ and POOH to ru	n CSG. Run 10 jts 13 3/8" 48# c 59 bbls FW – bump plug Circ	esg and circ. Cement w	80-90 RPM Survey @ 168' 1.00 deg and @ // Lead 192 sks (66 bbls) 35/65 Poz Tail w/ 200 surface. WOC Cut off csg and weld on 13
345' 0.50 deg. Circ and POOH to ru sks (48 bbls) Class C CMT Displ w/5/8" 3M csg head, and test head. W	on CSG. Run 10 jts 13 3/8" 48# of 59 bbls FW – bump plug Circ : OC for 18 hrs.	esg and circ. Cement w 30 bbls (89 sks) cmt to	/ Lead 192 sks (66 bbls) 35/65 Poz Tail w/ 200 surface. WOC Cut off csg and weld on 13
345' 0.50 deg. Circ and POOH to ru sks (48 bbls) Class C CMT Displ w/ 5/8" 3M csg head, and test head. W 04/15/06 NU BOP and test 250 low	on CSG. Run 10 jts 13 3/8" 48# of 59 bbls FW – bump plug Circ : OC for 18 hrs.	esg and circ. Cement w 30 bbls (89 sks) cmt to	v/ Lead 192 sks (66 bbls) 35/65 Poz Tail w/ 200
345' 0.50 deg. Circ and POOH to ru sks (48 bbls) Class C CMT Displ w/5/8" 3M csg head, and test head. W	on CSG. Run 10 jts 13 3/8" 48# of 59 bbls FW – bump plug Circ : OC for 18 hrs.	esg and circ. Cement w 30 bbls (89 sks) cmt to	/ Lead 192 sks (66 bbls) 35/65 Poz Tail w/ 200 surface. WOC Cut off csg and weld on 13
345' 0.50 deg. Circ and POOH to ru sks (48 bbls) Class C CMT Displ w/ 5/8" 3M csg head, and test head. W 04/15/06 NU BOP and test 250 low 250 low for 30 min. OK.	on CSG. Run 10 jts 13 3/8" 48# of 59 bbls FW – bump plug Circ of OC for 18 hrs. The stand 1,000 high test ok 30 min.	esg and circ. Cement w 30 bbls (89 sks) cmt to PU BHA and tag cmt (/ Lead 192 sks (66 bbls) 35/65 Poz Tail w/ 200 surface. WOC Cut off csg and weld on 13 @ 342'. Drld Cmt / Test Csg 1,000 high and
345' 0.50 deg. Circ and POOH to ru sks (48 bbls) Class C CMT Displ w/ 5/8" 3M csg head, and test head. W 04/15/06 NU BOP and test 250 low 250 low for 30 min. OK. I hereby certify that the information	on CSG. Run 10 jts 13 3/8" 48# of 59 bbls FW – bump plug Circ of OC for 18 hrs. The and 1,000 high test ok 30 min. The above is true and complete to the com	esg and circ. Cement was 30 bbls (89 sks) cmt to PU BHA and tag cmt (/ Lead 192 sks (66 bbls) 35/65 Poz Tail w/ 200 surface. WOC Cut off csg and weld on 13
345' 0.50 deg. Circ and POOH to ru sks (48 bbls) Class C CMT Displ w/ 5/8" 3M csg head, and test head. W 04/15/06 NU BOP and test 250 low 250 low for 30 min. OK. I hereby certify that the information grade tank has been/will be constructed or	on CSG. Run 10 jts 13 3/8" 48# of 59 bbls FW – bump plug Circ in OC for 18 hrs. The and 1,000 high test ok 30 min. The above is true and complete to the closed according to NMOCD guideling.	esg and circ. Cement was 30 bbls (89 sks) cmt to PU BHA and tag cmt (and the best of my knowledges , a general permit	w/ Lead 192 sks (66 bbls) 35/65 Poz Tail w/ 200 surface. WOC Cut off csg and weld on 13 342'. Drld Cmt / Test Csg 1,000 high and e and belief. I further certify that any pit or below-or an (attached) alternative OCD-approved plan .
345' 0.50 deg. Circ and POOH to ru sks (48 bbls) Class C CMT Displ w/ 5/8" 3M csg head, and test head. W 04/15/06 NU BOP and test 250 low 250 low for 30 min. OK. I hereby certify that the information	on CSG. Run 10 jts 13 3/8" 48# of 59 bbls FW – bump plug Circ in OC for 18 hrs. The and 1,000 high test ok 30 min. The above is true and complete to the closed according to NMOCD guideling.	esg and circ. Cement was 30 bbls (89 sks) cmt to PU BHA and tag cmt (and the best of my knowledges , a general permit	w/ Lead 192 sks (66 bbls) 35/65 Poz Tail w/ 200 surface. WOC Cut off csg and weld on 13 342'. Drld Cmt / Test Csg 1,000 high and e and belief. I further certify that any pit or below-or an (attached) alternative OCD-approved plan .
345' 0.50 deg. Circ and POOH to ru sks (48 bbls) Class C CMT Displ w/ 5/8" 3M csg head, and test head. Wood/15/06 NU BOP and test 250 low 250 low for 30 min. OK. I hereby certify that the information grade tank has been/will be constructed or SIGNATURE	an CSG. Run 10 jts 13 3/8" 48# 6 59 bbls FW – bump plug Circ in OC for 18 hrs. and 1,000 high test ok 30 min. above is true and complete to the closed according to NMOCD guideling.	esg and circ. Cement was 30 bbls (89 sks) cmt to PU BHA and tag cmt (and be best of my knowledges , a general permit and	// Lead 192 sks (66 bbls) 35/65 Poz Tail w/ 200 surface. WOC Cut off csg and weld on 13 @ 342'. Drld Cmt / Test Csg 1,000 high and e and belief. I further certify that any pit or belowor an (attached) alternative OCD-approved plan □.
345' 0.50 deg. Circ and POOH to ru sks (48 bbls) Class C CMT Displ w/ 5/8" 3M csg head, and test head. W 04/15/06 NU BOP and test 250 low 250 low for 30 min. OK. I hereby certify that the information grade tank has been/will be constructed or	an CSG. Run 10 jts 13 3/8" 48# 6 59 bbls FW – bump plug Circ in OC for 18 hrs. and 1,000 high test ok 30 min. above is true and complete to the closed according to NMOCD guideling.	esg and circ. Cement was 30 bbls (89 sks) cmt to PU BHA and tag cmt (and the best of my knowledges , a general permit	// Lead 192 sks (66 bbls) 35/65 Poz Tail w/ 200 surface. WOC Cut off csg and weld on 13 ② 342'. Drld Cmt / Test Csg 1,000 high and e and belief. I further certify that any pit or belowor an (attached) alternative OCD-approved plan □.
345' 0.50 deg. Circ and POOH to ru sks (48 bbls) Class C CMT Displ w/ 5/8" 3M csg head, and test head. Wood/15/06 NU BOP and test 250 low 250 low for 30 min. OK. I hereby certify that the information grade tank has been/will be constructed or SIGNATURE Type or print name For State Use Only	an CSG. Run 10 jts 13 3/8" 48# 6 59 bbls FW – bump plug Circ in OC for 18 hrs. The and 1,000 high test ok 30 min. The above is true and complete to the closed according to NMOCD guideling. TITLE _ Staff English E-main	esg and circ. Cement was 30 bbls (89 sks) cmt to PU BHA and tag cmt (and be best of my knowledges , a general permit magineer	# Lead 192 sks (66 bbls) 35/65 Poz Tail w/ 200 surface. WOC Cut off csg and weld on 13
345' 0.50 deg. Circ and POOH to ru sks (48 bbls) Class C CMT Displ w/ 5/8" 3M csg head, and test head. Wood/15/06 NU BOP and test 250 low 250 low for 30 min. OK. I hereby certify that the information grade tank has been/will be constructed or SIGNATURE Type or print name For State Use Only	an CSG. Run 10 jts 13 3/8" 48# 6 59 bbls FW – bump plug Circ in OC for 18 hrs. and 1,000 high test ok 30 min. above is true and complete to the closed according to NMOCD guideling.	esg and circ. Cement was 30 bbls (89 sks) cmt to PU BHA and tag cmt (and be best of my knowledges , a general permit magineer	// Lead 192 sks (66 bbls) 35/65 Poz Tail w/ 200 surface. WOC Cut off csg and weld on 13 @ 342'. Drld Cmt / Test Csg 1,000 high and e and belief. I further certify that any pit or belowor an (attached) alternative OCD-approved plan □.