Form 3160-5 (April 2004)

N.M. Oil Cons. DIV-Dist. 2

UNITED STATES 1301 W. Grand Avenue DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMANTOSIA, NIVI 88210

FORM APPROVED

OMB No. 1004-0135 Expires March 31, 2007

SUNDRY NOTICES AND REPORTS ON WELLS				5. Lease Serial No. NM-96210		
Do not use this form for proposals to drill or re enter an abandoned well. Use Form 3160-3 (APD) for such proposals.				6. If Indian, Allottee or Tribe Name		
SUBMIT IN TRIPLICATE - Other instructions on reverse side				7. If Unit or CA/Agreement, Name and/or No.		
1. Type of Well RECEIVED						
Oil Well X Gas V	Well Other	!	MAY 0 2 7006	8. Well Name and	No.	
2. Name of Operator		してに、うむするのま		Magellan Federal Unit #1		
Yates Petroleum Corporation 3a. Address	3b. Phone No. (include are			9. API Well No. 30-015-34603		
105 S. 4th Str., Artesia, NM 88210		•	505-748-1471		10. Field and Pool, or Exploratory Area	
4. Location of Well (Footage, Sec., T., R., M., C			Undes. Hackb	erry Draw; Morrow, North		
			11. County or Paris			
1650'FSL & 660'FEL of Section 5-T25S-R27E (Unit I, NESE)			E OF NOTICE P		, New Mexico	
12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA						
TYPE OF SUBMISSION TYPE OF ACTION						
	Acidize	Deepen	Production	(Start/Resume)	Water Shut-Off	
Notice of Intent	Alter Casing	Fracture Treat	Reclamation	1	Well Integrity	
X Subsequent Report	Casing Repair	New Construction	Recomplete		X Other Surface	
Subsequent Report	Change Plans	Plug and Abandon	Temporaril	/ Abandon	and Intermediate	
Final Abandonment Notice	Convert to Injection	Plug Back	Water Disp	osal	casing	
following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.) 4/11/06 Resumed drilling at 11:30 AM. Set 13-3/8" 48# H-40 8rd ST&C casing at 427'. Cemented with 447 sx Class C" + 2% CaCl2 + 1/4# Celloflake (yld 1.32, wt 14.8). Cement circulated to surface. Tested casing to 1500 psi for 30 min. WOC 19 hrs 40 min. Reduced hole to 12-1/4" and resumed drilling. 4/17/06 Set 9-5/8" 36# J-55 8rd ST&C casing at 2356'. Cemented with 850 sx 35:65:6 "C" + 2% CaCl + .25# Celloflake + 5# LCM (yld 1.98, wt 12.5). Tailed in with 200 sx Class "C" + 1% CaCl (yld 1.34, wt 14.8). Cement circulated to surface. Tested casing to 1500 psi for 30 min. WOC 33 hrs 15 min. Reduced hole to 8-3/4" ACCEPTED FOR RECORD ALEXIS C. SWOBODA APETROLEUM ENGINEER						
 I hereby certify that the foregoing is true a Name (Printed/Typed) 	nd correct					
Tina Huerta	 	Title R	egulatory Compli	ance Supervis	or	
Signature (Sina)	herta	Date A	pril 20, 2006			
THIS SPACE FOR FEDERAL OR STATE OFFICE USE						
Approved by			Title	Date	Ð	
Conditions of approval, if any, are attached. certify that the applicant holds legal or equita which would entitle the applicant to conduct of	able title to those rights in perations thereon.	the subject lease (Office			
Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willbully to make to any department or agency of the United						

States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction