

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone: (575) 748-1283 Fax: (575) 748-9720
District III
1000 Rio Brazos Road, Aztec, NM 87410
Phone: (505) 334-6178 Fax: (505) 334-6170
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505
Phone: (505) 476-3460 Fax: (505) 476-3462

State of New Mexico **NM OIL CONSERVATION**
Energy, Minerals & Natural Resources Department
ARTESIA DISTRICT
OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-102
Revised August 1, 2011
Submit one copy to appropriate
District Office

RECEIVED

☐ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

¹ API Number 30-015-45709	² Pool Code 98220	³ Pool Name PURPLE SAGE; WOLFCAMP (GAS)
⁴ Property Code 324971	⁵ Property Name CB CAL 15 22 002	⁶ Well Number 1H
⁷ OGRID No. 4323	⁸ Operator Name CHEVRON U.S.A. INC.	⁹ Elevation 2992'

¹⁰ Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
B	15	23 SOUTH	28 EAST, N.M.P.M.		518'	NORTH	1405'	EAST	EDDY

¹¹ Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
O	22	23 SOUTH	28 EAST, N.M.P.M.		100'	SOUTH	2178'	EAST	EDDY

¹² Dedicated Acres 640	¹³ Joint or Infill	¹⁴ Consolidation Code	¹⁵ Order No.
---	-------------------------------	----------------------------------	-------------------------

No allowable will be assigned to this completion until all interests have been consolidated or a non-standard unit has been approved by the division.

PROPOSED FIRST TAKE POINT X= 580,366 NAD 27 Y= 477,220 LAT. 32.311725 LONG. 104.073200 X= 621,549 NAD83 Y= 477,279 LAT. 32.311845 LONG. 104.073695	CB CAL 15 22 002 NO.1H WELL X= 581,139 NAD 27 Y= 477,045 LAT. 32.311239 LONG. 104.070700 X= 622,322 NAD83 Y= 477,104 LAT. 32.311360 LONG. 104.071195 ELEVATION +2992' NAVD 88		¹⁷ OPERATOR CERTIFICATION I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division. <i>Kayla McConnell</i> 1/29/19 Signature Date Kayla McConnell Printed Name gncv@chevron.com E-mail Address
PROPOSED MID POINT X= 580,369 NAD 27 Y= 472,232 LAT. 32.298014 LONG. 104.073230 X= 621,552 NAD83 Y= 472,291 LAT. 32.298135 LONG. 104.073725	CORNER COORDINATES TABLE (NAD 27) A - Y=477496.90, X=577205.98 B - Y=477585.85, X=582543.98 C - Y=472181.88, X=577232.84 D - Y=472268.72, X=582548.90 E - Y=468658.95, X=577288.92 F - Y=467012.61, X=582560.30		¹⁸ SURVEYOR CERTIFICATION I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief. 10/13/2017 Date of Survey Signature and Seal of Professional Surveyor: <i>Robert L. Lastrapes</i> 23006 06/05/2018 23006 Certificate Number

RUP 2-13-19

100k lb overpull	X	X	X
------------------	---	---	---

ONSHORE ORDER NO. 1

Chevron

CB CAL 15 22 002 1H

Eddy County, NM

CONFIDENTIAL -- TIGHT HOLE

DRILLING PLAN

PAGE:

3

5. CEMENTING PROGRAM

Slurry	Type	Cement Top	Cement Bottom	Weight (ppg)	Yield (sx/cu ft)	OH %Excess Open Hole	Sacks	Water gal/sk
Surface								
Tail	Class C	0'	450'	14.8	1.336	10	257	6.423
Intermediate								
Stage 2 Lead	Class C	0'	1,595'	11.9	2.57	10	217	14.73
Stage 2 Tail	Class C	1,595'	2,595'	14.8	1.337	10	258	6.42
DV Tool		2,595'						
Stage 1 Lead	Class C	2,595'	8,000'	11.9	2.57	10	724	14.73
Stage 1 Tail	Class C	8,000'	9,000'	14.8	1.337	10	258	6.42
Production								
Tail	Class C	6,000'	18,868'	13.2	1.84	10	1763	9.85
Acid Soluable Tail	Class H	18,868'	19,868'	15	2.18	10	116	9.55

1. Final cement volumes will be determined by caliper.

2. Surface casing shall have at least one centralizer installed on each of the bottom three joints starting with the shoe joint.

4. CASING PROGRAM

Purpose	From	To	Hole Size	Csg Size	Weight	Grade	Thread	Condition
Surface	0'	450'	17-1/2"	13-3/8"	54.5 #	J-55	STC	New
Intermediate	0'	9,000'	12-1/4"	9-5/8"	43.5#	L-80IC	LTC	New
Production	0'	19,868'	8-1/2"	5-1/2"	20#	P-110	TXP	New

SF Calculations based on the following "Worst Case" casing design:

Surface Casing: 450'

Intermediate Casing: 9,000' MD

Production Casing: 19,868' MD/9,565' TVD (9,995.65' VS @ 90 deg inc)

Casing String	Min SF Burst	Min SF Collapse	Min SF Tension	Min SF Tri-Axial
Surface	1.42	5.22	2.76	1.76
Intermediate	1.38	2.19	1.7	1.67
Production	1.1	1.64	2.19	1.32

Min SF is the smallest of a group of safety factors that include the following considerations:

	Surf	Int	Prod
Burst Design			
Pressure Test- Surface, Int, Prod Csg P external: Water P internal: Test psi + next section heaviest mud in csg	X	X	X
Displace to Gas- Surf Csg P external: Water P internal: Dry Gas from Next Csg Point	X		
Frac at Shoe, Gas to Surf- Int Csg P external: Water P internal: Dry Gas, 15 ppg Frac Gradient		X	
Stimulation (Frac) Pressures- Prod Csg P external: Water P internal: Max inj pressure w/ heaviest injected fluid			X
Tubing leak- Prod Csg (packer at KOP) P external: Water P internal: Leak just below surf, 8.7 ppg packer fluid			X
Collapse Design			
Full Evacuation P external: Water gradient in cement, mud above TOC P internal: none	X	X	X
Cementing- Surf, Int, Prod Csg P external: Wet cement P internal: water	X	X	X
Tension Design			

1. FORMATION TOPS

The estimated tops of important geologic markers are as follows:

FORMATION	SUB-SEA TVD	KBTVD	MD
Castille	1917	1103	
Lamar	435	2595	
Bell	398	2622	
Cherry	-414	3434	
Brushy	-1638	4658	
Bone Spring Lime	-3140	6160	
Avalon	-3547	6567	
First Bone Spring Sand	-4272	7292	
SBSG Sand	-5004	8024	
Third Bone Spring Carbonate	-6108	9128	
Third Bone Spring Sand	-6443	9403	
Wolfcamp A		9463	
Lateral TVD Wolfcamp A	-6545	9565	19868

2. ESTIMATED DEPTH OF WATER, OIL, GAS & OTHER MINERAL BEARING FORMATIONS

The estimated depths at which the top and bottom of the anticipated water, oil, gas, or other mineral bearing formations are expected to be encountered are as follows:

Substance	Formation	Depth
Deepest Expected Base of Fresh Water		450
Water	Castille	1103
Water	Cherry Canyon	3434
Oil/Gas	Brushy Canyon	4658
Oil/Gas	First Bone Spring Sand	7292
Oil/Gas	SBSG Sand	8024
Oil/Gas	Third Bone Spring Carbonate	9128
Oil/Gas	Third Bone Spring Sand	9403
Oil/Gas	Wolfcamp A	9463

All shows of fresh water and minerals will be reported and protected.

3. BOP EQUIPMENT

Will have a minimum of a 5000 psi rig stack (see proposed schematic). Stack will be tested as specified in the attached testing requirements. Batch drilling of the surface, intermediate, and production will take place. A full BOP test will be performed unless approval from BLM is received otherwise. Flex choke hose will be used for all wells on the pad (see attached specs) BOP test will be conducted by a third party.

Chevron requests a variance to use a FMC UHS Multibowl wellhead, which will be run through the rig floor on surface casing. BOPE will be nipped up and tested after cementing surface casing. Subsequent tests will be performed as needed, not to exceed 30 days. The field report from FMC and BOP test information will be provided in a subsequent report at the end of the well. Please see the attached wellhead schematic. An installation manual has been placed on file with the BLM office and remains unchanged from previous submittal.

BOP Schem



Wellhead S



Choke Hos

