

RECEIVED

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources Department

MAR 29 2019 Submit Original
to Appropriate
District Office

Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

DISTRICT II-ARTESIA O.C.D.

GAS CAPTURE PLAN

Date: 08/30/18

☒ Original

Operator & OGRID No.: BOPCO, LP [260737]

☐ Amended - Reason for Amendment:

This Gas Capture Plan outlines actions to be taken by the Operator to reduce well/production facility flaring/venting for new completion (new drill, recomple to new zone, re-frac) activity.

Note: Form C-129 must be submitted and approved prior to exceeding 60 days allowed by Rule (Subsection A of 19.15.18.12 NMAC).

Well(s)/Production Facility – Name of facility: Poker Lake Unit 25 BD East CTB

The well(s) that will be located at the production facility are shown in the table below.

| Well Name | API | Well Location (ULSTR) | Footages | Expected MCF/D | Flared or Vented | Comments |
|----------------------------|-----|-----------------------|-----------------------|----------------|------------------|----------|
| Poker Lake Unit 25 BD 701H | | E-25-25S-30E | 2595' FNL & 772' FWL | 2900 | Flared/Sold | |
| Poker Lake Unit 25 BD 901H | | E-25-25S-30E | 2560' FNL & 522' FWL | 3000 | Flared/Sold | |
| Poker Lake Unit 25 BD 102H | | E-25-25S-30E | 2560' FNL & 772' FWL | 2800 | Flared/Sold | |
| Poker Lake Unit 25 BD 121H | | E-25-25S-30E | 2525' FNL & 522' FWL | 4800 | Flared/Sold | |
| Poker Lake Unit 25 BD 122H | | E-25-25S-30E | 2525' FNL & 772' FWL | 4800 | Flared/Sold | |
| Poker Lake Unit 25 BD 125H | | G-25-25S-30E | 2310' FNL & 1980' FEL | 4300 | Flared/Sold | |
| Poker Lake Unit 25 BD 705H | | G-25-25S-30E | 2310' FNL & 2040' FEL | 2600 | Flared/Sold | |
| Poker Lake Unit 25 BD 905H | | G-25-25S-30E | 2310' FNL & 2010' FEL | 2700 | Flared/Sold | |
| Poker Lake Unit 25 BD 106H | | G-25-25S-30E | 2310' FNL & 1920' FEL | 2600 | Flared/Sold | |
| Poker Lake Unit 25 BD 126H | | G-25-25S-30E | 2310' FNL & 1950' FEL | 4300 | Flared/Sold | |
| Poker Lake Unit 25 BD 104H | | F-25-25S-30E | 1650' FNL & 2085' FWL | 2800 | Flared/Sold | |
| Poker Lake Unit 25 BD 123H | | F-25-25S-30E | 1615' FNL & 1835' FWL | 4800 | Flared/Sold | |
| Poker Lake Unit 25 BD 124H | | F-25-25S-30E | 1615' FNL & 2085' FWL | 3300 | Flared/Sold | |
| Poker Lake Unit 25 BD 703H | | F-25-25S-30E | 1685' FNL & 2085' FWL | 2900 | Flared/Sold | |
| Poker Lake Unit 25 BD 903H | | F-25-25S-30E | 1650' FNL & 1835' FWL | 3000 | Flared/Sold | |
| Poker Lake Unit 25 BD 707H | | H-25-25S-30E | 2310' FNL & 720' FEL | 2600 | Flared/Sold | |
| Poker Lake Unit 25 BD 907H | | H-25-25S-30E | 2310' FNL & 690' FEL | 2700 | Flared/Sold | |
| Poker Lake Unit 25 BD 108H | | H-25-25S-30E | 2310' FNL & 600' FEL | 2600 | Flared/Sold | |
| Poker Lake Unit 25 BD 127H | | H-25-25S-30E | 2310' FNL & 660' FEL | 4300 | Flared/Sold | |
| Poker Lake Unit 25 BD 128H | | H-25-25S-30E | 2310' FNL & 630' FEL | 4300 | Flared/Sold | |

Gathering System and Pipeline Notification

Well(s) will be connected to a production facility after flowback operations are complete, if gas transporter system is in place. The gas produced from production facility is dedicated to Lucid and will be connected to Lucid low/high pressure gathering system located in Eddy County, New Mexico. It will require 847.85' of pipeline to connect the facility to low/high pressure gathering system. BOPCO provides (periodically) to Lucid a drilling, completion and estimated first production date for wells that are scheduled to be drilled in the foreseeable future. In addition, BOPCO and Lucid have periodic conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed at Red Hills Plant, Sec. 13, T24S, R33E or Roadrunner, Sec. 32, T32S, R28E, Eddy County. The actual flow of the gas will be based on compression operating parameters and gathering system pressures.

Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on Lucid system at that time. Based on current information, it is BOPCO's belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation – On lease
 - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas – On lease
 - Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal – On lease
 - Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines