

RECEIVED

Form 3160-3  
(June 2015)

MAY 01 2019

FORM APPROVED  
OMB No. 1004-0137  
Expires: January 31, 2018

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
DISTRICT II-ARTESIA O.C.D.

APPLICATION FOR PERMIT TO DRILL OR REENTER

1a. Type of work: <input checked="" type="checkbox"/> DRILL <input type="checkbox"/> REENTER		5. Lease Serial No. NMNM012833
1b. Type of Well: <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other		6. If Indian, Allottee or Tribe Name
1c. Type of Completion: <input type="checkbox"/> Hydraulic Fracturing <input checked="" type="checkbox"/> Single Zone <input type="checkbox"/> Multiple Zone		7. If Unit or CA Agreement, Name and No.
2. Name of Operator PERCUSSION PETROLEUM OPERATING LLC		8. Lease Name and Well No. OSAGE BOYD 15 FEDERAL COM 10H 317253
3a. Address 919 Milam Street, Suite 2475 Houston TX 77002		9. API Well No. 30-015-45955
3b. Phone No. (include area code) (713)689-2337		10. Field and Pool, or Exploratory N. SEVEN RIVERS; GLORIETA -YESO
4. Location of Well (Report location clearly and in accordance with any State requirements. *) At surface NWNW / 649 FNL / 701 FWL / LAT 32.652008 / LONG -104.478904 At proposed prod. zone NWNW / 20 FNL / 525 FWL / LAT 32.668158 / LONG -104.479507		11. Sec., T. R. M. or Blk. and Survey or Area SEC 22 / T19S / R25E / NMP
14. Distance in miles and direction from nearest town or post office* 14 miles		12. County or Parish EDDY
13. State NM		
15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any) 649 feet	16. No of acres in lease 240	17. Spacing Unit dedicated to this well 160
18. Distance from proposed location* to nearest well, drilling, completed, applied for, on this lease, ft. 20 feet	19. Proposed Depth 2507 feet / 8003 feet	20. BLM/BIA Bond No. in file FED: NMB001424
21. Elevations (Show whether DF, KDB, RT, GL, etc.) 3475 feet	22. Approximate date work will start* 02/01/2019	23. Estimated duration 30 days
24. Attachments		

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, and the Hydraulic Fracturing rule per 43 CFR 3162.3-3 (as applicable)

- |  |   |
|--|---|
| 1. Well plat certified by a registered surveyor.   | 4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above). |
| 2. A Drilling Plan.  | 5. Operator certification.  |
| 3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office). | 6. Such other site specific information and/or plans as may be requested by the BLM.            |

25. Signature (Electronic Submission)	Name (Printed/Typed) Brian Wood / Ph: (505)466-8120	Date 11/05/2018
Title President		
Approved by (Signature) (Electronic Submission)	Name (Printed/Typed) Cody Layton / Ph: (575)234-5959	Date 03/22/2019
Title Assistant Field Manager Lands & Minerals		

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.  
Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

APPROVED WITH CONDITIONS  
Approval Date: 03/22/2019

RUP 5-6-19

## INSTRUCTIONS

**GENERAL:** This form is designed for submitting proposals to perform certain well operations, as indicated on Federal and Indian lands and leases for action by appropriate Federal agencies, pursuant to applicable Federal laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from local Federal offices.

**ITEM 1:** If the proposal is to redrill to the same reservoir at a different subsurface location or to a new reservoir, use this form with appropriate notations. Consult applicable Federal regulations concerning subsequent work proposals or reports on the well.

**ITEM 4:** Locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local Federal offices for specific instructions.

**ITEM 14:** Needed only when location of well cannot readily be found by road from the land or lease description. A plat, or plats, separate or on the reverse side, showing the roads to, and the surveyed location of, the well, and any other required information, should be furnished when required by Federal agency offices.

**ITEMS 15 AND 18:** If well is to be, or has been directionally drilled, give distances for subsurface location of hole in any present or objective productive zone.

**ITEM 22:** Consult applicable Federal regulations, or appropriate officials, concerning approval of the proposal before operations are started.

**ITEM 24:** If the proposal will involve hydraulic fracturing operations, you must comply with 43 CFR 3162.3-3, including providing information about the protection of usable water. Operators should provide the best available information about all formations containing water and their depths. This information could include data and interpretation of resistivity logs run on nearby wells. Information may also be obtained from state or tribal regulatory agencies and from local BLM offices.

## NOTICES

The Privacy Act of 1974 and regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

**AUTHORITY:** 30 U.S.C. 181 et seq., 25 U.S.C. 396; 43 CFR 3160

**PRINCIPAL PURPOSES:** The information will be used to: (1) process and evaluate your application for a permit to drill a new oil, gas, or service well or to reenter a plugged and abandoned well; and (2) document, for administrative use, information for the management, disposal and use of National Resource Lands and resources including (a) analyzing your proposal to discover and extract the Federal or Indian resources encountered; (b) reviewing procedures and equipment and the projected impact on the land involved; and (c) evaluating the effects of the proposed operation on the surface and subsurface water and other environmental impacts.

**ROUTINE USE:** Information from the record and/or the record will be transferred to appropriate Federal, State, and local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecution, in connection with congressional inquiries and for regulatory responsibilities.

**EFFECT OF NOT PROVIDING INFORMATION:** Filing of this application and disclosure of the information is mandatory only if you elect to initiate a drilling or reentry operation on an oil and gas lease.

The Paperwork Reduction Act of 1995 requires us to inform you that:

The BLM connects this information to a new evaluation of the technical, safety, and environmental factors involved with drilling for oil and/or gas on Federal and Indian oil and gas leases. This information will be used to analyze and approve applications. Response to this request is mandatory only if the operator elects to initiate drilling or reentry operations on an oil and gas lease. The BLM would like you to know that you do not have to respond to this or any other Federal agency-sponsored information collection unless it displays a currently valid OMB control number.

**BURDEN HOURS STATEMENT:** Public reporting burden for this form is estimated to average 8 hours per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management (1004-0137), Bureau Information Connection Clearance Officer (WO-630), 1849 C Street, N.W., Mail Stop 401 LS, Washington, D.C. 20240.

## **Additional Operator Remarks**

### **Location of Well**

1. SHL: NWNW / 649 FNL / 701 FWL / TWSP: 19S / RANGE: 25E / SECTION: 22 / LAT: 32.652008 / LONG: -104.478904 ( TVD: 0 feet, MD: 0 feet )  
PPP: NWNW / 1325 FNL / 525 FWL / TWSP: 19S / RANGE: 25E / SECTION: 15 / LAT: 32.664597 / LONG: -104.479503 ( TVD: 2532 feet, MD: 6707 feet )  
BHL: NWNW / 20 FNL / 525 FWL / TWSP: 19S / RANGE: 25E / SECTION: 15 / LAT: 32.668158 / LONG: -104.479507 ( TVD: 2507 feet, MD: 8003 feet )

## **BLM Point of Contact**

Name: Tenille Ortiz

Title: Legal Instruments Examiner

Phone: 5752342224

Email: tortiz@blm.gov

## **Review and Appeal Rights**

A person contesting a decision shall request a State Director review. This request must be filed within 20 working days of receipt of the Notice with the appropriate State Director (see 43 CFR 3165.3). The State Director review decision may be appealed to the Interior Board of Land Appeals, 801 North Quincy Street, Suite 300, Arlington, VA 22203 (see 43 CFR 3165.4). Contact the above listed Bureau of Land Management office for further information.

**PECOS DISTRICT  
DRILLING OPERATIONS  
CONDITIONS OF APPROVAL**

<b>OPERATOR'S NAME:</b>	Percussion Petroleum Operating LLC
<b>LEASE NO.:</b>	NMNM012833
<b>WELL NAME &amp; NO.:</b>	Osage Boyd 15 Federal Com 10H
<b>SURFACE HOLE FOOTAGE:</b>	649' FNL & 701' FWL
<b>BOTTOM HOLE FOOTAGE:</b>	20' FNL & 525' FWL
<b>LOCATION:</b>	Section 22, T 19S, R 25E, NMPM
<b>COUNTY:</b>	Eddy County, New Mexico

H2S	<input type="radio"/> Yes	<input checked="" type="radio"/> No	
Potash	<input checked="" type="radio"/> None	<input type="radio"/> Secretary	<input type="radio"/> R-111-P
Cave/Karst Potential	<input type="radio"/> Low	<input checked="" type="radio"/> Medium	<input type="radio"/> High
Variance	<input checked="" type="radio"/> None	<input type="radio"/> Flex Hose	<input type="radio"/> Other
Wellhead	<input checked="" type="radio"/> Conventional	<input type="radio"/> Multibowl	<input type="radio"/> Both
Other	<input type="checkbox"/> 4 String Area	<input type="checkbox"/> Capitan Reef	<input type="checkbox"/> WIPP
Other	<input type="checkbox"/> Fluid Filled	<input type="checkbox"/> Cement Squeeze	<input type="checkbox"/> Pilot Hole
Special Requirements	<input type="checkbox"/> Water Disposal	<input checked="" type="checkbox"/> COM	<input type="checkbox"/> Unit

**A. HYDROGEN SULFIDE**

1. Hydrogen Sulfide (H2S) monitors shall be installed prior to drilling out the surface shoe. If H2S is detected in concentrations greater than 100 ppm, the Hydrogen Sulfide area shall meet Onshore Order 6 requirements, which includes equipment and personnel/public protection items. If Hydrogen Sulfide is encountered, provide measured values and formations to the BLM.

**B. CASING**

1. The 9-5/8" surface casing shall be set at approximately 1279' and cemented to surface.
  - a. **If cement does not circulate to surface**, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with surface log readout will be used or a cement bond log shall be run to verify the top of the cement. Temperature survey will be run a minimum of **6 hours** after pumping cement, ideally between 8-10 hours after completing the cement job.
  - b. WOC time for a primary cement job will be a minimum of **8 hours** or **500 psi** compressive strength, whichever is greater. This is to include the lead cement.
  - c. If cement falls back, remedial cementing will be done prior to drilling out that string.

- d. WOC time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 psi compressive strength, whichever is greater.
2. The tapered 7" & 5-1/2" production casing shall be cemented to surface:
  - a. **If cement does not circulate to surface**, see B.1.a, c & d
3. Operator has proposed a contingency 13-3/8" casing to seal off lost circulation above 400'. This casing, if used, shall be cemented to surface.
  - a. **If cement does not circulate to surface**, see B.1.a, c & d

### **C. PRESSURE CONTROL**

1. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be **3000 (3M) psi**.

### **D. SPECIAL REQUIREMENTS**

1. The operator will submit a Communitization Agreement to the Carlsbad Field Office, 620 E Greene St. Carlsbad, New Mexico 88220, at least 90 days before the anticipated date of first production from a well subject to a spacing order issued by the New Mexico Oil Conservation Division. The Communitization Agreement will include the signatures of all working interest owners in all Federal and Indian leases subject to the Communitization Agreement (i.e., operating rights owners and lessees of record), or certification that the operator has obtained the written signatures of all such owners and will make those signatures available to the BLM immediately upon request.
2. The well sign on location shall include the surface and bottom hole lease numbers. When the Communitization Agreement number is known, it shall also be on the sign.

**DR 3/12/2019**

## GENERAL REQUIREMENTS

1. The BLM is to be notified in advance for a representative to witness:
  - a. Spudding well (minimum of 24 hours)
  - b. Setting and/or Cementing of all casing strings (minimum of 4 hours)
  - c. BOPE tests (minimum of 4 hours)
    - Chaves and Roosevelt Counties  
Call the Roswell Field Office, 2909 West Second St., Roswell NM 88201.  
During office hours call (575) 627-0272.  
After office hours call (575)
    - Eddy County  
Call the Carlsbad Field Office, 620 East Greene St., Carlsbad, NM 88220,  
(575) 361-2822
    - Lea County  
Call the Hobbs Field Station, 414 West Taylor, Hobbs NM 88240, (575)  
393-3612
2. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval.
  - a. In the event the operator has proposed to drill multiple wells utilizing a skid/walking rig. Operator shall secure the wellbore on the current well, after installing and testing the wellhead, by installing a blind flange of like pressure rating to the wellhead and a pressure gauge that can be monitored while drilling is performed on the other well(s).
  - b. When the operator proposes to set surface casing with Spudder Rig
    - Notify the BLM when moving in and removing the Spudder Rig.
    - Notify the BLM when moving in the 2<sup>nd</sup> Rig. Rig to be moved in within 90 days of notification that Spudder Rig has left the location.
    - BOP/BOPE test to be conducted per Onshore Oil and Gas Order No. 2 as soon as 2nd Rig is rigged up on well.
3. Floor controls are required for 3M or Greater systems. These controls will be on the rig floor, unobstructed, readily accessible to the driller and will be operational at all times during drilling and/or completion activities. Rig floor is defined as the area immediately around the rotary table; the area immediately above the substructure on which the draw works are located, this does not include the dog house or stairway area.

4. The record of the drilling rate along with the GR/N well log (one log per well pad is acceptable) run from TD to surface (horizontal well – vertical portion of hole) shall be submitted to the BLM office as well as all other logs run on the borehole 30 days from completion. If available, a digital copy of the logs is to be submitted in addition to the paper copies. The Rustler top and top and bottom of Salt are to be recorded on the Completion Report.

#### A. CASING

1. Changes to the approved APD casing program need prior approval if the items substituted are of lesser grade or different casing size or are Non-API. The Operator can exchange the components of the proposal with that of superior strength (i.e. changing from J-55 to N-80, or from 36# to 40#). Changes to the approved cement program need prior approval if the altered cement plan has less volume or strength or if the changes are substantial (i.e. Multistage tool, ECP, etc.). The initial wellhead installed on the well will remain on the well with spools used as needed.
2. Wait on cement (WOC) for Potash Areas: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi for all cement blends, 2) until cement has been in place at least 24 hours. WOC time will be recorded in the driller's log. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
3. Wait on cement (WOC) for Water Basin: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi at the shoe, 2) until cement has been in place at least 8 hours. WOC time will be recorded in the driller's log. See individual casing strings for details regarding lead cement slurry requirements. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
4. Provide compressive strengths including hours to reach required 500 pounds compressive strength prior to cementing each casing string. Have well specific cement details onsite prior to pumping the cement for each casing string.
5. No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.
6. On that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Formation at the shoe shall be tested to a minimum of the mud weight equivalent anticipated to control the formation pressure to the next casing depth or at total depth of the well. This test shall be performed before drilling more than 20 feet of new hole.
7. If hardband drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.

8. Whenever a casing string is cemented in the R-111-P potash area, the NMOCD requirements shall be followed.

## **B. PRESSURE CONTROL**

1. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in Onshore Oil and Gas Order No. 2 and API RP 53 Sec. 17.
2. If a variance is approved for a flexible hose to be installed from the BOP to the choke manifold, the following requirements apply: The flex line must meet the requirements of API 16C. Check condition of flexible line from BOP to choke manifold, replace if exterior is damaged or if line fails test. Line to be as straight as possible with no hard bends and is to be anchored according to Manufacturer's requirements. The flexible hose can be exchanged with a hose of equal size and equal or greater pressure rating. Anchor requirements, specification sheet and hydrostatic pressure test certification matching the hose in service, to be onsite for review. These documents shall be posted in the company man's trailer and on the rig floor.
3. 5M or higher system requires an HCR valve, remote kill line and annular to match. The remote kill line is to be installed prior to testing the system and tested to stack pressure.
4. If the operator has proposed a multi-bowl wellhead assembly in the APD. The following requirements must be met:
  - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
  - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
  - c. Manufacturer representative shall install the test plug for the initial BOP test.
  - d. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
  - e. Whenever any seal subject to test pressure is broken, all the tests in OOGO2.III.A.2.i must be followed.
5. The appropriate BLM office shall be notified a minimum of 4 hours in advance for a representative to witness the tests.
  - a. In a water basin, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. The casing cut-off and BOP installation can be initiated four hours after installing the slips, which will be approximately six hours after bumping the plug. For those casing strings not using slips, the minimum wait time before cut-off is eight hours after bumping the plug. BOP/BOPE testing can begin after cut-off or once cement reaches 500 psi compressive strength (including lead when specified),

whichever is greater. However, if the float does not hold, cut-off cannot be initiated until cement reaches 500 psi compressive strength (including lead when specified).

- b. In potash areas, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. For all casing strings, casing cut-off and BOP installation can be initiated at twelve hours after bumping the plug. However, **no tests** shall commence until the cement has had a minimum of 24 hours setup time, except the casing pressure test can be initiated immediately after bumping the plug (only applies to single stage cement jobs).
- c. The tests shall be done by an independent service company utilizing a test plug. The results of the test shall be reported to the appropriate BLM office.
- d. The test shall be run on a 5000 psi chart for a 2-3M BOP/BOP, on a 10000 psi chart for a 5M BOP/BOPE and on a 15000 psi chart for a 10M BOP/BOPE. If a linear chart is used, it shall be a one hour chart. A circular chart shall have a maximum 2 hour clock. If a twelve hour or twenty-four hour chart is used, tester shall make a notation that it is run with a two hour clock.
- e. All tests are required to be recorded on a calibrated test chart. A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.
- f. The BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes. This test shall be performed prior to the test at full stack pressure.
- g. BOP/BOPE must be tested by an independent service company within 500 feet of the top of the Wolfcamp formation if the time between the setting of the intermediate casing and reaching this depth exceeds 20 days. This test does not exclude the test prior to drilling out the casing shoe as per Onshore Order No. 2.

### **C. DRILLING MUD**

1. Mud system monitoring equipment, with derrick floor indicators and visual and audio alarms, shall be operating before drilling into the Wolfcamp formation, and shall be used until production casing is run and cemented.

### **D. WASTE MATERIAL AND FLUIDS**

2. All waste (i.e. drilling fluids, trash, salts, chemicals, sewage, gray water, etc.) created as a result of drilling operations and completion operations shall be safely contained and disposed of properly at a waste disposal facility. No waste material or fluid shall be disposed of on the well location or surrounding area.
3. Porto-johns and trash containers will be on-location during fracturing operations or any other crew-intensive operations.



U.S. Department of the Interior  
BUREAU OF LAND MANAGEMENT

# Operator Certification Data Report

04/29/2019

## Operator Certification

*I hereby certify that I, or someone under my direct supervision, have inspected the drill site and access route proposed herein; that I am familiar with the conditions which currently exist; that I have full knowledge of state and Federal laws applicable to this operation; that the statements made in this APD package are, to the best of my knowledge, true and correct; and that the work associated with the operations proposed herein will be performed in conformity with this APD package and the terms and conditions under which it is approved. I also certify that I, or the company I represent, am responsible for the operations conducted under this application. These statements are subject to the provisions of 18 U.S.C. 1001 for the filing of false statements.*

**NAME:** Brian Wood

**Signed on:** 11/05/2018

**Title:** President

**Street Address:** 37 Verano Loop

**City:** Santa Fe

**State:** NM

**Zip:** 87508

**Phone:** (505)466-8120

**Email address:** afmss@permitswest.com

## Field Representative

**Representative Name:**

**Street Address:**

**City:**

**State:**

**Zip:**

**Phone:**

**Email address:**



U.S. Department of the Interior  
BUREAU OF LAND MANAGEMENT

# Application Data Report

04/29/2019

APD ID: 10400035989

Submission Date: 11/05/2018

Highlighted data  
reflects the most  
recent changes

Operator Name: PERCUSSION PETROLEUM OPERATING LLC

Well Name: OSAGE BOYD 15 FEDERAL COM

Well Number: 10H

[Show Final Text](#)

Well Type: OIL WELL

Well Work Type: Drill

## Section 1 - General

APD ID: 10400035989

Tie to previous NOS?

Submission Date: 11/05/2018

BLM Office: CARLSBAD

User: Brian Wood

Title: President

Federal/Indian APD: FED

Is the first lease penetrated for production Federal or Indian? FED

Lease number: NMNM012833

Lease Acres: 240

Surface access agreement in place?

Allotted?

Reservation:

Agreement in place? NO

Federal or Indian agreement:

Agreement number:

Agreement name:

Keep application confidential? NO

Permitting Agent? YES

APD Operator: PERCUSSION PETROLEUM OPERATING LLC

Operator letter of designation:

## Operator Info

Operator Organization Name: PERCUSSION PETROLEUM OPERATING LLC

Operator Address: 919 Milam Street, Suite 2475

Zip: 77002

Operator PO Box:

Operator City: Houston

State: TX

Operator Phone: (713)589-2337

Operator Internet Address:

## Section 2 - Well Information

Well in Master Development Plan? NO

Master Development Plan name:

Well in Master SUPO? NO

Master SUPO name:

Well in Master Drilling Plan? NO

Master Drilling Plan name:

Well Name: OSAGE BOYD 15 FEDERAL COM

Well Number: 10H

Well API Number:

Field/Pool or Exploratory? Field and Pool

Field Name: N. SEVEN RIVERS; Pool Name:  
GLORIETA -YESO

Is the proposed well in an area containing other mineral resources? USEABLE WATER,NATURAL GAS,OIL

**Operator Name:** PERCUSSION PETROLEUM OPERATING LLC

**Well Name:** OSAGE BOYD 15 FEDERAL COM

**Well Number:** 10H

**Describe other minerals:**

**Is the proposed well in a Helium production area?** N    **Use Existing Well Pad?** NO    **New surface disturbance?**

**Type of Well Pad:** MULTIPLE WELL

**Multiple Well Pad Name:**  
OSAGE BOYD 15 FEDERAL  
COM

**Number:** 9H

**Well Class:** HORIZONTAL

**Number of Legs:** 1

**Well Work Type:** Drill

**Well Type:** OIL WELL

**Describe Well Type:**

**Well sub-Type:** INFILL

**Describe sub-type:**

**Distance to town:** 14 Miles

**Distance to nearest well:** 20 FT

**Distance to lease line:** 649 FT

**Reservoir well spacing assigned acres Measurement:** 160 Acres

**Well plat:** Osage\_10H\_Plat\_GasCap\_Plan\_20181105105815.pdf

**Well work start Date:** 02/01/2019

**Duration:** 30 DAYS

### Section 3 - Well Location Table

**Survey Type:** RECTANGULAR

**Describe Survey Type:**

**Datum:** NAD83

**Vertical Datum:** NAVD88

**Survey number:** 7977

	NS-Foot	NS Indicator	EW-Foot	EW Indicator	Twsp	Range	Section	Aliquot/Lot/Tract	Latitude	Longitude	County	State	Meridian	Lease Type	Lease Number	Elevation	MD	TVD
SHL Leg #1	649	FNL	701	FWL	19S	25E	22	Aliquot NWN W	32.65200 8	- 104.4789 04	EDD Y	NEW MEXI CO	NEW MEXI CO	F	FEE	347 5	0	0
KOP Leg #1	467	FNL	569	FWL	19S	25E	22	Aliquot NWN W	32.65250 63	- 104.4793 329	EDD Y	NEW MEXI CO	NEW MEXI CO	F	FEE	144 3	204 8	203 2
PPP Leg #1	132 5	FNL	525	FWL	19S	25E	15	Aliquot NWN W	32.66459 7	- 104.4795 03	EDD Y	NEW MEXI CO	NEW MEXI CO	F	NMNM 012833	943	670 7	253 2

Operator Name: PERCUSSION PETROLEUM OPERATING LLC

Well Name: OSAGE BOYD 15 FEDERAL COM

Well Number: 10H

	NS-Foot	NS Indicator	EW-Foot	EW Indicator	Twsp	Range	Section	Aliquot/Lot/Tract	Latitude	Longitude	County	State	Meridian	Lease Type	Lease Number	Elevation	MD	TVD
EXIT Leg #1	20	FNL	525	FWL	19S	25E	15	Aliquot NWN W	32.66815 8	- 104.4795 07	EDD Y	NEW MEXI CO	NEW MEXI CO	F	NMNM 012833	968	800 3	250 7
BHL Leg #1	20	FNL	525	FWL	19S	25E	15	Aliquot NWN W	32.66815 8	- 104.4795 07	EDD Y	NEW MEXI CO	NEW MEXI CO	F	NMNM 012833	968	800 3	250 7



APD ID: 10400035989

Submission Date: 11/05/2018

Highlighted data  
reflects the most  
recent changes

Operator Name: PERCUSSION PETROLEUM OPERATING LLC

Well Name: OSAGE BOYD 15 FEDERAL COM

Well Number: 10H

[Show Final Text](#)

Well Type: OIL WELL

Well Work Type: Drill

**Section 1 - Geologic Formations**

Formation ID	Formation Name	Elevation	True Vertical Depth	Measured Depth	Lithologies	Mineral Resources	Producing Formation
1	QUATERNARY	3475	0	0	OTHER : Caliche	USEABLE WATER	No
2	GRAYBURG	2870	605	605		NATURAL GAS,OIL	No
3	SAN ANDRES	2685	790	792	DOLOMITE	NATURAL GAS,OIL	No
4	GLORIETA	1125	2350	2357	DOLOMITE	NATURAL GAS,OIL	No
5	YESO	970	2505	2700	DOLOMITE	NATURAL GAS,OIL	Yes

**Section 2 - Blowout Prevention**

Pressure Rating (PSI): 3M

Rating Depth: 5000

**Equipment:** A 3000-psi 5000' rated BOP stack consisting of annular preventer and double (blind and pipe) ram will be used below surface casing to TD. See attached BOP and choke manifold diagrams.

**Requesting Variance?** NO

**Variance request:**

**Testing Procedure:** Pressure tests will be conducted before drilling out from under all casing strings. Third party test crews will conduct all tests. All tests will be recorded for 10-minutes on low pressure (500 psi) and 10-minutes on high pressure (3000-psi). After BOP testing is complete, test casing (without test plug) to 2000-psi for 30 minutes. All tests will be charted on a plot. BOPs will be function tested every day.

**Choke Diagram Attachment:**

Osage\_10H\_Choke\_20181105110439.pdf

**BOP Diagram Attachment:**

Osage\_10H\_BOP\_20181105110446.pdf

**Operator Name:** PERCUSSION PETROLEUM OPERATING LLC

**Well Name:** OSAGE BOYD 15 FEDERAL COM

**Well Number:** 10H

**Section 3 - Casing**

Casing ID	String Type	Hole Size	Csg Size	Condition	Standard	Tapered String	Top Set MD	Bottom Set MD	Top Set TVD	Bottom Set TVD	Top Set MSL	Bottom Set MSL	Calculated casing length MD	Grade	Weight	Joint Type	Collapse SF	Burst SF	Joint SF Type	Joint SF	Body SF Type	Body SF
1	SURFACE	12.25	9.625	NEW	API	N	0	1279	0	1271	3475		1279	J-55	36	LTC	1.125	1.125	DRY	1.8	DRY	1.8
2	PRODUCTI ON	8.75	7.0	NEW	API	Y	0	2275	0	2245	3475		2275	L-80	32	BUTT	1.125	1.125	DRY	1.8	DRY	1.8
3	PRODUCTI ON	8.75	5.5	NEW	API	Y	2275	8003	2245	2507			5728	L-80	17	BUTT	1.125	1.125	DRY	1.8	DRY	1.8

**Casing Attachments**

**Casing ID:** 1      **String Type:** SURFACE

**Inspection Document:**

**Spec Document:**

**Tapered String Spec:**

**Casing Design Assumptions and Worksheet(s):**

Osage\_10H\_Casing\_Design\_Assumptions\_20181105110513.pdf

**Operator Name:** PERCUSSION PETROLEUM OPERATING LLC

**Well Name:** OSAGE BOYD 15 FEDERAL COM

**Well Number:** 10H

**Casing Attachments**

**Casing ID:** 2                    **String Type:** PRODUCTION

**Inspection Document:**

**Spec Document:**

**Tapered String Spec:**

Osage\_10H\_Casing\_Design\_Assumptions\_20181105110540.pdf

**Casing Design Assumptions and Worksheet(s):**

Osage\_10H\_Casing\_Design\_Assumptions\_20181105110636.pdf

**Casing ID:** 3                    **String Type:** PRODUCTION

**Inspection Document:**

**Spec Document:**

**Tapered String Spec:**

Osage\_10H\_Casing\_Design\_Assumptions\_20181105110619.pdf

**Casing Design Assumptions and Worksheet(s):**

Osage\_10H\_Casing\_Design\_Assumptions\_20181105110646.pdf

**Section 4 - Cement**

String Type	Lead/Tail	Stage Tool Depth	Top MD	Bottom MD	Quantity(sx)	Yield	Density	Cu Ft	Excess%	Cement type	Additives
SURFACE	Lead		0	1279	637	1.32	14.8	840	100	Class C	2% CaCl + ¼ pound per sack celloflake

PRODUCTION	Lead		0	2275	495	1.97	12.6	975	50	65/65/6 Class C	6% gel + 5% salt + ¼ pound per sack celloflake + 0.2% C41-P
PRODUCTION	Tail		0	2275	1332	1.32	14.8	1758	50	Class C	2% CaCl + ¼ pound per sack celloflake
PRODUCTION	Lead		2275	8003	495	1.97	12.6	975	50	65/65/6 Class C	6% gel + 5% salt + ¼ pound per sack

**Operator Name:** PERCUSSION PETROLEUM OPERATING LLC

**Well Name:** OSAGE BOYD 15 FEDERAL COM

**Well Number:** 10H

String Type	Lead/Tail	Stage Tool Depth	Top MD	Bottom MD	Quantity(sx)	Yield	Density	Cu Ft	Excess%	Cement type	Additives
											celloflake + 0.2% C41-P
PRODUCTION	Tail		2275	8003	1332	1.32	14.8	1758	50	Class C	2% CaCl + ¼ pound per sack celloflake

**Section 5 - Circulating Medium**

**Mud System Type:** Closed

**Will an air or gas system be Used?** NO

**Description of the equipment for the circulating system in accordance with Onshore Order #2:**

**Diagram of the equipment for the circulating system in accordance with Onshore Order #2:**

**Describe what will be on location to control well or mitigate other conditions:** All necessary mud products (LCM) will be on site to handle any abnormal hole condition that may be encountered while drilling this well.

**Describe the mud monitoring system utilized:** An electronic/mechanical mud monitor with a minimum pit volume totalizer, stroke counter, and flow sensor will be used.

**Circulating Medium Table**

Top Depth	Bottom Depth	Mud Type	Min Weight (lbs/gal)	Max Weight (lbs/gal)	Density (lbs/cu ft)	Gel Strength (lbs/100 sqft)	PH	Viscosity (CP)	Salinity (ppm)	Filtration (cc)	Additional Characteristics
0	1279	OTHER : Fresh water/gel	8.4	9.2							
1279	2049	OTHER : Fresh water/cut brine	8.3	9.2							
2049	8003	OTHER : Cut brine	8.6	9.2							

**Operator Name:** PERCUSSION PETROLEUM OPERATING LLC

**Well Name:** OSAGE BOYD 15 FEDERAL COM

**Well Number:** 10H

### Section 6 - Test, Logging, Coring

**List of production tests including testing procedures, equipment and safety measures:**

A mud logger will be used from GL to TD. Samples will be collected every 10' in the lateral pay zone.

No electric logs are planned at this time.

**List of open and cased hole logs run in the well:**

MUDLOG

**Coring operation description for the well:**

No core or drill stem test is planned.

### Section 7 - Pressure

**Anticipated Bottom Hole Pressure:** 1083

**Anticipated Surface Pressure:** 525.96

**Anticipated Bottom Hole Temperature(F):** 108

**Anticipated abnormal pressures, temperatures, or potential geologic hazards?** NO

**Describe:**

**Contingency Plans geohazards description:**

**Contingency Plans geohazards attachment:**

**Hydrogen Sulfide drilling operations plan required?** YES

**Hydrogen sulfide drilling operations plan:**

Osage\_10H\_H2S\_Plan\_20181105110903.pdf

### Section 8 - Other Information

**Proposed horizontal/directional/multi-lateral plan submission:**

Osage\_10H\_Horizontal\_Drill\_Plan\_20181105110932.pdf


**Other proposed operations facets description:**

**Other proposed operations facets attachment:**

Osage\_10H\_Drill\_Plan\_20181105111020.pdf

Osage\_10H\_Contingency\_Plan\_20181105111027.pdf

**Other Variance attachment:**



### Pressure Testing

- a. All testing to be done with 3<sup>rd</sup> party testing crews
- b. All tests should be done for each BOP/Valve/Choke Manifold:
  1. Recorded for 10 minutes on low pressure (500 psi)
  2. Recorded for 10 minutes on high pressure (3000 psi)
  3. All BOP testing will be completed with a test plug in place in wellhead
- c. After BOP testing is complete, test casing (without test plug) to 2000 psi for 30 minutes
- d. Company representative to email all copies of all plots to Drilling Engineer as well as save in the well file.
- e. **BOP's shall be function tested every day.**


### Gas Buster Operation

- a. Flow should be directed to pits unless choke is needed to control gas
- b. Adjustable choke to adjusted only by Percussion Rep on location
- c. Flare should remain burning (pilot lit) anytime fluid is going through gas buster
- d. Choke needs to be monitored to not overrun gas buster



**Nipple-Up**

- a. Raise stack and center over the wellhead
- b. Install DSA and ring gaskets
- c. Lower stack onto DSA
- d. Torque DSA flange bolts in a star pattern to the specified torque
- e. Verify BOP is centered to the rotary table
- f. Install rotating head
- g. Install hydraulic lines to BOP
- h. Verify manifold line-up
- i. Test BOP & manifold





## Casing Design Criteria and Load Case Assumptions

Percussion Petroleum Operating, LLC.  
 919 Milam Street, Suite 2475  
 Houston, TX 77002

### Lakewood Federal Com horizontal Wells

1. Collapse:  $DF_c=1.125$ 
  - a. Full Internal Evacuation: Collapse force equal to the mud gradient in which the casing will be run (0.65 psi/ft). The effects of axial load on collapse will be considered.
  - b. Cementing: Collapse force equal to the gradient of planned cement slurries to planned depths and minimum mud gradient in which the casing will be run above that (0.65 psi/ft) and an internal force equal to mud gradient of displacement fluid (0.43 psi/ft)
  
2. Burst:  $DF_b=1.125$ 
  - a. Pressure Test: psi casing test with an external force equal to the mud gradient in which the casing will be run (0.65 psi/ft), which is a more conservative backup force than pore pressure.
  - b. Injection Down Casing: psi surface injection pressure plus an internal pressure gradient of 0.65 psi/ft with an external force equal to the mud gradient in which the casing will be run (0.65 psi/ft), which is a more conservative backup force than pore pressure.
  
3. Tensile:  $DF_T=1.8$ 
  - a. Overpull: A downward force of 100,000 lbs is applied at the shoe along with the weight of the casing string utilizing the effects of buoyancy (10.5 ppg).

4. Surface Casing Program									
Casing Size (in)	Weight (ppf)	Grade	Connection	ID	ID (drift)	Collapse (psi)	Burst (psi)	Tension (1,000 lbs)	Capacity (bbl/ft)
9-5/8"	36	J-55	STC	8.921	8.765	2,020	3,520	394	0.0773
Safety Factors									
	API Rec. SF	ACTUAL SF	Case	External Fluids		Internal Fluids			
Collapse	1.125	3.30	Lost Circulation	Mud		None			
Burst	1.125	1.46	Plug Bump	Green Cement + 2ksi surf pressure		Displacement Fluid/Mud			
Tension	1.8	2.80	100 klbs Overpull	Mud		Mud			

*Buoyed Casing Weight: 40,798 lbs (assuming 8.4 ppg fluid and 1,300' casing-worst case scenario)*



Production Casing Program									
Casing Size (in)	Weight (ppf)	Grade	Connection	ID	ID (drift)	Collapse (psi)	Burst (psi)	Tension (1,000 lbs)	Capacity (bbl/ft)
7"	32	L-80	BTC	6.094	5.969	8,600	9,060	745	0.0361
5-1/2"	17	L-80	BTC	4.892	4.767	6,280	7,740	348	0.0232
Safety Factors									
	API Rec. SF	ACTUAL SF	Case	External Fluids		Internal Fluids			
Collapse	1.125	3.75	Lost Circulation	Mud		None			
Burst	1.125	2.47	Plug Bump	Green Cement + 2ksi surf pressure		Displacement Fluid/Mud			
Tension	1.8	2.29	100 klbs Overpull	Mud		Mud			

*Buoyed Casing Weight: 86,522 lbs (assuming 8.4 ppg fluid and 3,500' TVD-worst case scenario)*



## Casing Design Criteria and Load Case Assumptions

Percussion Petroleum Operating, LLC.  
 919 Milam Street, Suite 2475  
 Houston, TX 77002

### Lakewood Federal Com horizontal Wells

1. Collapse:  $DF_c=1.125$ 
  - a. Full Internal Evacuation: Collapse force equal to the mud gradient in which the casing will be run (0.65 psi/ft). The effects of axial load on collapse will be considered.
  - b. Cementing: Collapse force equal to the gradient of planned cement slurries to planned depths and minimum mud gradient in which the casing will be run above that (0.65 psi/ft) and an internal force equal to mud gradient of displacement fluid (0.43 psi/ft)
  
2. Burst:  $DF_b=1.125$ 
  - a. Pressure Test: psi casing test with an external force equal to the mud gradient in which the casing will be run (0.65 psi/ft), which is a more conservative backup force than pore pressure.
  - b. Injection Down Casing: psi surface injection pressure plus an internal pressure gradient of 0.65 psi/ft with an external force equal to the mud gradient in which the casing will be run (0.65 psi/ft), which is a more conservative backup force than pore pressure.
  
3. Tensile:  $DF_T=1.8$ 
  - a. Overpull: A downward force of 100,000 lbs is applied at the shoe along with the weight of the casing string utilizing the effects of buoyancy (10.5 ppg).

4. Surface Casing Program									
Casing Size (in)	Weight (ppf)	Grade	Connection	ID	ID (drift)	Collapse (psi)	Burst (psi)	Tension (1,000 lbs)	Capacity (bbl/ft)
9-5/8"	.36	J-55	STC	8.921	8.765	2,020	3,520	394	0.0773
Safety Factors									
	API Rec. SF	ACTUAL SF	Case	External Fluids		Internal Fluids			
Collapse	1.125	3.30	Lost Circulation	Mud		None			
Burst	1.125	1.46	Plug Bump	Green Cement ± 2ksi surf pressure		Displacement Fluid/Mud			
Tension	1.8	2.80	100 klbs Overpull	Mud		Mud			

*Buoyed Casing Weight: 40,798 lbs (assuming 8.4 ppg fluid and 1,300' casing-worst case scenario)*



Production Casing Program									
Casing Size (in)	Weight (ppf)	Grade	Connection	ID	ID (drift)	Collapse (psi)	Burst (psi)	Tension (1,000 lbs)	Capacity (bbl/ft)
7"	32	L-80	BTC	6.094	5.969	8,600	9,060	745	0.0361
5-1/2"	17	L-80	BTC	4.892	4.767	6,280	7,740	348	0.0232
Safety Factors									
	API Rec. SF	ACTUAL SF	Case	External Fluids		Internal Fluids			
Collapse	1.125	3.75	Lost Circulation	Mud		None			
Burst	1.125	2.47	Plug Bump	Green Cement + 2ksi surf pressure		Displacement Fluid/Mud			
Tension	1.8	2.29	100 klbs Overpull	Mud		Mud			

*Buoyed Casing Weight: 86,522 lbs (assuming 8.4 ppg fluid and 3,500' TVD-worst case scenario)*



## Casing Design Criteria and Load Case Assumptions

Percussion Petroleum Operating, LLC.  
 919 Milam Street, Suite 2475  
 Houston, TX 77002

### Lakewood Federal Com horizontal Wells

1. Collapse:  $DF_c=1.125$ 
  - a. Full Internal Evacuation: Collapse force equal to the mud gradient in which the casing will be run (0.65 psi/ft). The effects of axial load on collapse will be considered.
  - b. Cementing: Collapse force equal to the gradient of planned cement slurries to planned depths and minimum mud gradient in which the casing will be run above that (0.65 psi/ft) and an internal force equal to mud gradient of displacement fluid (0.43 psi/ft)
  
2. Burst:  $DF_b=1.125$ 
  - a. Pressure Test: psi casing test with an external force equal to the mud gradient in which the casing will be run (0.65 psi/ft), which is a more conservative backup force than pore pressure.
  - b. Injection Down Casing: psi surface injection pressure plus an internal pressure gradient of 0.65 psi/ft with an external force equal to the mud gradient in which the casing will be run (0.65 psi/ft), which is a more conservative backup force than pore pressure.
  
3. Tensile:  $DF_T=1.8$ 
  - a. Overpull: A downward force of 100,000 lbs is applied at the shoe along with the weight of the casing string utilizing the effects of buoyancy (10.5 ppg).

4. Surface Casing Program									
Casing Size (in)	Weight (ppf)	Grade	Connection	ID	ID (drift)	Collapse (psi)	Burst (psi)	Tension (1,000 lbs)	Capacity (bbl/ft)
9-5/8"	36	J-55	STC	8.921	8.765	2,020	3,520	394	0.0773
Safety Factors									
	API Rec. SF	ACTUAL SF	Case	External Fluids		Internal Fluids:			
Collapse	1.125	3.30	Lost Circulation	Mud		None			
Burst	1.125	1.46	Plug Bump	Green Cement + 2ksi surf pressure		Displacement Fluid/Mud			
Tension	1.8	2.80	100 klbs Overpull	Mud		Mud			

**Buoyed Casing Weight: 40,798 lbs (assuming 8.4 ppg fluid and 1,300' casing-worst case scenario)**



Production Casing Program									
Casing Size (in)	Weight (ppf)	Grade	Connection	ID	ID (drift)	Collapse (psi)	Burst (psi)	Tension (1,000 lbs)	Capacity (bbl/ft)
7"	32	L-80	BTC	6.094	5.969	8,600	9,060	745	0.0361
5-1/2"	17	L-80	BTC	4.892	4.767	6,280	7,740	348	0.0232
Safety Factors									
	API Rec. SF	ACTUAL SF	Case	External Fluids		Internal Fluids			
Collapse	1.125	3.75	Lost Circulation	Mud		None			
Burst	1.125	2.47	Plug Bump	Green Cement + 2ksi surf pressure		Displacement Fluid/Mud			
Tension	1.8	2.29	100 klbs Overpull	Mud		Mud			

*Buoyed Casing Weight: 86,522 lbs (assuming 8.4 ppg fluid and 3,500' TVD-worst case scenario)*



## Casing Design Criteria and Load Case Assumptions

Percussion Petroleum Operating, LLC.  
919 Milam Street, Suite 2475  
Houston, TX 77002

### Lakewood Federal Com horizontal Wells

1. Collapse:  $DF_c=1.125$ 
  - a. Full Internal Evacuation: Collapse force equal to the mud gradient in which the casing will be run (0.65 psi/ft). The effects of axial load on collapse will be considered.
  - b. Cementing: Collapse force equal to the gradient of planned cement slurries to planned depths and minimum mud gradient in which the casing will be run above that (0.65 psi/ft) and an internal force equal to mud gradient of displacement fluid (0.43 psi/ft)
  
2. Burst:  $DF_b=1.125$ 
  - a. Pressure Test: psi casing test with an external force equal to the mud gradient in which the casing will be run (0.65 psi/ft), which is a more conservative backup force than pore pressure.
  - b. Injection Down Casing: psi surface injection pressure plus an internal pressure gradient of 0.65 psi/ft with an external force equal to the mud gradient in which the casing will be run (0.65 psi/ft), which is a more conservative backup force than pore pressure.
  
3. Tension:  $DF_T=1.8$ 
  - a. Overpull: A downward force of 100,000 lbs is applied at the shoe along with the weight of the casing string utilizing the effects of buoyancy (10.5 ppG).

4. Surface Casing Program									
Casing Size (in)	Weight (ppf)	Grade	Connection	ID	ID (drift)	Collapse (psi)	Burst (psi)	Tension (1,000 lbs)	Capacity (bbl/ft)
9-5/8"	36	J-55	STC	8.921	8.765	2,020	3,520	394	0.0773
Safety Factors									
	API Rec. SF	ACTUAL SF	Case	External Fluids			Internal Fluids		
Collapse	1.125	3.30	Lost Circulation	Mud			None		
Burst	1.125	1.46	Plug Bump	Green Cement + 2ksi surf pressure			Displacement Fluid/Mud		
Tension	1.8	2.80	100 klbs Overpull	Mud			Mud		

**Buoyed Casing Weight: 40,798 lbs (assuming 8.4 ppG fluid and 1,300' casing-worst case scenario)**



Production Casing Program									
Casing Size (in)	Weight (ppf)	Grade	Connection	ID	ID (drift)	Collapse (psi)	Burst (psi)	Tension (1,000 lbs)	Capacity (bbl/ft)
7"	32	L-80	BTC	6.094	5.969	8,600	9,060	745	0.0361
5-1/2"	17	L-80	BTC	4.892	4.767	6,280	7,740	348	0.0232
Safety Factors									
	API Rec. SF	ACTUAL SF	Case	External Fluids		Internal Fluids			
Collapse	1.125	3.75	Lost Circulation	Mud		None			
Burst	1.125	2.47	Plug Bump	Green Cement + 2ksi surf pressure		Displacement Fluid/Mud			
Tension	1.8	2.29	100 klbs Overpull	Mud		Mud			

*Buoyed Casing Weight: 86,522 lbs (assuming 8.4 ppg fluid and 3,500' TVD-worst case scenario)*



## Casing Design Criteria and Load Case Assumptions

Percussion Petroleum Operating, LLC.  
 919 Milam Street, Suite 2475  
 Houston, TX 77002

### Lakewood Federal.Com horizontal Wells

1. Collapse:  $DF_c=1.125$ 
  - a. Full Internal Evacuation: Collapse force equal to the mud gradient in which the casing will be run (0.65 psi/ft). The effects of axial load on collapse will be considered.
  - b. Cementing: Collapse force equal to the gradient of planned cement slurries to planned depths and minimum mud gradient in which the casing will be run above that (0.65 psi/ft) and an internal force equal to mud gradient of displacement fluid (0.43 psi/ft)
  
2. Burst:  $DF_B=1.125$ 
  - a. Pressure Test: psi casing test with an external force equal to the mud gradient in which the casing will be run (0.65 psi/ft), which is a more conservative backup force than pore pressure.
  - b. Injection Down Casing: psi surface injection pressure plus an internal pressure gradient of 0.65 psi/ft with an external force equal to the mud gradient in which the casing will be run (0.65 psi/ft), which is a more conservative backup force than pore pressure.
  
3. Tensile:  $DF_T=1.8$ 
  - a. Overpull: A downward force of 100,000 lbs is applied at the shoe along with the weight of the casing string utilizing the effects of buoyancy (10.5 ppg).

4. Surface Casing Program									
Casing Size (in)	Weight (ppf)	Grade	Connection	ID	ID (drift)	Collapse (psi)	Burst (psi)	Tension (1,000 lbs)	Capacity (bbl/ft)
9-5/8"	36	J-55	STC	8.921	8.765	2,020	3,520	394	0.0773
Safety Factors									
	API Rec. SF	ACTUAL SF	Case	External Fluids			Internal Fluids		
Collapse	1.125	3.30	Lost Circulation	Mud			None		
Burst	1.125	1.46	Plug Bump	Green Cement ± 2ksi surf pressure			Displacement Fluid/Mud		
Tension	1.8	2.80	100 klbs Overpull	Mud			Mud		

*Buoyed Casing Weight: 40,798 lbs (assuming 8.4 ppg fluid and 1,300' casing-worst case scenario)*



Production Casing Program									
Casing Size (in)	Weight (ppf)	Grade	Connection	ID	ID (drift)	Collapse (psi)	Burst (psi)	Tension (1,000 lbs)	Capacity (bbl/ft)
7"	32	L-80	BTC	6.094	5.969	8,600	9,060	745	0.0361
5-1/2"	17	L-80	BTC	4.892	4.767	6,280	7,740	348	0.0232
Safety Factors									
	API Rec. SF	ACTUAL SF	Case	External Fluids			Internal Fluids		
Collapse	1.125	3.75	Lost Circulation	Mud			None		
Burst	1.125	2.47	Plug Bump	Green Cement + 2ksi surf pressure			Displacement Fluid/Mud		
Tension	1.8	2.29	100 klbs Overpull	Mud			Mud		

*Buoyed Casing Weight: 86,522 lbs (assuming 8.4 ppg fluid and 3,500' TVD-worst case scenario)*



## Hydrogen Sulfide Drilling Operations Plan

Percussion Petroleum Operating, LLC.  
919 Milam Street, Suite 2475  
Houston, TX 77002

1. H<sub>2</sub>S Safety Instructions to the following:
  - Characteristics of H<sub>2</sub>S.
  - Physical effects and hazards.
  - Principal and operation of H<sub>2</sub>S detectors, warning system and briefing areas.
  - Evacuation procedures, routes and First Aid.
  - Proper use of safety equipment and life support systems.
  - Essential personnel meeting medical evaluation criteria will receive additional training on the proper use of 30 min pressure demand air packs.
2. H<sub>2</sub>S Detection & Alarm Systems:
  - H<sub>2</sub>S sensor/detectors to be located on the drilling rig floor, in the base of the sub structure/cellar area, on the mud returns pits by the shale shaker. Additional H<sub>2</sub>S monitors may be placed as deemed necessary.
  - An audio alarm system will be installed on the derrick, the floor, and in the doghouse.
3. Windsocks and Wind Streamers:
  - Windsocks at mud pit area should be high enough to be visible.
  - Windsock on the rig floor/top of doghouse should be high enough to be visible.
4. Condition Flags & Signs:
  - Warning sign on access road to location
  - Flags to be displayed on sign at entrance to location
    - i. Green Flag – Normal Safe Operation Condition
    - ii. Yellow Flag – Potential Pressure and Danger
    - iii. Red Flag – Danger (H<sub>2</sub>S present in dangerous concentrations) Only H<sub>2</sub>S trained personnel admitted on location
5. Well Control Equipment:
  - See attached APD



6. Communications:

- While working under masks, chalkboards will be used for communications
- Hand signals will be used where chalk board is inappropriate
- Two-way radio will be used to communicate off location in case of emergency help is required. In most cases cellular telephones will be available at drilling foreman's trailer or living quarters.

7. Drilling Stem Testing:

- No Drill Stem Tests or hole coring is planned at this time.

8. Drilling contractor supervisor will be required to be familiar with the effects H<sub>2</sub>S has on tubular goods and other mechanical equipment.

9. If H<sub>2</sub>S is encountered, mud system will be altered if necessary to maintain control of formation. A mud gas separator will be brought into service along with H<sub>2</sub>S scavenger chemicals if necessary.

10. Emergency Contacts:

Emergency Contact Information - H <sub>2</sub> S Contingency Plan				
Percussion Petroleum Operating, LLC	713-518-1331			
Key Parties at Percussion Petroleum		Office	Mobile	Email
Lelan J. Anders	Vice President of Operations	713-429-1291	281-908-1752	Lelan@PercussionPetroleum.com
Lupe Carrillo	Chief Operating Officer	713-589-9509	832-776-1869	Lupe@PercussionPetroleum.com
John H. Campbell III	Chief Executive Officer	713-589-4683	936-718-6488	John@PercussionPetroleum.com

Artesia, New Mexico:	
Ambulance	911
State Police	575-746-2703
City Police	575-746-2703
Sheriff's Office	575-746-9888
Fire Department	575-746-2701
Local Emergency Planning Committee	575-746-2122
New Mexico Oil Conservation Division	575-748-1283

Carlsbad, New Mexico:	
Ambulance	911
State Police	575-885-3137
City Police	575-885-2111
Sheriff's Office	575-887-7551
Fire Department	575-887-3798
Local Emergency Planning Committee	575-887-6544
New Mexico Oil Conservation Division	575-887-6544





Santa Fe, New Mexico:	
New Mexico Emergency Response Commission	505-476-9600
New Mexico Emergency Response Commission (24 hr)	505-827-9126
New Mexico State Emergency Operations Center	505-476-9635

Federal Contacts:	
Carlsbad BLM Office	575-234-5972
National Emergency Response Center (Washington, DC)	800-424-8802

Medical:	
Flight for Life - Lubbock, TX	806-743-9911
AeroCare - Lubbock, TX	806-747-8923
Med Flight Air Ambulance - Albuquerque, NM	505-842-4433
SB Air Med Service - Albuquerque, NM	505-842-4949

Well Control/Other:	
Wild Well Control	281-784-4700
Boots & Coots IWC	800-256-9688
B.J. Services	575-746-3569
Halliburton	575-746-2757

SECTION 22, TOWNSHIP 19 SOUTH, RANGE 25 EAST, N.M.P.M.,  
 EDDY COUNTY, NEW MEXICO.



**PERCUSSION PETROLEUM OPERATING, LLC**

REF: OSAGE BOYD 15 FEDERAL COM 10H / WELL PAD TOPO

THE OSAGE BOYD 15 FEDERAL COM 10H LOCATED 649' FROM  
 THE NORTH LINE AND 701' FROM THE WEST LINE OF  
 SECTION 22, TOWNSHIP 19 SOUTH, RANGE 25 EAST,  
 N.M.P.M., EDDY COUNTY, NEW MEXICO.




P.O. Box 1786 (575) 393-7316 - Office  
 1120 N. West County Rd. (575) 392-2206 - Fax  
 Hobbs, New Mexico 88241 basin-surveys.com

# Percussion Petroleum Operating, LLC

Osage Boyd 15" Federal Com 9H/10H/11H  
H<sub>2</sub>S Contingency Plan:  
Radius Map

Section 22, Township 19S, Range 25E,  
Eddy County, New Mexico



⊙ Surface Hole Location



NAD 1983 New Mexico State Plane East  
FIPS 3001 Feet



Prepared by Perma West, Inc., September 13, 2018  
for Percussion Petroleum Operating, LLC.





Database:	WBDS_SQL_2	Local Co-ordinate Reference:	Well #10H - Slot 10
Company:	Percussion Petroleum, LLC	TVD Reference:	RKB = 17' @ 3492.00usft
Project:	Eddy County, NM	MD Reference:	RKB = 17' @ 3492.00usft
Site:	Osage-Boyd 15 FED.COM	North Reference:	Grid
Well:	#10H	Survey Calculation Method:	Minimum Curvature
Wellbore:	OH		
Design:	Plan #1		

Project:	Eddy County, NM		
Map System:	US State Plane 1983	System Datum:	Mean Sea Level
Geo Datum:	North American Datum 1983		
Map Zone:	New Mexico Eastern Zone		

Site:	Osage-Boyd 15 FED.COM				
Site Position:	Map	Northing:	600,962.30 usft	Latitude:	32.652008
From:		Easting:	496,514.50 usft	Longitude:	-104.478969
Position Uncertainty:	0.00 usft	Slot Radius:	13.200 in	Grid Convergence:	-0.08 °

Well:	#10H - Slot 10					
Well Position	+N/S	-0.20 usft	Northing:	600,962.10 usft	Latitude:	32.652008
	+E/W	20.00 usft	Easting:	496,534.50 usft	Longitude:	-104.478904
Position Uncertainty:	0.00 usft	Wellhead Elevation:		Ground Level:	3,475.00 usft	

Wellbore:	OH				
Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	IGRF2015	07/18/18	7.29	60.29	47,981.41681924

Design:	Plan #1				
Audit Notes:					
Version:	Phase:	PLAN	Tie On Depth:	0.00	
Vertical Section:	Depth From (TVD) (usft)	+N/S (usft)	+E/W (usft)	Direction (°)	
	0.00	0.00	0.00	358.27	

Plan Survey Tool Program:	Date: 07/18/18				
Depth From (usft)	Depth To (usft)	Survey (Wellbore)	Tool Name	Remarks	
1	0.00	8,002.49	Plan #1 (OH)	MWD+IGRF	
				OWSG MWD + IGRF or WM	

Database:	WBDS_SQL_2	Local Co-ordinate Reference:	Well #10H - Slot 10
Company:	Percussion Petroleum, LLC	TVD Reference:	RKB = 17' @ 3492.00usft
Project:	Eddy County, NM	MD Reference:	RKB = 17' @ 3492.00usft
Site:	Osage Boyd 15 FED COM	North Reference:	Grid
Well:	#10H	Survey Calculation Method:	Minimum Curvature
Wellbore:	OH		
Design:	Plan #1		

Plan Sections

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)	TFO (°)	Target
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
350.00	0.00	0.00	350.00	0.00	0.00	0.00	0.00	0.00	0.00	
787.31	8.75	324.11	785.62	26.99	-19.53	2.00	2.00	0.00	324.11	
2,048.00	8.75	324.11	2,031.65	182.29	-131.91	0.00	0.00	0.00	0.00	
2,877.25	90.00	0.02	2,532.00	750.90	-176.90	10.00	9.80	4.33	36.22	OB 15: 10H FTP
6,999.70	90.00	0.02	2,532.00	4,873.35	-175.80	0.00	0.00	0.00	0.00	OB 15: 10H IP1
7,080.98	91.62	359.88	2,530.85	4,954.62	-175.87	2.00	1.99	-0.17	-4.77	
7,885.98	91.62	359.88	2,508.09	5,759.30	-177.56	0.00	0.00	0.00	0.00	
7,972.32	89.90	0.04	2,506.95	5,845.63	-177.62	2.00	-1.99	0.18	174.72	
8,002.50	89.90	0.04	2,507.00	5,875.80	-177.60	0.00	0.00	0.00	0.00	OB 15: 10H PBHL

Database:	WBDS_SQL_2	Local Co-ordinate Reference:	Well #10H - Slot 10
Company:	Percussion Petroleum, LLC	TVD Reference:	RKB = 17' @ 3492.00usft
Project:	Eddy County, NM	MD Reference:	RKB = 17' @ 3492.00usft
Site:	Osage, Boyd 15, FED.COM	North Reference:	Grid
Well:	#10H	Survey Calculation Method:	Minimum Curvature
Wellbore:	OH		
Design:	Plan #1		

Planned Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (%/100ft)	Build Rate (%/100ft)	Turn Rate (%/100ft)	
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
100.00	0.00	0.00	100.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
200.00	0.00	0.00	200.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
300.00	0.00	0.00	300.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
350.00	0.00	0.00	350.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
400.00	-1.00	324.11	400.00	0.35	-0.26	0.36	2.00	2.00	0.00	0.00
500.00	3.00	324.11	499.93	3.18	-2.30	3.25	2.00	2.00	0.00	0.00
600.00	5.00	324.11	599.68	8.83	-6.39	9.02	2.00	2.00	0.00	0.00
700.00	7.00	324.11	699.13	17.30	-12.52	17.67	2.00	2.00	0.00	0.00
787.31	8.75	324.11	785.62	26.99	-19.53	27.57	2.00	2.00	0.00	0.00
800.00	8.75	324.11	798.16	28.55	-20.66	29.16	0.00	0.00	0.00	0.00
900.00	8.75	324.11	896.99	40.87	-29.57	41.75	0.00	0.00	0.00	0.00
1,000.00	8.75	324.11	995.83	53.19	-38.49	54.33	0.00	0.00	0.00	0.00
1,100.00	8.75	324.11	1,094.67	65.51	-47.40	66.91	0.00	0.00	0.00	0.00
1,200.00	8.75	324.11	1,193.50	77.83	-56.32	79.49	0.00	0.00	0.00	0.00
1,300.00	8.75	324.11	1,292.34	90.15	-65.23	92.08	0.00	0.00	0.00	0.00
1,400.00	8.75	324.11	1,391.18	102.47	-74.14	104.66	0.00	0.00	0.00	0.00
1,500.00	8.75	324.11	1,490.02	114.79	-83.06	117.24	0.00	0.00	0.00	0.00
1,600.00	8.75	324.11	1,588.85	127.10	-91.97	129.82	0.00	0.00	0.00	0.00
1,700.00	8.75	324.11	1,687.69	139.42	-100.89	142.41	0.00	0.00	0.00	0.00
1,800.00	8.75	324.11	1,786.53	151.74	-109.80	154.99	0.00	0.00	0.00	0.00
1,900.00	8.75	324.11	1,885.36	164.06	-118.72	167.57	0.00	0.00	0.00	0.00
2,000.00	8.75	324.11	1,984.20	176.38	-127.63	180.16	0.00	0.00	0.00	0.00
2,048.00	8.75	324.11	2,031.65	182.29	-131.91	186.20	0.00	0.00	0.00	0.00
2,050.00	8.91	324.87	2,033.62	182.54	-132.09	186.45	-10.00	-8.11	-38.16	
2,100.00	13.30	337.57	2,082.68	191.03	-136.51	195.07	-10.00	8.78	25.40	
2,150.00	18.01	343.90	2,130.82	203.78	-140.85	207.94	-10.00	9.41	12.65	
2,200.00	22.83	347.64	2,177.66	220.69	-145.07	224.97	-10.00	9.66	7.49	
2,250.00	27.72	350.13	2,222.86	241.64	-149.14	246.03	-10.00	9.77	4.97	
2,300.00	32.64	351.92	2,266.07	266.46	-153.04	270.96	-10.00	9.84	3.58	
2,350.00	37.58	353.28	2,306.96	294.97	-156.72	299.57	-10.00	9.88	2.73	
2,400.00	42.53	354.37	2,345.22	326.95	-160.16	331.64	-10.00	9.90	2.18	
2,450.00	47.49	355.27	2,380.56	362.16	-163.34	366.92	-10.00	9.92	1.80	
2,500.00	52.45	356.04	2,412.71	400.32	-166.23	405.16	-10.00	9.93	1.54	
2,550.00	57.42	356.71	2,441.42	441.15	-168.81	446.05	-10.00	9.94	1.34	
2,600.00	62.40	357.31	2,466.48	484.34	-171.06	489.29	-10.00	9.95	1.20	
2,650.00	67.37	357.86	2,487.70	529.56	-172.96	534.54	-10.00	9.95	1.10	
2,700.00	72.35	358.37	2,504.91	576.46	-174.50	581.47	-10.00	9.95	1.02	
2,750.00	77.33	358.85	2,517.98	624.69	-175.67	629.71	-10.00	9.96	0.97	
2,800.00	82.31	359.32	2,526.82	673.88	-176.45	678.91	-10.00	9.96	0.93	
2,850.00	87.29	359.77	2,531.35	723.66	-176.85	728.67	-10.00	9.96	0.91	
2,877.25	90.00	0.02	2,532.00	750.90	-176.90	755.90	-10.00	9.96	0.90	
2,900.00	90.00	0.02	2,532.00	773.65	-176.89	778.64	0.00	0.00	0.00	
3,000.00	90.00	0.02	2,532.00	873.65	-176.87	878.59	0.00	0.00	0.00	
3,100.00	90.00	0.02	2,532.00	973.65	-176.84	978.55	0.00	0.00	0.00	
3,200.00	90.00	0.02	2,532.00	1,073.65	-176.81	1,078.50	0.00	0.00	0.00	
3,300.00	90.00	0.02	2,532.00	1,173.65	-176.79	1,178.45	0.00	0.00	0.00	
3,400.00	90.00	0.02	2,532.00	1,273.65	-176.76	1,278.41	0.00	0.00	0.00	
3,500.00	90.00	0.02	2,532.00	1,373.65	-176.73	1,378.36	0.00	0.00	0.00	
3,600.00	90.00	0.02	2,532.00	1,473.65	-176.71	1,478.32	0.00	0.00	0.00	
3,700.00	90.00	0.02	2,532.00	1,573.65	-176.68	1,578.27	0.00	0.00	0.00	
3,800.00	90.00	0.02	2,532.00	1,673.65	-176.65	1,678.22	0.00	0.00	0.00	
3,900.00	90.00	0.02	2,532.00	1,773.65	-176.63	1,778.18	0.00	0.00	0.00	
4,000.00	90.00	0.02	2,532.00	1,873.65	-176.60	1,878.13	0.00	0.00	0.00	

Database:	WBDS_SQL_2	Local Co-ordinate Reference:	Well #10H - Slot 10
Company:	Percussion Petroleum, LLC	TVD Reference:	RKB = 17' @ 3492.00usft
Project:	Eddy County, NM	MD Reference:	RKB = 17' @ 3492.00usft
Site:	Osage Boyd 15 FED COM	North Reference:	Grid
Well:	#10H	Survey Calculation Method:	Minimum Curvature
Wellbore:	OH		
Design:	Plan #1		

Planned Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/S (usft)	+E/W (usft)	Vertical Section (usft)	Dogleg Rate (%/100ft)	Build Rate (%/100ft)	Turn Rate (%/100ft)	
4,100.00	90.00	0.02	2,532.00	1,973.65	-176.57	1,978.08	0.00	0.00	0.00	
4,200.00	90.00	0.02	2,532.00	2,073.65	-176.55	2,078.04	0.00	0.00	0.00	
4,300.00	90.00	0.02	2,532.00	2,173.65	-176.52	2,177.99	0.00	0.00	0.00	
4,400.00	90.00	0.02	2,532.00	2,273.65	-176.49	2,277.94	0.00	0.00	0.00	
4,500.00	90.00	0.02	2,532.00	2,373.65	-176.47	2,377.90	0.00	0.00	0.00	
4,600.00	90.00	0.02	2,532.00	2,473.65	-176.44	2,477.85	0.00	0.00	0.00	
4,700.00	90.00	0.02	2,532.00	2,573.65	-176.41	2,577.80	0.00	0.00	0.00	
4,800.00	90.00	0.02	2,532.00	2,673.65	-176.39	2,677.76	0.00	0.00	0.00	
4,900.00	90.00	0.02	2,532.00	2,773.65	-176.36	2,777.71	0.00	0.00	0.00	
5,000.00	90.00	0.02	2,532.00	2,873.65	-176.33	2,877.66	0.00	0.00	0.00	
5,100.00	90.00	0.02	2,532.00	2,973.65	-176.31	2,977.62	0.00	0.00	0.00	
5,200.00	90.00	0.02	2,532.00	3,073.65	-176.28	3,077.57	0.00	0.00	0.00	
5,300.00	90.00	0.02	2,532.00	3,173.65	-176.25	3,177.53	0.00	0.00	0.00	
5,400.00	90.00	0.02	2,532.00	3,273.65	-176.23	3,277.48	0.00	0.00	0.00	
5,500.00	90.00	0.02	2,532.00	3,373.65	-176.20	3,377.43	0.00	0.00	0.00	
5,600.00	90.00	0.02	2,532.00	3,473.65	-176.17	3,477.39	0.00	0.00	0.00	
5,700.00	90.00	0.02	2,532.00	3,573.65	-176.15	3,577.34	0.00	0.00	0.00	
5,800.00	90.00	0.02	2,532.00	3,673.65	-176.12	3,677.29	0.00	0.00	0.00	
5,900.00	90.00	0.02	2,532.00	3,773.65	-176.09	3,777.25	0.00	0.00	0.00	
6,000.00	90.00	0.02	2,532.00	3,873.65	-176.07	3,877.20	0.00	0.00	0.00	
6,100.00	90.00	0.02	2,532.00	3,973.65	-176.04	3,977.15	0.00	0.00	0.00	
6,200.00	90.00	0.02	2,532.00	4,073.65	-176.01	4,077.11	0.00	0.00	0.00	
6,300.00	90.00	0.02	2,532.00	4,173.65	-175.99	4,177.06	0.00	0.00	0.00	
6,400.00	90.00	0.02	2,532.00	4,273.65	-175.96	4,277.01	0.00	0.00	0.00	
6,500.00	90.00	0.02	2,532.00	4,373.65	-175.93	4,376.97	0.00	0.00	0.00	
6,600.00	90.00	0.02	2,532.00	4,473.65	-175.91	4,476.92	0.00	0.00	0.00	
6,700.00	90.00	0.02	2,532.00	4,573.65	-175.88	4,576.88	0.00	0.00	0.00	
6,800.00	90.00	0.02	2,532.00	4,673.65	-175.85	4,676.83	0.00	0.00	0.00	
6,900.00	90.00	0.02	2,532.00	4,773.65	-175.83	4,776.78	0.00	0.00	0.00	
6,999.70	90.00	0.02	2,532.00	4,873.35	-175.80	4,876.44	0.00	0.00	0.00	
7,080.98	91.62	359.88	2,530.85	4,954.62	-175.87	4,957.67	2.00	1.99	-0.17	
7,100.00	91.62	359.88	2,530.31	4,973.63	-175.91	4,976.68	0.00	0.00	0.00	
7,200.00	91.62	359.88	2,527.49	5,073.59	-176.12	5,076.60	0.00	0.00	0.00	
7,300.00	91.62	359.88	2,524.66	5,173.55	-176.33	5,176.52	0.00	0.00	0.00	
7,400.00	91.62	359.88	2,521.83	5,273.51	-176.54	5,276.44	0.00	0.00	0.00	
7,500.00	91.62	359.88	2,519.01	5,373.47	-176.75	5,376.36	0.00	0.00	0.00	
7,600.00	91.62	359.88	2,516.18	5,473.43	-176.96	5,476.28	0.00	0.00	0.00	
7,700.00	91.62	359.88	2,513.35	5,573.39	-177.17	5,576.20	0.00	0.00	0.00	
7,800.00	91.62	359.88	2,510.52	5,673.35	-177.38	5,676.12	0.00	0.00	0.00	
7,885.98	91.62	359.88	2,508.09	5,759.30	-177.56	5,762.03	0.00	0.00	0.00	
7,900.00	91.34	359.91	2,507.73	5,773.31	-177.59	5,776.04	2.00	-1.99	0.18	
7,972.32	89.90	0.04	2,506.95	5,845.63	-177.62	5,848.33	2.00	-1.99	0.18	
8,002.50	89.90	0.04	2,507.00	5,875.80	-177.60	5,878.48	0.00	0.00	0.00	

Database:	WBDS_SQL_2	Local Co-ordinate Reference:	Well #10H - Slot 10
Company:	Percussion Petroleum, LLC	TVD Reference:	RKB = 17' @ 3492.00usft
Project:	Eddy County, NM	MD Reference:	RKB = 17' @ 3492.00usft
Site:	Osage Boyd 15 FED COM	North Reference:	Grid
Well:	#10H	Survey Calculation Method:	Minimum Curvature
Wellbore:	OH		
Design:	Plan #1		

Design Targets										
Target Name	hit/miss target	Dip Angle	Dip Dir.	TVD	+N/-S	+E/-W	Northing	Easting	Latitude	Longitude
	- Shape	(°)	(°)	(usft)	(usft)	(usft)	(usft)	(usft)		
OB 15 10H SHL (649	- plan hits target center	0.00	360.00	0.00	0.00	0.00	600,962.10	496,534.50	32.652008	-104.478904
	- Point									
OB 15 10H LTP	- plan misses target center by 0.29usft at 7922.40usft MD (2507.29 TVD, 5795.70 N, -177.61 E)	0.00	360.00	2,507.00	5,795.70	-177.60	606,757.80	496,356.90	32.667938	-104.479507
	- Point									
OB 15 10H PBHL (20	- plan hits target center	0.00	360.00	2,507.00	5,875.80	-177.60	606,837.90	496,356.90	32.668158	-104.479508
	- Point									
OB 15 10H FTP	- plan hits target center	0.00	360.00	2,532.00	750.90	-176.90	601,713.00	496,357.60	32.654071	-104.479483
	- Point									
OB 15 10H IPT	- plan hits target center	0.00	360.00	2,532.00	4,873.35	-175.80	605,835.45	496,358.70	32.665403	-104.479497
	- Point									



**PERCUSSION  
PETROLEUM  
LLC**

## **Percussion Petroleum, LLC**

**Eddy County, NM**

**Osage Boyd 15 FED COM**

**#10H**

**OH**

**Plan.#1**

## **Anticollision Report**

**18 July, 2018**

**WELLBENDERS  
DIRECTIONAL SERVICES**



Company:	Percussion Petroleum, LLC	Local Co-ordinate Reference:	Well #10H - Slot 10
Project:	Eddy County, NM	TVD Reference:	RKB = 17' @ 3492.00usft
Reference Site:	Osage Boyd 15 FED.COM	MD Reference:	RKB = 17' @ 3492.00usft
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	#10H	Survey/Calculation Method:	Minimum Curvature
Well Error:	0.00 usft	Output errors are at	2:00 sigma
Reference Wellbore:	OH	Database:	WBDS_SQL_2
Reference Design:	Plan #1	Offset TVD Reference:	Reference Datum

Reference:	Plan #1
Filter type:	NO GLOBAL FILTER Using user defined selection & filtering criteria
Interpolation Method:	Stations
Depth Range:	0.00 to 8,002.50usft
Results Limited by:	Maximum center-center distance of 1,000.00 us
Warning Levels Evaluated at:	2:00 Sigma
Error Model:	ISCWSA
Scan Method:	Closest Approach 3D
Error Surface:	Pedal Curve
Casing Method:	Not applied

Survey Tool Program	Date	07/18/18		
From (usft)	To (usft)	Survey (Wellbore)	Tool Name	Description
0.00	8,002.49	Plan #1 (OH)	MWD+IGRF	OWSG:MWD + IGRF or WMM

Site Name	Reference Measured Depth (usft)	Offset Measured Depth (usft)	Distance Between Centres (usft)	Distance Between Ellipses (usft)	Separation Factor	Warning
Osage Boyd 15 FED.COM						
#11H - OH - Plan #1	350.00	350.00	20.20	18.11	9.666	CC
#11H - OH - Plan #1	400.00	400.05	20.40	17.95	8.334	ES
#11H - OH - Plan #1	8,002.50	8,191.04	277.41	125.47	1.826	SF
#9H - OH - Plan #1	350.00	350.00	20.00	17.91	9.570	CC
#9H - OH - Plan #1	400.00	399.72	20.10	17.65	8.220	ES
#9H - OH - Plan #1	8,002.50	8,357.47	377.87	252.26	3.008	SF

Offset Design													Offset Site Error:	0.00 usft
Survey Program: 0-MWD+IGRF													Offset Well Error:	0.00 usft
Reference	Offset	Semi-Major Axis			Distance			Minimum Separation			Warning			
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	Offset Wellbore Centre +N/S (usft)	+E/W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor		
0.00	0.00	0.00	0.00	0.00	0.00	90.00	0.00	20.20	20.20					
100.00	100.00	100.00	100.00	0.15	0.15	90.00	0.00	20.20	20.20	19.90	0.30	67.892		
200.00	200.00	200.00	200.00	0.51	0.51	90.00	0.00	20.20	20.20	19.19	1.01	19.912		
300.00	300.00	300.00	300.00	0.87	0.87	90.00	0.00	20.20	20.20	18.47	1.73	11.667		
350.00	350.00	350.00	350.00	1.04	1.04	90.00	0.00	20.20	20.20	18.11	2.09	9.666	CC	
400.00	400.00	400.05	400.04	1.22	1.22	125.66	0.43	20.14	20.40	17.95	2.45	8.334	ES	
500.00	499.93	500.12	500.05	1.58	1.59	124.00	3.90	19.67	21.98	18.82	3.16	6.949		
600.00	599.68	600.12	599.81	1.95	1.95	121.30	10.81	18.73	25.20	21.31	3.89	6.475		
700.00	699.13	700.02	699.19	2.32	2.32	119.02	20.81	17.37	30.10	25.45	4.64	6.483		
787.31	785.62	787.14	785.81	2.67	2.66	120.85	29.97	16.13	35.78	30.46	5.32	6.729		
800.00	798.16	800.21	798.39	2.72	2.71	121.34	31.30	15.95	36.71	31.29	5.42	6.775		
900.00	896.99	900.51	897.53	3.14	3.10	124.47	41.79	14.52	44.11	37.90	6.20	7.110		
1,000.00	995.83	1,000.81	996.67	3.57	3.50	126.69	52.28	13.09	51.60	44.60	7.00	7.376		
1,100.00	1,094.67	1,101.11	1,095.81	4.00	3.90	128.35	62.77	11.67	59.15	51.35	7.79	7.591		
1,200.00	1,193.50	1,201.41	1,194.95	4.44	4.30	129.63	73.26	10.24	66.73	58.14	8.59	7.769		
1,300.00	1,292.34	1,301.70	1,294.08	4.88	4.70	130.66	83.75	8.82	74.35	64.95	9.39	7.917		
1,400.00	1,391.18	1,402.00	1,393.22	5.32	5.10	131.49	94.23	7.39	81.98	71.78	10.19	8.043		
1,500.00	1,490.02	1,502.30	1,492.36	5.75	5.50	132.18	104.72	5.97	89.62	78.63	11.00	8.151		
1,600.00	1,588.85	1,602.60	1,591.50	6.21	5.91	132.76	115.21	4.54	97.28	85.48	11.80	8.245		
1,700.00	1,687.69	1,702.90	1,690.64	6.65	6.31	133.25	125.70	3.12	104.95	92.34	12.60	8.327		
1,800.00	1,786.53	1,803.20	1,789.78	7.10	6.71	133.68	136.19	1.69	112.62	99.21	13.41	8.399		

CC - Min centre to center distance or covergent point; SF - min separation factor; ES - min ellipse separation

Company:	Percussion Petroleum, LLC:	Local Co-ordinate Reference:	Well #10H - Slot 10
Project:	Eddy County, NM	TVD Reference:	RKB = 17' @ 3492.00usft
Reference Site:	Osage Boyd 15 FED COM	MD Reference:	RKB = 17' @ 3492.00usft
Site Error:	0.00 usft:	North Reference:	Grid
Reference Well:	#10H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.00 usft:	Output errors are at	2.00 sigma
Reference Wellbore:	OH	Database:	WBDS_SQL_2:
Reference Design:	Plan #1	Offset TVD Reference:	Reference Datum

Offset Design Osage Boyd 15 FED COM - #11H - OH - Plan #1													Offset Site Error:	0.00 usft
Survey Program: D-MWD+IGRF													Offset Well Error:	0.00 usft
Reference		Offset		Semi-Major Axis		Highside Toolface (°)	Offset Wellbore Centro		Distance		Minimum Separation (usft)	Separation Factor	Warning	
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)		+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)				
1,900.00	1,885.36	1,903.49	1,888.91	7.55	7.12	134.05	146.67	0.27	120.30	106.08	14.21	8.463		
2,000.00	1,984.20	2,003.79	1,988.05	8.00	7.52	134.38	157.16	-1.16	127.98	112.96	15.02	8.521		
2,048.00	2,031.65	2,044.07	2,035.64	8.21	7.68	134.53	162.20	-1.84	131.67	116.29	15.38	8.564		
2,050.00	2,033.62	2,046.06	2,037.62	8.22	7.69	133.77	162.41	-1.87	131.82	116.43	15.39	8.565		
2,100.00	2,082.68	2,104.20	2,087.08	8.47	7.93	122.00	167.64	-2.58	136.02	120.20	15.82	8.598		
2,150.00	2,130.82	2,145.06	2,136.07	8.74	8.09	118.17	172.82	-3.29	141.10	124.93	16.17	8.728		
2,200.00	2,177.66	2,193.49	2,184.22	9.05	8.29	118.16	177.92	-3.98	147.58	131.06	16.52	8.933		
2,250.00	2,222.86	2,242.28	2,232.71	9.38	8.49	120.33	183.26	-4.68	156.13	139.27	16.86	9.261		
2,300.00	2,266.07	2,295.54	2,285.10	9.76	8.73	123.31	192.73	-5.43	166.09	148.86	17.23	9.639		
2,350.00	2,306.96	2,350.76	2,338.24	10.18	9.02	126.16	207.64	-6.20	176.81	159.19	17.62	10.035		
2,400.00	2,345.22	2,408.10	2,391.63	10.63	9.36	128.77	228.45	-6.97	187.95	169.94	18.00	10.440		
2,450.00	2,380.56	2,467.69	2,444.63	11.13	9.77	131.10	255.63	-7.73	199.16	180.80	18.37	10.843		
2,500.00	2,412.71	2,529.64	2,496.42	11.68	10.24	133.15	289.58	-8.48	210.15	191.44	18.71	11.231		
2,550.00	2,441.42	2,594.02	2,546.04	12.26	10.81	134.92	330.52	-9.20	220.59	201.55	19.04	11.586		
2,600.00	2,466.48	2,660.83	2,592.34	12.89	11.47	136.42	378.63	-9.87	230.21	210.83	19.38	11.878		
2,650.00	2,487.70	2,729.99	2,634.03	13.56	12.25	137.65	433.76	-10.48	238.73	218.96	19.77	12.075		
2,700.00	2,504.91	2,801.31	2,669.75	14.27	13.12	138.64	495.43	-11.00	245.91	225.66	20.25	12.145		
2,750.00	2,517.98	2,874.49	2,698.15	15.00	14.12	139.39	562.82	-11.42	251.53	230.65	20.88	12.047		
2,800.00	2,526.82	2,949.11	2,718.03	15.76	15.19	139.89	634.69	-11.71	255.41	233.71	21.70	11.769		
2,850.00	2,531.35	3,024.66	2,728.48	16.54	16.35	140.15	709.46	-11.87	257.44	234.67	22.77	11.308		
2,877.25	2,532.00	3,066.02	2,730.00	16.97	16.99	140.19	750.78	-11.90	257.74	234.29	23.45	10.991		
2,900.00	2,532.00	3,088.91	2,730.00	17.33	17.35	140.20	773.67	-11.90	257.73	233.77	23.96	10.758		
3,000.00	2,532.00	3,188.91	2,730.00	18.96	18.97	140.20	873.67	-11.92	257.71	231.46	26.25	9.819		
3,100.00	2,532.00	3,288.91	2,730.00	20.64	20.65	140.21	973.67	-11.93	257.68	229.07	28.61	9.006		
3,200.00	2,532.00	3,388.91	2,730.00	22.36	22.36	140.22	1,073.67	-11.94	257.65	226.62	31.04	8.302		
3,300.00	2,532.00	3,488.91	2,730.00	24.10	24.10	140.22	1,173.67	-11.96	257.63	224.12	33.51	7.689		
3,400.00	2,532.00	3,588.91	2,730.00	25.87	25.86	140.23	1,273.67	-11.97	257.60	221.59	36.01	7.153		
3,500.00	2,532.00	3,688.91	2,730.00	27.66	27.65	140.24	1,373.67	-11.99	257.58	219.03	38.55	6.682		
3,600.00	2,532.00	3,788.91	2,730.00	29.47	29.45	140.24	1,473.67	-12.00	257.55	216.44	41.11	6.265		
3,700.00	2,532.00	3,888.91	2,730.00	31.29	31.27	140.25	1,573.67	-12.01	257.52	213.84	43.69	5.894		
3,800.00	2,532.00	3,988.91	2,730.00	33.12	33.10	140.26	1,673.67	-12.03	257.50	211.21	46.29	5.563		
3,900.00	2,532.00	4,088.91	2,730.00	34.96	34.93	140.27	1,773.67	-12.04	257.47	208.58	48.89	5.266		
4,000.00	2,532.00	4,188.91	2,730.00	36.81	36.78	140.27	1,873.67	-12.06	257.45	205.93	51.52	4.997		
4,100.00	2,532.00	4,288.91	2,730.00	38.66	38.63	140.28	1,973.67	-12.07	257.42	203.27	54.15	4.754		
4,200.00	2,532.00	4,388.91	2,730.00	40.52	40.49	140.29	2,073.67	-12.08	257.39	200.61	56.79	4.533		
4,300.00	2,532.00	4,488.91	2,730.00	42.38	42.35	140.29	2,173.67	-12.10	257.37	197.94	59.43	4.331		
4,400.00	2,532.00	4,588.91	2,730.00	44.25	44.22	140.30	2,273.67	-12.11	257.34	195.26	62.08	4.145		
4,500.00	2,532.00	4,688.91	2,730.00	46.12	46.09	140.31	2,373.67	-12.13	257.32	192.58	64.74	3.975		
4,600.00	2,532.00	4,788.91	2,730.00	48.00	47.96	140.31	2,473.67	-12.14	257.29	189.89	67.40	3.817		
4,700.00	2,532.00	4,888.91	2,730.00	49.88	49.84	140.32	2,573.67	-12.15	257.27	187.20	70.07	3.672		
4,800.00	2,532.00	4,988.91	2,730.00	51.76	51.72	140.33	2,673.67	-12.17	257.24	184.50	72.74	3.537		
4,900.00	2,532.00	5,088.91	2,730.00	53.64	53.61	140.33	2,773.67	-12.18	257.21	181.80	75.41	3.411		
5,000.00	2,532.00	5,188.91	2,730.00	55.53	55.49	140.34	2,873.67	-12.19	257.19	179.10	78.08	3.294		
5,100.00	2,532.00	5,288.91	2,730.00	57.42	57.38	140.35	2,973.67	-12.21	257.16	176.40	80.76	3.184		
5,200.00	2,532.00	5,388.91	2,730.00	59.31	59.27	140.36	3,073.67	-12.22	257.14	173.69	83.44	3.082		
5,300.00	2,532.00	5,488.91	2,730.00	61.20	61.16	140.36	3,173.67	-12.24	257.11	170.99	86.12	2.985		
5,400.00	2,532.00	5,588.91	2,730.00	63.09	63.05	140.37	3,273.67	-12.25	257.08	168.28	88.81	2.895		
5,500.00	2,532.00	5,688.91	2,730.00	64.99	64.94	140.38	3,373.67	-12.26	257.06	165.57	91.49	2.810		
5,600.00	2,532.00	5,788.91	2,730.00	66.88	66.84	140.38	3,473.67	-12.28	257.03	162.86	94.18	2.729		
5,700.00	2,532.00	5,888.91	2,730.00	68.78	68.73	140.39	3,573.67	-12.29	257.01	160.14	96.86	2.653		
5,800.00	2,532.00	5,988.91	2,730.00	70.68	70.63	140.40	3,673.67	-12.31	256.98	157.43	99.55	2.581		
5,900.00	2,532.00	6,088.91	2,730.00	72.58	72.53	140.40	3,773.67	-12.32	256.95	154.71	102.24	2.513		

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation.

<b>Company:</b>	Percussion Petroleum, LLC	<b>Local Co-ordinate Reference:</b>	Well #10H - Slot 10
<b>Project:</b>	Eddy County, NM	<b>TVD Reference:</b>	RKB = 17' @ 3492.00usft
<b>Reference Site:</b>	Osage Boyd 15 FED COM	<b>MD Reference:</b>	RKB = 17' @ 3492.00usft
<b>Site Error:</b>	0.00 usft	<b>North Reference:</b>	Grid
<b>Reference Well:</b>	#10H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Well Error:</b>	0.00 usft	<b>Output errors are at</b>	2:00 sigma
<b>Reference Wellbore</b>	OH	<b>Database:</b>	WBDS_SQL_2
<b>Reference Design:</b>	Plan #1	<b>Offset TVD Reference:</b>	Reference Datum

Offset Design: Osage Boyd 15 FED COM - #11H - OH - Plan #1													Offset Site Error:	0.00 usft
Survey Program: 0-MVD-HGRF													Offset Well Error:	0.00 usft
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Semi-Major Axis			Highside Toolface (°)	Offset Wellbore Centre		Distance		Minimum Separation (usft)	Separation Factor	Warning
				Reference (usft)	Offset (usft)	Reference (usft)		Offset (usft)	N-S (usft)	E-W (usft)	Between Centres (usft)			
6,000.00	2,532.00	6,188.91	2,730.00	74.47	74.43	140.41	3,873.67	-12.33	256.93	152.00	104.93	2.449		
6,100.00	2,532.00	6,288.91	2,730.00	76.37	76.33	140.42	3,973.67	-12.35	256.90	149.28	107.62	2.387		
6,200.00	2,532.00	6,388.91	2,730.00	78.28	78.23	140.43	4,073.67	-12.36	256.88	146.57	110.31	2.329		
6,300.00	2,532.00	6,488.91	2,730.00	80.18	80.13	140.43	4,173.67	-12.38	256.85	143.85	113.00	2.273		
6,400.00	2,532.00	6,588.91	2,730.00	82.08	82.03	140.44	4,273.67	-12.39	256.83	141.13	115.69	2.220		
6,500.00	2,532.00	6,688.91	2,730.00	83.98	83.94	140.45	4,373.67	-12.40	256.80	138.41	118.38	2.169		
6,600.00	2,532.00	6,788.91	2,730.00	85.89	85.84	140.45	4,473.67	-12.42	256.77	135.70	121.08	2.121		
6,700.00	2,532.00	6,888.91	2,730.00	87.79	87.74	140.46	4,573.67	-12.43	256.75	132.98	123.77	2.074		
6,800.00	2,532.00	6,988.91	2,730.00	89.69	89.65	140.47	4,673.67	-12.44	256.72	130.26	126.46	2.030		
6,900.00	2,532.00	7,088.91	2,730.00	91.60	91.55	140.47	4,773.67	-12.46	256.70	127.54	129.15	1.988		
6,999.70	2,532.00	7,188.61	2,730.00	93.50	93.45	140.48	4,873.37	-12.47	256.67	124.83	131.84	1.947		
7,000.60	2,532.00	7,188.51	2,730.00	93.52	93.47	140.48	4,874.27	-12.47	256.67	124.81	131.86	1.946		
7,080.98	2,530.85	7,269.89	2,730.00	95.05	95.00	140.62	4,954.64	-12.48	257.60	123.86	133.74	1.926		
7,100.00	2,530.31	7,288.89	2,730.00	95.41	95.36	140.69	4,973.65	-12.49	258.04	123.92	134.12	1.924		
7,200.00	2,527.49	7,388.85	2,730.00	97.32	97.27	141.05	5,073.61	-12.50	260.35	124.26	136.09	1.913		
7,300.00	2,524.66	7,488.81	2,730.00	99.23	99.17	141.41	5,173.57	-12.51	262.68	124.63	138.05	1.903		
7,400.00	2,521.83	7,588.77	2,730.00	101.13	101.08	141.75	5,273.53	-12.53	265.02	125.03	139.99	1.893		
7,500.00	2,519.01	7,688.73	2,730.00	103.04	102.98	142.10	5,373.49	-12.54	267.36	125.45	141.91	1.884		
7,600.00	2,516.18	7,788.69	2,730.00	104.95	104.89	142.43	5,473.45	-12.56	269.72	125.90	143.82	1.875		
7,700.00	2,513.35	7,888.65	2,730.00	106.86	106.80	142.76	5,573.41	-12.57	272.08	126.36	145.72	1.867		
7,800.00	2,510.52	7,988.61	2,730.00	108.77	108.71	143.09	5,673.37	-12.58	274.46	126.85	147.60	1.859		
7,885.98	2,508.09	8,074.56	2,730.00	110.41	110.35	143.36	5,759.32	-12.60	276.51	127.29	149.21	1.853		
7,900.00	2,507.73	8,088.57	2,730.00	110.68	110.61	143.41	5,773.33	-12.60	276.81	127.33	149.48	1.852		
7,972.32	2,506.95	8,160.87	2,730.00	112.06	111.99	143.50	5,845.63	-12.60	277.46	126.31	151.15	1.836		
8,002.50	2,507.00	8,191.04	2,730.00	112.64	112.57	143.50	5,875.80	-12.60	277.41	125.47	151.94	1.826 SF		



Anticollision Report



Company:	Percussion Petroleum, LLC	Local Co-ordinate Reference:	Well #10H - Slot 10
Project:	Eddy County, NM	TVD/Reference:	RKB = 17' @ 3492.00usft
Reference Site:	Osage Boyd 15 FED COM	MD/Reference:	RKB = 17' @ 3492.00usft
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	#10H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.00 usft	Output errors are at:	2.00 sigma
Reference Wellbore:	OH	Database:	WBDS_SQL_2
Reference Design:	Plan #1	Offset TVD/Reference:	Reference Datum

Offset Design Osage Boyd 15 FED COM - #9H - OH - Plan #1													Offset Site Error:	0.00 usft
Survey Program: 0-MWD-IGRF													Offset Well Error:	0.00 usft
Reference	Vertical	Measured	Vertical	Semi Major	Offset	Highside	Offset Wellbore	Distance		Minimum	Separation	Warning		
Depth	Depth	Depth	Depth	Reference	Reference	Toolface	Centre	Between	Between	Separation	Factor			
(usft)	(usft)	(usft)	(usft)	(usft)	(usft)	(°)	+N/S	-E/W	Centres	Ellipses	(usft)			
							(usft)	(usft)	(usft)	(usft)	(usft)			
0.00	0.00	0.00	0.00	0.00	0.00	-89.43	0.20	-20.00	20.00					
100.00	100.00	100.00	100.00	0.15	0.15	-89.43	0.20	-20.00	20.00	19.70	0.30	67.223		
200.00	200.00	200.00	200.00	0.51	0.51	-89.43	0.20	-20.00	20.00	18.99	1.01	19.716		
300.00	300.00	300.00	300.00	0.87	0.87	-89.43	0.20	-20.00	20.00	18.27	1.73	11.552		
350.00	350.00	350.00	350.00	1.04	1.04	-89.43	0.20	-20.00	20.00	17.91	2.09	9.570 CC		
400.00	400.00	399.72	399.71	1.22	1.22	-53.82	0.45	-20.35	-20.10	17.65	2.44	8.220 ES		
500.00	499.93	499.14	499.07	1.58	1.58	-56.00	2.47	-23.15	-20.88	17.72	3.15	6.821		
600.00	599.68	598.54	598.22	1.95	1.94	-59.88	6.50	-28.74	-22.52	18.65	3.87	5.819		
700.00	699.13	697.89	697.04	2.32	2.31	-64.70	12.54	-37.11	-25.14	20.53	4.61	5.457		
787.31	785.62	784.59	782.92	2.67	2.66	-69.08	19.44	-46.99	-28.31	23.03	5.28	5.361		
800.00	798.16	797.18	795.37	2.72	2.71	-69.66	20.57	-48.25	-28.86	23.48	5.38	5.362		
900.00	896.99	893.26	893.51	3.14	3.16	-71.54	30.34	-61.81	-34.09	27.86	6.22	5.478		
1,000.00	995.83	1,003.41	991.88	3.57	3.61	-72.46	40.37	-75.71	-39.57	32.50	7.06	5.603		
1,100.00	1,094.67	1,096.43	1,090.24	4.00	4.03	-73.16	50.40	-89.62	-45.06	37.17	7.89	5.714		
1,200.00	1,193.50	1,203.72	1,188.61	4.44	4.52	-73.71	60.42	-103.52	-50.55	41.77	8.78	5.758		
1,300.00	1,292.34	1,303.87	1,288.97	4.88	4.98	-74.15	70.45	-117.43	-56.05	46.40	9.65	5.807		
1,400.00	1,391.18	1,404.02	1,385.34	5.32	5.44	-74.51	80.48	-131.33	-61.55	51.02	10.53	5.846		
1,500.00	1,490.02	1,504.18	1,483.70	5.76	5.91	-74.81	90.50	-145.24	-67.05	55.64	11.41	5.877		
1,600.00	1,588.85	1,604.33	1,582.07	6.21	6.38	-75.07	100.53	-159.14	-72.55	60.26	12.29	5.902		
1,700.00	1,687.69	1,704.48	1,680.43	6.65	6.85	-75.29	110.55	-173.05	-78.06	64.88	13.18	5.922		
1,800.00	1,786.53	1,795.37	1,778.80	7.10	7.28	-75.48	120.58	-186.95	-83.56	69.53	14.03	5.956		
1,900.00	1,885.36	1,904.78	1,877.16	7.55	7.80	-75.64	130.61	-200.88	-89.07	74.11	14.96	5.953		
2,000.00	1,984.20	1,995.06	1,975.53	8.00	8.22	-75.79	140.63	-214.76	-94.58	78.77	15.81	5.982		
2,048.00	2,031.65	2,042.99	2,022.75	8.21	8.45	-75.86	145.44	-221.44	-97.22	80.98	16.24	5.987		
2,050.00	2,033.62	2,044.99	2,024.71	8.22	8.46	-75.60	145.65	-221.71	-97.33	81.08	16.26	5.987		
2,100.00	2,082.68	2,094.79	2,073.77	8.47	8.70	-80.04	150.65	-228.65	-100.99	84.24	16.76	6.027		
2,150.00	2,130.82	2,144.09	2,122.34	8.74	8.93	-88.96	155.60	-235.51	-106.56	89.22	17.34	6.145		
2,200.00	2,177.66	2,207.47	2,170.06	9.05	9.23	-106.58	160.46	-242.26	-114.59	96.54	18.05	6.350		
2,250.00	2,222.86	2,239.73	2,216.56	9.38	9.38	-113.59	165.20	-248.83	-125.78	107.15	18.62	6.754		
2,300.00	2,266.07	2,285.33	2,261.49	9.76	9.60	-119.93	169.78	-255.18	-140.72	121.49	19.23	7.316		
2,350.00	2,306.96	2,328.99	2,304.50	10.18	9.81	-125.42	174.16	-261.26	-159.78	140.00	19.78	8.078		
2,400.00	2,345.22	2,370.37	2,345.27	10.63	10.01	-129.95	178.32	-267.03	-183.06	162.81	20.25	9.038		
2,450.00	2,380.56	2,417.05	2,391.19	11.13	10.23	-134.41	183.55	-273.52	-210.13	189.41	20.72	10.142		
2,500.00	2,412.71	2,476.47	2,448.86	11.68	10.55	-138.96	195.12	-281.67	-238.20	217.04	21.16	11.255		
2,550.00	2,441.42	2,542.29	2,511.00	12.26	10.94	-142.71	214.90	-290.44	-266.13	244.65	21.48	12.390		
2,600.00	2,466.48	2,616.17	2,577.52	12.89	11.43	-145.85	245.49	-299.83	-293.19	271.58	21.61	13.569		
2,650.00	2,487.70	2,700.01	2,647.58	13.56	12.06	-148.50	290.33	-309.72	-318.58	297.11	21.46	14.842		
2,700.00	2,504.91	2,795.81	2,718.71	14.27	12.89	-150.70	353.55	-319.74	-341.31	320.35	20.96	16.282		
2,750.00	2,517.98	2,905.07	2,785.81	15.00	14.01	-152.45	439.05	-329.18	-360.22	340.20	20.02	17.992		
2,800.00	2,526.82	3,027.71	2,840.47	15.76	15.48	-153.69	548.31	-336.85	-373.99	355.32	18.67	20.037		
2,850.00	2,531.35	2,850.00	2,868.60	16.54	13.35	-154.23	654.74	-340.77	-381.26	365.83	15.43	24.708		
2,877.25	2,532.00	3,235.54	2,877.00	16.97	18.36	-154.44	751.68	-341.90	-382.43	366.02	16.40	23.312		
2,879.73	2,532.00	2,879.73	2,876.76	17.01	13.73	-154.43	742.51	-341.87	-382.35	368.50	13.85	27.612		
2,900.00	2,532.00	3,257.50	2,877.00	17.33	18.69	-154.44	773.74	-341.89	-382.42	365.61	16.81	22.750		
3,000.00	2,532.00	3,357.80	2,877.00	18.96	20.21	-154.45	873.74	-341.83	-382.41	363.83	18.58	20.586		
3,100.00	2,532.00	3,457.60	2,877.00	20.64	21.79	-154.45	973.74	-341.77	-382.40	361.98	20.42	18.728		
3,200.00	2,532.00	3,557.60	2,877.00	22.36	23.42	-154.45	1,073.74	-341.72	-382.38	360.06	22.32	17.132		
3,300.00	2,532.00	3,657.60	2,877.00	24.10	25.09	-154.46	1,173.74	-341.66	-382.37	358.10	24.27	15.756		
3,400.00	2,532.00	3,757.60	2,877.00	25.87	26.80	-154.46	1,273.74	-341.60	-382.36	356.11	26.25	14.565		
3,500.00	2,532.00	3,857.60	2,877.00	27.66	28.53	-154.47	1,373.74	-341.55	-382.35	354.08	28.26	13.528		
3,600.00	2,532.00	3,957.60	2,877.00	29.47	30.28	-154.47	1,473.74	-341.49	-382.33	352.04	30.30	12.620		
3,700.00	2,532.00	4,057.60	2,877.00	31.29	32.06	-154.47	1,573.74	-341.43	-382.32	349.97	32.35	11.819		

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation.

<b>Company:</b>	Percussion Petroleum, LLC	<b>Local Co-ordinate Reference:</b>	Well #10H - Slot 10
<b>Project:</b>	Eddy County, NM	<b>TVD Reference:</b>	RKB = 17' @ 3492.00usft
<b>Reference Site:</b>	Osage Boyd 15 FED COM	<b>MD Reference:</b>	RKB = 17' @ 3492.00usft
<b>Site Error:</b>	0.00 usft	<b>North Reference:</b>	Grid
<b>Reference Well:</b>	#10H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Well Error:</b>	0.00 usft	<b>Output errors are at</b>	2.00 sigma
<b>Reference Wellbore:</b>	OH	<b>Database:</b>	WBDS_SQL_2
<b>Reference Design:</b>	Plan #1	<b>Offset TVD Reference:</b>	Reference Datum


Offset Design   Osage Boyd 15 FED.COM - #9H - OH - Plan #1													Offset Site Error:	0.00 usft
Survey Program: 0-MWD-HGRF													Offset Well Error:	0.00 usft
Measured Depth (usft)	Vertical Depth (usft)	Offset		Semi Major Axis		Highside Toolface (°)	Offset Wellbore Centre		Distance		Minimum Separation (usft)	Separation Factor	Warning	
		Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)		N/S (usft)	E/W (usft)	Between Centres (usft)	Between Ellipses (usft)				
3,800.00	2,532.00	4,157.60	2,877.00	33.12	33.85	-154.48	1,673.74	-341.38	382.31	347.89	34.41	11.109		
3,900.00	2,532.00	4,257.60	2,877.00	34.96	35.65	-154.48	1,773.74	-341.32	382.29	345.80	36.49	10.476		
4,000.00	2,532.00	4,357.60	2,877.00	36.81	37.46	-154.49	1,873.74	-341.27	382.28	343.70	38.58	9.909		
4,100.00	2,532.00	4,457.60	2,877.00	38.66	39.28	-154.49	1,973.74	-341.21	382.27	341.59	40.68	9.397		
4,200.00	2,532.00	4,557.60	2,877.00	40.52	41.11	-154.49	2,073.74	-341.15	382.26	339.47	42.78	8.935		
4,300.00	2,532.00	4,657.60	2,877.00	42.38	42.95	-154.50	2,173.74	-341.10	382.24	337.35	44.89	8.514		
4,400.00	2,532.00	4,757.60	2,877.00	44.25	44.79	-154.50	2,273.74	-341.04	382.23	335.22	47.01	8.131		
4,500.00	2,532.00	4,857.60	2,877.00	46.12	46.65	-154.51	2,373.74	-340.98	382.22	333.09	49.13	7.780		
4,600.00	2,532.00	4,957.60	2,877.00	48.00	48.50	-154.51	2,473.74	-340.93	382.20	330.95	51.25	7.457		
4,700.00	2,532.00	5,057.60	2,877.00	49.88	50.36	-154.51	2,573.74	-340.87	382.19	328.81	53.38	7.160		
4,800.00	2,532.00	5,157.60	2,877.00	51.76	52.22	-154.52	2,673.74	-340.81	382.18	326.67	55.51	6.885		
4,900.00	2,532.00	5,257.60	2,877.00	53.64	54.09	-154.52	2,773.74	-340.76	382.17	324.52	57.65	6.630		
5,000.00	2,532.00	5,357.60	2,877.00	55.53	55.96	-154.53	2,873.74	-340.70	382.15	322.37	59.78	6.392		
5,100.00	2,532.00	5,457.60	2,877.00	57.42	57.84	-154.53	2,973.74	-340.64	382.14	320.22	61.92	6.172		
5,200.00	2,532.00	5,557.60	2,877.00	59.31	59.71	-154.53	3,073.74	-340.59	382.13	318.07	64.06	5.965		
5,300.00	2,532.00	5,657.60	2,877.00	61.20	61.59	-154.54	3,173.74	-340.53	382.11	315.91	66.20	5.772		
5,400.00	2,532.00	5,757.60	2,877.00	63.09	63.47	-154.54	3,273.74	-340.47	382.10	313.76	68.34	5.591		
5,500.00	2,532.00	5,857.60	2,877.00	64.99	65.36	-154.55	3,373.74	-340.42	382.09	311.60	70.49	5.421		
5,600.00	2,532.00	5,957.60	2,877.00	66.88	67.24	-154.55	3,473.74	-340.36	382.08	309.44	72.63	5.260		
5,700.00	2,532.00	6,057.60	2,877.00	68.78	69.13	-154.55	3,573.74	-340.30	382.06	307.28	74.78	5.109		
5,800.00	2,532.00	6,157.60	2,877.00	70.68	71.01	-154.56	3,673.74	-340.25	382.05	305.12	76.93	4.966		
5,900.00	2,532.00	6,257.60	2,877.00	72.58	72.90	-154.56	3,773.74	-340.19	382.04	302.96	79.07	4.831		
6,000.00	2,532.00	6,357.60	2,877.00	74.47	74.79	-154.57	3,873.74	-340.13	382.03	300.80	81.22	4.703		
6,100.00	2,532.00	6,462.58	2,876.66	76.37	76.78	-154.54	3,978.72	-340.12	381.76	298.44	83.31	4.582		
6,200.00	2,532.00	6,562.86	2,875.03	78.28	78.68	-154.42	4,078.99	-340.26	380.36	294.69	85.67	4.440		
6,300.00	2,532.00	6,662.84	2,873.41	80.18	80.58	-154.29	4,178.96	-340.40	378.97	290.92	88.05	4.304		
6,400.00	2,532.00	6,762.83	2,871.79	82.08	82.47	-154.16	4,278.94	-340.53	377.58	287.14	90.44	4.175		
6,500.00	2,532.00	6,862.82	2,870.17	83.98	84.37	-154.03	4,378.91	-340.67	376.20	283.36	92.84	4.052		
6,600.00	2,532.00	6,962.80	2,868.54	85.89	86.27	-153.89	4,478.88	-340.81	374.81	279.55	95.26	3.935		
6,700.00	2,532.00	7,062.79	2,866.92	87.79	88.17	-153.76	4,578.86	-340.95	373.43	275.74	97.68	3.823		
6,800.00	2,532.00	7,162.78	2,865.30	89.69	90.07	-153.63	4,678.83	-341.09	372.05	271.92	100.12	3.716		
6,900.00	2,532.00	7,262.76	2,863.67	91.60	91.97	-153.49	4,778.80	-341.23	370.67	268.09	102.58	3.614		
6,999.70	2,532.00	7,362.45	2,862.06	93.50	93.86	-153.36	4,878.48	-341.37	369.29	264.26	105.04	3.516		
7,045.90	2,531.63	7,408.65	2,861.31	94.38	94.74	-153.33	4,924.67	-341.44	368.98	262.86	106.12	3.477		
7,080.98	2,530.85	7,443.73	2,860.74	95.05	95.41	-153.35	4,959.74	-341.49	368.16	262.29	106.87	3.454		
7,100.00	2,530.31	7,462.75	2,860.43	95.41	95.77	-153.36	4,978.76	-341.51	369.36	262.11	107.25	3.444		
7,200.00	2,527.49	7,562.74	2,858.81	97.32	97.67	-153.46	5,078.74	-341.65	370.40	261.13	109.27	3.390		
7,300.00	2,524.66	7,662.73	2,857.18	99.23	99.57	-153.55	5,178.72	-341.79	371.45	260.16	111.29	3.338		
7,400.00	2,521.83	7,762.73	2,855.56	101.13	101.48	-153.64	5,278.70	-341.93	372.50	259.20	113.29	3.288		
7,500.00	2,519.01	7,862.72	2,853.94	103.04	103.38	-153.73	5,378.68	-342.07	373.55	258.25	115.30	3.240		
7,600.00	2,516.18	7,962.71	2,852.31	104.95	105.28	-153.82	5,478.66	-342.21	374.60	257.30	117.30	3.194		
7,700.00	2,513.35	8,062.70	2,850.69	106.86	107.19	-153.91	5,578.63	-342.35	375.65	256.36	119.29	3.149		
7,800.00	2,510.52	8,162.70	2,849.07	108.77	109.09	-154.00	5,678.61	-342.49	376.70	255.42	121.28	3.106		
7,885.98	2,508.09	8,248.67	2,847.67	110.41	110.73	-154.08	5,764.58	-342.61	377.60	254.62	122.98	3.070		
7,900.00	2,507.73	8,262.69	2,847.45	110.68	111.00	-154.09	5,778.59	-342.63	377.72	254.45	123.27	3.064		
7,972.32	2,506.95	8,329.61	2,846.78	112.06	112.27	-154.10	5,845.51	-342.66	377.79	252.85	124.94	3.024		
7,975.92	2,506.95	8,332.85	2,846.79	112.13	112.34	-154.10	5,848.75	-342.66	377.79	252.77	125.02	3.022		
8,002.50	2,507.00	8,357.47	2,846.93	112.64	112.80	-154.11	5,873.37	-342.62	377.87	252.26	125.61	3.008	SF	

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

Company:	Percussion Petroleum, LLC	Local Co-ordinate Reference:	Well #10H - Slot 10
Project:	Eddy County, NM	TVD Reference:	RKB = 17' @ 3492.00usft
Reference Site:	Osage Boyd 15 FED COM	MD Reference:	RKB = 17' @ 3492.00usft
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	#10H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.00 usft	Output errors are at:	2.00 sigma
Reference Wellbore:	OH	Database:	WBDS_SQL_2
Reference Design:	Plan #1	Offset TVD Reference:	Reference Datum

Reference Depths are relative to RKB = 17' @ 3492.00usft  
 Offset Depths are relative to Offset Datum  
 Central Meridian is -104:333334

Coordinates are relative to: #10H - Slot 10  
 Coordinate System is US State Plane, 1983, New Mexico Eastern Zone  
 Grid Convergence at Surface is -0.08°



**LEGEND**

□ OH, Oh, Rsp #1 VO      ◆ OH, Oh, Rsp #1 VO


CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

Company:	Percussion Petroleum, LLC	Local Coordinate Reference:	Well #10H - Slot 10
Project:	Eddy County, NM	TVD Reference:	RKB = 17' @ 3492.00usft
Reference Site:	Osage Boyd 15 FED COM	MD Reference:	RKB = 17' @ 3492.00usft
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	#10H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.00 usft	Output errors are at:	2.00 sigma
Reference Wellbore:	OH	Database:	WBDS_SQL_2
Reference Design:	Plan #1	Offset TVD Reference:	Reference Datum

Reference Depths are relative to RKB = 17' @ 3492.00usft  
 Offset Depths are relative to Offset Datum  
 Central Meridian is -104.333334

Coordinates are relative to #10H - Slot 10  
 Coordinate System is US State Plane 1983, New Mexico Eastern Zone  
 Grid Convergence at Surface is -0.08°

### Separation Factor Plot



**LEGEND**

—■— OH, Plan #1, MD      —●— #10H, OH, Plan #1, MD

Percussion Petroleum Operating, LLC  
Osage Boyd 15 Federal Com 10H  
SHL: 649' FNL & 701' FWL 22-19S-25E  
BHL: 20' FNL & 525' FWL 15-19S-25E  
Eddy County, NM

DRILL PLAN PAGE 1

Drilling Program

1. ESTIMATED TOPS

Formation/Lithology	TVD	MD	Contents
Quaternary caliche	000'	000'	water
Grayburg dolomite	605'	605'	hydrocarbons
San Andres dolomite	790'	792'	hydrocarbons
(KOP	2032'	2393'	hydrocarbons)
Glorieta silty dolomite	2350'	2357'	hydrocarbons
Yeso dolomite	2505'	2700'	hydrocarbons
TD	2507'	8003'	hydrocarbons

2. NOTABLE ZONES

Glorieta and Yeso are the goals. Closest water well (RA 02909) is 2755' south. Water bearing strata were found at 120' in this 188' deep well.

3. PRESSURE CONTROL

A 3000-psi 5000' rated BOP stack consisting of annular preventer and double (blind and pipe) ram will be used below surface casing to TD. See attached BOP and choke manifold diagrams.

Pressure tests will be conducted before drilling out from under all casing strings. Third party test crews will conduct all tests. All tests will be recorded for 10-minutes on low pressure (500 psi) and 10-minutes on high pressure (3000-psi). After BOP testing is complete, test casing (without test plug) to 2000-psi for 30 minutes. All tests will be charted on a plot. BOPs will be function tested every day.

Percussion Petroleum Operating, LLC  
 Osage Boyd 15 Federal Com 10H  
 SHL: 649' FNL & 701' FWL 22-19S-25E  
 BHL: 20' FNL & 525' FWL 15-19S-25E  
 Eddy County, NM

DRILL PLAN PAGE 2

4. CASING & CEMENT

All casing will be API and new. A contingency plan is attached.

Hole O. D.	Set MD	Set TVD	Casing O. D.	Weight (lb/ft)	Grade	Joint	Collapse	Burst	Tension
12.25"	0' - 1279'	0' - 1271'	Surface 9.625"	36	J-55	LTC	1.125	1.125	1.8
8.75"	0' - 2275'	0' - 2245'	Prod. 1 7"	32	L-80	BTC	1.125	1.125	1.8
8.75"	2275' - 8003'	2245' - 2507'	Prod. 2 5.5"	17	L-80	BTC	1.125	1.125	1.8

Casing Name	Type	Sacks	Yield	Cu. Ft.	Weight	Blend
Surface	Lead	637	1.32	840	14.8	Class C + 2% CaCl + ¼ pound per sack celloflake
TOC = GL		100% Excess			Stop collar 10' above shoe with centralizer. One on 1st collar and every 4 <sup>th</sup> collar to GL.	
Production	Lead	495	1.97	975	12.6	65/65/6 Class C + 6% gel + 5% salt + ¼ pound per sack celloflake + 0.2% C41-P
	Tail	1332	1.32	1758	14.8	Class C + 2% CaCl + ¼ pound per sack celloflake
TOC = GL		50% Excess			Stop collar 10' above shoe with centralizer. One on 1st collar and every 10 collars to 1200' with 1 centralizer in 9.625" casing.	

5. MUD PROGRAM

An electronic/mechanical mud monitor with a minimum pit volume totalizer, stroke counter, and flow sensor will be used. All necessary mud products (LCM) will be on site to handle any abnormal hole condition that may be encountered while drilling this well. A closed loop system will be used.

Percussion Petroleum Operating, LLC  
Osage Boyd 15 Federal Com 10H  
SHL: 649' FNL & 701' FWL 22-19S-25E  
BHL: 20' FNL & 525' FWL 15-19S-25E  
Eddy County, NM

DRILL PLAN PAGE 3

Type	Interval (MD)	lb/gal	Viscosity	Fluid Loss	Plastic Viscosity	Yield Point
fresh water/gel	0' - 1279'	8.4 - 9.2	36-42	NC	3-5	5-7
fresh water/cut brine	1279' - 2049'	8.3 - 9.2	28-30	NC	1	1
cut brine	2049' - 8003'	8.6 - 9.2	29-32	NC	4-5	6-10

## 6. CORES, TESTS, & LOGS

No core or drill stem test is planned.

A mud logger will be used from GL to TD. Samples will be collected every 10' in the lateral pay zone.

No electric logs are planned at this time.

## 7. DOWN HOLE CONDITIONS

No abnormal pressure or temperature is expected. Maximum expected bottom hole pressure is  $\approx 1083$  psi. Expected bottom hole temperature is  $\approx 108$  F.

A Hydrogen Sulfide Drilling Operation Plan is attached.

## 8. OTHER INFORMATION

Anticipated spud date is upon approval. It is expected it will take  $\approx 1$  month to drill and complete the well.

St. Devote LLC has operating rights in NMNM-012833. St. Devote LLC is a subsidiary of Percussion.

## Contingency Planning – Osage Federal Area Wells

Prepared by Lelan J. Anders, Percussion Petroleum Operating, LLC.

### INTRODUCTION:

This document is designed to address the issues that could arise at any time drilling horizontal Yeso wells. Percussion Petroleum Operating (PPO) is going to follow regularly used practices and procedures in order to drill the wells to TD and still keep them economical to operate.

### SCENARIO:

If a complete loss of circulation occurs while drilling above 400 ft MD:

### CORRECTIVE ACTIONS:

1. Pump an LCM sweep and attempt to regain circulation – if unsuccessful go to step 2
2. Continue drilling at attempt to seal off lost circulation zone with drill cuttings
  1. Monitor torque and drag on drill string to determine if pipe is sticking
  2. Have contingency plan to "drill dry" – have plenty of water on hand and well control in place
  3. Continue to "dry drill" until torque and drag dictate a different plan
3. If "dry drilling" is unsuccessful – Run contingency surface casing string
  1. Ream out 12-1/4" open hole to 17-1/2" open hole
  2. Run contingency 13-3/8" 48# H-40, STC casing to no more than 400' MD
  3. Cement 13-3/8" casing using Class C cement
    - i. Pump at minimum 200% excess cement
      1. 400 sks 65/35/6 Class C Cement, 12.8 ppg, 1.87 yield, 10.15 gal/sk to be used on initial cement job.
    - ii. Top off cement from surface using 1" if necessary
      1. Top off will be 200 sks of 65/35/6 Class C Cement, 12.8 ppg, 1.87 yield, 10.15 gal/sk
      2. Second top off will be performed with same cement if needed.
    - iii. Insure that cement has cured for a minimum of 12 hours prior to drilling out
  4. Install 13-3/8" 3M wellhead and drill to surface casing depth with 12-1/4" OD bit
  5. Run and cement surface casing as planned



APD ID: 10400035989

Submission Date: 11/05/2018

Highlighted data  
reflects the most  
recent changes.

Operator Name: PERCUSSION PETROLEUM OPERATING LLC

Well Name: OSAGE BOYD 15 FEDERAL COM

Well Number: 10H

Show Final Text

Well Type: OIL WELL

Well Work Type: Drill

### Section 1 - Existing Roads

Will existing roads be used? YES

Existing Road Map:

Osage\_10H\_Road\_Map\_20181105111356.pdf

Existing Road Purpose: ACCESS

Row(s) Exist? NO

ROW ID(s)

ID:

Do the existing roads need to be improved? NO

Existing Road Improvement Description:

Existing Road Improvement Attachment:

### Section 2 - New or Reconstructed Access Roads

Will new roads be needed? YES

New Road Map:

Osage\_10H\_New\_Road\_Map\_20181105111415.pdf

New road type: RESOURCE

Length: 1098.6 Feet

Width (ft.): 30

Max slope (%): 0

Max grade (%): 5

Army Corp of Engineers (ACOE) permit required? NO

ACOE Permit Number(s):

New road travel width: 14

New road access erosion control: Crowned and ditched

New road access plan or profile prepared? NO

New road access plan attachment:

Access road engineering design? NO

Access road engineering design attachment:

**Operator Name:** PERCUSSION PETROLEUM OPERATING LLC

**Well Name:** OSAGE BOYD 15 FEDERAL COM

**Well Number:** 10H

**Access surfacing type:** OTHER

**Access topsoil source:** ONSITE

**Access surfacing type description:** Caliche

**Access onsite topsoil source depth:** 6

**Offsite topsoil source description:**

**Onsite topsoil removal process:** Grader

**Access other construction information:**

**Access miscellaneous information:**

**Number of access turnouts:**

**Access turnout map:**

### Drainage Control

**New road drainage crossing:** OTHER

**Drainage Control comments:** Crowned and ditched

**Road Drainage Control Structures (DCS) description:** None

**Road Drainage Control Structures (DCS) attachment:**

### Access Additional Attachments

**Additional Attachment(s):**

### Section 3 - Location of Existing Wells

**Existing Wells Map?** YES

**Attach Well map:**

Osage\_10H\_Well\_Map\_20181105111436.pdf

**Existing Wells description:**

### Section 4 - Location of Existing and/or Proposed Production Facilities

**Submit or defer a Proposed Production Facilities plan?** SUBMIT

**Production Facilities description:** A 1465' long 4" O D. HDPE flow line will be laid parallel to roads on the surface east and southeast to a proposed central tank battery (CTB). CTB will sit on the south side of Percussion's existing three well Ross Ranch Goodman pad. Maximum operating pressure will be 125 psi. A 1393.2' 3-phase raptor safe overhead power line will be built east to tie into an existing power line that serves the Ross Ranch Goodman pad. A 1549.8' long 4" O D. HDPE crude oil line will be laid on the surface from the CTB southwest to an existing crude oil line at Percussion's Ross Ranch 22 #2 pad. Maximum operating pressure will be 125 psi.

**Production Facilities map:**

Osage\_10H\_Production\_Facilities\_20181105111502.pdf

**Operator Name:** PERCUSSION PETROLEUM OPERATING LLC

**Well Name:** OSAGE BOYD 15 FEDERAL COM

**Well Number:** 10H

### Section 5 - Location and Types of Water Supply

#### Water Source Table

**Water source use type:** DUST CONTROL,  
INTERMEDIATE/PRODUCTION CASING, STIMULATION, SURFACE  
CASING

**Water source type:** GW WELL

**Describe type:**

**Source longitude:**

**Source latitude:**

**Source datum:**

**Water source permit type:** PRIVATE CONTRACT

**Source land ownership:** PRIVATE

**Water source transport method:** PIPELINE

**Source transportation land ownership:** PRIVATE

**Water source volume (barrels):** 10000

**Source volume (acre-feet):** 1.288931

**Source volume (gal):** 420000

#### Water source and transportation map:

Osage\_10H\_Water\_Source\_Map\_20181105111552.pdf

**Water source comments:** Water will be piped via temporary 13,500' long surface 10" Kevlar lay flat pipelines (2) from Percussion's existing lined fresh water pond on its own land in NE4 26-19s-25e. Pipeline route will not be bladed or excavated. Route is all private. Route follows existing roads, pads, and pipelines.

**New water well?** NO

#### New Water Well Info

**Well latitude:**

**Well Longitude:**

**Well datum:**

**Well target aquifer:**

**Est. depth to top of aquifer(ft):**

**Est thickness of aquifer:**

**Aquifer comments:**

**Aquifer documentation:**

**Well depth (ft):**

**Well casing type:**

**Well casing outside diameter (in.):**

**Well casing inside diameter (in.):**

**New water well casing?**

**Used casing source:**

**Drilling method:**

**Drill material:**

**Grout material:**

**Grout depth:**

**Casing length (ft.):**

**Casing top depth (ft.):**

**Well Production type:**

**Completion Method:**

**Water well additional information:**

**Operator Name:** PERCUSSION PETROLEUM OPERATING LLC

**Well Name:** OSAGE BOYD 15 FEDERAL COM

**Well Number:** 10H

**State appropriation permit:**

**Additional information attachment:**

### Section 6 - Construction Materials

**Construction Materials description:** NM One Call (811) will be notified before construction starts. Top 6" of soil and brush will be stockpiled north of the pad. V-door will face east. Closed loop drilling system will be used. Caliche will be hauled from existing caliche pit on private land. Arkland caliche pit is in NWNE 23-19s-25e.

**Construction Materials source location attachment:**

Osage\_10H\_Construction\_Methods\_20181105111610.pdf

### Section 7 - Methods for Handling Waste

**Waste type:** DRILLING

**Waste content description:** Drill cuttings, mud, salts, and other chemicals

**Amount of waste:** 1000 barrels

**Waste disposal frequency :** Daily

**Safe containment description:** Steel tanks

**Safe containmant attachment:**

**Waste disposal type:** HAUL TO COMMERCIAL FACILITY **Disposal location ownership:** PRIVATE

**Disposal type description:**

**Disposal location description:** R360's state approved (NM-01-0006) disposal site at Halfway, NM

### Reserve Pit

**Reserve Pit being used?** NO

**Temporary disposal of produced water into reserve pit?**

**Reserve pit length (ft.)** **Reserve pit width (ft.)**

**Reserve pit depth (ft.)** **Reserve pit volume (cu. yd.)**

**Is at least 50% of the reserve pit in cut?**

**Reserve pit liner**

**Reserve pit liner specifications and installation description**

### Cuttings Area

**Cuttings Area being used?** NO

**Are you storing cuttings on location?** YES

**Description of cuttings location** Steel tanks on pad

**Operator Name:** PERCUSSION PETROLEUM OPERATING LLC

**Well Name:** OSAGE BOYD 15 FEDERAL COM

**Well Number:** 10H

**Cuttings area length (ft.)**

**Cuttings area width (ft.)**

**Cuttings area depth (ft.)**

**Cuttings area volume (cu. yd.)**

**Is at least 50% of the cuttings area in cut?**

**WCuttings area liner**

**Cuttings area liner specifications and installation description**

### Section 8 - Ancillary Facilities

**Are you requesting any Ancillary Facilities?:** NO

**Ancillary Facilities attachment:**

**Comments:**

### Section 9 - Well Site Layout

**Well Site Layout Diagram:**

Osage\_10H\_Well\_Site\_Layout\_20181105111629.pdf

**Comments:**

### Section 10 - Plans for Surface Reclamation

**Type of disturbance:** New Surface Disturbance

**Multiple Well Pad Name:** OSAGE BOYD 15 FEDERAL COM

**Multiple Well Pad Number:** 9H

**Recontouring attachment:**

Osage\_10H\_Interim\_Reclamation\_Diagram\_20181105111643.pdf

Osage\_10H\_Recontour\_Plat\_20181105111659.pdf

**Drainage/Erosion control construction:** Crowned and ditched

**Drainage/Erosion control reclamation:** Harrowed on the contour

**Well pad proposed disturbance (acres):** 2.34

**Well pad interim reclamation (acres):** 0.68

**Well pad long term disturbance (acres):** 1.66

**Road proposed disturbance (acres):** 0.76

**Road interim reclamation (acres):** 0

**Road long term disturbance (acres):** 0.76

**Powerline proposed disturbance (acres):** 0.96

**Powerline interim reclamation (acres):** 0.96

**Powerline long term disturbance (acres):** 0

**Pipeline proposed disturbance (acres):** 8.28

**Pipeline interim reclamation (acres):** 8.28

**Pipeline long term disturbance (acres):** 0

**Other proposed disturbance (acres):** 0.55

**Other interim reclamation (acres):** 0

**Other long term disturbance (acres):** 0.55

**Total interim reclamation:** 9.92

**Operator Name:** PERCUSSION PETROLEUM OPERATING LLC

**Well Name:** OSAGE BOYD 15 FEDERAL COM

**Well Number:** 10H

**Total proposed disturbance:** 12.89

**Total long term disturbance:** 2.97

**Disturbance Comments:**

**Reconstruction method:** Interim reclamation will be completed within 6 months of completing the well. Interim reclamation will consist of shrinking the well pad 0.68 acre by removing caliche and reclaiming 50' on the north and west sides of the pad. This will leave 1.66 acres for the anchors, pump jacks, and tractor-trailer turn around. Disturbed areas will be contoured to match pre-construction grades. Soil and brush will be evenly spread over disturbed areas and harrowed on the contour. Disturbed areas will be seeded in accordance with surface owner's requirements.

**Topsoil redistribution:** Enough stockpiled topsoil will be retained to cover the remainder of the pad when the well is plugged. Once the last well is plugged, then the rest of the pad will be similarly reclaimed within 6 months of plugging. Noxious weeds will be controlled.

**Soil treatment:** None

**Existing Vegetation at the well pad:**

**Existing Vegetation at the well pad attachment:**

**Existing Vegetation Community at the road:**

**Existing Vegetation Community at the road attachment:**

**Existing Vegetation Community at the pipeline:**

**Existing Vegetation Community at the pipeline attachment:**

**Existing Vegetation Community at other disturbances:**

**Existing Vegetation Community at other disturbances attachment:**

**Non native seed used?** NO

**Non native seed description:**

**Seedling transplant description:**

**Will seedlings be transplanted for this project?** NO

**Seedling transplant description attachment:**

**Will seed be harvested for use in site reclamation?** NO

**Seed harvest description:**

**Seed harvest description attachment:**

**Seed Management**

**Seed Table**

**Operator Name:** PERCUSSION PETROLEUM OPERATING LLC

**Well Name:** OSAGE BOYD 15 FEDERAL COM

**Well Number:** 10H

**Seed type:**

**Seed source:**

**Seed name:**

**Source name:**

**Source address:**

**Source phone:**

**Seed cultivar:**

**Seed use location:**

**PLS pounds per acre:**

**Proposed seeding season:**

Seed Summary	
Seed Type	Pounds/Acre

**Total pounds/Acre:**

**Seed reclamation attachment:**

**Operator Contact/Responsible Official Contact Info**

**First Name:**

**Last Name:**

**Phone:**

**Email:**

**Seedbed prep:**

**Seed BMP:**

**Seed method:**

**Existing invasive species?** NO

**Existing invasive species treatment description:**

**Existing invasive species treatment attachment:**

**Weed treatment plan description:** To BLM standards

**Weed treatment plan attachment:**

**Monitoring plan description:** To BLM standards

**Monitoring plan attachment:**

**Success standards:** To BLM satisfaction

**Pit closure description:** No pit

**Pit closure attachment:**

**Section 11 - Surface Ownership**

**Operator Name:** PERCUSSION PETROLEUM OPERATING LLC

**Well Name:** OSAGE BOYD 15 FEDERAL COM

**Well Number:** 10H

**Disturbance type:** PIPELINE

**Describe:**

**Surface Owner:** PRIVATE OWNERSHIP

**Other surface owner description:**

**BIA Local Office:**

**BOR Local Office:**

**COE Local Office:**

**DOD Local Office:**

**NPS Local Office:**

**State Local Office:**

**Military Local Office:**

**USFWS Local Office:**

**Other Local Office:**

**USFS Region:**

**USFS Forest/Grassland:**

**USFS Ranger District:**

**Fee Owner:** Jerome Hugh Jones

**Phone:** (575)365-4797

**Surface use plan certification:** NO

**Surface use plan certification document:**

**Surface access agreement or bond:** Agreement

**Surface Access Agreement Need description:** See attached

**Surface Access Bond BLM or Forest Service:**

**BLM Surface Access Bond number:**

**USFS Surface access bond number:**

**Fee Owner Address:** c/o Ross Ranch PO Box 216  
Lakewood NM 88254

**Email:**

**Disturbance type:** PIPELINE

**Describe:**

**Surface Owner:** PRIVATE OWNERSHIP

**Other surface owner description:**

**BIA Local Office:**

**Operator Name:** PERCUSSION PETROLEUM OPERATING LLC

**Well Name:** OSAGE BOYD 15 FEDERAL COM

**Well Number:** 10H

**BOR Local Office:**

**COE Local Office:**

**DOD Local Office:**

**NPS Local Office:**

**State Local Office:**

**Military Local Office:**

**USFWS Local Office:**

**Other Local Office:**

**USFS Region:**

**USFS Forest/Grassland:**

**USFS Ranger District:**

**Fee Owner:** Ross & Barbara Whitney

**Phone:** (816)525-1233

**Surface use plan certification:** NO

**Surface use plan certification document:**

**Surface access agreement or bond:** Agreement

**Surface Access Agreement Need description:** See attached

**Surface Access Bond BLM or Forest Service:**

**BLM Surface Access Bond number:**

**USFS Surface access bond number:**

**Fee Owner Address:** 25601 E. 130th Street Greenwood  
MO 64034

**Email:**

**Disturbance type:** WELL PAD

**Describe:**

**Surface Owner:** PRIVATE OWNERSHIP

**Other surface owner description:**

**BIA Local Office:**

**BOR Local Office:**

**COE Local Office:**

**DOD Local Office:**

**NPS Local Office:**

**State Local Office:**

**Operator Name:** PERCUSSION PETROLEUM OPERATING LLC

**Well Name:** OSAGE BOYD 15 FEDERAL COM

**Well Number:** 10H

**Military Local Office:**

**USFWS Local Office:**

**Other Local Office:**

**USFS Region:**

**USFS Forest/Grassland:**

**USFS Ranger District:**

**Fee Owner:** Jerome Hugh Jones et al

**Phone:** (575)365-4797

**Surface use plan certification:** NO

**Surface use plan certification document:**

**Surface access agreement or bond:** Agreement

**Surface Access Agreement Need description:** See attached

**Surface Access Bond BLM or Forest Service:**

**BLM Surface Access Bond number:**

**USFS Surface access bond number:**

**Fee Owner Address:** c/o Ross Ranch PO Box 216

Lakewood NM 88254

**Email:**

**Disturbance type:** EXISTING ACCESS ROAD

**Describe:**

**Surface Owner:** PRIVATE OWNERSHIP

**Other surface owner description:**

**BIA Local Office:**

**BOR Local Office:**

**COE Local Office:**

**DOD Local Office:**

**NPS Local Office:**

**State Local Office:**

**Military Local Office:**

**USFWS Local Office:**

**Other Local Office:**

**USFS Region:**

**USFS Forest/Grassland:**

**USFS Ranger District:**

**Operator Name:** PERCUSSION PETROLEUM OPERATING LLC

**Well Name:** OSAGE BOYD 15 FEDERAL COM

**Well Number:** 10H

**Fee Owner:** Jerome Hugh Joes et al

**Phone:** (575)365-4797

**Surface use plan certification:** NO

**Surface use plan certification document:**

**Surface access agreement or bond:** Agreement

**Surface Access Agreement Need description:** See attached

**Surface Access Bond BLM or Forest Service:**

**BLM Surface Access Bond number:**

**USFS Surface access bond number:**

**Fee Owner Address:** c/o Ross Ranch PO Box 216

Lakewood NM 88254

**Email:**

**Disturbance type:** NEW ACCESS ROAD

**Describe:**

**Surface Owner:** PRIVATE OWNERSHIP

**Other surface owner description:**

**BIA Local Office:**

**BOR Local Office:**

**COE Local Office:**

**DOD Local Office:**

**NPS Local Office:**

**State Local Office:**

**Military Local Office:**

**USFWS Local Office:**

**Other Local Office:**

**USFS Region:**

**USFS Forest/Grassland:**

**USFS Ranger District:**

**Operator Name:** PERCUSSION PETROLEUM OPERATING LLC

**Well Name:** OSAGE BOYD 15 FEDERAL COM

**Well Number:** 10H

**Fee Owner:** Jerome Hugh Jones et al

**Phone:** (575)365-4797

**Surface use plan certification:** NO

**Surface use plan certification document:**

**Surface access agreement or bond:** Agreement

**Surface Access Agreement Need description:** See attached

**Surface Access Bond BLM or Forest Service:**

**BLM Surface Access Bond number:**

**USFS Surface access bond number:**

**Fee Owner Address:** c/o Ross Ranch PO Box 216  
Lakewood NM 88254

**Email:**

**Disturbance type:** OTHER

**Describe:** Central Tank Battery

**Surface Owner:** PRIVATE OWNERSHIP

**Other surface owner description:**

**BIA Local Office:**

**BOR Local Office:**

**COE Local Office:**

**DOD Local Office:**

**NPS Local Office:**

**State Local Office:**

**Military Local Office:**

**USFWS Local Office:**

**Other Local Office:**

**USFS Region:**

**USFS Forest/Grassland:**

**USFS Ranger District:**

**Operator Name:** PERCUSSION PETROLEUM OPERATING LLC

**Well Name:** OSAGE BOYD 15 FEDERAL COM

**Well Number:** 10H

**Fee Owner:** Jerome Hugh Jones et al

**Phone:** (575)365-4797

**Surface use plan certification:** NO

**Surface use plan certification document:**

**Surface access agreement or bond:** Agreement

**Surface Access Agreement Need description:** See attached

**Surface Access Bond BLM or Forest Service:**

**BLM Surface Access Bond number:**

**USFS Surface access bond number:**

**Fee Owner Address:** c/o Ross Ranch PO Box 216  
Lakewood NM 88254

**Email:**

## Section 12 - Other Information

**Right of Way needed?** NO

**Use APD as ROW?**

**ROW Type(s):**

### ROW Applications

**SUPO Additional Information:**

**Use a previously conducted onsite?** YES


**Previous Onsite information:** On-site inspection was held with Matt Wirth (BLM) on July 12, 2018. Lone Mountain inspected the well pad and submitted archaeology report NMCRIS-141110 on August 6, 2018. APAC inspected the oil line and submitted report NMCRIS-141712 on October 25, 2018.

### Other SUPO Attachment

Osage\_10H\_SUPO\_20181105111835.pdf

Osage\_10H\_Surface\_Use\_Agreement\_20181105140047.pdf


104.51667° W 104.50000° W 104.48333° W 104.46667° W 104.45000° W 104.43333° W 104.41667° W 104.40000° W 104.38333° W WG84 104.35000° W



MAP 1


Osage Boyd 15. Federal Com  
9H, 10H, & 11H pad

Map created with ©2013 National Geographic ©2005 Tale Atlas, Rel. 8/2005




TN 1 MN  
7°  
09/09/18





SECTION 22, TOWNSHIP 19 SOUTH, RANGE 25 EAST, N.M.P.M.,  
 EDDY COUNTY, NEW MEXICO.

MAP 4



Ross Ranch 22 #3  
 Goodman 22 #1H  
 Goodman 22 #2H

**PERCUSSION PETROLEUM OPERATING, LLC**  
 OSAGE BOYD 15 FEDERAL COM 10H  
 ELEV. - 3475'

Lot - N 32.652008'  
 Long - W 104.478904'  
 NMSPC - N 600962.1  
 E 496534.5  
 (NAD-83)

ARTESIA, NM IS ±14 MILES TO THE NORTHEAST OF LOCATION.



Directions to Location:

FROM US HIGHWAY 285, GO WEST ON ROCKING R. RED ROAD 4.6 MILES TO LEASE ROAD, THEN GO SOUTHERLY ON LEASE ROAD 0.1 MILE TO THE PERCUSSION ROSS RANCH 22 #3 LOCATION AND PROPOSED LEASE ROAD.




P.O. Box 1786 (575) 393-7316 - Office  
 1120 N. West County Rd. (575) 392-2206 - Fax  
 Hobbs, New Mexico 88241 basin-surveys.com

**PERCUSSION PETROLEUM OPERATING, LLC**

REF: OSAGE BOYD 15 FEDERAL COM 10H / WELL PAD TOPO


THE OSAGE BOYD 15 FEDERAL COM 10H LOCATED 649' FROM THE NORTH LINE AND 701' FROM THE WEST LINE OF SECTION 22, TOWNSHIP 19 SOUTH, RANGE 25 EAST, N.M.P.M., EDDY COUNTY, NEW MEXICO.




MAP 2

Osage Boyd 15 Federal Com 9H, 10H, & 11H pad

Map created with ©2010 National Geographic ©2005 TeleAtlas, RA 1/8/2005



TN MN  
7°  
09/09/18



Osage Boyd 15  
Federal Com  
9H, 10H & 11H  
pad

Osage Boyd 15  
Federal Com  
12H, 13H &  
14H pad


Ross Ranch 22 #3  
Goodman 22 #1H  
Goodman 22 #2H  
expanded after  
date of air photo

1098.6 new road

MAP 3

400 ft

Google Earth



BLM O&G lease  
NMNM-012833

1 mile radius

1 mile radius

SHL

BHL

**LEGEND**

- New
- ★ Active
- ✦ HRZ
- ⊙ BHL
- ⊕ P&A
- ⊗ INJ
- ⊖ SWD
- ⊙ Water



Quad: DAYTON  
Scale: 1 inch = 2,000 ft.

Osage Boyd 15  
Federal Com  
9H, 10H & 11H  
pad

Osage Boyd 15  
Federal Com  
12H, 13H &  
14H pad

1393.2'  
proposed  
power line

1465'  
proposed  
flowlines

CTB

MAP 6

Google Earth

100 ft






SECTION 22, TOWNSHIP 19 SOUTH, RANGE 25 EAST. N.M.P.M.,  
EDDY COUNTY, NEW MEXICO.

MAP 7B

OWNER: JEROME HUGH JONES, ETAL

process equipment on north




bermed tank battery on south

LEGAL DESCRIPTION

A TRACT OF LAND LOCATED IN SECTION 22, TOWNSHIP 19 SOUTH, RANGE 25 EAST, N.M.P.M., EDDY COUNTY, NEW MEXICO AND BEING MORE PARTICULARLY DESCRIBED AS FOLLOWS.

BEGINNING AT A POINT WHICH LIES S.89°53'53\"/>

I HEREBY CERTIFY THAT THIS PLAN WAS PREPARED FROM FIELD NOTES OF AN ORIGINAL SURVEY AND MEETS OR EXCEEDS ALL REQUIREMENTS FOR LAND SURVEYS AS SPECIFIED BY THIS STATE.



GARY L. JONES, P.L.S. No. 7977  
 No. 5074  
 P.O. Box 1786 (575) 393-7316 -- Office  
 1120 N. West County Rd. (575) 392-2206 -- Fax  
 Hobbs, New Mexico 88241 basinsurveys.com


**PERCUSSION PETROLEUM OPERATING, LLC**

REF: PROPOSED OSAGE BOYD TANK BATTERY

A TRACT OF LAND LOCATED IN  
 SECTION 22, TOWNSHIP 19 SOUTH, RANGE 25 EAST,  
 N.M.P.M., EDDY COUNTY, NEW MEXICO.

SECTION 22, TOWNSHIP 19 SOUTH, RANGE 25 EAST. N.M.P.M.,  
 EDDY COUNTY, NEW MEXICO.


MAP 7C



OWNER: ROSS P & BARBARA  
 WHITNEY TRUST

1. SEE DOCUMENTS FILED FOR RECORD IN THIS OFFICE WHICH DESCRIBE IN DETAIL THE RECONSTRUCTION OF THIS SECTION.
2. COORDINATES AND BEARINGS ARE BASED ON THE NEW MEXICO STATE PLANE COORDINATE SYSTEM. NAD 83 AND DISTANCES ARE OF SURFACE VALUE.

0+00 BEGIN SURVEY AT  
 NORTHEAST CORNER  
 OF PAD  
 N32°38'54.99\"/>



LEGAL DESCRIPTION


A STRIP OF LAND 30.0 FEET WIDE, LOCATED IN SECTION 22, TOWNSHIP 19 SOUTH, RANGE 25 EAST, N.M.P.M., EDDY COUNTY, NEW MEXICO AND BEING 15.0 FEET LEFT AND 15.0 FEET RIGHT OF THE FOLLOWING DESCRIBED CENTERLINE SURVEY:

BEGINNING AT A POINT WHICH LIES S20°46'36\"/>

I HEREBY CERTIFY THAT THIS PLAN WAS PREPARED FROM FIELD NOTES OF AN ACTUAL SURVEY AND MEETS OR EXCEEDS ALL REQUIREMENTS FOR LAND SURVEYS AS SPECIFIED BY THIS STATE.




GARY L. JONES No. 7977  
 No. 5074



**PERCUSSION PETROLEUM OPERATING, LLC**

REF: PROPOSED CRUDE OIL LINE TO OSAGE BATTERY


A PIPELINE CROSSING FEE LAND IN  
 SECTION 22, TOWNSHIP 19 SOUTH, RANGE 25 EAST,  
 N.M.P.M., EDDY COUNTY, NEW MEXICO.



P.O. Box 1786 (575) 393-7316 - Office  
 1120 N. West County Rd. (575) 392-2206 - Fax  
 Hobbs, New Mexico 88241 basinsurveys.com


SECTION 22, TOWNSHIP 19 SOUTH, RANGE 25 EAST. N.M.P.M.,  
EDDY COUNTY, NEW MEXICO.

MAP 7D



OWNER: JEROME HUGH JONES ET AL

1. SEE DOCUMENTS FILED FOR RECORD IN THIS OFFICE WHICH DESCRIBE IN DETAIL THE RECONSTRUCTION OF THIS SECTION.
2. COORDINATES AND BEARINGS ARE BASED ON THE NEW MEXICO STATE PLANE COORDINATE SYSTEM NAD 83 AND DISTANCES ARE OF SURFACE VALUE.




LEGAL DESCRIPTION

A STRIP OF LAND 30.0 FEET WIDE, LOCATED IN SECTION 22, TOWNSHIP 19 SOUTH, RANGE 25 EAST, N.M.P.M., EDDY COUNTY, NEW MEXICO AND BEING 15.0 FEET LEFT AND 15.0 FEET RIGHT OF THE FOLLOWING DESCRIBED CENTERLINE SURVEY.

BEGINNING AT A POINT ON A POINT ON THE WEST PROPERTY LINE WHICH LIES S45°54'38" E, 1826.7 FEET FROM THE NORTHWEST CORNER OF SAID SECTION 22; THENCE N44°04'34" E, 189.2 FEET; THENCE N71°55'21" E, 503.2 FEET TO THE END OF THIS LINE WHICH LIES S35°48'21" W, 1202.0 FEET FROM THE NORTH QUARTER CORNER OF SAID SECTION 22. SAID STRIP OF LAND BEING 692.4 FEET OR 41.96 RODS IN LENGTH.

I, HEREBY CERTIFY THAT THIS PLAN WAS PREPARED FROM FIELD NOTES OF A SURVEY AND MEETS OR EXCEEDS ALL REQUIREMENTS FOR LAND SURVEYS AS SPECIFIED BY THIS STATE.



GARY L. JONES, P.S. No. 7977  
No. 5074



P.O. Box 1786 (575) 393-7316 - Office  
1120 N. West County Rd. (575) 392-2206 - Fax  
Hobbs, New Mexico 88241 basinsurveys.com




PERCUSSION PETROLEUM OPERATING, LLC

REF: PROPOSED CRUDE OIL LINE TO OSAGE BATTERY

A PIPELINE CROSSING FEE LAND IN  
SECTION 22, TOWNSHIP 19 SOUTH, RANGE 25 EAST,  
N.M.P.M., EDDY COUNTY, NEW MEXICO.





Osage Boyd 15  
Federal Com  
9H 10H 11H

water supply lines

Percussion's  
ponds



MAP 8

Google Earth

© 2000 II

SECTION 22, TOWNSHIP 19 SOUTH, RANGE 25 EAST, N.M.P.M.,  
 EDDY COUNTY, NEW MEXICO.

MAP 9



**PERCUSSION PETROLEUM OPERATING, LLC**

REF: OSAGE BOYD 15 FEDERAL COM 10H / WELL PAD TOPO


THE OSAGE BOYD 15 FEDERAL COM 10H LOCATED 649' FROM  
 THE NORTH LINE AND 701' FROM THE WEST LINE OF  
 SECTION 22, TOWNSHIP 19 SOUTH, RANGE 25 EAST,  
 N.M.P.M., EDDY COUNTY, NEW MEXICO.



P.O. Box 1786 (575) 393-7316 - Office  
 1120 N. West County Rd. (575) 392-2206 - Fax  
 Hobbs, New Mexico 88241 basin-surveys.com

SECTION 22, TOWNSHIP 19 SOUTH, RANGE 25 EAST, N.M.P.M.,  
 EDDY COUNTY, NEW MEXICO.

MAP 10



**PERCUSSION PETROLEUM OPERATING, LLC**

REF: OSAGE BOYD 15 FEDERAL COM 9H, 10H & 11H / WELL PAD TOPO




THE OSAGE BOYD 15 FEDERAL COM 9H, 10H & 11H LOCATED IN  
 SECTION 22, TOWNSHIP 19 SOUTH, RANGE 25 EAST,  
 N.M.P.M., EDDY COUNTY, NEW MEXICO.



P.O. Box 1796 (575) 393-7316 - Office  
 1120 N. West County Rd. (575) 392-2206 - Fax  
 Hobbs, New Mexico 88241 basin surveys.com

SECTION 22, TOWNSHIP 19 SOUTH, RANGE 25 EAST, N.M.P.M.,  
EDDY COUNTY, NEW MEXICO.


MAP 11



**PERCUSSION PETROLEUM OPERATING, LLC**

REF: OSAGE BOYD 15 FEDERAL COM 9H,10H&11H / PAD CROSS SECTION

THE OSAGE BOYD 15 FEDERAL COM 9H,10H&11H LOCATED IN  
SECTION 22, TOWNSHIP 19 SOUTH, RANGE 25 EAST,  
N.M.P.M., EDDY COUNTY, NEW MEXICO.





focused on excellence in the oilfield  
P.O. Box 1786 (575) 393-7316 Office  
1120 N. West County Rd. (575) 392-2206 Fax  
Hobbs, New Mexico 88241 basin-surveys.com



SECTION 22, TOWNSHIP 19 SOUTH, RANGE 25 EAST, N.M.P.M.,  
 EDDY COUNTY, NEW MEXICO.

MAP 13



**PERCUSSION PETROLEUM OPERATING, LLC**

REF: OSAGE BOYD 15 FEDERAL COM 10H / WELL PAD TOPO  
 THE OSAGE BOYD 15 FEDERAL COM 10H LOCATED 649' FROM  
 THE NORTH LINE AND 701' FROM THE WEST LINE OF  
 SECTION 22, TOWNSHIP 19 SOUTH, RANGE 25 EAST,  
 N.M.P.M., EDDY COUNTY, NEW MEXICO.




P.O. Box 1786 (575) 393-7316 - Office  
 1120 N. West County Rd. (575) 392-2206 - Fax  
 Hobbs, New Mexico 88241 basin surveys.com

Percussion's  
Osage Boyd 15 Federal Com 10H  
rig diagram

Prevailing Wind  
out of South  
or SSE


1" = 50'

NORTH 




SECTION 22, TOWNSHIP 19 SOUTH, RANGE 25 EAST, N.M.P.M.,  
 EDDY COUNTY, NEW MEXICO.

MAP 14



interim reclaim 50'  
on north & west



**PERCUSSION PETROLEUM OPERATING, LLC**


REF: OSAGE BOYD 15 FEDERAL COM 10H / WELL PAD TOPO  
 THE OSAGE BOYD 15 FEDERAL COM 10H LOCATED 649' FROM  
 THE NORTH LINE AND 701' FROM THE WEST LINE OF  
 SECTION 22, TOWNSHIP 19 SOUTH, RANGE 25 EAST,  
 N.M.P.M., EDDY COUNTY, NEW MEXICO.



P.O. Box 1786 (575) 393-7316 - Office  
 1120 N. West County Rd. (575) 392-2206 - Fax  
 Hobbs, New Mexico 88241 basin-surveys.com

SECTION 22, TOWNSHIP 19 SOUTH, RANGE 25 EAST, N.M.P.M.,  
 EDDY COUNTY, NEW MEXICO.

MAP 15






**PERCUSSION PETROLEUM OPERATING, LLC**  
 REF: OSAGE BOYD 15 FEDERAL COM 9H,10H&11H / WELL PAD TOPO  
 THE OSAGE BOYD 15 FEDERAL COM 9H,10H&11H LOCATED IN  
 SECTION 22, TOWNSHIP 19 SOUTH, RANGE 25, EAST,  
 N.M.P.M., EDDY COUNTY, NEW MEXICO.



P.O. Box 1786 (575) 393-7316 -- Office  
 1120 N. West County Rd. (575) 392-2206 -- Fax  
 Hobbs, New Mexico 88241 basin-surveys.com

SECTION 22, TOWNSHIP 19 SOUTH, RANGE 25 EAST, N.M.P.M.,  
 EDDY COUNTY, NEW MEXICO.

MAP 16



**PERCUSSION PETROLEUM OPERATING, LLC**

REF: OSAGE BOYD 15 FEDERAL COM 9H,10H&11H / PAD CROSS SECTION

THE OSAGE BOYD 15 FEDERAL COM 9H,10H&11H LOCATED IN  
 SECTION 22, TOWNSHIP 19 SOUTH, RANGE 25 EAST,  
 N.M.P.M., EDDY COUNTY, NEW MEXICO.



P.O. Box 1786 (575) 393-7316 - Office  
 1120 N. West County Rd. (575) 392-2206 - Fax  
 Hobbs, New Mexico 88241 [basinsurveys.com](http://basinsurveys.com)

Percussion Petroleum Operating, LLC  
Osage Boyd 15 Federal Com 10H  
SHL 649' FNL & 701' FWL 22-19S-25E  
Eddy County, NM

SURFACE PLAN PAGE 1

1. ROAD DIRECTIONS & DESCRIPTIONS (See MAPS 1 - 4)

From the junction of US 82 & US 285 in Artesia...  
Go South 13.2 miles on US 285 to the equivalent of Mile Post 56.5  
Then turn right and go West 4.6 miles on paved County Road 21 (Rocking R)  
Then turn left and go SW 0.2 mile on a caliche road to the SW corner of  
Percussion's existing Ross Ranch Goodman pad  
Then go West 620' cross-country to the SE corner of the 12H 13H 14H pad  
Continue West 340' across the 12H 13H 14H pad to its SW corner  
Continue West 138.6' cross country to the SE corner of the 9H 10H 11H pad

Non-county roads will be maintained as needed to Gold Book standards. This includes pulling ditches and preserving the crown. This will be done at least once a year, and more often as needed.

2. ROAD TO BE BUILT OR UPGRADED (See MAPS 3 & 4)

The 1098.6' of new resource road will be crowned and ditched, have a 14' wide driving surface, and be surfaced with caliche. Maximum disturbed width = 30'. Maximum grade = 5%. Maximum cut or fill = 3'. No culvert, cattle guard, or vehicle turn out is needed. Upgrade will consist of filling potholes with caliche as needed.

3. EXISTING WELLS (See MAP 5)

Existing oil, gas, water, disposal, and P & A wells are within a mile. No injection well is within a mile radius.

4. PROPOSED PRODUCTION FACILITIES (See MAPS 6 - 7E)

A 1465' long, 4" O D. HDPE flow line will be laid parallel to roads on the surface east and southeast to a proposed central tank battery (CTB). CTB will sit on the

Percussion Petroleum Operating, LLC  
Osage Boyd 15 Federal Com 10H  
SHL 649' FNL & 701' FWL 22-19S-25E  
Eddy County, NM

SURFACE PLAN PAGE 2

south side of Percussion's existing three well Ross Ranch Goodman pad. Maximum operating pressure will be <125 psi.

A 1393.2' 3-phase raptor safe overhead power line will be built east to tie into an existing power line that serves the Ross Ranch Goodman pad.

A 1549.8' long  $\approx$ 4" O.D. HDPE crude oil line will be laid on the surface from the CTB southwest to an existing crude oil line at Percussion's Ross Ranch 22 #2 pad. Maximum operating pressure will be <125 psi.

#### 5. WATER SUPPLY (See MAP 8)

Water will be piped via temporary  $\approx$ 13,500' long surface 10" Kevlar lay flat pipelines (2) from Percussion's existing lined fresh water pond on its own land in NE4 26-19s-25e. Pipeline route will not be bladed or excavated. Route is all private. Route follows existing roads, pads, and pipelines.

#### 6. CONSTRUCTION MATERIALS & METHODS (See MAPS 9 - 12)

NM One Call (811) will be notified before construction starts. Top  $\approx$ 6" of soil and brush will be stockpiled north of the pad. V-door will face east. Closed loop drilling system will be used. Caliche will be hauled from existing caliche pit on private land. Arkland caliche pit is in NWNE 23-19s-25e.

#### 7. WASTE DISPOSAL

All trash will be placed in a portable trash cage. It will be hauled to the Eddy County landfill. There will be no trash burning. Contents (drill cuttings, mud, salts, and other chemicals) of the mud tanks will be hauled to R360's state approved (NM-01-0006) disposal site at Halfway. Human waste will be disposed of in chemical toilets and hauled to the Artesia wastewater treatment plant.

Percussion Petroleum Operating, LLC  
Osage Boyd 15 Federal Com 10H  
SHL 649' FNL & 701' FWL 22-19S-25E  
Eddy County, NM

SURFACE PLAN PAGE 3

#### 8. ANCILLARY FACILITIES

There will be no airstrip or camp. Camper trailers will be on location for the company man, tool pusher, and mud logger.

#### 9. WELL SITE LAYOUT (See MAP 13)

Also see Rig Layout diagram for depictions of the well pad, trash cage, access onto the location, parking, living facilities, and rig orientation.

#### 10. RECLAMATION (See MAPS 14 - 16)

Interim reclamation will be completed within 6 months of completing the well. Interim reclamation will consist of shrinking the well pad 0.68 acre by removing caliche and reclaiming 50' on the north and west sides of the pad. This will leave 1.66 acres for the anchors, pump jacks, and tractor-trailer turn around. Disturbed areas will be contoured to match pre-construction grades. Soil and brush will be evenly spread over disturbed areas and harrowed on the contour. Disturbed areas will be seeded in accordance with surface owner's requirements.

Enough stockpiled topsoil will be retained to cover the remainder of the pad when the well is plugged. Once the last well is plugged, then the rest of the pad will be similarly reclaimed within 6 months of plugging. Noxious weeds will be controlled.

Percussion Petroleum Operating, LLC  
Osage Boyd 15 Federal Com 10H  
SHL 649' FNL & 701' FWL 22-19S-25E  
Eddy County, NM

SURFACE PLAN PAGE 4

Land use will be:

30' x 1098.6' road = 0.76 acre  
30' x 1393.2' power line = 0.96 acre  
30' x 1465' flowline = 1.01 acres  
30' x 1549.8' crude oil line = 1.07 acres  
297.6' x 198.6' x 132.7' x 108.7' CTB = 0.55 acre  
20' x 13,500' water line from pond = 6.20 acres  
+ 300 x 340' well pad = 2.34 acres  
12.89 acres short term  
- 0.96 acre power line  
- 1.01 acres flowline  
- 1.07 acres oil line  
- 6.20 acres water line from pond  
- 0.68 acre interim reclamation on well pad  
2.97 acres (0.76 ac. road + 0.55 ac. CTB + 1.66 ac. pad) long term

## 11. SURFACE OWNER

Well pad, road, power line, CTB, flow line, and 692.4' of oil line construction will be on private land (NWNW & E2NW4 22-19s-25e) owned by Jerome Hugh Jones et al and leased to Ross Ranch, P. O. Box 216, Lakewood NM 88254. Ranch phone number is (575) 365-4797. Jones phone number is (703) 352-0067. Percussion has an agreement with the Ranch and Jones.

Remaining 857.4' of oil line construction will be on private land (SWNW 22-19s-25e) owned by Ross & Barbara Whitney Trust, 25601 E. 130<sup>th</sup> St., Greenwood MO 64034. Phone number is (816) 525-1233. Percussion has an agreement with the Trust.

## 12. OTHER INFORMATION

On-site inspection was held with Matt Wirth (BLM) on July 12, 2018. Lone Mountain inspected the well pad and submitted archaeology report NMCRIS-141110 on August 6, 2018. APAC inspected the oil line and submitted report NMCRIS-141712 on October 25, 2018.

Percussion Petroleum Operating, LLC  
Osage Boyd 15 Federal Com 10H  
SHL 649' FNL & 701' FWL 22-19S-25E  
Eddy County, NM

SURFACE PLAN PAGE 5

CERTIFICATION

I hereby certify that I, or someone under my direct supervision, have inspected the drill site and access route proposed herein; that I am familiar with the conditions which currently exist; that I have full knowledge of state and Federal laws applicable to this operation; that the statements made in this APD package are, to the best of my knowledge, true and correct; and that the work associated with the operations proposed herein will be performed in conformity with this APD package and the terms and conditions under which it is approved. I also certify that I, or the company I represent, am responsible for the operations conducted under this application. These statements are subject to the provisions of 18 U. S. C. 1001 for the filing of false statements. Executed this 4th day of November, 2018.



---

Brian Wood, Consultant  
Permits West, Inc.

37 Verano Loop, Santa Fe, NM 87508

(505) 466-8120

FAX: (505) 466-9682

Cellular: (505) 699-2276

Field representative will be:

Lelan Anders, Operations Manager  
Percussion Petroleum Operating, LLC  
919 Milam, Suite 2475  
Houston TX 77002  
Office: (713) 429-1291  
Mobile: (281) 908-1752

November 4, 2018

To Who It May Concern:

Osage Boyd 15 Federal Com 9H 10H 11H well pad, road, power line, CTB, flow line, and 692.4' of oil line construction will be on private land (NWNW & E2NW4 22-19s-25e) owned by Jerome Hugh Jones et al and leased to Ross Ranch, P. O. Box 216, Lakewood NM 88254. Ranch phone number is (575) 365-4797. Jones phone number is (703) 352-0067. Percussion has an agreement with the Ranch and Jones.

Remaining 857.4' of oil line construction will be on private land (SWNW 22-19s-25e) owned by Ross & Barbara Whitney Trust, 25601 E. 130<sup>th</sup> St., Greenwood MO 64034. Phone number is (816) 525-1233. Percussion has an agreement with the Trust.

A handwritten signature in black ink, appearing to read "B. Wood", with a long horizontal flourish extending to the right.

Brian Wood



**Section 1 - General**

Would you like to address long-term produced water disposal? NO

**Section 2 - Lined Pits**

Would you like to utilize Lined Pit PWD options? NO

Produced Water Disposal (PWD) Location:

PWD surface owner:

PWD disturbance (acres):

Lined pit PWD on or off channel:

Lined pit PWD discharge volume (bbl/day):

Lined pit specifications:

Pit liner description:

Pit liner manufacturers information:

Precipitated solids disposal:

Describe precipitated solids disposal:

Precipitated solids disposal permit:

Lined pit precipitated solids disposal schedule:

Lined pit precipitated solids disposal schedule attachment:

Lined pit reclamation description:

Lined pit reclamation attachment:

Leak detection system description:

Leak detection system attachment:

Lined pit Monitor description:

Lined pit Monitor attachment:

Lined pit: do you have a reclamation bond for the pit?

Is the reclamation bond a rider under the BLM bond?

Lined pit bond number:

Lined pit bond amount:

Additional bond information attachment:

### **Section 3 - Unlined Pits**

Would you like to utilize Unlined Pit PWD options? NO

Produced Water Disposal (PWD) Location:

PWD surface owner:

PWD disturbance (acres):

Unlined pit PWD on or off channel:

Unlined pit PWD discharge volume (bbl/day):

Unlined pit specifications:

Precipitated solids disposal:

Describe precipitated solids disposal:

Precipitated solids disposal permit:

Unlined pit precipitated solids disposal schedule:

Unlined pit precipitated solids disposal schedule attachment:

Unlined pit reclamation description:

Unlined pit reclamation attachment:

Unlined pit Monitor description:

Unlined pit Monitor attachment:

Do you propose to put the produced water to beneficial use?

Beneficial use user confirmation:

Estimated depth of the shallowest aquifer (feet):

Does the produced water have an annual average Total Dissolved Solids (TDS) concentration equal to or less than that of the existing water to be protected?

TDS lab results:

Geologic and hydrologic evidence:

State authorization:

Unlined Produced Water Pit Estimated percolation:

Unlined pit: do you have a reclamation bond for the pit?

Is the reclamation bond a rider under the BLM bond?

Unlined pit bond number:

Unlined pit bond amount:

Additional bond information attachment:

### **Section 4 - Injection**

Would you like to utilize Injection PWD options? NO

Produced Water Disposal (PWD) Location:

PWD surface owner:

PWD disturbance (acres):

Injection PWD discharge volume (bbl/day):

Injection well mineral owner:

Injection well type:

Injection well number:

Assigned injection well API number?

Injection well new surface disturbance (acres):

Minerals protection information:

Mineral protection attachment:

Underground Injection Control (UIC) Permit?

UIC Permit attachment:

Injection well name:

Injection well API number:

### Section 5 - Surface Discharge

Would you like to utilize Surface Discharge PWD options? NO

Produced Water Disposal (PWD) Location:

PWD surface owner:

PWD disturbance (acres):

Surface discharge PWD discharge volume (bbl/day):

Surface Discharge NPDES Permit?

Surface Discharge NPDES Permit attachment:

Surface Discharge site facilities information:

Surface discharge site facilities map:

### Section 6 - Other

Would you like to utilize Other PWD options? NO

Produced Water Disposal (PWD) Location:

PWD surface owner:

PWD disturbance (acres):

Other PWD discharge volume (bbl/day):

Other PWD type description:

Other PWD type attachment:

Have other regulatory requirements been met?

Other regulatory requirements attachment:



U.S. Department of the Interior  
BUREAU OF LAND MANAGEMENT

## Bond Info Data Report

04/29/2019

### Bond Information

Federal/Indian APD: FED

BLM Bond number: NMB001424

BIA Bond number:

Do you have a reclamation bond? NO

Is the reclamation bond a rider under the BLM bond?

Is the reclamation bond BLM or Forest Service?

BLM reclamation bond number:

Forest Service reclamation bond number:

Forest Service reclamation bond attachment:

Reclamation bond number:

Reclamation bond amount:

Reclamation bond rider amount:

Additional reclamation bond information attachment: