D	UNITED STATES EPARTMENT OF THE IN SUREAU OF LAND MANAG	NTERIOR FLOR	Artesia	OMB NO Expires: Jan	PPROVED . 1004-0137 mary 31, 2018
SUNDRY	NOTICES AND REPOI	RTS ON WELLS		ase Serial No. MLC028775B	
abandoned we	is form for proposals to II. Use form 3160-3 (APL	drill or to re-ented an 4 o D) for such proposals.	6. If	Indian, Allottee or	Tribe Name
SUBMIT IN	TRIPLICATE - Other inst	ructions on page 211-AHI	ESTAO.C.D. 7. 1f	Unit or CA/Agreen 10123980	nent, Name and/or
I. Type of Well Oil Well Gas Well Ot	her			Il Name and No. UNIT 109	
2. Name of Operator COG OPERATING LLC	Contact: E-Mail: dflores2@c	DELILAH FLORES		91 Well No. 0-015-03143-00	)-S1
3a. Address 600 W ILLINOIS AVENUE MIDLAND, TX 79701		3b. Phone No. (include area cod Ph: 575-748-6946		ield and Pool or E RAYBURG	xploratory Area
4. Location of Well (Footage, Sec., 7	T., R., M., or Survey Description)	) -	11. C	ounty or Parish, St	tate
Sec 27 T17S R29E SENW Tr	act 2 2615FNL 2615FWL	~	E	ODY COUNTY,	NM
12. CHECK THE A	PPROPRIATE BOX(ES)	TO INDICATE NATURE	OF NOTICE, REPO	ORT, OR OTH	ER DATA
TYPE OF SUBMISSION		TYPE OF ACTION			
□ Notice of Intent	Acidize	Deepen	Production (St	art/Resume)	U Water Shut-
—	Alter Casing	🗖 Hydraulic Fracturing	g 🗖 Reclamation		🗖 Well Integri
🛛 Subsequent Report	Casing Repair	New Construction	Recomplete		🗖 Other
Final Abandonment Notice	Change Plans	🛛 Plug and Abandon	Temporarily A	.bandon	
	Convert to Injection	Plug Back	Water Disposa	1	
Attach the Bond under which the wo following completion of the involved testing has been completed. Final Al determined that the site is ready for f 07/03/19 Moved plugging equ	rk will be performed or provide d operations. If the operation res bandonment Notices must be file final inspection.	give subsurface locations and mea the Bond No. on file with BLM/B sults in a multiple completion or re ed only after all requirements, inclu- ved Pump Jack, locked out/t	A. Required subsequen completion in a new inte uding reclamation, have	epths of all pertine t reports must be f rval, a Form 3160 been completed an	nt markers and zor iled within 30 days -4 must be filed on id the operator has
Attach the Bond under which the wo following completion of the involved testing has been completed. Final Al determined that the site is ready for f 07/03/19 Moved plugging equ & pump. Dug out cellar. Pump 2650'. 07/08/19 Spotted 35 s> Pressure tested csg, held 500 plug @ 2155'. Perfd csg @ 77 500 PSI: Tagged plug @ 605' circulate). WOC. 07/10/19 Pre 150'. Established injection rat CACL @ 150' & displaced to 500 PSI. Perfd csg @ 50'. Es C cmt w/ 2% CACL @ 50' & d	rk will be performed or provide i d operations. If the operation res bandonment Notices must be file final inspection. tipment to location. Remov o'd 15 BBLs Brine H20 to k <u>k cmt @ 2650-2435'</u> . WOC ) PSI. Spotted 25 sx class 20'. Sq2'd 50 <u>sx class C cr</u> '. Perf'd csg <u>@ 375'</u> . Sq2'd essure tested 7" csg, held e but could not circulate up 100'. WOC. Tagged plug ( <u>tabli</u> shed an injection rate <u>ilsplaced.to 10'. WOC.(07</u> /	give subsurface locations and mea the Bond No. on file with BLM/B sults in a multiple completion or re ed only after all requirements, incli ved Pump Jack, locked out/t sill well. NU BOP. POH w/ tt . Tagged plug @ 2425'. Se C cmt @ 2300-2145'. WOC nt @ 720-620'. WOC. Press 55 sx class C cmt @ 375-2 500 PSI. Tagged plug @ 18 p the.7". Sqz'd 50 sx class C @ 90'. Perfd csg @ 90'. Pre but could not circulate. Sqz 1/19Wagged plug @ 30'. S	sured and true vertical de A. Required subsequen completion in a new inte agged out.POH w/ n 90. Set 7" CIBP @ 7" CIBP @ 2300'. . 07/09/19 Tagged sure tested csg, held 00' (cmt did not 00' Period csg @ cmt w/ 2% ssured up on perfs d 50 sx class pootted 5 sx class C	epths of all pertine: t reports must be f rrval, a Form 3160 been completed an rods <b>RECLAN</b> <b>RECI</b>	nt markers and zor iled within 30 days -4 must be filed on d the operator has MATION PROCE ATTACHED
Attach the Bond under which the wo following completion of the involved testing has been completed. Final Al determined that the site is ready for f 07/03/19 Moved plugging equ & pump. Dug out cellar. Pump 2650'. 07/08/19 Spotted 35 sx Pressure tested csg, held 500 plug @ 2155'. Perfd csg @ 7' 500 PSt. Tagged plug @ 605' circulate). WOC. 07/10/19 Pre 150'. Established injection rate CACL @ 150' & displaced to 500 PSI. Perfd csg @ 50'. Es C cmt w/ 2% CACL @ 50' & d cmt @ 30' to surface. Rigged	rk will be performed or provide i d operations. If the operation resibandonment Notices must be file final inspection. upment to location. Remov o'd 15 BBLs Brine H20 to k <u>k cmt @ 2650-2435'</u> . WOC O PSI. Spotted 25 sx class 20', Sqz'd 50 <u>sx class C cr</u> . Perf'd csg <u>@ 375'</u> . Sqz'd essure tested 7" csg, held e but.could.not circulate up 100'. WOC. Tagged plug ( itablished an injection rate displaced to 10'. WOC. [07] down & moved off. 07/11/	give subsurface locations and mea the Bond No. on file with BLM/B sults in a multiple completion or re ed only after all requirements, incli ved Pump Jack, locked out/t sill well. NU BOP. POH w/ tt . Tagged plug @ 2425'. Se C cmt @ 2300-2145'. WOC nt @ 720-620'. WOC. Press 55 sx class C cmt @ 375-2 500 PSI. Tagged plug @ 18 p the.7". Sqz'd 50 sx class C @ 90'. Perfd csg @ 90'. Pre but could not circulate. Sqz 1/19Wagged plug @ 30'. S	sured and true vertical de A. Required subsequen completion in a new inte ading reclamation, have agged out.POH w/ r 9. Set 7" CIBP @ 2300'. .07/09/19 Tagged sure tested csg, held 00' (cmt did not 0'.Perf'd csg @ .cmt W/ 2% ssured up on perfs d 50 sx class potted 5 sx class c relder, dug out	epths of all pertine: t reports must be f rrval, a Form 3160 been completed an rods RECLAN RECI DUE GC 7/2 completed for ref	nt markers and zor iled within 30 days -4 must be filed on d the operator has MATION PROCE ATTACHED LAMATIC I-11-20 2/2 NIMOC
Attach the Bond under which the wo following completion of the involved testing has been completed. Final Al determined that the site is ready for f 07/03/19 Moved plugging equ & pump. Dug out cellar. Pump 2650'. 07/08/19 Spotted 35 sy Pressure tested csg, held 500 plug @ 2155'. Perf d csg @ 7 500 PSI: Tagged plug @ 605' circulate) WOC. 07/10/19 Pre 150'. Established injection rate CACL @ 150' & displaced to 500 PSI. Perf'd csg @ 50'. Es C cmt w/ 2% CACL @ 50' & d cmt @ 30' to surface. Rigged	rk will be performed or provide d d operations. If the operation res bandonment Notices must be file final inspection. tipment to location. Remov o'd 15 BBLs Brine H20 to k <u>c cmt @ 2650-2435'</u> . WOC 0 PSI. Spotted 25 sx class 20'. Sq2'd 50 <u>sx class</u> C cr 2. Perf'd csg @ <u>375'</u> . Sq2'd essure tested 7" csg, held e but.could.not circulate up 100'. WOC. Tagged plug ( <u>tablished an injection rate</u> <u>tisplaced.to 10'. WOC.</u> <u>down &amp; moved off. 07/11/</u> s true and correct. Electronic Submission #4 For COG O	give subsurface locations and mea the Bond No. on file with BLM/B sults in a multiple completion or re ed only after all requirements, incli ved Pump Jack, locked out/t sill well. NU BOP. POH w/ tt . Tagged plug @ 2425'. Se C cmt @ 2300-2145'. WOC nt @ 720-620'. WOC. Press 55 sx class C cmt @ 375-2 500 PSI. Tagged plug @ 18 p the.7". Sqz'd 50 sx class C @ 90'. Perfd csg @ 90'. Pre but could not circulate. Sqz 1/19Wagged plug @ 30'. S	sured and true vertical de A. Required subsequen completion in a new inte agged out.POH w/ n g. Set 7" CIBP @ 7" CIBP @ 2300'. 07/09/19 Tagged sure tested csg, held 00' (cmt did not 00. Perf d csg @ cmt w/ 2% ssured up on perfs d 50 sx class potted 5 sx class for velder, dug out	epths of all pertine: t reports must be f rrval, a Form 3160 been completed an rods RECLAN RECI DUE COULT CO	nt markers and zor iled within 30 days -4 must be filed on d the operator has MATION PROCE ATTACHED LAMATION - 11-20 20 20 FOR RECC
Attach the Bond under which the wo following completion of the involved testing has been completed. Final Al determined that the site is ready for f 07/03/19 Moved plugging equ & pump. Dug out cellar. Pump 2650'. 07/08/19 Spotted 35 sy Pressure tested csg, held 500 plug @ 2155'. Perf d csg @ 7 500 PSI: Tagged plug @ 605' circulate) WOC. 07/10/19 Pre 150'. Established injection rate CACL @ 150' & displaced to 500 PSI. Perf'd csg @ 50'. Es C cmt w/ 2% CACL @ 50' & d cmt @ 30' to surface. Rigged	rk will be performed or provide i d operations. If the operation res bandonment Notices must be file final inspection. tipment to location. Remov o'd 15 BBLs Brine H20 to k <u>k cmt @ 2650-2435'</u> . WOC ) PSI. Spotted 25 sx class 20'. Sqz'd 50 <u>sx class C cr</u> ?. Perf'd csg @ <u>375'</u> . Sqz'd essure tested 7" csg, held e but.could.not circulate up 100'. WOC. Tagged plug ( <u>tablished an injection rate</u> lisplaced to 10'. WOC. <u>077</u> down & moved off. 07/11/ s true and correct. Electronic Submission #4 For COG 0 nitted to AFMSS for process	give subsurface locations and mea the Bond No. on file with BLM/B sults in a multiple completion or re cd only after all requirements, inclu- ved Pump Jack, locked out/ft sill well. NU BOP. POH w/ tt J. Tagged plug @ 2425'. Se C cmt @ 2300-2145'. WOC nt @ 720-620'. WOC. Press 55 sx class C cmt @ 375-2 500 PSI. Tagged plug @ 18 p the.7". Sqz'd 50 sx class C @ 90'. Perfd csg @ 90'. Pre but could not circulate. Sqz 11/19/Tagged plug @ 30'. S 19 Moved in backhoe and w PERATING LLC, sent to the sing by DEBORAH MCKINNE	sured and true vertical de A. Required subsequen completion in a new inte agged out.POH w/ n g. Set 7" CIBP @ 7" CIBP @ 2300'. 07/09/19 Tagged sure tested csg, held 00' (cmt did not 00. Perf d csg @ cmt w/ 2% ssured up on perfs d 50 sx class potted 5 sx class for velder, dug out	epths of all pertine: t reports must be f rrval, a Form 3160 been completed an rods RECLAN RECL DUE CCEPTED FOR FOR FOR FOR CONTRACTOR	nt markers and zor iled within 30 days -4 must be filed on d the operator has MATION PROCE ATTACHED LAMATIC I-11-20 2/2 NIMOC
Attach the Bond under which the wo following completion of the involved testing has been completed. Final Al determined that the site is ready for f 07/03/19 Moved plugging equ & pump. Dug out cellar. Pump 2650'. 07/08/19 Spotted 35 sy Pressure tested csg, held 500 plug @ 2155'. Perf'd csg @ 7 500 PSI: Tagged plug @ 605' circulate). WOC. 07/10/19 Pre 150'. Established injection rate CACL @ 150' & displaced to 500 PSI. Perf'd csg @ 50'. Es C cmt w/ 2% CACL @ 50' & d cmt @ 30'.to_surface. Rigged	rk will be performed or provide d operations. If the operation res bandonment Notices must be file final inspection. tipment to location. Remov o'd 15 BBLs Brine H20 to k <u>c cmt @ 2650-2435'</u> . WOC ) PSI. Spotted 25 sx class 20'. Sq2'd 50 <u>sx class C cr</u> ?. Perf'd csg @ <u>375'</u> . Sq2'd essure tested 7" csg, held e but.could.not circulate up 100'. WOC. Tagged plug ( tablished an injection rate lisplaced to 10'. WOC. [07] down & moved off. 07/11/ s true and correct. Electronic Submission #4 For COG OI nitted to AFMSS for process FLORES	give subsurface locations and mea the Bond No. on file with BLM/B sults in a multiple completion or re cd only after all requirements, inclu- ved Pump Jack, locked out/ft sill well. NU BOP. POH w/ tt J. Tagged plug @ 2425'. Se C cmt @ 2300-2145'. WOC nt @ 720-620'. WOC. Press 55 sx class C cmt @ 375-2 500 PSI. Tagged plug @ 18 p the.7". Sqz'd 50 sx class C @ 90'. Perfd csg @ 90'. Pre but could not circulate. Sqz 11/19/Tagged plug @ 30'. S 19 Moved in backhoe and w PERATING LLC, sent to the sing by DEBORAH MCKINNE	sured and true vertical de A. Required subsequen completion in a new inte ding reclamation, have agged out.POH w/ r 90. Set 7" CIBP @ 7" CIBP @ 2300'. . 07/09/19 Tagged sure tested csg, held 00' (cmt did not 00' Perf'd csg @ . cmt W/ 2% ssured up on perfs 'd 50 sx class potted 5 sx class potted 5 sx class relder, dug out	rods RECLAN RECLAN RECLAN RECLAN CODUE	nt markers and zor iled within 30 days -4 must be filed on d the operator has MATION PROCE ATTACHED LAMATIC -//-2019 FOR RECC 1 7 2019
Attach the Bond under which the wo following completion of the involved testing has been completed. Final Al determined that the site is ready for f 07/03/19 Moved plugging equ & pump. Dug out cellar. Pump 2650'. 07/08/19 Spotted 35 sy Pressure tested csg, held 500 plug @ 2155'. Perf d csg @ 7/ 500 PSI: Tagged plug @ 605' circulate). WOC. 07/10/19 Pre 150'. Established injection rate CACL @ 150' & displaced to 500 PSI. Perf d csg @ 50'. Ess C cmt w/ 2% CACL @ 50' & d cmt @ 30'.to_surface. Rigged 14. I hereby certify that the foregoing is Name (Printed/Typed) DELILAH	rk will be performed or provide d operations. If the operation res bandonment Notices must be file final inspection. upment to location. Remov o'd 15 BBLs Brine H20 to k <u>k cmt @ 2650-2435'</u> . WOC ) PSI. Spotted 25 sx class 20'. Sqz'd 50 <u>sx class C cr</u> '. Perf d csg @ <u>375'</u> . Sqz'd essure tested 7" csg, held e but.could.not circulate up 100'. WOC. Tagged plug ( <u>itablished an injection rate</u> lisplaced.to 10'. WOC. [07] down & moved off. 07/11/ s true and correct. Electronic Submission #4 For COG 0 nitted to AFMSS for process FLORES Submission)	give subsurface locations and mea the Bond No. on file with BLM/B sults in a multiple completion or re ed only after all requirements, inclu- ved Pump Jack, locked out/f sill well. NU BOP. POH w/ tt J. Tagged plug @ 2425'. Se C cmt @ 2300-2145'. WOC nt @ 720-620'. WOC. Press 55 sx class C cmt @ 375-2 500 PSI. Tagged plug @ 18 p the.7". Sqz'd 50 sx class C @ 90'. Perfd csg @ 90'. Pre but could not circulate. Sqz 11/19/Tagged plug @ 30'. S 19 Moved in backhoe and w PERATING LLC, sent to the sing by DEBORAH MCKINNE Title REGL	sured and true vertical de A. Required subsequen completion in a new inte ading reclamation, have agged out.POH w/ r g. Set 7" CIBP @ 2300'. .07/09/19 Tagged Sure tested csg, held 00' (cmt did not 0'.Perf'd csg @ .cmt W/ 2% ssured Up on perfs 'd 50 sx class potted 5 sx class potted 5 sx class velder, dug out ell Information Syste Carlsbad Y on 07/15/2019 [19P LATORY TECHNIC 2019	rods RECLAN RECLAN RECLAN RECLAN CODUE	nt markers and zor iled within 30 days -4 must be filed on d the operator has MATION PROCE ATTACHED LAMATIC -//-20' -//-20' FOR RECC 1 7 2019
Attach the Bond under which the wo following completion of the involved testing has been completed. Final Al determined that the site is ready for f 07/03/19 Moved plugging equ & pump. Dug out cellar. Pump 2650'. 07/08/19 Spotted 35 sx Pressure tested csg, held 500 plug @ 2155'. Perfd csg @ 7' 500 PSt. Tagged plug @ 605' circulate). WOC. 07/10/19 Pre 150'. Established injection ratu CACL @ 150' & displaced to 500 PSI. Perf'd csg @ 50'. Es C cmt w/ 2% CACL @ 50' & d cmt @ 30' to surface. Rigged 14. 1 hereby certify that the foregoing is Name (Printed/Typed) DELILAH Signature (Electronic S	rk will be performed or provide d operations. If the operation res bandonment Notices must be file final inspection. upment to location. Remov o'd 15 BBLs Brine H20 to k <u>k cmt @ 2650-2435'</u> . WOC ) PSI. Spotted 25 sx class 20'. Sqz'd 50 <u>sx class C cr</u> '. Perf d csg @ <u>375'</u> . Sqz'd essure tested 7" csg, held e but.could.not circulate up 100'. WOC. Tagged plug ( <u>itablished an injection rate</u> lisplaced.to 10'. WOC. [07] down & moved off. 07/11/ s true and correct. Electronic Submission #4 For COG 0 nitted to AFMSS for process FLORES Submission)	give subsurface locations and mea the Bond No. on file with BLM/B sults in a multiple completion or re cd only after all requirements, inclu- ved Pump Jack, locked out/ft (ill well. NU BOP. POH w/ tt C. Tagged plug @ 2425'. Set C cmt @ 2300-2145'. WOC mt @ 720-620'. WOC. Press 55 sx class C cmt @ 375-2 500 PSI. Tagged plug @ 16 p the.7". Sqz'd 50 sx class C 0 90'. Perf'd csg @ 90'. Pre but could not circulate. Sqz 11/19Tagged plug @ 30'. S 19 Moved in backhoe and w PERATING LLC, sent to the sing by DEBORAH MCKINNE Title REGL Date 07/15/	sured and true vertical de A. Required subsequen completion in a new inte ading reclamation, have agged out.POH w/ r g. Set 7" CIBP @ 2300'. .07/09/19 Tagged Sure tested csg, held 00' (cmt did not 0'.Perf'd csg @ .cmt W/ 2% ssured Up on perfs 'd 50 sx class potted 5 sx class potted 5 sx class velder, dug out ell Information Syste Carlsbad Y on 07/15/2019 [19P LATORY TECHNIC 2019	rods RECLAN RECLAN RECLAN RECLAN CODUE	nt markers and zor iled within 30 days -4 must be filed on d the operator has MATION PROCE ATTACHED LAMATIC -//-2019 FOR RECC 1 7 2019
Attach the Bond under which the wo following completion of the involved testing has been completed. Final Al determined that the site is ready for f 07/03/19 Moved plugging equ & pump. Dug out cellar. Pump 2650'. 07/08/19 Spotted 35 sy Pressure tested csg, held 500 plug @ 2155'. Perf d csg @ 7/ 500 PSI: Tagged plug @ 605' circulate). WOC. 07/10/19 Pre 150'. Established injection rate CACL @ 150' & displaced to 500 PSI. Perf d csg @ 50'. Ess C cmt w/ 2% CACL @ 50' & d cmt @ 30'.to_surface. Rigged 14. I hereby certify that the foregoing is Name (Printed/Typed) DELILAH	rk will be performed or provide i d operations. If the operation res bandonment Notices must be file final inspection. tipment to location. Remov o'd 15 BBLs Brine H20 to k k cmt @ 2650-2435'. WOC ) PSI. Spotted 25 sx class 20'. Sqz'd 50 sx class C cr '. Perf'd csg @ 375'. Sqz'd essure tested 7" csg, held e but.could.not circulate.ut 100'. WOC. Tagged plug (i tablished an injection rate lisplaced.to 10'. WOC. 07/ down & moved off. 07/11/ s true and correct. Electronic Submission #4 For COG 0 nitted to AFMSS for process FLORES Submission) THIS SPACE FO	give subsurface locations and mea the Bond No. on file with BLM/B sults in a multiple completion or re ed only after all requirements, inclu- ved Pump Jack, locked out/ft (ill well. NU BOP. POH w/ tt 2. Tagged plug @ 2425'. Sei C cmt @ 2300-2145'. WOC mt @ 720-620'. WOC. Press 55 sx class C cmt @ 375-2 500 PSI. Tagged plug @ 175-2 500 PSI. Tagged plug @ 0'. Pre but could not circulate. Sqz 11/19) Tagged plug @ 30'. S 19 Moved in backhoe and w PERATING LLC, sent to the sing by DEBORAH MCKINNE Title REGU Date 07/15/ DR FEDERAL OR STATE	sured and true vertical de A. Required subsequen completion in a new inte ading reclamation, have agged out.POH w/ r g. Set 7" CIBP @ 2300'. .07/09/19 Tagged Sure tested csg, held 00' (cmt did not 0'.Perf'd csg @ .cmt W/ 2% ssured Up on perfs 'd 50 sx class potted 5 sx class potted 5 sx class velder, dug out ell Information Syste Carlsbad Y on 07/15/2019 [19P LATORY TECHNIC 2019	rods RECLAN RECLAN RECLAN RECLAN CODUE	nt markers and zor iled within 30 days -4 must be filed on d the operator has IATION PROCE ATTACHED LAMATION I- //- 201 FOR RECO TOR RECO TOR RECO TO 2019

## Additional data for EC transaction #473233 that would not fit on the form

## 32. Additional remarks, continued

1

cellar, cut off well head, and Chase Messer w/ BLM verified cement to surface. Welded on "Above Ground Dry Hole Marker". Backfilled cellar, cut off deadmen, cleaned location, and moved off.



## United States Department of the Interior

BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 E. Greene St. Carlsbad, New Mexico 88220-6292 www.blm.gov/nm



In Reply Refer To: 1310

## **Reclamation Objectives and Procedures**

**Reclamation Objective:** Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its predisturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any and all contaminants, scrap/trash, equipment, pipelines and powerlines (Contact service companies, allowing plenty of time to have the risers and power lines and poles removed prior to reclamation, don't wait till the last day and try to get them to remove infrastructure). Strip and remove caliche, contour the location to blend with the surrounding landscape, re-distribute the native soils, provide erosion control as needed, rip and seed as specified in the original APD COA. This will apply to well pads, facilities, and access roads. Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

- The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of Operations must include adequate measures for stabilization and reclamation of disturbed lands. Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD process as per Onshore Oil and Gas Order No. 1.
- 2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Appropriate time for submittal would be when filing the Vell Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months.
- 3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.
- 4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you

have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.

- 5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
- 6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
- 7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos Supervisory Petroleum Engineering Tech 575-234-5909 (Office), 575-361-2648 (Cell)

Arthur Arias Environmental Protection Specialist 575-234-6230

Crisha Morgan Environmental Protection Specialist 575-234-5987

Melissa Horn Environmental Protection Specialist 575-234-5951

Kelsey Wade Environmental Protection Specialist 575-234-2220

Trishia Bad Bear, Hobbs Field Station Natural Resource Specialist 575-393-3612