

Current Completion

Elev: 3,011'

KB: 3,028'

Apollo Fee No.1

API # 30-015-33282-00

660' FSL & 660' FWL

Sec 4 T23S R28E

Eddy Co, NM

17-1/2" hole
13-3/8", 48#, H40 @ 430'
355 sx, circ

12-1/4" hole
9-5/8", 40#, L80 LTC @ 6,040'
2700 sx cmt, circ
TOC @ 6,500' EM Hobbs CBL 6/04

8-3/4" hole
5-1/2", 17# SP-110 LTC @ 11,715'
535 sx

PBTD = 12,510'

TD = 12,597'

Spud Well Mar 2004**PB to Current Zone Jan 2006****IPF Nat @ 653 mcf/d, 100 psi FTP, 48/64"**

2-7/8", 6.5#, L-80 tbgr

Arrow-set 10K pkr w/ on/off @ 8400

CIBP @ 8850' w/ 35' cement
Wolfcamp D Perfs - 10,834'-11,046' (90 holes)
CIBP @ 11,082' w/ 35' cement fill
Strawn Perfs - 11,092'-11,234' (60 holes)
CIBP @ 11,250' w/ 35' cement fill
Arrow-set 10K pkr w/ on/off tl w/ 2.25 fn @ 11,261
Atoka perfs 11,372'-86' 6 spf (84 holes)
RBP @ 11,402' 8' sand fill
Atoka Perfs 11,410'-20'
w/ aut rel. .98", OD 3.375", ID 1.56"
3.375" gun 6 JSPF, 11.93'
CIBP @ 12,050' cap w/ 35' cmt
Upper Morrow Perfs
12,088'-98' 10 spf (60 holes)
12,116'-124' 8 spf (48 holes)
CIBP @ 12,350'

Middle Morrow Perfs
12,396'-400' 6 spf (24 holes)
Middle Morrow Perfs
12,406'-10' 6 spf (24 holes)
CIBP @ 12,480'
Lower Morrow Perfs
12,504'-14' 6 spf (60 holes)