

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**Carlsbad Field Office**  
**Operator Copy**

FORM APPROVED  
OMB NO. 1004-0137  
Expires: January 31, 2018

**SUNDRY NOTICES AND REPORTS ON WELLS**  
*Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.*

Case Serial No. NMNM004825
6. If Indian, Allottee or Tribe Name
7. If Unit or CA/Agreement, Name and/or No.
8. Well Name and No. PENNZOIL 32 FED 122H
9. API Well No. 30-015-44574-00-X1
10. Field and Pool or Exploratory Area GETTY
11. County or Parish, State EDDY COUNTY, NM

**SUBMIT IN TRIPLICATE - Other instructions on page 2**

1. Type of Well <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other
2. Name of Operator MATADOR PRODUCTION COMPANY Contact: CADE LABOLT Mail: cade.labolt@matadorresources.com
3a. Address ONE LINCOLN CENTER 5400 LBJ FREEWAY SUITE DALLAS, TX 75240
3b. Phone No. (include area code) 1500 972-629-2158
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Sec 33 T20S R29E SWNW 2030FNL 348FWL 32.531578 N Lat, 104.087471 W Lon

**12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA**

TYPE OF SUBMISSION	TYPE OF ACTION				
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off	
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Hydraulic Fracturing	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity	
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input checked="" type="checkbox"/> Other	
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	Change to Original A PD	
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal		

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.

Pennzoil 32 Fed 122H to Pennzoil 3231 Fed Com 126H

BLM Bond No. NMB001079  
Surety Bond No. RLB0015172

*Approved by NMC on 8/6/2019 Engineer JOE BLM*  
*previous COAs Apply.*

**NM OIL CONSERVATION**  
ARTESIA DISTRICT  
AUG 21 2019

The purpose of this sundry is to extend the lateral of the subject well (API# 30-015-44574) from 1 mile to 2 mile in length.

Please see the attached C102 to revise the SHL of Matador's Pennzoil 32 Fed 122H from 2030' FNL and 348' FWL of Sec. 33 T20S R29E to 2000' FNL and 378' FWL of Sec. 33 T20S R29E.

Please see the attached C102 to revise the BHL of Matador's Pennzoil 32 Fed 122H from 1870' FNL and

**RECEIVED**

*Approved. DCS 08/05/2019. DOI - BLM - NM - PDZO - 2017 - 0094 - EA. SAME COA'S APPLY*

14. I hereby certify that the foregoing is true and correct. Electronic Submission #473051 verified by the BLM Well Information System For MATADOR PRODUCTION COMPANY, sent to the Carlsbad Committed to AFMSS for processing by PRISCILLA PEREZ on 07/12/2019 (19PP2789SE)	
Name (Printed/Typed) CADE LABOLT	Title ASSOCIATE LANDMAN
Signature (Electronic Submission)	Date 07/11/2019

**THIS SPACE FOR FEDERAL OR STATE OFFICE USE**

Approved By <i>[Signature]</i>	Title <i>AFM - L &amp; M</i>	Date <i>08/05/2019</i>
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.		Office <i>AFM</i>

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

**\*\* BLM REVISED \*\* BLM REVISED \*\* BLM REVISED \*\* BLM REVISED \*\* BLM REVISED \*\***

*PWP 10-29-19*  
*Need 102*

**Additional data for EC transaction #473051 that would not fit on the form**

**32. Additional remarks, continued**

240' FWL of Sec. 32 T20S R29E to 2323' FNL and 60' FWL of Sec. 31 T20S R29E. The BHL given represents the terminus of the well. The last perforation point will be 2323' FNL and 100' FWL lying within the S2N2 of Sec. 31 T20S R29E.

**Mud**

Matador requests to change production hole section mud program to OBM.

Name	Hole Size	Mud Weight	Visc	Fluid Loss	Type	Mud
Surface	26"	8.40	28	NC	FW	Spud Mud
Intermediate 1	17-1/2"	10.00	30-32	NC	Brine	Water
Intermediate 2	12-1/4"	8.4-8.6	28-30	NC	FW	
Production	8-3/4"	8.5-9.5	30-55	NC	Cut brine/OBM	

Matador requests a variance for the use of a diverter along with a 2000 psi annular to be installed after running 20" surface casing.

Matador requests the option to cut off 20" SOW wellhead and run 13-3/8" SOW multi-bowl wellhead system once 1st intermediate string is run and cemented.

Matador requests the option to run a DV tool with annular packer as contingency in the intermediate 1 or 2 section on 13-3/8" or 9-5/8" casing if lost circulation is encountered. If losses occur, the DV tool with packer will be placed at least 100' above the loss zone to give the option to pump cement as either a single stage or two stage.

**Example:**

Assuming DV tool is set at 1500' MD but if the setting depth changes, cement volumes will be adjusted proportionately.

Stage 1:  
Lead 695 1.78 13.5 Class C + Bentonite + 2% CaCL2 + 3% NaCl + LCM  
Tail 288 1.35 14.4 Class C + 5% NaCl + LCM  
100% excess, TOC = 0' MD

Stage 2:  
Lead 350 1.78 13.5 Class C + Bentonite + 2% CaCL2 + 3% NaCl + LCM  
100% excess, TOC = 0' MD

Matador requests the name of the Pennzoil 32 Fed 122H be changed to the Pennzoil 3231 Fed Com 126H