

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
APPLICATION FOR PERMIT TO DRILL OR REENTER

1a. Type of work: <input checked="" type="checkbox"/> DRILLED <input type="checkbox"/> REENTER		5. Lease Serial No. NMNM088134
1b. Type of Well: <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other		6. If Indian, Allottee or Tribe Name
1c. Type of Completion: <input type="checkbox"/> Hydraulic Fracturing <input checked="" type="checkbox"/> Single Zone <input type="checkbox"/> Multiple Zone		7. If Unit or CA Agreement, Name and No.
2. Name of Operator DEVON ENERGY PRODUCTION COMPANY LP		8. Lease Name and Well No. MR. POTATO HEAD 11-14 FED COM 331H
3a. Address 333 West Sheridan Avenue Oklahoma City OK 73102	3b. Phone No. (include area code) (800)583-3866	9. API Well No. 326251 30-015-46425
4. Location of Well (Report location clearly and in accordance with any State requirements. *) At surface NWNW / 350 FNL / 1105 FWL / LAT 32.2384591 / LONG -103.9602093 At proposed prod. zone SWSW / 20 FSL / 1100 FWL / LAT 32.210296 / LONG -103.9601929		10. Field and Pool, or Exploratory PIERCE CROSSING BONE SPRING, EA
14. Distance in miles and direction from nearest town or post office*		11. Sec., T. R. M. or Blk. and Survey or Area SEC 11 / T24S / R29E / NMP
15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any) 350 feet	16. No of acres in lease 560	12. County or Parish EDDY
17. Spacing Unit dedicated to this well 320	18. Distance from proposed location* to nearest well, drilling, completed, applied for, on this lease, ft. 1025 feet	13. State NM
19. Proposed Depth 10070 feet / 20221 feet	20. BLM/BIA Bond No. in file FED: NMB000807	
21. Elevations (Show whether DF, KDB, RT, GL, etc.) 3052 feet	22. Approximate date work will start* 10/15/2020	23. Estimated duration 45 days
24. Attachments		

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, and the Hydraulic Fracturing rule per 43 CFR 3162.3-3 (as applicable)

- | | |
|--|---|
| 1. Well plat certified by a registered surveyor. | 4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above). |
| 2. A Drilling Plan. | 5. Operator certification. |
| 3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office). | 6. Such other site specific information and/or plans as may be requested by the BLM. |

25. Signature (Electronic Submission)	Name (Printed/Typed) Erin Workman / Ph: (405)552-7970	Date 09/17/2018
Title Regulatory Compliance Professional		
Approved by (Signature) (Electronic Submission)	Name (Printed/Typed) Cody Layton / Ph: (575)234-5959	Date 10/18/2019
Title Assistant Field Manager Lands & Minerals CARLSBAD		

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.
Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.



**PECOS DISTRICT
DRILLING CONDITIONS OF APPROVAL**

OPERATOR'S NAME:	DEVON ENERGY PRODUCTION CO. LP
LEASE NO.:	NMNM88134
WELL NAME & NO.:	331H – MR. POTATO HEAD 11-14 FED COM
SURFACE HOLE FOOTAGE:	350'/N & 1105'/W
BOTTOM HOLE FOOTAGE:	20'/S & 990'/W
LOCATION:	Section 11 T.24 S., R.29 E., NMP
COUNTY:	EDDY County, New Mexico

COA

H2S	<input type="radio"/> Yes	<input checked="" type="radio"/> No	
Potash	<input checked="" type="radio"/> None	<input type="radio"/> Secretary	<input type="radio"/> R-111-P
Cave/Karst Potential	<input type="radio"/> Low	<input checked="" type="radio"/> Medium	<input type="radio"/> High
Variance	<input type="radio"/> None	<input checked="" type="radio"/> Flex Hose	<input type="radio"/> Other
Wellhead	<input type="radio"/> Conventional	<input type="radio"/> Multibowl	<input checked="" type="radio"/> Both
Other	<input type="checkbox"/> 4 String Area	<input type="checkbox"/> Capitan Reef	<input type="checkbox"/> WIPP
Other	<input checked="" type="checkbox"/> Fluid Filled	<input checked="" type="checkbox"/> Cement Squeeze	<input type="checkbox"/> Pilot Hole
Special Requirements	<input type="checkbox"/> Water Disposal	<input checked="" type="checkbox"/> COM	<input type="checkbox"/> Unit

A. HYDROGEN SULFIDE

Hydrogen Sulfide (H2S) monitors shall be installed prior to drilling out the surface shoe. If H2S is detected in concentrations greater than 100 ppm, the Hydrogen Sulfide area shall meet Onshore Order 6 requirements, which includes equipment and personnel/public protection items. If Hydrogen Sulfide is encountered, provide measured values and formations to the BLM.

B. CASING

Primary Casing Design:

1. The 13-3/8 inch surface casing shall be set at approximately **400 feet** (a minimum of 70 feet (Eddy County) into the Rustler Anhydrite and above the salt) and cemented to the surface.
 - a. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with surface log readout will be used or a cement bond log shall be run to verify the top of the cement. Temperature survey will be run a minimum of six hours after pumping cement and ideally between 8-10 hours after completing the cement job.

- b. Wait on cement (WOC) time for a primary cement job will be a minimum of **8 hours** or 500 pounds compressive strength, whichever is greater. (This is to include the lead cement)
- c. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength, whichever is greater.
- d. If cement falls back, remedial cementing will be done prior to drilling out that string.

Intermediate casing must be kept fluid filled to meet BLM minimum collapse requirement.

2. The minimum required fill of cement behind the 7-5/8 inch intermediate casing is:

Option 1 (Single Stage):

- Cement to surface. If cement does not circulate see B.1.a, c-d above.
Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry due to cave/karst or potash.

Option 2:

Operator has proposed a DV tool, the depth may be adjusted as long as the cement is changed proportionally. The DV tool may be cancelled if cement circulates to surface on the first stage.

- a. First stage to DV tool: Cement to circulate. If cement does not circulate off the DV tool, contact the appropriate BLM office before proceeding with second stage cement job.
 - b. Second stage above DV tool:
 - Cement to surface. If cement does not circulate, contact the appropriate BLM office.
Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry due to cave/karst or potash.
- ❖ In Medium Cave/Karst Areas if cement does not circulate to surface on the first two casing strings, the cement on the 3rd casing string must come to surface.

Operator has proposed to pump down 13-3/8" X 7-5/8" annulus. Operator must run a CBL from TD of the 7-5/8" casing to surface. Submit results to BLM.

3. The minimum required fill of cement behind the 5-1/2 inch production casing is:

- Cement should tie-back at least **200 feet** into previous casing string. Operator shall provide method of verification.
Cement excess is less than 25%, more cement might be required.

Alternate Casing Design:

4. The 13-3/8 inch surface casing shall be set at approximately **400 feet** (a minimum of 70 feet (Eddy County) into the Rustler Anhydrite and above the salt) and cemented to the surface.

- e. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with surface log readout will be used or a cement bond log shall be run to verify the top of the cement. Temperature survey will be run a minimum of six hours after pumping cement and ideally between 8-10 hours after completing the cement job.
- f. Wait on cement (WOC) time for a primary cement job will be a minimum of **8 hours** or 500 pounds compressive strength, whichever is greater. (This is to include the lead cement)
- g. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength, whichever is greater.
- h. If cement falls back, remedial cementing will be done prior to drilling out that string.

Intermediate casing must be kept fluid filled to meet BLM minimum collapse requirement.

5. The minimum required fill of cement behind the 8-5/8 inch intermediate casing is:

Option 1 (Single Stage):

- Cement to surface. If cement does not circulate see B.1.a, c-d above.
Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry due to cave/karst or potash.

Option 2:

Operator has proposed a DV tool, the depth may be adjusted as long as the cement is changed proportionally. The DV tool may be cancelled if cement circulates to surface on the first stage.

c. First stage to DV tool: Cement to circulate. If cement does not circulate off the DV tool, contact the appropriate BLM office before proceeding with second stage cement job.

d. Second stage above DV tool:

- Cement to surface. If cement does not circulate, contact the appropriate BLM office.

Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry due to cave/karst or potash.

❖ In Medium Cave/Karst Areas if cement does not circulate to surface on the first two casing strings, the cement on the 3rd casing string must come to surface.

Operator has proposed to pump down 13-3/8" X 8-5/8" annulus. Operator must run a CBL from TD of the 8-5/8" casing to surface. Submit results to BLM.

Variance requested to drill 10.625" hole with TLW connection is Approved. Cement excess is less than -19%, more cement will be required.

6. The minimum required fill of cement behind the 5-1/2 inch production casing is:

- Cement should tie-back at least **200 feet** into previous casing string. Operator shall provide method of verification.

Cement excess is less than 25%, more cement might be required.

C. PRESSURE CONTROL

1. Variance approved to use flex line from BOP to choke manifold. Manufacturer's specification to be readily available. No external damage to flex line. Flex line to be installed as straight as possible (no hard bends).'

2.

Option 1:

a. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be **5000 (5M)** psi.

b. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the intermediate casing shoe shall be **5000 (5M)** psi.

Option 2:

1. Operator has proposed a multi-bowl wellhead assembly. This assembly will only be tested when installed on the surface casing. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be **5000 (5M)** psi.
 - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
 - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
 - c. Manufacturer representative shall install the test plug for the initial BOP test.
 - d. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
 - e. Whenever any seal subject to test pressure is broken, all the tests in OOGO2.III.A.2.i must be followed.

D. SPECIAL REQUIREMENT (S)

Communitization Agreement

- The operator will submit a Communitization Agreement to the Carlsbad Field Office, 620 E Greene St. Carlsbad, New Mexico 88220, at least 90 days before the anticipated date of first production from a well subject to a spacing order issued by the New Mexico Oil Conservation Division. The Communitization Agreement will include the signatures of all working interest owners in all Federal and Indian leases subject to the Communitization Agreement (i.e., operating rights owners and lessees of record), or certification that the operator has obtained the written signatures of all such owners and will make those signatures available to the BLM immediately upon request.
- If the operator does not comply with this condition of approval, the BLM may take enforcement actions that include, but are not limited to, those specified in 43 CFR 3163.1.
- In addition, the well sign shall include the surface and bottom hole lease numbers. When the Communitization Agreement number is known, it shall also be on the sign.

GENERAL REQUIREMENTS

The BLM is to be notified in advance for a representative to witness:

- a. Spudding well (minimum of 24 hours)
- b. Setting and/or Cementing of all casing strings (minimum of 4 hours)
- c. BOPE tests (minimum of 4 hours)

Chaves and Roosevelt Counties
Call the Roswell Field Office, 2909 West Second St., Roswell NM 88201.
During office hours call (575) 627-0272.
After office hours call (575)

Eddy County
Call the Carlsbad Field Office, 620 East Greene St., Carlsbad, NM 88220,
(575) 361-2822

Lea County
Call the Hobbs Field Station, 414 West Taylor, Hobbs NM 88240, (575)
393-3612

1. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval.
 - a. In the event the operator has proposed to drill multiple wells utilizing a skid/walking rig. Operator shall secure the wellbore on the current well, after installing and testing the wellhead, by installing a blind flange of like pressure rating to the wellhead and a pressure gauge that can be monitored while drilling is performed on the other well(s).
 - b. When the operator proposes to set surface casing with Spudder Rig
 - Notify the BLM when moving in and removing the Spudder Rig.
 - Notify the BLM when moving in the 2nd Rig. Rig to be moved in within 90 days of notification that Spudder Rig has left the location.
 - BOP/BOPE test to be conducted per Onshore Oil and Gas Order No. 2 as soon as 2nd Rig is rigged up on well.
2. Floor controls are required for 3M or Greater systems. These controls will be on the rig floor, unobstructed, readily accessible to the driller and will be operational at all times during drilling and/or completion activities. Rig floor is defined as the area immediately around the rotary table; the area immediately above the substructure on which the draw works are located, this does not include the dog house or stairway area.

3. The record of the drilling rate along with the GR/N well log run from TD to surface (horizontal well – vertical portion of hole) shall be submitted to the BLM office as well as all other logs run on the borehole 30 days from completion. If available, a digital copy of the logs is to be submitted in addition to the paper copies. The Rustler top and top and bottom of Salt are to be recorded on the Completion Report.

A. CASING

1. Changes to the approved APD casing program need prior approval if the items substituted are of lesser grade or different casing size or are Non-API. The Operator can exchange the components of the proposal with that of superior strength (i.e. changing from J-55 to N-80, or from 36# to 40#). Changes to the approved cement program need prior approval if the altered cement plan has less volume or strength or if the changes are substantial (i.e. Multistage tool, ECP, etc.). The initial wellhead installed on the well will remain on the well with spools used as needed.
2. Wait on cement (WOC) for Potash Areas: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi for all cement blends, 2) until cement has been in place at least 24 hours. WOC time will be recorded in the driller's log.
3. Wait on cement (WOC) for Water Basin: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi at the shoe, 2) until cement has been in place at least 8 hours. WOC time will be recorded in the driller's log. See individual casing strings for details regarding lead cement slurry requirements.
4. Provide compressive strengths including hours to reach required 500 pounds compressive strength prior to cementing each casing string. Have well specific cement details onsite prior to pumping the cement for each casing string.
5. No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.
6. On that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Formation at the shoe shall be tested to a minimum of the mud weight equivalent anticipated to control the formation pressure to the next casing depth or at total depth of the well. This test shall be performed before drilling more than 20 feet of new hole.
7. If hardband drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.

8. Whenever a casing string is cemented in the R-111-P potash area, the NMOCD requirements shall be followed.

B. PRESSURE CONTROL

1. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in Onshore Oil and Gas Order No. 2 and API RP 53 Sec. 17.
2. If a variance is approved for a flexible hose to be installed from the BOP to the choke manifold, the following requirements apply: Check condition of flexible line from BOP to choke manifold, replace if exterior is damaged or if line fails test. Line to be as straight as possible with no hard bends and is to be anchored according to Manufacturer's requirements. The flexible hose can be exchanged with a hose of equal size and equal or greater pressure rating. Anchor requirements, specification sheet and hydrostatic pressure test certification matching the hose in service, to be onsite for review. These documents shall be posted in the company man's trailer and on the rig floor.
3. 5M or higher system requires an HCR valve, remote kill line and annular to match. The remote kill line is to be installed prior to testing the system and tested to stack pressure.
4. If the operator has proposed a multi-bowl wellhead assembly in the APD. The following requirements must be met:
 - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
 - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
 - c. Manufacturer representative shall install the test plug for the initial BOP test.
 - d. Whenever any seal subject to test pressure is broken, all the tests in OOGO2.III.A.2.i must be followed.
 - e. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
5. The appropriate BLM office shall be notified a minimum of 4 hours in advance for a representative to witness the tests.
 - a. In a water basin, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. The casing cut-off and BOP installation can be initiated four hours after installing the slips, which will be approximately six hours after bumping the

plug. For those casing strings not using slips, the minimum wait time before cut-off is eight hours after bumping the plug. BOP/BOPE testing can begin after cut-off or once cement reaches 500 psi compressive strength (including lead when specified), whichever is greater. However, if the float does not hold, cut-off cannot be initiated until cement reaches 500 psi compressive strength (including lead when specified).

- b. In potash areas, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. For all casing strings, casing cut-off and BOP installation can be initiated at twelve hours after bumping the plug. However, **no tests** shall commence until the cement has had a minimum of 24 hours setup time.
- c. The tests shall be done by an independent service company utilizing a test plug not a cup or J-packer. The operator also has the option of utilizing an independent tester to test without a plug (i.e. against the casing) pursuant to Onshore Order 2 with the pressure not to exceed 70% of the burst rating for the casing. Any test against the casing must meet the WOC time for water basin (8 hours) or potash (24 hours) or 500 pounds compressive strength, whichever is greater, prior to initiating the test (see casing segment as lead cement may be critical item).
- d. The test shall be run on a 5000 psi chart for a 2-3M BOP/BOP, on a 10000 psi chart for a 5M BOP/BOPE and on a 15000 psi chart for a 10M BOP/BOPE. If a linear chart is used, it shall be a one hour chart. A circular chart shall have a maximum 2 hour clock. If a twelve hour or twenty-four hour chart is used, tester shall make a notation that it is run with a two hour clock.
- e. The results of the test shall be reported to the appropriate BLM office.
- f. All tests are required to be recorded on a calibrated test chart. A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.
- g. The BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes if test is done with a test plug and 30 minutes without a test plug. This test shall be performed prior to the test at full stack pressure.
- h. BOP/BOPE must be tested by an independent service company within 500 feet of the top of the Wolfcamp formation if the time between the setting of the intermediate casing and reaching this depth exceeds 20 days. This test does not exclude the test prior to drilling out the casing shoe as per Onshore Order No. 2.

C. DRILLING MUD

Mud system monitoring equipment, with derrick floor indicators and visual and audio alarms, shall be operating before drilling into the Wolfcamp formation, and shall be used until production casing is run and cemented.

D. WASTE MATERIAL AND FLUIDS

All waste (i.e. drilling fluids, trash, salts, chemicals, sewage, gray water, etc.) created as a result of drilling operations and completion operations shall be safely contained and disposed of properly at a waste disposal facility. No waste material or fluid shall be disposed of on the well location or surrounding area.

Porto-johns and trash containers will be on-location during fracturing operations or any other crew-intensive operations.



**Devon Energy Center
333 West Sheridan Avenue
Oklahoma City, Oklahoma 73102-5015**


Hydrogen Sulfide (H₂S) Contingency Plan

For

Mr Potato Head 11-14 Fed Com 331H

**Sec-11 T-24S R-29E
350' FNL & 1105' FWL
LAT. = 32.2384591' N (NAD83)
LONG = 103.9602093' W**

Eddy County NM



Assumed 100 ppm ROE = 3000' (Radius of Exposure)
100 ppm H₂S concentration shall trigger activation of this plan.

Escape

Crews shall escape upwind of escaping gas in the event of an emergency release of gas. Escape can be facilitated from the location entrance road. Crews should then block the entrance to the location from the lease road so as not to allow anyone traversing into a hazardous area. The blockade should be at a safe

distance outside of the ROE. There are no homes or buildings in or near the ROE.

Assumed 100 ppm ROE = 3000'

100 ppm H₂S concentration shall trigger activation of this plan.

Emergency Procedures

In the event of a release of gas containing H₂S, the first responder(s) must

- **Isolate the area and prevent entry by other persons into the 100 ppm ROE.**
- **Evacuate any public places encompassed by the 100 ppm ROE.**
- **Be equipped with H₂S monitors and air packs in order to control the release.**
- **Use the “buddy system” to ensure no injuries occur during the response**
- **Take precautions to avoid personal injury during this operation.**
- **Contact operator and/or local officials to aid in operation. See list of phone numbers attached.**
- **Have received training in the**
 - **Detection of H₂S, and**
 - **Measures for protection against the gas,**
 - **Equipment used for protection and emergency response.**

Ignition of Gas Source

Should control of the well be considered lost and ignition considered, take care to protect against exposure to Sulfur Dioxide (SO₂). Intentional ignition must be coordinated with the NMOCD and local officials. Additionally the NM State Police may become involved. NM State Police shall be the Incident Command on scene of any major release. Take care to protect downwind whenever there is an ignition of the gas

Characteristics of H₂S and SO₂

Common Name	Chemical Formula	Specific Gravity	Threshold Limit	Hazardous Limit	Lethal Concentration
Hydrogen Sulfide	H₂S	1.189 Air = 1	10 ppm	100 ppm/hr	600 ppm
Sulfur Dioxide	SO₂	2.21 Air = 1	2 ppm	N/A	1000 ppm

Contacting Authorities

Devon Energy Corp. personnel must liaison with local and state agencies to ensure a proper response to a major release. Additionally, the OCD must be notified of the release as soon as possible but no later than 4 hours. Agencies

will ask for information such as type and volume of release, wind direction, location of release, etc. Be prepared with all information available. The following call list of essential and potential responders has been prepared for use during a release. Devon Energy Corp. Company response must be in coordination with the State of New Mexico's 'Hazardous Materials Emergency Response Plan' (HMER)

Hydrogen Sulfide Drilling Operation Plan

I. HYDROGEN SULFIDE (H₂S) TRAINING

All personnel, whether regularly assigned, contracted, or employed on an unscheduled basis, will receive training from a qualified instructor in the following areas prior to commencing drilling operations on this well:

1. The hazards and characteristics of hydrogen sulfide (H₂S)
2. The proper use and maintenance of personal protective equipment and life support systems.
3. The proper use of H₂S detectors, alarms, warning systems, briefing areas, evacuation procedures, and prevailing winds.
4. The proper techniques for first aid and rescue procedures.

In addition, supervisory personnel will be trained in the following areas:

1. The effects of H₂S metal components. If high tensile tubulars are to be used, personnel will be trained in their special maintenance requirements.
2. Corrective action and shut-in procedures when drilling or reworking a well and blowout prevention and well control procedures.
3. The contents and requirements of the H₂S Drilling Operations Plan and Public Protection Plan.

There will be an initial training session just prior to encountering a known or probable H₂S zone (within 3 days or 500 feet) and weekly H₂S and well control drills for all personnel in each crew. The initial training session shall include a review of the site specific H₂S Drilling Operations Plan and the Public Protection Plan.

II. HYDROGEN SULFIDE TRAINING

Note: All H₂S safety equipment and systems will be installed, tested, and operational when drilling reaches a depth of 500 feet above, or three days

prior to penetrating the first zone containing or reasonably expected to contain H₂S.

1. Well Control Equipment

- A. Flare line
- B. Choke manifold – Remotely Operated
- C. Blind rams and pipe rams to accommodate all pipe sizes with properly sized closing unit
- D. Auxiliary equipment may include if applicable: annular preventer and rotating head.
- E. Mud/Gas Separator

2. Protective equipment for essential personnel:

30-minute SCBA units located at briefing areas, as indicated on well site diagram, with escape units available in the top doghouse. As it may be difficult to communicate audibly while wearing these units, hand signals shall be utilized.

3. H₂S detection and monitoring equipment:

Portable H₂S monitors positioned on location for best coverage and response. These units have warning lights which activate when H₂S levels reach 10 ppm and audible sirens which activate at 15 ppm. Sensor locations:

- Bell nipple
- Rig floor
- Cellar
- Possum Belly/Shale shaker
- Choke manifold

Visual warning systems:

- A. Wind direction indicators as shown on well site diagram
- B. Caution/ Danger signs shall be posted on roads providing direct access to locations. Signs will be painted a high visibility yellow with black lettering of sufficient size to be reasonable distance from the immediate location. Bilingual signs will be used when appropriate.

4. Mud program:

The mud program has been designed to minimize the volume of H₂S circulated to surface. Proper mud weight, safe drilling practices and the use of H₂S scavengers will minimize hazards when penetrating H₂S bearing zones.

5. Metallurgy:

- A. All drill strings, casings, tubing, wellhead, blowout preventer, drilling spool, kill lines, choke manifold lines, and valves shall be H₂S trim.
- B. All elastomers used for packing and seals shall be H₂S trim.

6. Communication:

- A. Company personnel have/use cellular telephones in the field.
- B. Land line (telephone) communications at Office

7. Well testing:

- A. Drill stem testing will be performed with a minimum number of personnel in the immediate vicinity, which are necessary to safety and adequately conduct the test. The drill stem testing will be conducted during daylight hours and formation

fluids will not be flowed to the surface. All drill-stem-testing operations conducted in an H₂S environment will use the closed chamber method of testing.

B. There will be no drill stem testing.

Devon Energy Corp. Company Call List	
Drilling Supervisor – Basin – Mark Kramer	405-823-4796
EHS Professional – Laura Wright	405-439-8129
Agency Call List	
Lea County (575)	Hobbs
	Lea County Communication Authority 393-3981
	State Police 392-5588
	City Police 397-9265
	Sheriff's Office 393-2515
	Ambulance 911
	Fire Department 397-9308
	LEPC (Local Emergency Planning Committee) 393-2870
	NMOCD 393-6161
	US Bureau of Land Management 393-3612
Eddy County (575)	Carlsbad
	State Police 885-3137
	City Police 885-2111
	Sheriff's Office 887-7551
	Ambulance 911
	Fire Department 885-3125
	LEPC (Local Emergency Planning Committee) 887-3798
	US Bureau of Land Management 887-6544
	NM Emergency Response Commission (Santa Fe) (505) 476-9600

	24 HR	(505) 827-9126
	National Emergency Response Center	(800) 424-8802
	National Pollution Control Center: Direct	(703) 872-6000
	For Oil Spills	(800) 280-7118
	Emergency Services	
	Wild Well Control	(281) 784-4700
	Cudd Pressure Control	(915) 699-0139 (915) 563-3356
	Halliburton	(575) 746-2757
	B. J. Services	(575) 746-3569
Give GPS position :	Native Air – Emergency Helicopter – Hobbs	(575) 392-6429
	Flight For Life - Lubbock, TX	(806) 743-9911
	Aerocare - Lubbock, TX	(806) 747-8923
	Med Flight Air Amb - Albuquerque, NM	(575) 842-4433
	Lifeguard Air Med Svc. Albuquerque, NM	(800) 222-1222
	Poison Control (24/7)	(575) 272-3115
	Oil & Gas Pipeline 24 Hour Service	(800) 364-4366
	NOAA – Website - www.nhc.noaa.gov	

WCDSC Permian NM

Eddy County (NAD 83 NM Eastern)

Sec 11-T24S-R29E

Mr. Potato Head 11-14 Fed Com 331H

Wellbore #1

Plan: Permit Plan 2

Standard Planning Report - Geographic

04 April, 2019

Planning Report - Geographic

Database:	EDM r5000.141_Prod US	Local Co-ordinate Reference:	Well Mr. Potato Head 11-14 Fed Com 331H
Company:	WCDSC Permian NM	TVD Reference:	RKB @ 3077.30ft
Project:	Eddy County (NAD 83 NM Eastern)	MD Reference:	RKB @ 3077.30ft
Site:	Sec 11-T24S-R29E	North Reference:	Grid
Well:	Mr. Potato Head 11-14 Fed Com 331H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Permit Plan 2		

Project	Eddy County (NAD 83 NM Eastern)		
Map System:	US State Plane 1983	System Datum:	Mean Sea Level
Geo Datum:	North American Datum 1983		
Map Zone:	New Mexico Eastern Zone		

Site	Sec 11-T24S-R29E				
Site Position:	Northing:	451,030.14 usft	Latitude:	32.239417	
From: Map	Easting:	655,595.01 usft	Longitude:	-103.963784	
Position Uncertainty:	5.00 ft	Slot Radius:	13-3/16 "	Grid Convergence:	0.20 °

Well	Mr. Potato Head 11-14 Fed Com 331H					
Well Position	+N/-S	0.00 ft	Northing:	450,685.36 usft	Latitude:	32.238459
	+E/-W	0.00 ft	Easting:	656,701.50 usft	Longitude:	-103.960210
Position Uncertainty		0.50 ft	Wellhead Elevation:		Ground Level:	3,052.30 ft

Wellbore	Wellbore #1				
Magnetics	Model Name	Sample Date	Declination	Dip Angle	Field Strength
	IGRF2015	4/3/2019	(°)	(°)	(nT)
			6.94	59.99	47,723.90776844

Design	Permit Plan 2			
Audit Notes:				
Version:	Phase:	PROTOTYPE	Tie On Depth:	0.00
Vertical Section:	Depth From (TVD)	+N/-S	+E/-W	Direction
	(ft)	(ft)	(ft)	(°)
	0.00	0.00	0.00	179.77

Plan Survey Tool Program	Date	4/4/2019		
Depth From	Depth To	Survey (Wellbore)	Tool Name	Remarks
(ft)	(ft)			
1	0.00	20,221.24 Permit Plan 2 (Wellbore #1)	MWD+HDGM	
			OWSG MWD + HDGM	

Plan Sections										
Measured	Inclination	Azimuth	Vertical	+N/-S	+E/-W	Dogleg	Build	Turn	TFO	Target
Depth	(°)	(°)	Depth	(ft)	(ft)	Rate	Rate	Rate	(°)	
(ft)			(ft)			(°/100usft)	(°/100usft)	(°/100usft)		
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
2,600.00	0.00	0.00	2,600.00	0.00	0.00	0.00	0.00	0.00	0.00	
2,738.27	1.38	14.93	2,738.25	1.61	0.43	1.00	1.00	0.00	14.93	
9,056.68	1.38	14.93	9,054.83	148.93	39.71	0.00	0.00	0.00	0.00	
9,148.86	0.00	0.00	9,147.00	150.00	40.00	1.50	-1.50	0.00	180.00	
9,498.90	0.00	0.00	9,497.04	150.00	40.00	0.00	0.00	0.00	0.00	
10,398.90	90.00	180.00	10,070.00	-422.96	40.04	10.00	10.00	0.00	180.00	PBHL - Mr. Potatohead
20,221.24	90.00	180.00	10,070.00	-10,245.29	40.65	0.00	0.00	0.00	0.00	PBHL - Mr. Potatohead

Planning Report - Geographic

Database:	EDM r5000.141_Prod US	Local Co-ordinate Reference:	Well Mr. Potato Head 11-14 Fed Com 331H
Company:	WCDSC Permian NM	TVD Reference:	RKB @ 3077.30ft
Project:	Eddy County (NAD 83 NM Eastern)	MD Reference:	RKB @ 3077.30ft
Site:	Sec 11-T24S-R29E	North Reference:	Grid
Well:	Mr. Potato Head 11-14 Fed Com 331H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Permit Plan 2		

Planned Survey										
Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N-S (ft)	+E-W (ft)	Map Northing (usft)	Map Easting (usft)	Latitude	Longitude	
0.00	0.00	0.00	0.00	0.00	0.00	450,685.36	656,701.50	32.238459	-103.960210	
100.00	0.00	0.00	100.00	0.00	0.00	450,685.36	656,701.50	32.238459	-103.960210	
200.00	0.00	0.00	200.00	0.00	0.00	450,685.36	656,701.50	32.238459	-103.960210	
300.00	0.00	0.00	300.00	0.00	0.00	450,685.36	656,701.50	32.238459	-103.960210	
400.00	0.00	0.00	400.00	0.00	0.00	450,685.36	656,701.50	32.238459	-103.960210	
500.00	0.00	0.00	500.00	0.00	0.00	450,685.36	656,701.50	32.238459	-103.960210	
600.00	0.00	0.00	600.00	0.00	0.00	450,685.36	656,701.50	32.238459	-103.960210	
700.00	0.00	0.00	700.00	0.00	0.00	450,685.36	656,701.50	32.238459	-103.960210	
800.00	0.00	0.00	800.00	0.00	0.00	450,685.36	656,701.50	32.238459	-103.960210	
900.00	0.00	0.00	900.00	0.00	0.00	450,685.36	656,701.50	32.238459	-103.960210	
1,000.00	0.00	0.00	1,000.00	0.00	0.00	450,685.36	656,701.50	32.238459	-103.960210	
1,100.00	0.00	0.00	1,100.00	0.00	0.00	450,685.36	656,701.50	32.238459	-103.960210	
1,200.00	0.00	0.00	1,200.00	0.00	0.00	450,685.36	656,701.50	32.238459	-103.960210	
1,300.00	0.00	0.00	1,300.00	0.00	0.00	450,685.36	656,701.50	32.238459	-103.960210	
1,400.00	0.00	0.00	1,400.00	0.00	0.00	450,685.36	656,701.50	32.238459	-103.960210	
1,500.00	0.00	0.00	1,500.00	0.00	0.00	450,685.36	656,701.50	32.238459	-103.960210	
1,600.00	0.00	0.00	1,600.00	0.00	0.00	450,685.36	656,701.50	32.238459	-103.960210	
1,700.00	0.00	0.00	1,700.00	0.00	0.00	450,685.36	656,701.50	32.238459	-103.960210	
1,800.00	0.00	0.00	1,800.00	0.00	0.00	450,685.36	656,701.50	32.238459	-103.960210	
1,900.00	0.00	0.00	1,900.00	0.00	0.00	450,685.36	656,701.50	32.238459	-103.960210	
2,000.00	0.00	0.00	2,000.00	0.00	0.00	450,685.36	656,701.50	32.238459	-103.960210	
2,100.00	0.00	0.00	2,100.00	0.00	0.00	450,685.36	656,701.50	32.238459	-103.960210	
2,200.00	0.00	0.00	2,200.00	0.00	0.00	450,685.36	656,701.50	32.238459	-103.960210	
2,300.00	0.00	0.00	2,300.00	0.00	0.00	450,685.36	656,701.50	32.238459	-103.960210	
2,400.00	0.00	0.00	2,400.00	0.00	0.00	450,685.36	656,701.50	32.238459	-103.960210	
2,500.00	0.00	0.00	2,500.00	0.00	0.00	450,685.36	656,701.50	32.238459	-103.960210	
2,600.00	0.00	0.00	2,600.00	0.00	0.00	450,685.36	656,701.50	32.238459	-103.960210	
2,700.00	1.00	14.93	2,699.99	0.84	0.22	450,686.20	656,701.73	32.238462	-103.960209	
2,738.27	1.38	14.93	2,738.25	1.61	0.43	450,686.97	656,701.93	32.238464	-103.960208	
2,800.00	1.38	14.93	2,799.97	3.05	0.81	450,688.41	656,702.32	32.238468	-103.960207	
2,900.00	1.38	14.93	2,899.94	5.38	1.44	450,690.74	656,702.94	32.238474	-103.960205	
3,000.00	1.38	14.93	2,999.91	7.71	2.06	450,693.07	656,703.56	32.238480	-103.960203	
3,100.00	1.38	14.93	3,099.88	10.05	2.68	450,695.41	656,704.18	32.238487	-103.960201	
3,200.00	1.38	14.93	3,199.85	12.38	3.30	450,697.74	656,704.81	32.238493	-103.960199	
3,300.00	1.38	14.93	3,299.82	14.71	3.92	450,700.07	656,705.43	32.238500	-103.960197	
3,400.00	1.38	14.93	3,399.79	17.04	4.54	450,702.40	656,706.05	32.238506	-103.960195	
3,500.00	1.38	14.93	3,499.76	19.37	5.17	450,704.73	656,706.67	32.238512	-103.960193	
3,600.00	1.38	14.93	3,599.74	21.70	5.79	450,707.06	656,707.29	32.238519	-103.960191	
3,700.00	1.38	14.93	3,699.71	24.03	6.41	450,709.39	656,707.91	32.238525	-103.960189	
3,800.00	1.38	14.93	3,799.68	26.37	7.03	450,711.73	656,708.54	32.238532	-103.960187	
3,900.00	1.38	14.93	3,899.65	28.70	7.65	450,714.06	656,709.16	32.238538	-103.960184	
4,000.00	1.38	14.93	3,999.62	31.03	8.27	450,716.39	656,709.78	32.238544	-103.960182	
4,100.00	1.38	14.93	4,099.59	33.36	8.90	450,718.72	656,710.40	32.238551	-103.960180	
4,200.00	1.38	14.93	4,199.56	35.69	9.52	450,721.05	656,711.02	32.238557	-103.960178	
4,300.00	1.38	14.93	4,299.53	38.02	10.14	450,723.38	656,711.64	32.238564	-103.960176	
4,400.00	1.38	14.93	4,399.50	40.36	10.76	450,725.72	656,712.27	32.238570	-103.960174	
4,500.00	1.38	14.93	4,499.47	42.69	11.38	450,728.05	656,712.89	32.238576	-103.960172	
4,600.00	1.38	14.93	4,599.44	45.02	12.00	450,730.38	656,713.51	32.238583	-103.960170	
4,700.00	1.38	14.93	4,699.42	47.35	12.63	450,732.71	656,714.13	32.238589	-103.960168	
4,800.00	1.38	14.93	4,799.39	49.68	13.25	450,735.04	656,714.75	32.238596	-103.960166	
4,900.00	1.38	14.93	4,899.36	52.01	13.87	450,737.37	656,715.37	32.238602	-103.960164	
5,000.00	1.38	14.93	4,999.33	54.34	14.49	450,739.70	656,716.00	32.238608	-103.960162	
5,100.00	1.38	14.93	5,099.30	56.68	15.11	450,742.04	656,716.62	32.238615	-103.960160	
5,200.00	1.38	14.93	5,199.27	59.01	15.74	450,744.37	656,717.24	32.238621	-103.960158	
5,300.00	1.38	14.93	5,299.24	61.34	16.36	450,746.70	656,717.86	32.238628	-103.960156	

Planning Report - Geographic

Database:	EDM r5000.141_Prod US	Local Co-ordinate Reference:	Well Mr. Potato Head 11-14 Fed Com 331H
Company:	WCDSC Permian NM	TVD Reference:	RKB @ 3077.30ft
Project:	Eddy County (NAD 83 NM Eastern)	MD Reference:	RKB @ 3077.30ft
Site:	Sec 11-T24S-R29E	North Reference:	Grid
Well:	Mr. Potato Head 11-14 Fed Com 331H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Permit Plan 2		

Planned Survey									
Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Map Northing (usft)	Map Easting (usft)	Latitude	Longitude
5,400.00	1.38	14.93	5,399.21	63.67	16.98	450,749.03	656,718.48	32.238634	-103.960154
5,500.00	1.38	14.93	5,499.18	66.00	17.60	450,751.36	656,719.11	32.238640	-103.960152
5,600.00	1.38	14.93	5,599.15	68.33	18.22	450,753.69	656,719.73	32.238647	-103.960150
5,700.00	1.38	14.93	5,699.12	70.66	18.84	450,756.02	656,720.35	32.238653	-103.960148
5,800.00	1.38	14.93	5,799.10	73.00	19.47	450,758.36	656,720.97	32.238660	-103.960146
5,900.00	1.38	14.93	5,899.07	75.33	20.09	450,760.69	656,721.59	32.238666	-103.960144
6,000.00	1.38	14.93	5,999.04	77.66	20.71	450,763.02	656,722.21	32.238672	-103.960142
6,100.00	1.38	14.93	6,099.01	79.99	21.33	450,765.35	656,722.84	32.238679	-103.960140
6,200.00	1.38	14.93	6,198.98	82.32	21.95	450,767.68	656,723.46	32.238685	-103.960138
6,300.00	1.38	14.93	6,298.95	84.65	22.57	450,770.01	656,724.08	32.238692	-103.960136
6,400.00	1.38	14.93	6,398.92	86.98	23.20	450,772.34	656,724.70	32.238698	-103.960134
6,500.00	1.38	14.93	6,498.89	89.32	23.82	450,774.68	656,725.32	32.238704	-103.960132
6,600.00	1.38	14.93	6,598.86	91.65	24.44	450,777.01	656,725.94	32.238711	-103.960129
6,700.00	1.38	14.93	6,698.83	93.98	25.06	450,779.34	656,726.57	32.238717	-103.960127
6,800.00	1.38	14.93	6,798.80	96.31	25.68	450,781.67	656,727.19	32.238724	-103.960125
6,900.00	1.38	14.93	6,898.77	98.64	26.30	450,784.00	656,727.81	32.238730	-103.960123
7,000.00	1.38	14.93	6,998.75	100.97	26.93	450,786.33	656,728.43	32.238736	-103.960121
7,100.00	1.38	14.93	7,098.72	103.31	27.55	450,788.67	656,729.05	32.238743	-103.960119
7,200.00	1.38	14.93	7,198.69	105.64	28.17	450,791.00	656,729.67	32.238749	-103.960117
7,300.00	1.38	14.93	7,298.66	107.97	28.79	450,793.33	656,730.30	32.238756	-103.960115
7,400.00	1.38	14.93	7,398.63	110.30	29.41	450,795.66	656,730.92	32.238762	-103.960113
7,500.00	1.38	14.93	7,498.60	112.63	30.04	450,797.99	656,731.54	32.238769	-103.960111
7,600.00	1.38	14.93	7,598.57	114.96	30.66	450,800.32	656,732.16	32.238775	-103.960109
7,700.00	1.38	14.93	7,698.54	117.29	31.28	450,802.65	656,732.78	32.238781	-103.960107
7,800.00	1.38	14.93	7,798.51	119.63	31.90	450,804.99	656,733.40	32.238788	-103.960105
7,900.00	1.38	14.93	7,898.48	121.96	32.52	450,807.32	656,734.03	32.238794	-103.960103
8,000.00	1.38	14.93	7,998.45	124.29	33.14	450,809.65	656,734.65	32.238801	-103.960101
8,100.00	1.38	14.93	8,098.43	126.62	33.77	450,811.98	656,735.27	32.238807	-103.960099
8,200.00	1.38	14.93	8,198.40	128.95	34.39	450,814.31	656,735.89	32.238813	-103.960097
8,300.00	1.38	14.93	8,298.37	131.28	35.01	450,816.64	656,736.51	32.238820	-103.960095
8,400.00	1.38	14.93	8,398.34	133.61	35.63	450,818.97	656,737.14	32.238826	-103.960093
8,500.00	1.38	14.93	8,498.31	135.95	36.25	450,821.31	656,737.76	32.238833	-103.960091
8,600.00	1.38	14.93	8,598.28	138.28	36.87	450,823.64	656,738.38	32.238839	-103.960089
8,700.00	1.38	14.93	8,698.25	140.61	37.50	450,825.97	656,739.00	32.238845	-103.960087
8,800.00	1.38	14.93	8,798.22	142.94	38.12	450,828.30	656,739.62	32.238852	-103.960085
8,900.00	1.38	14.93	8,898.19	145.27	38.74	450,830.63	656,740.24	32.238858	-103.960083
9,000.00	1.38	14.93	8,998.16	147.60	39.36	450,832.96	656,740.87	32.238865	-103.960081
9,056.68	1.38	14.93	9,054.83	148.93	39.71	450,834.29	656,741.22	32.238868	-103.960079
9,100.00	0.73	14.93	9,098.14	149.70	39.92	450,835.06	656,741.42	32.238870	-103.960079
9,148.86	0.00	0.00	9,147.00	150.00	40.00	450,835.36	656,741.50	32.238871	-103.960079
9,200.00	0.00	0.00	9,198.14	150.00	40.00	450,835.36	656,741.50	32.238871	-103.960079
9,300.00	0.00	0.00	9,298.14	150.00	40.00	450,835.36	656,741.50	32.238871	-103.960079
9,400.00	0.00	0.00	9,398.14	150.00	40.00	450,835.36	656,741.50	32.238871	-103.960079
9,498.90	0.00	0.00	9,497.04	150.00	40.00	450,835.36	656,741.50	32.238871	-103.960079
KOP & FTP @ 9499' MD, 200' FNL, 1100' FWL									
9,500.00	0.11	180.00	9,498.14	150.00	40.00	450,835.36	656,741.50	32.238871	-103.960079
9,600.00	10.11	180.00	9,597.61	141.10	40.00	450,826.46	656,741.51	32.238847	-103.960079
9,700.00	20.11	180.00	9,694.03	115.07	40.00	450,800.43	656,741.51	32.238775	-103.960079
9,800.00	30.11	180.00	9,784.47	72.69	40.00	450,758.05	656,741.51	32.238659	-103.960079
9,900.00	40.11	180.00	9,866.17	15.25	40.01	450,700.61	656,741.51	32.238501	-103.960080
10,000.00	50.11	180.00	9,936.66	-55.51	40.01	450,629.85	656,741.52	32.238306	-103.960081
10,100.00	60.11	180.00	9,993.78	-137.43	40.02	450,547.93	656,741.52	32.238081	-103.960082
10,200.00	70.11	180.00	10,035.82	-228.03	40.02	450,457.33	656,741.53	32.237832	-103.960083
10,300.00	80.11	180.00	10,061.48	-324.55	40.03	450,360.82	656,741.53	32.237567	-103.960084

Planning Report - Geographic

Database:	EDM r5000.141_Prod US	Local Co-ordinate Reference:	Well Mr. Potato Head 11-14 Fed Com 331H
Company:	WCDSC Permian NM	TVD Reference:	RKB @ 3077.30ft
Project:	Eddy County (NAD 83 NM Eastern)	MD Reference:	RKB @ 3077.30ft
Site:	Sec 11-T24S-R29E	North Reference:	Grid
Well:	Mr. Potato Head 11-14 Fed Com 331H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Permit Plan 2		

Planned Survey										
Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N-S (ft)	+E-W (ft)	Map Northing (usft)	Map Easting (usft)	Latitude	Longitude	
10,398.90	90.00	180.00	10,070.00	-422.96	40.04	450,262.40	656,741.54	32.237296	-103.960085	
10,400.00	90.00	180.00	10,070.00	-424.06	40.04	450,261.31	656,741.54	32.237293	-103.960085	
10,500.00	90.00	180.00	10,070.00	-524.06	40.04	450,161.31	656,741.55	32.237018	-103.960086	
10,600.00	90.00	180.00	10,070.00	-624.06	40.05	450,061.31	656,741.55	32.236743	-103.960087	
10,700.00	90.00	180.00	10,070.00	-724.06	40.05	449,961.31	656,741.56	32.236468	-103.960088	
10,800.00	90.00	180.00	10,070.00	-824.06	40.06	449,861.31	656,741.57	32.236194	-103.960089	
10,900.00	90.00	180.00	10,070.00	-924.06	40.07	449,761.31	656,741.57	32.235919	-103.960090	
11,000.00	90.00	180.00	10,070.00	-1,024.06	40.07	449,661.31	656,741.58	32.235644	-103.960091	
11,100.00	90.00	180.00	10,070.00	-1,124.06	40.08	449,561.31	656,741.58	32.235369	-103.960093	
11,200.00	90.00	180.00	10,070.00	-1,224.06	40.09	449,461.31	656,741.59	32.235094	-103.960094	
11,300.00	90.00	180.00	10,070.00	-1,324.06	40.09	449,361.31	656,741.60	32.234819	-103.960095	
11,400.00	90.00	180.00	10,070.00	-1,424.06	40.10	449,261.31	656,741.60	32.234544	-103.960096	
11,500.00	90.00	180.00	10,070.00	-1,524.06	40.10	449,161.31	656,741.61	32.234269	-103.960097	
11,600.00	90.00	180.00	10,070.00	-1,624.06	40.11	449,061.31	656,741.62	32.233995	-103.960098	
11,700.00	90.00	180.00	10,070.00	-1,724.06	40.12	448,961.31	656,741.62	32.233720	-103.960099	
11,800.00	90.00	180.00	10,070.00	-1,824.06	40.12	448,861.31	656,741.63	32.233445	-103.960100	
11,900.00	90.00	180.00	10,070.00	-1,924.06	40.13	448,761.31	656,741.63	32.233170	-103.960101	
12,000.00	90.00	180.00	10,070.00	-2,024.06	40.14	448,661.31	656,741.64	32.232895	-103.960103	
12,100.00	90.00	180.00	10,070.00	-2,124.06	40.14	448,561.31	656,741.65	32.232620	-103.960104	
12,200.00	90.00	180.00	10,070.00	-2,224.06	40.15	448,461.31	656,741.65	32.232345	-103.960105	
12,300.00	90.00	180.00	10,070.00	-2,324.06	40.15	448,361.31	656,741.66	32.232070	-103.960106	
12,400.00	90.00	180.00	10,070.00	-2,424.06	40.16	448,261.31	656,741.67	32.231795	-103.960107	
12,500.00	90.00	180.00	10,070.00	-2,524.06	40.17	448,161.31	656,741.67	32.231521	-103.960108	
12,600.00	90.00	180.00	10,070.00	-2,624.06	40.17	448,061.31	656,741.68	32.231246	-103.960109	
12,700.00	90.00	180.00	10,070.00	-2,724.06	40.18	447,961.31	656,741.68	32.230971	-103.960110	
12,800.00	90.00	180.00	10,070.00	-2,824.06	40.19	447,861.31	656,741.69	32.230696	-103.960111	
12,900.00	90.00	180.00	10,070.00	-2,924.06	40.19	447,761.31	656,741.70	32.230421	-103.960112	
13,000.00	90.00	180.00	10,070.00	-3,024.06	40.20	447,661.31	656,741.70	32.230146	-103.960114	
13,100.00	90.00	180.00	10,070.00	-3,124.06	40.20	447,561.31	656,741.71	32.229871	-103.960115	
13,200.00	90.00	180.00	10,070.00	-3,224.06	40.21	447,461.31	656,741.72	32.229596	-103.960116	
13,300.00	90.00	180.00	10,070.00	-3,324.06	40.22	447,361.31	656,741.72	32.229322	-103.960117	
13,400.00	90.00	180.00	10,070.00	-3,424.06	40.22	447,261.31	656,741.73	32.229047	-103.960118	
13,500.00	90.00	180.00	10,070.00	-3,524.06	40.23	447,161.31	656,741.73	32.228772	-103.960119	
13,600.00	90.00	180.00	10,070.00	-3,624.06	40.24	447,061.31	656,741.74	32.228497	-103.960120	
13,700.00	90.00	180.00	10,070.00	-3,724.06	40.24	446,961.31	656,741.75	32.228222	-103.960121	
13,800.00	90.00	180.00	10,070.00	-3,824.06	40.25	446,861.31	656,741.75	32.227947	-103.960122	
13,900.00	90.00	180.00	10,070.00	-3,924.06	40.25	446,761.31	656,741.76	32.227672	-103.960123	
14,000.00	90.00	180.00	10,070.00	-4,024.06	40.26	446,661.31	656,741.77	32.227397	-103.960125	
14,100.00	90.00	180.00	10,070.00	-4,124.06	40.27	446,561.31	656,741.77	32.227122	-103.960126	
14,200.00	90.00	180.00	10,070.00	-4,224.06	40.27	446,461.31	656,741.78	32.226848	-103.960127	
14,300.00	90.00	180.00	10,070.00	-4,324.06	40.28	446,361.31	656,741.78	32.226573	-103.960128	
14,400.00	90.00	180.00	10,070.00	-4,424.06	40.29	446,261.31	656,741.79	32.226298	-103.960129	
14,500.00	90.00	180.00	10,070.00	-4,524.06	40.29	446,161.31	656,741.80	32.226023	-103.960130	
14,600.00	90.00	180.00	10,070.00	-4,624.06	40.30	446,061.31	656,741.80	32.225748	-103.960131	
14,700.00	90.00	180.00	10,070.00	-4,724.06	40.30	445,961.31	656,741.81	32.225473	-103.960132	
14,800.00	90.00	180.00	10,070.00	-4,824.06	40.31	445,861.31	656,741.82	32.225198	-103.960133	
14,900.00	90.00	180.00	10,070.00	-4,924.06	40.32	445,761.31	656,741.82	32.224923	-103.960134	
14,905.00	90.00	180.00	10,070.00	-4,929.06	40.32	445,756.31	656,741.82	32.224910	-103.960135	
Cross Section @ 14905' MD, 0' FNL, 1100' FWL										
15,000.00	90.00	180.00	10,070.00	-5,024.06	40.32	445,661.31	656,741.83	32.224648	-103.960136	
15,100.00	90.00	180.00	10,070.00	-5,124.06	40.33	445,561.32	656,741.83	32.224374	-103.960137	
15,200.00	90.00	180.00	10,070.00	-5,224.06	40.34	445,461.32	656,741.84	32.224099	-103.960138	
15,300.00	90.00	180.00	10,070.00	-5,324.06	40.34	445,361.32	656,741.85	32.223824	-103.960139	
15,400.00	90.00	180.00	10,070.00	-5,424.06	40.35	445,261.32	656,741.85	32.223549	-103.960140	

Planning Report - Geographic

Database:	EDM r5000.141_Prod US	Local Co-ordinate Reference:	Well Mr. Potato Head 11-14 Fed Com 331H
Company:	WCDSC Permian NM	TVD Reference:	RKB @ 3077.30ft
Project:	Eddy County (NAD 83 NM Eastern)	MD Reference:	RKB @ 3077.30ft
Site:	Sec 11-T24S-R29E	North Reference:	Grid
Well:	Mr. Potato Head 11-14 Fed Com 331H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Permit Plan 2		

Planned Survey										
Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Map Northing (usft)	Map Easting (usft)	Latitude	Longitude	
15,500.00	90.00	180.00	10,070.00	-5,524.06	40.35	445,161.32	656,741.86	32.223274	-103.960141	
15,600.00	90.00	180.00	10,070.00	-5,624.06	40.36	445,061.32	656,741.87	32.222999	-103.960142	
15,700.00	90.00	180.00	10,070.00	-5,724.06	40.37	444,961.32	656,741.87	32.222724	-103.960143	
15,800.00	90.00	180.00	10,070.00	-5,824.06	40.37	444,861.32	656,741.88	32.222449	-103.960144	
15,900.00	90.00	180.00	10,070.00	-5,924.06	40.38	444,761.32	656,741.88	32.222175	-103.960146	
16,000.00	90.00	180.00	10,070.00	-6,024.06	40.39	444,661.32	656,741.89	32.221900	-103.960147	
16,100.00	90.00	180.00	10,070.00	-6,124.06	40.39	444,561.32	656,741.90	32.221625	-103.960148	
16,200.00	90.00	180.00	10,070.00	-6,224.06	40.40	444,461.32	656,741.90	32.221350	-103.960149	
16,300.00	90.00	180.00	10,070.00	-6,324.06	40.40	444,361.32	656,741.91	32.221075	-103.960150	
16,400.00	90.00	180.00	10,070.00	-6,424.06	40.41	444,261.32	656,741.92	32.220800	-103.960151	
16,500.00	90.00	180.00	10,070.00	-6,524.06	40.42	444,161.32	656,741.92	32.220525	-103.960152	
16,600.00	90.00	180.00	10,070.00	-6,624.06	40.42	444,061.32	656,741.93	32.220250	-103.960153	
16,700.00	90.00	180.00	10,070.00	-6,724.06	40.43	443,961.32	656,741.93	32.219975	-103.960154	
16,800.00	90.00	180.00	10,070.00	-6,824.06	40.44	443,861.32	656,741.94	32.219701	-103.960155	
16,900.00	90.00	180.00	10,070.00	-6,924.06	40.44	443,761.32	656,741.95	32.219426	-103.960157	
17,000.00	90.00	180.00	10,070.00	-7,024.06	40.45	443,661.32	656,741.95	32.219151	-103.960158	
17,100.00	90.00	180.00	10,070.00	-7,124.06	40.45	443,561.32	656,741.96	32.218876	-103.960159	
17,200.00	90.00	180.00	10,070.00	-7,224.06	40.46	443,461.32	656,741.97	32.218601	-103.960160	
17,300.00	90.00	180.00	10,070.00	-7,324.06	40.47	443,361.32	656,741.97	32.218326	-103.960161	
17,400.00	90.00	180.00	10,070.00	-7,424.06	40.47	443,261.32	656,741.98	32.218051	-103.960162	
17,500.00	90.00	180.00	10,070.00	-7,524.06	40.48	443,161.32	656,741.98	32.217776	-103.960163	
17,600.00	90.00	180.00	10,070.00	-7,624.06	40.49	443,061.32	656,741.99	32.217501	-103.960164	
17,700.00	90.00	180.00	10,070.00	-7,724.06	40.49	442,961.32	656,742.00	32.217227	-103.960165	
17,800.00	90.00	180.00	10,070.00	-7,824.06	40.50	442,861.32	656,742.00	32.216952	-103.960166	
17,900.00	90.00	180.00	10,070.00	-7,924.06	40.50	442,761.32	656,742.01	32.216677	-103.960168	
18,000.00	90.00	180.00	10,070.00	-8,024.06	40.51	442,661.32	656,742.02	32.216402	-103.960169	
18,100.00	90.00	180.00	10,070.00	-8,124.06	40.52	442,561.32	656,742.02	32.216127	-103.960170	
18,200.00	90.00	180.00	10,070.00	-8,224.06	40.52	442,461.32	656,742.03	32.215852	-103.960171	
18,300.00	90.00	180.00	10,070.00	-8,324.06	40.53	442,361.32	656,742.03	32.215577	-103.960172	
18,400.00	90.00	180.00	10,070.00	-8,424.06	40.54	442,261.32	656,742.04	32.215302	-103.960173	
18,500.00	90.00	180.00	10,070.00	-8,524.06	40.54	442,161.32	656,742.05	32.215028	-103.960174	
18,600.00	90.00	180.00	10,070.00	-8,624.06	40.55	442,061.32	656,742.05	32.214753	-103.960175	
18,700.00	90.00	180.00	10,070.00	-8,724.06	40.55	441,961.32	656,742.06	32.214478	-103.960176	
18,800.00	90.00	180.00	10,070.00	-8,824.06	40.56	441,861.32	656,742.07	32.214203	-103.960177	
18,900.00	90.00	180.00	10,070.00	-8,924.06	40.57	441,761.32	656,742.07	32.213928	-103.960179	
19,000.00	90.00	180.00	10,070.00	-9,024.06	40.57	441,661.32	656,742.08	32.213653	-103.960180	
19,100.00	90.00	180.00	10,070.00	-9,124.06	40.58	441,561.32	656,742.08	32.213378	-103.960181	
19,200.00	90.00	180.00	10,070.00	-9,224.06	40.59	441,461.32	656,742.09	32.213103	-103.960182	
19,300.00	90.00	180.00	10,070.00	-9,324.06	40.59	441,361.32	656,742.10	32.212828	-103.960183	
19,400.00	90.00	180.00	10,070.00	-9,424.06	40.60	441,261.32	656,742.10	32.212554	-103.960184	
19,500.00	90.00	180.00	10,070.00	-9,524.06	40.60	441,161.32	656,742.11	32.212279	-103.960185	
19,600.00	90.00	180.00	10,070.00	-9,624.06	40.61	441,061.32	656,742.12	32.212004	-103.960186	
19,700.00	90.00	180.00	10,070.00	-9,724.06	40.62	440,961.32	656,742.12	32.211729	-103.960187	
19,800.00	90.00	180.00	10,070.00	-9,824.06	40.62	440,861.32	656,742.13	32.211454	-103.960189	
19,900.00	90.00	180.00	10,070.00	-9,924.06	40.63	440,761.32	656,742.13	32.211179	-103.960190	
20,000.00	90.00	180.00	10,070.00	-10,024.06	40.64	440,661.32	656,742.14	32.210904	-103.960191	
20,100.00	90.00	180.00	10,070.00	-10,124.06	40.64	440,561.33	656,742.15	32.210629	-103.960192	
20,121.24	90.00	180.00	10,070.00	-10,145.30	40.64	440,540.09	656,742.15	32.210571	-103.960192	
LTP @ 20121' MD, 120' FSL, 1100' FWL										
20,200.00	90.00	180.00	10,070.00	-10,224.06	40.65	440,461.33	656,742.15	32.210354	-103.960193	
20,221.23	90.00	180.00	10,070.00	-10,245.29	40.65	440,440.10	656,742.15	32.210296	-103.960193	
PBHL; 20' FSL, 1100' FWL										
20,221.24	90.00	180.00	10,070.00	-10,245.29	40.65	440,440.09	656,742.15	32.210296	-103.960193	

Planning Report - Geographic

Database:	EDM r5000.141_Prod US	Local Co-ordinate Reference:	Well Mr. Potato Head 11-14 Fed Com 331H
Company:	WCDCS Permian NM	TVD Reference:	RKB @ 3077.30ft
Project:	Eddy County (NAD 83 NM Eastern)	MD Reference:	RKB @ 3077.30ft
Site:	Sec 11-T24S-R29E	North Reference:	Grid
Well:	Mr. Potato Head 11-14 Fed Com 331H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Permit Plan 2		

Design Targets									
Target Name	Dip Angle	Dip Dir.	TVD	+N/-S	+E/-W	Northing	Easting	Latitude	Longitude
- hit/miss target	(°)	(°)	(ft)	(ft)	(ft)	(usft)	(usft)		
- Shape									
PBHL - Mr. Potatohead	0.00	0.00	0.00	-10,245.29	40.65	440,440.09	656,742.15	32.210296	-103.960193
- plan misses target center by 10070.00ft at 20221.24ft MD (10070.00 TVD, -10245.29 N, 40.65 E)									
- Point									

Plan Annotations				
Measured Depth	Vertical Depth	Local Coordinates		Comment
(ft)	(ft)	+N/-S (ft)	+E/-W (ft)	
9,498.90	9,497.04	150.00	40.00	KOP & FTP @ 9499' MD, 200' FNL, 1100' FWL
14,905.00	10,070.00	-4,929.06	40.32	Cross Section @ 14905' MD, 0' FNL, 1100' FWL
20,121.24	10,070.00	-10,145.30	40.64	LTP @ 20121' MD, 120' FSL, 1100' FWL
20,221.23	10,070.00	-10,245.29	40.65	PBHL; 20' FSL, 1100' FWL

2. Casing Program (Primary Design)

Hole Size	Casing Interval		Csg. Size	Wt (PPF)	Grade	Conn	Min SF Collapse	Min SF Burst	Min SF Tension
	From	To							
17 1/2	0	400 TVD	13 3/8	48.0	H40	STC	1.125	1.25	1.6
9 7/8	0	8741 TVD	7 5/8	29.7	P110	Flushmax III	1.125	1.25	1.6
6 3/4	0	TD	5 1/2	20.0	P110	Vam SG	1.125	1.25	1.6
BLM Minimum Safety Factor							1.125	1	1.6 Dry 1.8 Wet

- All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 IILB.1.h Must have table for contingency casing.
- Rustler top will be validated via drilling parameters (i.e. reduction in ROP) and surface casing setting depth revised accordingly if needed.
- A variance is requested for collapse rating on intermediate casing. Operator will keep pipe full while running casing.
- Int casing shoe will be selected based on drilling data/gamma, setting depth with be revised accordingly if needed.
- A variance is requested to wave the centralizer requirement for the Intermediate casing and production casing.
- A variance is requested to set intermediate casing in the curve if hole conditions dictate that a higher shoe strength is required.

Casing Program (Alternative Design)

Hole Size	Casing Interval		Csg. Size	Wt (PPF)	Grade	Conn	Min SF Collapse	Min SF Burst	Min SF Tension
	From	To							
17 1/2	0	400 TVD	13 3/8	48.0	H40	STC	1.125	1.25	1.6
9 7/8	0	8741 TVD	8 5/8	32.0	P110	TLW	1.125	1.25	1.6
7 7/8	0	TD	5 1/2	17.0	P110	BTC	1.125	1.25	1.6
BLM Minimum Safety Factor							1.125	1	1.6 Dry 1.8 Wet

- All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 IILB.1.h Must have table for contingency casing.
- Rustler top will be validated via drilling parameters (i.e. reduction in ROP) and surface casing setting depth revised accordingly if needed.
- A variance is requested for collapse rating on intermediate casing. Operator will keep pipe full while running casing.
- Int casing shoe will be selected based on drilling data/gamma, setting depth with be revised accordingly if needed.
- A variance is requested to wave the centralizer requirement for the Intermediate casing and production casing.
- Variance requested to drill 10.625" hole instead of 9.875" for intermediate 1, the 8.625" connection will change from TLW to BTC.
- A variance is requested to set intermediate casing in the curve if hole conditions dictate that a higher shoe strength is required.

Mr. Potato Head 11-14 Fed Com 331H

	Y or N
Is casing new? If used, attach certification as required in Onshore Order #1	Y
Does casing meet API specifications? If no, attach casing specification sheet.	Y
Is premium or uncommon casing planned? If yes attach casing specification sheet.	N
Does the above casing design meet or exceed BLM's minimum standards? If not provide justification (loading assumptions, casing design criteria).	Y
Will the intermediate pipe be kept at a minimum 1/3 fluid filled to avoid approaching the collapse pressure rating of the casing?	Y
Capitan Reef	
Is well located within Capitan Reef?	N
If yes, does production casing cement tie back a minimum of 50' above the Reef?	
Is well within the designated 4 string boundary.	
SOPA	
Is well located in SOPA but not in R-111-P?	N
If yes, are the first 2 strings cemented to surface and 3 rd string cement tied back 500' into previous casing?	
R-111-P and SOPA	
Is well located in R-111-P and SOPA?	N
If yes, are the first three strings cemented to surface?	
Is 2 nd string set 100' to 600' below the base of salt?	
High Cave/Karst	
Is well located in high Cave/Karst?	N
If yes, are there two strings cemented to surface?	
(For 2 string wells) If yes, is there a contingency casing if lost circulation occurs?	
Critical Cave/Karst	
Is well located in critical Cave/Karst?	N
If yes, are there three strings cemented to surface?	

3. Cementing Program (Primary Design)

Casing	# Sk	TOC	Wt (lb/gal)	Yld (ft ³ /sack)	Slurry Description
Surface	328	Surf	13.2	1.44	Lead: Class C Cement + additives
Int 1	739	Surf	9	3.27	Lead: Class C Cement + additives
	104	4000' above shoe	13.2	1.44	Tail: Class H / C + additives
Int 1 Two Stage w/ DV @ TVD of Delaware	677	Surf	9	3.27	1st stage Lead: Class C Cement + additives
	93	500' above shoe	13.2	1.44	1st stage Tail: Class H / C + additives
	209	Surf	9	3.27	2nd stage Lead: Class C Cement + additives
	93	500' above DV	13.2	1.44	2nd stage Tail: Class H / C + additives
Int 1 Intermediate Squeeze	As Needed	Surf	9	1.44	Squeeze Lead: Class C Cement + additives
	739	Surf	9	3.27	Lead: Class C Cement + additives
	104	4000' above shoe	13.2	1.44	Tail: Class H / C + additives
Production	37	8241	9.0	3.3	Lead: Class H / C + additives
	684	9499	13.2	1.4	Tail: Class H / C + additives

If a DV tool is ran the depth(s) will be adjusted based on hole conditions and cement volumes will be adjusted proportionally. Slurry weights will be adjusted based on estimated fracture gradient of the formation. DV tool will be set a minimum of 50 feet below previous casing and a minimum of 200 feet above current shoe. If cement is not returned to surface during the primary cement job on the surface casing string, a planned top job will be conducted immediately after completion of the primary job.

Casing String	% Excess
Surface	50%
Intermediate 1	30%
Intermediate 1 (Two Stage)	25%
Prod	10%

3. Cementing Program (Alternative Design)

Casing	# Sk	TOC	Wt ppg	Yld (ft ³ /sack)	Slurry Description
Surface	328	Surf	13.2	1.44	Lead: Class C Cement + additives
Int 1	451	Surf	9	3.27	Lead: Class C Cement + additives
	67	4000' above shoe	13.2	1.44	Tail: Class H / C + additives
Int 1 Two Stage w DV @ ~4500	397	Surf	9	3.27	1st stage Lead: Class C Cement + additives
	55	500' above shoe	13.2	1.44	1st stage Tail: Class H / C + additives
	140	Surf	9	3.27	2nd stage Lead: Class C Cement + additives
	55	500' above DV	13.2	1.44	2nd stage Tail: Class H / C + additives
Int 1 Intermediate Squeeze	As Needed	Surf	13.2	1.44	Squeeze Lead: Class C Cement + additives
	451	Surf	9	3.27	Lead: Class C Cement + additives
	67	4000' above shoe	13.2	1.44	Tail: Class H / C + additives
Int 1 (10.625" Hole Size)	713	Surf	9	3.27	Lead: Class C Cement + additives
	105	4000' above shoe	13.2	1.44	Tail: Class H / C + additives
Production	73	8241	9.0	3.3	Lead: Class H / C + additives
	1419	9499	13.2	1.4	Tail: Class H / C + additives

If a DV tool is ran the depth(s) will be adjusted based on hole conditions and cement volumes will be adjusted proportionally. Slurry weights will be adjusted based on estimated fracture gradient of the formation. DV tool will be set a minimum of 50 feet below previous casing and a minimum of 200 feet above current shoe. If cement is not returned to surface during the primary cement job on the surface casing string, a planned top job will be conducted immediately after completion of the primary job.

Casing String	% Excess
Surface	50%
Intermediate 1	30%
Intermediate 1 (Two Stage)	25%
Prod	10%

4. Pressure Control Equipment (Three String Design)

BOP installed and tested before drilling which hole?	Size?	Min. Required WP	Type	✓	Tested to:
Int 1	13-58"	5M	Annular	X	50% of rated working pressure
			Blind Ram	X	5M
			Pipe Ram		
			Double Ram	X	
			Other*		
Production	13-5/8"	5M	Annular (5M)	X	50% of rated working pressure
			Blind Ram	X	5M
			Pipe Ram		
			Double Ram	X	
			Other*		
			Annular (5M)		
			Blind Ram		
			Pipe Ram		
			Double Ram		
			Other*		
N	A variance is requested for the use of a diverter on the surface casing. See attached for schematic.				
Y	A variance is requested to run a 5 M annular on a 10M system				

5. Mud Program (Three String Design)

Section	Type	Weight (ppg)
Surface	FW Gel	8.5-9
Intermediate	DBE / Cut Brine	10-10.5
Production	OBM	8.5-9

Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept on location at all times.

What will be used to monitor the loss or gain of fluid?	PVT/Pason/Visual Monitoring
---	-----------------------------

6. Logging and Testing Procedures

Logging, Coring and Testing	
X	Will run GR/CNL from TD to surface (horizontal well - vertical portion of hole). Stated logs run will be in the Completion Report and submitted to the BLM.
	No logs are planned based on well control or offset log information.
	Drill stem test? If yes, explain.
	Coring? If yes, explain.

Additional logs planned	Interval
Resistivity	Int. shoe to KOP
Density	Int. shoe to KOP
X CBL	Production casing
X Mud log	Intermediate shoe to TD
PEX	

7. Drilling Conditions

Condition	Specify what type and where?
BH pressure at deepest TVD	4713
Abnormal temperature	No

Mitigation measure for abnormal conditions. Describe. Lost circulation material/sweeps/mud-scavengers.

Hydrogen Sulfide (H2S) monitors will be installed prior to drilling out the surface shoe. If H2S is detected in concentrations greater than 100 ppm, the operator will comply with the provisions of Onshore Oil and Gas Order #6. If Hydrogen Sulfide is encountered measured values and formations will be provided to the BLM.

N	H2S is present
Y	H2S plan attached.