Form 3160-5 (April2004)

UNITEDSTATES

OCD-ARTES

FORMAPPROVED

OM B No	o. 1004-0	0137
Expires:	March	31, 200

ıd/or No					
Poker Lake Unit #235					
9. API Well No.					
30-015-34309					
10. Field and Pool, or Exploratory Area Nash Draw (Delaware.BS,Avalon) 11. County or Parish, State					
			Eddy New Mexico		

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

Spudded well at 9:30 am CST on 4/20/06. Drilled 12-1/4" hole to 635'. Ran 15 jts 8-5/8", 32#, J-55, LTC casing set at 625'. Cemented with 200 sx 35:65 Poz Class C + 3% S1 + 6% D20 + 1/4 pps D130 lead (12.6 ppg, yld 1.99) and 225 sx Class C + 2% S1 tail (14.8 ppg, yld 1.32). Circ 300 sx to pit. WOC 25 hrs. Test casing to 1000 psi for 30 min. Drill 7-7/8" hole to 7500'. Ran 32 jts 5-1/2", 17# and 158 jts 15.50# J-55 LTC casing & set at 7500'. Cemented with 540 sx LiteCrete + 2 pps D153 + 2 pps D24 + 0.05 gps D604 + 0.03 gps M45 + 0.04 gps D801 lead (10.2 ppg, yld 2.4). 255 sx LiteCrete + 2 pps D153 + 2 pps D24 + 0.05 gps D604AM + 0.03 gps M45 + 0.04 gps D801 tail (10.5 ppg, yld 2.23). TOC by temperature survey 1780'. Released rig at 12:00 pm CST on 4/30/06. Prep for completion.

ACCEPTED FOR RECORD MAY 1 5 2006 ALEXIS C. SWOBODA PETROLEUM ENGINEER

le								
	Administrative Assistant	:						
ite	05/05/2006							
THIS SPACE FOR FEDERAL OR STATE OFFICE USE								
Т	Title	Date						
or C	Office							
	R S	R STATE OFFICE USE						

States any false, fictitious or fraudulent statements or représentations as to any matter within its jurisdiction.

PRECISION PRESSURE DATA, INC.

TEMPERATURE SURVEY REPORT

Company _	BASS ENTERPRIS	SESL	_ease	POKER LAKE UNIT	Well#	235	
Field		0	County	EDDY	State	NEW MEXICO	
Survey Date	4/30/2006		Time	16:39	Company Rep.	HECTOR	
		Top of Cemel	nt	1780			
		Total Depth		7408			
		Zero @		GL			
·		Plug Down @)	04/30/06 @ 05:30			
		Casing Size		5 1/2			
		Hole Size		7 7/8			
		Sacks of Cerr	nent	795			
		Ran By		C. HOMER			
		Calculated By		D WEST			

TEMPERATURE SURVEY REPORT

