

Submit 3 Copies To Appropriate District Office

District I

1625 N. French Dr., Hobbs, NM 88240

District II

1301 W. Grand Ave., Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

Form C-103

May 27, 2004

|   |
|---|
| WELL API NO.<br>30-005-63782  |
| 5. Indicate Type of Lease<br>STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/> |
| 6. State Oil & Gas Lease No.  |
| 7. Lease Name or Unit Agreement Name<br>Assault   |
| 8. Well Number No. 1  |
| 9. OGRID Number<br>230387   |
| 10. Pool name or Wildcat<br>Wildcat, Wolfcamp Gas, 97489  |

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other ☐

2. Name of Operator  
Parallel Petroleum Corporation

3. Address of Operator  
1004 N. Big Spring St., Suite 400, Midland, Texas 70701

4. Well Location BHL: UL M, 660' FSL, 760' FWL, Sec 27, T14S, R26E

SL: Unit Letter D : 400 feet from the North line and 760 feet from the West line  
Section 27 Township 14-S Range 26-E NMPM County Chaves

11. Elevation (Show whether DR, RKB, RT, GR, etc.)  
GR 3424'

Pit or Below-grade Tank Application or Closure

Pit type \_\_\_\_\_ Depth to Groundwater 65' Distance from nearest fresh water well 633' Distance from nearest surface water 3800'

Pit Liner Thickness: 12 mil Below-Grade Tank: Volume \_\_\_\_\_ bbls; Construction Material \_\_\_\_\_

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☒ MULTIPLE COMPL ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☐  
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Originally planned and permitted for 13-3/8" surface casing at 300' and 9-5/8" intermediate casing at 1300'.  
Change to one string of 9-5/8" surface casing set at 1300'+.

Drill 12-1/4" hole using FRESH WATER mud only and fresh gel sweeps to a depth of 1300-1400'. Set 9-5/8" 36# J55 LT&C casing. Cement with Lead: 125 sacks 50:50 Poz, Class C + 5% bwow Sodium Chloride + 10% bwoc Bentonite + 151.7% fresh water. Tail: 200 sacks Class C + 1% bwoc Calcium Chloride + 56.3% fresh water. Circulate cement to surface. Top out with 1" pipe in annulus if necessary.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines X, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE Deane Durham TITLE Engineer DATE 6 June 2006

Type or print name Deane Durham E-mail address: ddurham@plll.com Telephone No. (432) 684-3727

For State Use Only

APPROVED BY: FOR RECORDS ONLY TITLE \_\_\_\_\_ DATE JUN 09 2006

Conditions of Approval (if any):