

DISTRICT I

P.O. Box 1980, Hobbs NM 88240

DISTRICT II

P.O. Drawer DD, Artesia NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec NM 87410

State of New Mexico
Energy, Minerals and Natural Resources Department

OIL CONSERVATION DIVISION

P.O. Box 2088

Santa Fe, New Mexico 87504-2088

AUG 2003

RECEIVED

OCD-ARTESIA

WELL API NO.	30-005-61527
5. Indicate Type of Lease	State ☐ FEE ☒
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name	RIC
8. Well No	7
9. Pool Name or Wildcat	PECOS SLOPE ABO

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL ☐ GAS ☐
WELL ☐ WELL ☒ OTHER ☐

2. Name of Operator
Yates Petroleum Corporation

3. Address of Operator
105 South 4th., Artesia, NM 88210

4. Well Location
Unit Letter _____ : 660 Feet From The NORTH Line and 660 Feet From The EAST Line
Section 31 Township T6S Rang R25E NMPM CHAVES COUNTY

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. Notify NMOCD at least 24 hours before starting work. Call office for new directions if any abnormalities are noticed during plugging operations. MIRU WSU & all safety equipment. Load tubing & casing w/ 2% KCL: water; ND wellhead & NU BOP. POH w/ tubing.
2. RU wireline truck & RIH w/ 4-1/2" gauge ring to 3500' to make sure casing is clear, then RIH w/ 4-1/2" CIBP & set plug @ 3500'. RIH w/ tubing to top of CIBP & circ hole w/ 10.0 ppg mud w/ 25# gel in mud; spot 25 sx cement on top of CIBP - POH w/ tubing.
3. RU wireline & RIH w/ perforating gun & shoot 4 holes @ 1300'; RIH w/ packer on tubing to 925' & squeeze 100 sx cement behind casing to cover the Glorieta & the base of 8-5/8" casing. POH w/ tubing & packer. RIH w/ perforating gun & shoot 4 holes @ 100'; RIH w/ packer on tubing to 50' & squeeze 50 sx cement behind casing to surface - POH w/ tubing & packer. Spot 5 sx of cement to surface to fill up casing.
4. ND BOP & remove wellhead; install dry-hole marker & clean location.

See Attached

I hereby certify that the information above is a true and complete to the best of my knowledge and belief.

SIGNATURE

Donna Clack

TITLE

Regulatory Technician

DATE

8/12/03

TYPE OR PRINT NAME

DONNA CLACK

TELEPHONE NO.

505-748-1471

(This space for State Use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other ☐

2. Name of Operator

Yates Petroleum Corporation

3. Address of Operator

105 S. 4th Street Artesia, NM 88210

4. Well Location

Unit Letter A : 660 feet from the North line and 660 feet from the East line.

Section 31 Township 6S Range 25E NMPM Chaves County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

3838' GR


Ric

8. Well No.

7

9. Pool name or Wildcat

Pecos Slope Abo



11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☒	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	MULTIPLE COMPLETION ☐	CASING TEST AND CEMENT JOB ☐	
OTHER: ☐		OTHER: ☐	

Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Yate Petroleum Corporation proposes to plug and abandon this well as follows:

1. Notify the NMOCD at least 24 hrs before starting the work. Load the tubing and the casing with 2% KCL water.
2. Set a 4-1/2" gauge ring to 3500' to make sure the casing is clear then RIH with a 4-1/2" CIBP and set at 3500'. Circulate the hole with 10.0 ppg mud with 25#/bbl of gel in the mud and spot 25 sx cement on top of the CIBP.
3. Perforate with 4 holes at 1300' and squeeze with 100 sx cement behind the casing to cover the Glorieta and the base of the 8-5/8" casing. Perforate with 4 holes at 100' and squeeze with 50 sx cement behind the casing to the surface. Spot 5 sx cement at the surface to fill up the casing. - WOC 24/145-T25
4. ND the BOP and remove the wellhead and install a dry-hole marker and clean up the location.

- ① Place 100' of cnt inside: outside of csy.
- ② Perf csy @ 1000' - Place 100' of cnt inside: outside of csy. 900-1000' T25
- ③ Perf csy @ 306 - Place 100' of cnt inside: outside of csy. 306-306 - T25

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tina Huerta TITLE Regulatory Compliance Supervisor DATE June 5, 2003

Type or print name Tina Huerta

(This space for State use)

Telephone No. 505-748-1471

APPROVED BY [Signature] TITLE [Signature]

Conditions of approval, if any:

JUN 11 2003
DATE