Form 316045 (September 2001)

1. Type of Well

2. Name of Operator

Mewbourne Oil Company

14744

UNITED STATES DEPARTMENT OF THE INTERIOR

FORM APPROVED OMB No. 1004-0135

Golden Lane 4 Federal #1

9. API Well No.

Expires: January 31, 2004 BUREAU OF LAND MANAGEMENT 5. Lease Serial No. **SUNDRY NOTICES AND REPORTS ON WELLS** NM-029588 Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals 26272829 6. If Indian, Allottee or Tribe Name 7. If Unit or CA/Agreement, Name and/or No. SUBMIT IN TRIPLICATE - Other instructions on 2021 Oil Well Gas Well Other 8. Well Name and No.

3a. Address		3b. Phone No (include area code)		30-015-34692			
PO Box 5270 Hobbs, NM 88240		3b. Phone No. (include area code) 505-393-5905		10. Field and Pool, or Exploratory Area			
4. Location of Well (Footage, Sec., T, R., M., or Survey Description)		on)			Golden Lane Morrow		
(- 11.6)				11. County or Pa	arish, State		
660' FSL & 660' FWL Unit M	1 Sec 4-T21S-R29E						
				Eddy County,	NM		
12. CHECK AP	PROPRIATE BOX(ES) T	O INDICATE NATUR	RE OF NOTICE, RE	EPORT, OR O	THER DATA		
TYPE OF SUBMISSION		TY	PE OF ACTION				
	Acidize	Deepen Deepen	Production (Start/	Resume)	Water Shut-Off		
Notice of Intent	Alter Casing	Fracture Treat	Reclamation		Well Integrity		
Subsequent Report	Casing Repair	New Construction	Recomplete		Other		
	Change Plans	Plug and Abandon	Temporarily Aba	ndon			
Final Abandonment Notice	Convert to Injection	Plug Back	✓ Water Disposal				

(0)

Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

Water is produced from the Morrow formation at appprox 35 BPD. The water is stored on lease in a water tank. The water is trucked from the lease by Mesquite Water Disposal to the Big Eddy Federal 100 WDW (permit #SWD461) located in Unit L, Sec 8-T21S-R28E. Attached is the latest water analysis.

14. 1 hereby certify that the foregoing is true and correct Name (PrintedlTyped)					
Kristi Green	Title F	Hobbs Regulatory			
Signature Arrite Glen		07/27/06			
U ATHIS SPACE FO	RFEDERALOR	STATE OFFICE USE	The second second		
Approved by (Signature)		Name (Printed/Typed)	Title		
Conditions of approval, if any, are attached. Approval of this notice of certify that the applicant holds legal or equitable title to those rights which would entitle the applicant to conduct operations thereon.	does not warrant or i	Office		Date	

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.



Water Analysis

Date:

23-Jun-06

2708 West County Road, Hobbs NM 88240 Phone (505) 392-5556 Fax (505) 392-7307

Analyzed For

Company	Well Name Golden Lane4 Fed#1 Swab Sample		Co	ounty	State New México 1 (PM)	
Mewbourne			d#1 I	_ea		
Sample Source			Sample #	1 (F		
Formation			Depth			
Specific Gravity	1.045		SG @	60 °F	1.049	
ρН	6.00		St	dfides	Absent	
Temperature (*F)	78		Reducing A	gents		
Cations			,			
Sodium (Calc)		in Mg/L	20,364	in PPM	19,420	
Calcium		in Mg/L	4,800	in PPM	4,578	
Magnesium		in Mg/L	720	in PPM	687	
Soluable Iron (FE2)		in Mg/L	2,000.0	in PPM	1,907	
Anions	···					
Chlorides		in Mg/L	44,000	in PPM	41,961	
Sulfates		in Mg/L	210	in PPM	200	
Bicarbonates		in Mg/L	381	in PPM	363	
Total Hardness (as CaCO3		in Mg/L	15,000	in PPM	14,305	
Total Dissolved Solids (Cal	(c)	in Mg/L	72, 4 75	in PPM	69,116	
Equivalent NaCl Concentration in		in Mg/L	67,301	in PPM	64,182	
Scaling Tendencies						
Calcium Carbonate Index					,827,072	

Below 500,000 Remote / 500,000 - 1,000,000 Possible / Above 1,000,000 Probable

*Calcium Sulfate (Gyp) Index

1,008,000

Below 500,000 Remats / 500,000 - 10,000,00 Possible / Above 10,000,000 Probable

*This Calculation is only an approximation and is only valid before treatment of a wall or several weeks after treatment.

Remarks

rw=.110@78f