Submit 3 Copies To Appropriate District Office	State of New Mexico		Form C-103			
District I	cilicity, winiciais and water a resources			Revised May 08, 2003 WELL API NO.		
District II				30-015-34779		
1301 W. Grand Ave., Artesia, NM 88210 District III	UI W Grand Ave., Artesia, NM 88210			5. Indicate Type of Lease		
1000 Rio Brazos Rd., Aztec, NM 87410 Santa Fe, NM 87505 District IV			STATE FEE			
1220 S. St. Francis Dr., Santa Fe, NM 87505		* .	6. State Oi	il & Gas Lease N	0.	
SUNDRY NOTIC (DO NOT USE THIS FORM FOR PROPO DIFFERENT RESERVOIR. USE "APPLIC PROPOSALS.)	CES AND REPORTS ON WEDSALS TO DRILL OR TO DEEREN CATION FOR PERMIT" (FOR WC-1	OR PLUG BACK TO A 101) FOR SUCH	1625 FEDE		eement Name:	
1. Type of Well:		100 w	8. Well Nu			
Oil Well Gas Well X	Other	-c0[]\\\r\\	9. OGRID	301		
2. Name of Operator LCX Energy, LLC		OCD - ARTESIA 57	9. OGRID	218885		
3. Address of Operator	1 (2 h/m)		10. Pool n	ame or Wildcat		
110 N. Marienfeld, Ste. 20 4. Well Location	10, Midland, TX 79701	ुरामधारा दूर		DD CREEK WOLFC	AMP	
Unit Letter A :	660 feet from the NO	ORTH line and	760	feet from the	EAST line	
Section 30	Township 16S	Range 25E	NMPM	Count	y EDDY	
	11. Elevation (Show whether	<i>r DR, RKB, RT, GR, et</i> 571' GR	c.)			
12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data						
NOTICE OF INTE	* * *	_ 	• '	T REPORT (OF:	
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	02402.1		RING CASING 🔲	
TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DRILLI	NG OPNS.	☐ PLUG	AND DONMENT	
PULL OR ALTER CASING	MULTIPLE COMPLETION	CASING TEST AND CEMENT JOB				
OTHER:		OTHER: SPUD			X	
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.						
12/15/05 - 12/16/06 SPUD 17 1/2" HOLE AT 10:00 AM. DRILL TO 351', SWEEP HOLE, POOH W/ BIT. RU CASING CREW. RUN 8 JTS 13 3/8" 48# H40 ST&C CASING, TEXAS PATTERN GUIDE SHOE, INSERT FLOAT AT 303', SET CASING AT 347'. RAN 4 CENTRALIZERS. CIRCULATE THROUGH CASING. RIG UP CEMENTERS, CEMENT CASING W/ 245 SX 35/65 POZ CL C + ADDITIVES, WT 12.6 PPG, TAIL IN W/ 204 SX CL C+ 2% S1, WT-14.8 PPG. DISPLACE W/ 48 BBLS FW. BUMP PLUG W/673 PSI, FLOAT HELD OK. CIRCULATE 63 SX CEMENT TO PIT. WOC 7 HOURS, CUT OFF CONDUCTOR PIPE AND 13 3/8" CASING. WELD ON 13 3/8" WELL HEAD, TEST TO 1000# FOR 15 MINS. NIPPLE UP BOPS.						
I hereby certify that the information above SIGNATURE Type or print name KANICIA CARRI	S TI	-	f. Ory Agent	DATE _ Telephone No.	12/22/06 432-262-4013	
(This space for State use)	ECODO ONV		<u></u>		DEO 2 2000	
APPROVED BYConditions of approval, if any:	RECORDS ONLY	ITLE		DATE	DEC 2 8 2000	