Form 3160-5 (April 2004)

Month - Year MAR 1 OCD - ARTE

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OM B No. 1004-0137 Expires: March 31, 2007

## 5. Lease Serial No.

NM-38463

| 0 1 -   | I SUNDRI   | NOTICES AND RE   |  |  |  |  |
|---|--|--|--|--|--|--|
| IR 192<br>- Artesia                             | Do not use to abandoned w  | his form for proposals<br>vell. Use Form 3160-3 (  |  |  | 6. If Indian, Allottee or Tribe Name   |  |
| -   | SUBMIT IN TRIPLICATE- Other instructions on reverse side.  |  |  |  | 7. If Unit or CA/Agreement, Name and/or No.  |  |
|   | 1. Type of Well Gas Well Other   |  |  | 8. Well Name and No.   |  |  |
|   | 2. Name of Operator Pogo Producing Company   |  |  | Pure Gold B Federal # 7  9. API Well No.   |  |  |
| ·   | 3a Address<br>P. O. Box 10340, MId   | land, TX 79702   | 3b. Phone No. (include<br>432-685-8100   | area code)   | 30-015- 35295  |  |
|   | 4. Location of Well (Footage, Sec.,  |  |  |  | 10. Field and Pool, or Exploratory Area<br>Sand Dunes Delaware West  |  |
|   | 1980' FNL & 1720' FE   | L, Section 20, T2  | 3S, R31E   |  | 11. County or Parish, State  Eddy County, NM   |  |
|   | 12. CHECK A  | PPROPRIATE BOX(ES) TO  | INDICATE NATUR   | E OF NOTICE, R   | EPORT, OR OTHER DATA   |  |
|   | TYPE OF SUBMISSION   |  | TYP  | E OF ACTION  |  |  |
|   | Notice of Intent   | Acidize  X Alter Casing  | Deepen Fracture Treat  | Production (Statement   Reclamation  | rt/Resume)   |  |
|   | Subsequent Report  | Casing Repair  | New Construction   | Recomplete   | Other  |  |
|   | Final Abandonment Notice   | Change Plans Convert to Injection  | Plug and Abandon Plug Back   | ☐ Temporarily Aba  | andon  |  |
|   | following completion of the inv  | he work will be performed or proviously object operations. If the operation hal Abandonment Notices shall be   | de the Bond No. on file w<br>results in a multiple compl   | ith BLM/BIA. Require<br>etion or recompletion in   | e vertical depths of all pertinent markers and zones,<br>d subsequent reports shall be filed within 30 days<br>a new interval, a Form 3160-4 shall be filed once<br>tion, have been completed, and the operator has  |  |
| le Size   | Attach the Bond under which the following completion of the investing has been completed. Find determined that the site is ready   | the work will be performed or provi-<br>volved operations. If the operation<br>nal Abandonment Notices shall be<br>by for final inspection.)   | de the Bond No. on file w<br>results in a multiple compl   | ith BLM/BIA. Require<br>etion or recompletion in<br>hents, including reclama<br>Cement Qua   | d subsequent reports shall be filed within 30 days a new interval, a Form 3160-4 shall be filed once ution, have been completed, and the operator has  |  |
| 1/2"  | Attach the Bond under which the following completion of the invitesting has been completed. Fit determined that the site is ready the Casing Size & Gr 20" Sched 10 13-3/8" H-40   | the work will be performed or proviously object on the work will be performed or proviously object on the operation of the op | de the Bond No. on file w results in a multiple compl filed only after all requiren  Setting Depth 40' 800'  | ith BLM/BIA. Require<br>etion or recompletion in<br>cents, including reclama<br>Cement Qua<br>2.2 yds Redi<br>650 sks circu  | d subsequent reports shall be filed within 30 days a new interval, a Form 3160-4 shall be filed once tion, have been completed, and the operator has antity  antity  -mix grouted  alated  |  |
| 1/2"  | Attach the Bond under which the following completion of the invitesting has been completed. Fit determined that the site is ready  Casing Size & Gr 20" Sched 10 13-3/8" H-40 8-5/8" J-55  | the work will be performed or proviously object on the work will be performed or proviously object on the operation of the op | de the Bond No. on file w results in a multiple compl filed only after all requiren  Setting Depth 40' 800' 4100'  | ith BLM/BIA. Require<br>etion or recompletion in<br>cents, including reclama<br>Cement Qua<br>2.2 yds Redi<br>650 sks circu<br>1300 sks circu  | d subsequent reports shall be filed within 30 days a new interval, a Form 3160-4 shall be filed once tion, have been completed, and the operator has antity  -mix grouted ulated culated   |  |
| 1/2"  | Attach the Bond under which the following completion of the invitesting has been completed. Fit determined that the site is ready  Casing Size & Gr 20" Sched 10 13-3/8" H-40 8-5/8" J-55 5-1/2" J-55  | the work will be performed or proviously objections. If the operation and Abandonment Notices shall be sty for final inspection.)  Tade Csg Weight  53#  48#  32#  17#   | de the Bond No. on file w results in a multiple compl filed only after all requiren  Setting Depth 40' 800' 4100' Surf-1000'   | ith BLM/BIA. Require etion or recompletion in tents, including reclama  Cement Qua  2.2 yds Redi  650 sks circi  1300 sks circi  1st stage 500   | d subsequent reports shall be filed within 30 days a new interval, a Form 3160-4 shall be filed once tion, have been completed, and the operator has untity  -mix grouted alated culated sks "C" 14.1 ppg, circ  |  |
| 1/2"<br>8"<br>8"                                | Attach the Bond under which the following completion of the invitesting has been completed. Fit determined that the site is ready  Casing Size & Gr 20" Sched 10 13-3/8" H-40 8-5/8" J-55 5-1/2" J-55 5-1/2" J-55  | the work will be performed or proviously object on the work will be performed or proviously object on the standard or proviously for final inspection.)  Trade Csg Weight  53#  48#  32#  17#  15.5#   | de the Bond No. on file w results in a multiple compl filed only after all requiren  Setting Depth 40' 800' 4100' Surf-1000' 1000'-6000'                                 | ith BLM/BIA. Require etion or recompletion in tents, including reclama  Cement Qua 2.2 yds Redi 650 sks circu 1300 sks circu 1st stage 500 2nd stage 450   | d subsequent reports shall be filed within 30 days a new interval, a Form 3160-4 shall be filed once tion, have been completed, and the operator has untity  -mix grouted alated culated sks "C" 14.1 ppg, circ 0 sks "C" 12.8 ppg, circ   |  |
| 1/2"<br>/8"<br>/8"                              | Attach the Bond under which the following completion of the invitesting has been completed. Find determined that the site is ready  Casing Size & Gr 20" Sched 10 13-3/8" H-40 8-5/8" J-55 5-1/2" J-55 5-1/2" J-55 5-1/2" J-55   | the work will be performed or proviously object on the second of the operation of the opera | de the Bond No. on file w results in a multiple compl filed only after all requiren  Setting Depth 40' 800' 4100' Surf-1000'   | cith BLM/BIA. Require etion or recompletion in the test, including reclamate Cement Qua 2.2 yds Redii 650 sks circu 1300 sks circu 1st stage 500 2nd stage 450 3rd stage 450   | d subsequent reports shall be filed within 30 days a new interval, a Form 3160-4 shall be filed once tion, have been completed, and the operator has untity  -mix grouted alated culated sks "C" 14.1 ppg, circ  |  |
| 1/2"<br>/8"<br>/8"<br>/8"<br>/8"<br>EE /        | Attach the Bond under which the following completion of the invitesting has been completed. Find determined that the site is ready  Casing Size & Gr 20" Sched 10 13-3/8" H-40 8-5/8" J-55 5-1/2" J-55 5-1/2" J-55 5-1/2" J-55 ATTACHED FOI  | the work will be performed or proviously object on the second of the operation of the opera | de the Bond No. on file w results in a multiple compl filed only after all requiren  Setting Depth 40' 800' 4100' Surf-1000' 1000'-6000' 6000'-8200'                     | cith BLM/BIA. Require etion or recompletion in itents, including reclama 2.2 yds Redi 650 sks circu 1300 sks circu 1st stage 500 2nd stage 450 3rd stage 450 Stage tools (circulation)   | d subsequent reports shall be filed within 30 days a new interval, a Form 3160-4 shall be filed once tion, have been completed, and the operator has untity  -mix grouted culated culated sks "C" 14.1 ppg, circ of sks "C" 12.8 ppg, circ of sks "C" |  |
| 1/2"<br>/8"<br>/8"<br>/8"<br>/8"<br>EE /        | Attach the Bond under which the following completion of the invitesting has been completed. Find determined that the site is ready  Casing Size & Gr 20" Sched 10 13-3/8" H-40 8-5/8" J-55 5-1/2" J-55 5-1/2" J-55 5-1/2" J-55 ATTACHED FOI  | the work will be performed or proviously object on the work will be performed or proviously object on the performed or proviously of the operation of the performed or proviously of the operation.)  Tade Csg Weight 53# 48# 32# 17# 15.5# 17#  R  PROVAL Stler @ 522', Top of Sale   | de the Bond No. on file w results in a multiple compl filed only after all requiren  Setting Depth 40' 800' 4100' Surf-1000' 1000'-6000' 6000'-8200'                     | cith BLM/BIA. Require etion or recompletion in itents, including reclama 2.2 yds Redi 650 sks circu 1300 sks circu 1st stage 500 2nd stage 450 3rd stage 450 Stage tools (circulation)   | d subsequent reports shall be filed within 30 days a new interval, a Form 3160-4 shall be filed once tion, have been completed, and the operator has untity  -mix grouted alated culated sks "C" 14.1 ppg, circ of sks "C" 12.8 pp |  |
| 1/2"<br>/8"<br>/8"<br>/8"<br>/8"<br>EE /        | Attach the Bond under which the following completion of the invitesting has been completed. Find determined that the site is ready  Casing Size & Gr 20" Sched 10 13-3/8" H-40 8-5/8" J-55 5-1/2" J-55 5-1/2" J-55 5-1/2" J-55 5-1/2" J-55 J-1/2" J-1/2" J-55 J-1/2" J-57 J-1/2" | the work will be performed or proviously object on the work will be performed or proviously object on the performed or proviously of the operation of the performed or proviously of the operation.)  Tade Csg Weight 53# 48# 32# 17# 15.5# 17#  R  PROVAL Stler @ 522', Top of Sale   | de the Bond No. on file w results in a multiple compl filed only after all requiren  Setting Depth 40' 800' 4100' Surf-1000' 1000'-6000' 6000'-8200'                     | cith BLM/BIA. Require etion or recompletion in itents, including reclama 2.2 yds Redi 650 sks circu 1300 sks circu 1st stage 500 2nd stage 450 3rd stage 450 Stage tools (circulation)   | d subsequent reports shall be filed within 30 days a new interval, a Form 3160-4 shall be filed once tion, have been completed, and the operator has untity  -mix grouted alated culated sks "C" 14.1 ppg, circ of sks "C" 12.8 pp |  |
| 1/2"<br>/8"<br>/8"<br>/8"<br>/8"<br>EE /        | Attach the Bond under which the following completion of the invitesting has been completed. Find determined that the site is ready  Casing Size & Gr 20" Sched 10 13-3/8" H-40 8-5/8" J-55 5-1/2" J-55 5-1/2" J-55 5-1/2" J-55 5-1/2" J-55 4TTACHED FOI DITIONS OF AP t, Glenn Curry, picked Rus   | the work will be performed or proviously object on the work will be performed or proviously object on the performed or proviously of the operation of the performed or proviously of the operation.)  Tade Csg Weight 53# 48# 32# 17# 15.5# 17#  R  PROVAL Stler @ 522', Top of Sale   | de the Bond No. on file w results in a multiple compl filed only after all requiren  Setting Depth 40' 800' 4100' Surf-1000' 1000'-6000' 6000'-8200'                     | cement Qua 2.2 yds Redi 650 sks circu 1300 sks circu 1st stage 500 2nd stage 450 3rd stage 450 Stage tools (comply)  | d subsequent reports shall be filed within 30 days a new interval, a Form 3160-4 shall be filed once tion, have been completed, and the operator has untity  -mix grouted alated culated sks "C" 14.1 ppg, circ of sks "C" 12.8 pp |  |
| 1/2"<br>/8"<br>/8"<br>/8"<br>EE /               | Attach the Bond under which the following completion of the invitesting has been completed. Find determined that the site is ready  Casing Size & Gr 20" Sched 10 13-3/8" H-40 8-5/8" J-55 5-1/2" J-55 5-1/2" J-55 5-1/2" J-55 T-1/2" J-57 T-1/2" J-57 T-1/2" J-57 T-1/2" J-1/2" J-57 T-1/ | the work will be performed or proviously object operations. If the operation and Abandonment Notices shall be a for final inspection.)  Tade Csg Weight 53# 48# 32# 17# 15.5# 17#  R  PROVAL Stler @ 522', Top of Sala going is true and correct   | de the Bond No. on file w results in a multiple compl filed only after all requiren  Setting Depth 40' 800' 4100' Surf-1000' 1000'-6000' 6000'-8200'  t @ 860', Basal An | ch BLM/BIA. Require etion or recompletion in tents, including reclamare.  Cement Qua 2.2 yds Redii 650 sks circu 1300 sks circu 1300 sks circu 1st stage 500 2nd stage 450 3rd stage 450 Stage tools (anhydrite @ 4024 Sr. Eng Tech 03/09/07 | d subsequent reports shall be filed within 30 days a new interval, a Form 3160-4 shall be filed once tion, have been completed, and the operator has untity  -mix grouted alated culated sks "C" 14.1 ppg, circ of sks "C" 12.8 pp |  |
| ;<br>;1/2"<br>;/8"<br>/8"<br>/8"<br>EE <i>L</i> | Attach the Bond under which the following completion of the invitesting has been completed. Find determined that the site is ready  Casing Size & Gr 20" Sched 10 13-3/8" H-40 8-5/8" J-55 5-1/2" J-55 5-1/2" J-55 5-1/2" J-55 T-1/2" J-57 T-1/2" J-57 T-1/2" J-57 T-1/2" J-1/2" J-57 T-1/ | the work will be performed or proviously object operations. If the operation and Abandonment Notices shall be so for final inspection.)  Tade Csg Weight 53# 48# 32# 17# 15.5# 17# R  PROVAL stler @ 522', Top of Sala going is true and correct   | de the Bond No. on file w results in a multiple compl filed only after all requiren  Setting Depth 40' 800' 4100' Surf-1000' 1000'-6000' 6000'-8200'  t @ 860', Basal An | cement Qua 2.2 yds Redi 650 sks circt 1300 sks circt 130 sks circt 1st stage 500 2nd stage 450 3rd stage 450 Stage tools (anhydrite @ 4024  Sr. Eng Tech 03/09/07  | d subsequent reports shall be filed within 30 days a new interval, a Form 3160-4 shall be filed once tion, have been completed, and the operator has untity  -mix grouted alated culated sks "C" 14.1 ppg, circ of sks "C" 12.8 pp |  |

## Pure Gold "B" Federal #7 Pogo Producing Company March 13, 2007 Conditions of Approval

- 1. 20" Sched 10 53# casing to be cemented to surface with ready mix.
- 2. 13-3/8" H-40 48# casing to be set a minimum of 25 feet into the Rustler Anhydrite at approximately 800 feet and above the salt.
- 3. 8-5/8" J-55 32# casing to be set at least 100 feet below and not more than 600 feet below the base of the salt at approximately 4100 feet.

WWI 031307