Form 3160-5 (April 2004)

## **UNITED STATES** DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

OCD-ARTESIA

FORM APPROVED OM B No. 1004-0137 Expires: March 31, 2007

5. Lease Serial No.

NM-38463

## SUNDRY NOTICES AND REPORTS ON WELL

AR 1 9 2007 - ARTESIA. I	Do not use this form for proposals to drill or to re-entern abandoned well. Use Form 3160-3 (APD) for such propos			6. If Indian, Allottee or Tribe Name
	SUBMIT IN TRIPLICATE- Other instructions on reverse side.			7. If Unit or CA/Agreement, Name and/or No.
-	1. Type of Well Gas Well Other			8. Well Name and No. Pure Gold B Federal #8
	2. Name of Operator Pogo Producing Company			9. API Well No.
-	3a Address 3b. Phone No. (include area code)		30-015- 27821 35297	
	P. 0. Box 10340, Midland, TX 79702 432-685-8  4. Location of Well (Footage, Sec., T., R., M., or Survey Description)		432-685-8100	10. Field and Pool, or Exploratory Area Sand Dunes Delaware West
-	1980' FNL & 380' FEL Section 20, T23S, R31E		11. County or Parish, State  Eddy County, NM	
	12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, R			, REPORT, OR OTHER DATA
	TYPE OF SUBMISSION		TYPE OF ACTION	I
	X Notice of Intent	Acidize  X Alter Casing	Deepen Production Fracture Treat Reclamatio	
	Subsequent Report	Casing Repair  Change Plans	New Construction Recomplete	
	Final Abandonment Notice	Convert to Injection	Plug and Abandon Temporaril Plug Back Water Disp	y Abandon oosal
Hole Size	determined that the site is ready	for final inspection.)		clamation, have been completed, and the operator has  Quantity
26"	20" Sched 10	53#		Redi-mix grouted
17-1/2"	13-3/8" H-40	48#	•	circulated
11"	8-5/8" J-55	32#		s circulated
7-7/8"	5-1/2" J-55	17#	Surf-1000' 1st stage	500 sks "C" 14.1 ppg, circ
7-7/8"	5-1/2" J-55	15.5#	1000'-6000' 2 <sup>nd</sup> stage	450 sks "C" 12.8 ppg, circ
7-7/8"	5-1/2" J-55	17#	6000'-8200' 3 <sup>rd</sup> stage	450 sks "C" 12.8 ppg, circ
	ATTACHED FO		•	ols @ 3900' & 6000'
CON Geologist,	DITIONS OF AI Glenn Curry, picked Rus	PROVAL tler @ 522', Top of Salt	a @ 860', Basal Anhydrite @	4024' & Delaware Lime @ 4256'.
=	14. Thereby certify that the fore	going is true and correct	1	
	Name (Printed/Typed) Cathy Wright		Title Sr. Eng T	ech
=	Signature Cally	Must	Date 03/09/07	APPROVED
=	Signature Caffyld	MAT THIS SPACE FOR F		
=	Signature Caffy (	MAT THIS SPACE FOR F	Date 03/09/07	

PETROLEUM ENGINEER Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

## Pure Gold "B" Federal #8 Pogo Producing Company March 13, 2007 Conditions of Approval

- 1. 20" Sched 10 53# casing to be cemented to surface with ready mix.
- 2. 13-3/8" H-40 48# casing to be set a minimum of 25 feet into the Rustler Anhydrite at approximately 800 feet and above the salt.
- 3. 8-5/8" J-55 32# casing to be set at least 100 feet below and not more than 600 feet below the base of the salt at approximately 4100 feet.

WWI 031307