Form 3160-5 (April 2004)

## **UNITED STATES**

DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED
OM B No. 1004-0137
Expires: March 31, 2007

	Expire	s: Ma	arch	31,	2
ease Seria	l No.				_

SUNDRY NOTICES AND REPORTS ON TELL  Do not use this form for proposals to drill or to an abandoned well. Use Form 3160-3 (APD) for such proposals.				5. Lease Serial No. NM-38464  6. If Indian, Allottee or Tribe Name	
SUBMIT IN TR	IPLICATE- Other insti	ructions on reve	rse side.	7. If Unit or CA/Agreement, Name and/or No.	
1. Type of Well Oil Well	Gas Well Other			8. Well Name and No. Pure Gold A Federal # 16	
Name of Operator     Pogo	Producing Company			9 API Well No.	
3a Address 3b. Phone No. (include area code)			30-015- 35309		
P. O. Box 10340, Midland, TX 79702 432-685-8100			10. Field and Pool, or Exploratory Area		
4. Location of Well (Footage, Sec.,	T., R., M., or Survey Description)			Sand Dunes Delaware West	
1860' FNL & 660' FEL	, Section 21,	, T23S, R31E		11. County or Parish, State  Eddy County, NM	
12. CHECK A	PPROPRIATE BOX(ES) TO	INDICATE NATUR	RE OF NOTICE, R	EPORT, OR OTHER DATA	
TYPE OF SUBMISSION		TY	PE OF ACTION		
Notice of Intent     Subsequent Report     Final Abandonment Notice	Acidize  XX Alter Casing  Casing Repair  Change Plans  Convert to Injection	Deepen Fracture Treat New Construction Plug and Abandon Plug Back	Production (Sta Reclamation Recomplete Temporarily Ab	Well Integrity Other	
	ed Operation (clearly state all pertin			y proposed work and approximate duration thereof.	

If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

Hole Size	Casing Size & Grade	Csg Weight	Setting Depth	Cement Quantity
26"	20" Sched 10	53#	40'	2.2 yds Redi-mix grouted
17-1/2"	13-3/8" H-40	48#	800'	650 sks circulated
11"	8-5/8" J-55	32#	4100'	1300 sks circulated
7-7/8"	5-1/2" J-55	17#	Surf-1000'	1 <sup>st</sup> stage 500 sks "C" 14.1 ppg, circ
7-7/8"	5-1/2" <b>J</b> -55	15.5#	1000'-6000'	2 <sup>nd</sup> stage 450 sks "C" 12.8 ppg, circ
7-7/8"	5-1/2" I-55 OD	17#	6000'-8200'	3 <sup>rd</sup> stage 450 sks "C" 12.8 ppg, circ
CEE ATT	ACHED FOR			Stage tools @ 3900' & 6000'
	n	7 A T		

## CONDITIONS OF APPROVAL

Geologist, Glenn Curry, picked Rustler @ 522', Top of Salt @ 860', Basal Anhydrite @ 4024' & Delaware Lime @ 4256'.

14. I hereby certify that the foregoing is true and correct Name (Printed/Typed) Cathy Wright	Title	Sr. Eng Tech			
Signature Cally What	Date	03/09/07	APPROVED		
/ THIS SPACE FOR FEDERAL OR STATE OFFICE USE					
Approved by	Title		Date MAR 1 3 2007		
Conditions of approval, if any, are attached. Approval of this notice does not warrant certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.	se Offic		WESLEY W. INGRAM		
Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.					

## Pure Gold "A" Federal #16 Pogo Producing Company March 13, 2007 Conditions of Approval

- 1. 20" Sched 10 53# casing to be cemented to surface with ready mix.
- 2. 13-3/8" H-40 48# casing to be set a minimum of 25 feet into the Rustler Anhydrite at approximately 800 feet and above the salt.
- 3. 8-5/8" J-55 32# casing to be set at least 100 feet below and not more than 600 feet below the base of the salt at approximately 4100 feet.

WWI 031307