District I 1625 N. French Dr., Hobbs, NM \$8240 District H District H 1301 W. Grand Avenne, Artesia, NM 88210 District H 1000 Ris Banzos Rood, Autoc, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico **Energy Minerals and Natural Resources**

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 June 1, 2004

For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Po

Pit or Below-Grade Tank Registration or Closure

Type of action: Registration of a pit o	or below-gende tank: 🔲 Closuse of a pit or below-gen	le trak
	(505)393-590 <u>5</u> canil allows:	·
Masses P.O. Box 5270 Hobbs Nm 81	241	
Forty Niner Ridge Unit # 101 ATTE	30-015-34331 West Out Of A	Sec 16 T 235 R 30E
Letitule	N32'17'58.6 " Immelio3:5	3' /8.8" NAD: 1927 [] 1983 []
efice Owner: Pederal State Private Indian		
	Below-strak	
rge: Drilling K Production Disposal D	Volume:bbi Type of fluid: Construction material: Dual-to-walled, with lask detection? Yes-[] Faut, explain why not.	
Westower Benegerey		
the Chairman Command C	Duable-walled, with link detection? Yes [] If we	t, explain vily not.
ner type: Synthetic Thickness /2 mil Clay		
l Yoluno bil	Less Stem 50 feet	(20 prints)
olity to Summy mater. (noticely signatures glown posters of his so assessed	50 feet or more, but loss than 100 feet	(10 points)
high water elevation of ground water.)	100 feet or macc /50'	(Operints)
	Yes	
Fellhand protection area: (Lass than 200 feet from a private domestic	No)	(20 points)
water source, or loss than 1000 feet from all other unter sources.)	4	(opens)
Distance to surface water: (horizontal distance to all wetlands, player, imigation canals, disches, and percential and ophomeral watercourses.)	Loss than 200 foot	(20 points)
	290 fact or more, but less than 1000 feet	(10 points)
	1000 fleet or more	(O points)
	Ranking Score (Total Paints)	
ner are burying in place) coaise of officie of it offices, name of facility mediation start date and end date. (4) Groundwater encountered: No place of the coaise sand on the coaise and one of sample incutions and one of Afficiant Comments: Refer to Affice of Affice of the coaise o	Yes I If yes, show depth below ground surface N	1.
I hereby certify that the information above in true and complete to the be	at of any knowledge and belief. I further curtify that	the above described pit or below grade (an)
the best field be constructed or closed according to MADCD guidate Date: 5/24/67 Printed Name/Title Du Sty L. Wilson/Field Age	at supply	ative OCD-approved plan [].
otherwise endanger public health or the environment. Mer does it selieve		any other federal, state, or local laws and/or
regulations. Approval: Printed Name/Title		



P.O. Box 310 Hobbs, NM 88241-0310

New Mexic Environmental Services

Hobbs. New Mexico Off 505.392.8584 Cell 505.631.2442 Fax 505.392.3085

Hobbs, New Mexico

Reserve Pit Remediation

SURFACE PIT CLOSURE PLAN

PIT PARAMETERS

COMPANY: Mewbourne Oil Co.

WELL SITE: Forty Niner Ridge Unit #101

LEGAL DESCRIPTION: Unit N Sec 16 T23s R30e, 660

FSL 1980 FWL, Eddy co.

The reserve pit inset on this leasehold is being permitted to close as per New Mexico OCD "Pit and Below Grade Tank Guidelines" dated November 1, 2004.

This pit was excavated and formed to the dimensions roughly 150' X 150' X 6' deep. A 12 mil membrane liner and pad was used to prevent leakage to the surface soils. A visual examination of the membrane liner indicates that the liner had maintained its integrity.

After the drilling and completion phase of this project, the water phase of the pit contents were pumped and hauled to an approved water injection facility. It is estimated that the volume of solids remaining are to +/- 1800 yards. The burial cell is to be excavated and lined with a minimum 12 mil membrane that complies with ASTM Standards: D-5747, D-5199, D-5994, and D-4833. The cuttings will be loaded as to allow for > 36" freeboard to ground level. After the cuttings are loaded the 12 mil liner will be folded over the top, and a 20 mil minimum thickness liner meeting the minimum requirements as outlined in ASTM Standard Methods: D-5747, D-5199, D-5994, D-4833; will be used to cap and cover to an extended area that exceeds three feet in all directions from the

edge of the burial cell. This cap will be constructed as to slope and allow for water runoff from burial cell.

A minimum of 36" of top soil will be used to cover the burial cell. This soil must be capable of supporting plant growth. A seed mixture will be used as to conform to local BLM and OCD requirements.

After the drilling solids are buried, the natural contour of the surrounding soils will be mechanically shaped as to prevent erosion of the well site until vegetation is established.