UNITED STATES N.M. OII CONS. DIV-DIST. 2 OMB NO. 1004-0135 DEPARTMENT OF THE INTERIOR OI W. Grand Avenue Serial No. BUREAU OF LAND MANAGEMENTS OI W. Grand Avenue Serial No.

SUNDRY NOTICES AND REPORTS ON WILLS AND AND

SUBMIT IN TRIPLICATE - Other instructions on reverse side					7. If Unit or CA/Agreement, Name and/or No.	
•	Type of Well Gas Well	l a.,		01112	8. Well Name and No.	
	Name of Operator	■ Other	// 20	101112137	Chiricahua R 21	Fed #1
٤.	Threshold Development Company			9. API Well No.		
Ba.	Address I 3b. Phone No			clude area code)	30-035-20034	
	Address Taylor St Penthouse II 817-		3b. Phone No. (in 817-87)	7.5.74.84V	10. Field and Pool, or Exploratory Area	
ŧ.	Location of Well (Footage, Sec.	, T., R., M., or Survey Description	1) (-	SECENED OF	Wildcat Explor	atory
	1115' FNT. & 660'	FWL of Section 2	1-T24S-R18E	KEUNRTESIN S	11. County or Parish, State	
	Unit D. NWNW	, T., R., M., or Survey Description FWL of Section 2		RECEIVESIA SOCO ARTESIA	/	
					Otero Co., N	1
12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION						
	TYPE OF SUBMISSION	·				
		Acidize	Deepen Deepen	Production (St	tart/Resume) 🔲 Water Shut-Off	
L	Notice of Intent	Alter Casing	☐ Fracture Treat	Reclamation	Well Integrity	
X	Subsequent Report	Casing Repair	New Construction	on Recomplete	Other Rat H	ole Spud,
	Subsequent Report	Change Plans	Plug and Aband	on 🔲 Temporarily	Abandon Rotary t	ools,
	Final Abandonment Notice	Convert to Injection	Plug Back	Water Disposa	surf. casing &	cement
If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BLA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.) Spudded a 26" hole with rat hole machine at 9:30 AM 7-1-2003. Drilled to 40'. Set 40' of 16" conductor pipe. Cemented to surface. TD 40'. Waiting on rotary tools. Resumed drilling a 14-3/4" hole with rotary tools at 6:30 AM 8-3-2003. NOTE: J. R. Hogwood w/BLM-Roswell on location and witnessed resuming drilling. TD 600'. Reached TD at 10:30 PM 8-3-2003. Ran 14 joints of 11-3/4" 42# H-40 (606.31') of casing set at 600'. 1-Texas Pattern guide shoe set at 600'. Insert float set at 558'. Cemented with 200 sacks Premium Plus, 1% thickset A, 1/4# thickset B (yield 1.51, weight 14.0) and 100 sacks Howco Lite, 1/4#/sack flocele, 5#/sack gilsonite and 2% CaC12 (yield 1.99, weight 12.5). Tailed in with 200 sacks Premium Plus and 2% CaC12 (yield 1.99, weight 14.8). PD 5:30 AM 8-4-2003. Bumped plug to 500 psi for 5 minutes, 14. Thereby certify that the foregoing is true and correct CONTINUED ON NEXT PAGE:						
	Name (Printed/Typed)		(NUMI INOD.	
	Rusty Klein//		Titl	e Agent		
==	Signature # U.S.	to Plen	Dat	e August 15	, 2003	
	And the state of t	/THIS SPACE	FOR FEDERAL 0	R STATE OFFICE U	SE ALLON	
Δ.	pproved by			Title	Date	
	onditions of approval, if any, are	attached. Approval of this not	ce does not warrant o		Louis	
ce	rtify that the applicant holds leg	gal or equitable title to those rig	hts in the subject leas	ase Office		
=	hich would entitle the applicant to	COMPTED FOR RECORD				
Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.						
					SEP 9 2003	
					1 / L	

ARMANDO A. LOPEZ

THRESHOLD DEVELOPMENT COMPANY Chiricahua R 21 Federal #1 Section 21-T24S-R18E Otero County, New Mexico

SUNDRY NOTICE CONTINUED:

OK. Cement did not circulate. WOC 8 hours. Ran Temperature Survey and found top of cement at 70'. Ran 1". Tagged cement at 89'. Spotted 50 sacks Class C with 2% CaCl2. PD 2:00 PM 8-4-2003. WOC 2 hours. Ran 1". Tagged cement at 84'. Spotted 50 sacks Class C with 2% CaCl2. PD 4:05 PM 8-4-2003. Circulated 25 sacks. WOC. Nippled up and tested to 1500 psi for 15 minutes, OK. Drilled out at 9:30 PM 8-6-2003. WOC 64 hours. Reduced hole to 10-5/8". Resumed drilling. NOTE: J. R. Hogwood w/BLM-Roswell on location and witnessed casing and cement.

Rusty Klein

Agent

August 15, 2003