

Submit 3 Copies To Appropriate District  
Office  
District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
811 South First, Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM  
87505

State of New Mexico  
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

Form C-103  
Revised March 25, 1999

WELL API NO.  
30-015-32889

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

Humidor State Unit

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH  
PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other ☐

2. Name of Operator

Yates Petroleum Corporation

3. Address of Operator

105 S. 4<sup>th</sup> Street Artesia, NM 88210

7. Well No.

1

8. Pool name or Wildcat

Wildcat Morrow

4. Well Location

Unit Letter A : 990 feet from the North line and 990 feet from the East line

Section 23 Township 24S Range 27E NMPM Eddy County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

3182' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

MULTIPLE  
COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING  
CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND  
ABANDONMENT ☐

CASING TEST AND  
CEMENT JOB ☐

OTHER: Surface and Intermediate casing 1 ☒

Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

9/5/03 - Set 20" 94# casing at 606'. Pumped 800 sx 35:65:6 "C" with additives. Tailed in with 452 sx "C" with additives. Cement circulated to surface. WOC 30 hrs. Reduced hole to 17-1/2" and resumed drilling.

9/11/03 - Set 13-3/8" 54.5# & 61# casing at 2452'. Cemented with 1900 sx 35:65:6 "C" with additives. Tailed in with 200 sx "C" with additives. Cement circulated to surface. WOC 51 hrs and 45 mins. Reduced hole to 12-1/4" and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tina Huerta TITLE Regulatory Compliance Supervisor DATE September 16, 2003

Type or print name Tina L. Huerta

Telephone No. 505-748-1471

(This space for State use)

APPROVED BY Tina W. Guen TITLE District Supervisor

DATE

Conditions of approval, if any:

SEP 18 2003