## Form 3160-5 (April 2004)

## OCD-ARTESIA UNITED STATES

DEPARTMENT OF THE INTERIOR

FORM APPROVED OM B No 1004-0137

	Expires.	March	31, 200
Lease Seria	l No		

BUREAU OF LAND MANAGEMENT			5 Lease Serial No NMNM 02860	
SUNDRY NOTICES AND REI	<del> </del>	6 If Indian, Allottee or Tribe Name		
Do not use this form for proposals to abandoned well. Use Form 3160-3 (				
SUBMIT IN TRIPLICATE- Other instructions on reverse side.			7 If Unit or CA/Agreement, Name and/or No	
1 Type of Well			71016	
	JUN 29 200	8 Well Name	and No. ke Unit #289	
2 Name of Operator BEPCO, L. P.	OCD-ARTES			
3a Address	3b Phone No (include area coa		5590	
P. O. Box 2760 Midland, TX 79702	432-683-2277		Pool, or Exploratory Area	
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)		11 County or		
SESW, UL N, 800' FSL & 2280' FWL, Sec 18, T24S, R30E, Lat N 32.212472 deg, Lon W 103.922139 deg	Mer NMI'	Eddy Co.	, NM	
12. CHECK APPROPRIATE BOX(ES) TO	INDICATE NATURE OF I	NOTICE, REPORT, OR	OTHER DATA	
TYPE OF SUBMISSION	TYPE OF A	CTION		
Acidize	Deepen Pr	oduction (Start/Resume)	Water Shut-Off	
Notice of Intent Alter Casing	Fracture Treat	eclamation	Well Integrity	
Subsequent Report Casing Repair		zcompiete L	Other Drilling	
Final Abandonment Notice Change Plans Convert to Injection		emporarily Abandon 'ater Disposal	Operations	
testing has been completed. Final Abandonment Notices shall be determined that the site is ready for final inspection.)  Spud well on 6/5/07. Drill 12-1/4" hole to 632'. Ran 15 j yld 1.56) + 280 sx 35/65 Poz Class C + 6% D20 + 5% D2 pps D130 ( wt 14.8, yld 1.35) tail. Displaced with 36.5 bt 3-4% CaCl in 5 stages (wt 14.8, yld 1.34) lead followed? Drilled 7-7/8" hole to 7372'. Ran 130 jts 5-1/2", 15.50#, stages: Stage 1 - 150 sx Litecrete (wt 10.2, yld 2.32) lead bbls mud. Bumped plug - floats held. Dropped opening 10% D20 + 0.2% D46 + 0.125 pps D130 + 5% D44 (wt 1 w/ 119 bbls FW. Bumped plug - held. Circ cement to su	ts 8-5/8", 32#, J-55, 8rd, LTC of 4 + 0.125 pps D130 (wt 12.7, yl) is FW, bumped plug - floats how 25 sx Thixotropic (wt 14.6, yl) J-55, 8rd, LTC and 46 jts 5-1/2 followed by 300 sx Litecrete (whomb, open DV tool, circ to su 1.9, yld 2.50) lead followed by	esg set at 632'. Cemented wild 1.96) lead followed by 200 eld. Did not circ to surface. eld 1.56). WOC 31 hrs. Test ", 17#, J-55, 8rd, LTC set avt 10.5, yld 2.00)tail. Displarface. Stage 2 - cemented w	ith 150 sx Thixotropic (wt 14.6, 0 sx Class C + 2% S1 + 0.125 Top out w/ 250 sx Class C + ed csg to 1000 psi - held ok. it 7371'. Cemented in two ced with 60 bbls FW and 114 ith 1420 sx 35/65 Poz Class C +	
14 Thereby certify that the foregoing is true and correct Name (Printed/Typed)				
		ıtle Administrative Assistant		
Signature Con notte Childre	Date Q-3	15-07		
THIS SPACE FOR FEDERAL OR STATE OFFICE USE  Approved by  Conditions of approval, if any, are attached Approval of this notice does not warrant or				
		CEPTE	Drund	
Approved by  Conditions of approval, if any, are attached Approval of this notice	does not warrant or	ACOLIDA	le le	
certify that the applicant holds legal or equitable title to those rights		\\\.	UN 27 2007	
which would entitle the applicant to conduct operations thereon.  Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212 make it.	a crime for any narron lengues -t-	and willfully a males at	department or age of the Tiles of	
Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it States any false, fictitious or fraudulent statements or representations	as to any matter within its jurisdic	and willfully to make to any o	ERICK WKJUGINEER	
(Instructions on page 2)		FI	department or agency westher United REDERICK WINGINEER TROLEUM ENGINEER	
Accepted for record - NMOCD				
7/1/1				
			/*/*/	