

Submit To Appropriate District Office State Lease - 6 copies Fee Lease - 5 copies District I 1625 N French Dr., Hobbs, NM 88240 District II 1301 W Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410 District IV 1220 S St. Francis Dr., Santa Fe, NM 87505		State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505		Form C-105 Revised June 10, 2003	
		WELL API NO. 30-015-22378			
		5. Indicate Type of Lease STATE ☒ FEE ☐			
		State Oil & Gas Lease No.			
WELL COMPLETION OR RECOMPLETION REPORT AND LOG					
1a. Type of Well. OIL WELL ☐ GAS WELL ☒ DRY ☐ OTHER _____ b. Type of Completion. NEW ☐ WORK ☐ DEEPEN ☐ PLUG ☒ DIFF. WELL OVER BACK RESVR. ☐ OTHER _____				7. Lease Name or Unit Agreement Name Eddy GF State Com	
2. Name of Operator Samson Resources Company				8. Well No. 2	
3. Address of Operator 200 N. Loraine St, Ste. 1010 Midland, TX 79701 ATTN: R. M. Burditt				9. Pool name or Wildcat Forehand Ranch; Wolfcamp	
4. Well Location Unit Letter K : 1980 Feet From The South Line and 1980 Feet From The West Line Section 16 Township 23S Range 27E NMPM Eddy County					
10. Date Spudded 2/12/1978		11. Date T.D. Reached 3/24/1978		12. Date Compl. (Ready to Prod.) 3/28/07	
				13. Elevations (DF& RKB, RT, GR, etc.) 3142' GR	
14. Elev. Casinghead					
15. Total Depth 12297		16. Plug Back T.D. 11910		17. If Multiple Compl. How Many Zones?	
				18. Intervals Drilled By X	
				19. Producing Interval(s), of this completion - Top, Bottom, Name 9806'-10183', Wolfcamp	
				20. Was Directional Survey Made No	
				21. Type Electric and Other Logs Run Gamma Ray Compensated Neutron - Density, Dual Laterolog/RXO	
				22. Was Well Cored No	
23. CASING RECORD (Report all strings set in well)					
CASING SIZE		WEIGHT LB./FT.		DEPTH SET	
13.375"		48#		404'	
9.625"		40#		2398'	
5.5"		17#		12297	
24. LINER RECORD					
SIZE		TOP		BOTTOM	
25. TUBING RECORD					
SIZE		DEPTH SET		PACKER SET	
26. Perforation record (interval, size, and number) 12054' - 12188', 2 spf Abandoned (7/1990) w/CIBP @ 11928' 11792' - 11894', 2 spf 11670' - 11678', 2 spf 9806' - 10183'					
27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.					
DEPTH INTERVAL		AMOUNT AND KIND MATERIAL USED			
12054' - 12188'		Acidz w/6000 gal & 7.5% MS acid w/1000 scf N2/bbl			
11792' - 11894'		Acidz w/1500 gals, 7.5% NeFe acid			
11670' - 11678'		Acidz w/500 gals 7.5% morrowiacid w/24 ball sealers			
7820' - 7924'		Sqz hole in csg w/150 sx Premium Plus Class H			
9806' - 10183'		Acidz w/3000 gals 7.5% NeFe acid. Frac w/75,305# 18/40 VersiProp and 1275 bbls fluid			
28. PRODUCTION					
Date First Production 2/23/2007		Production Method (Flowing, gas lift, pumping - Size and type pump) Flowing		Well Status (Prod or Shut-in) Prod	
Date of Test See DHC-3914		Hours Tested		Choke Size	
Flow Tubing Press.		Casing Pressure		Calculated 24-Hour Rate	
29. Disposition of Gas (Sold, used for fuel, vented, etc.) Sold		Test Witnessed By			
30. List Attachments					
31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief					
Signature Kenneth Krawietz		Printed Name Kenneth Krawietz		Title District Engineer	
E-mail Address kkrawietz@samson.com				Date 8/2/2007	

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Salt	T. Strawn 10839	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates	T. Miss 12187	T. Cliff House	T. Leadville
T. 7 Rivers	T. Devonian	T. Menefee	T. Madison
T. Queen	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg	T. Montoya	T. Mancos	T. McCracken
T. San Andres	T. Simpson	T. Gallup	T. Ignacio Otzte
T. Glorieta	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T.
T. Blinebry	T. Gr. Wash	T. Morrison	T.
T. Tubb	T. Delaware Sand 4182	T. Todilto	T.
T. Drinkard	T. Bone Springs 5444	T. Entrada	T.
T. Abo	T. Morrow 11619	T. Wingate	T.
T. Wolfcamp 8913	T.	T. Chinle	T.
T. Penn	T.	T. Permian	T.
T. Cisco (Bough C)	T.	T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....

No. 2, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....

No. 2, from.....to.....feet.....

No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology