District J.
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

## State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 AUG 14 2007

Form C-144 June 1, 2004

June 1, 2004
For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

Pit or Below-Gra	ade Tank Registration or Closu	<u>re</u>
Is pit or below-grade tar.  Type of action: Registration of a pit	nk covered by a "general plan"? Yes No or below-grade tank Closure of a pit or below-gra	DAL de tank ⊠
	e: 432-687-1575 e-mail addre	ss: jlowery@eeronline.com
Pit	Below-grade tank	
Type: Drilling Production Disposal Workover Emergency Lined Unlined Line type: Synthetic Thickness 12 mil Clay Pit Volume: 11000 bbl	Volume:bbl Type of fluid:	
Depth to ground water (vertical distance from bottom of pit to seasonal high water elevation of ground water.)	Less than 50 feet 50 feet or more, but less than 100 feet 100 feet or more	(20 points) (10 points) XXX ( 0 points)
Wellhead protection area: (Less than 200 feet from a private domestic water source, or less than 1000 feet from all other water sources.)	Yes No	(20 points) ( 0 points) XXX
Distance to surface water: (horizontal distance to all wetlands, playas, irrigation canals, ditches, and perennial and ephemeral watercourses.)	Less than 200 feet 200 feet or more, but less than 1000 feet 1000 feet or more	(20 points) (10 points) ( 0 points) XXX
	Ranking Score (Total Points)	10 Points
If this is a pit closure: (1) Attach a diagram of the facility showing the pit' your are burying in place) onsite  offsite  for If offsite, name of facility_remediation start date and end date. (4) Groundwater encountered: No  offsite  for the soil sample results and a diagram of sample locations and excava  Additional Comments: Work Plan for the closure of drilling pit. The drill	Yes If yes, show depth below ground surface tions.	lescription of remedial action taken including ft. and attach sample results.
and lined with a 12 mil synthetic liner on former drilling pit site. Drilling	oit contents will then be emplaced into the encapsulation	on trench A 20 mil synthetic liner will
then be placed over the pit contents with a min of a 3" over lap of the under	rlying trench area. Then encapsulation trench will the	n be backfilled back to grade using a min of 3'
of clean soil and like material. A one call and 48 hr notice will be provided  1 week after permit approval.  If burial trench is to be constructed in pit area, samples are to be obtained and analyses submitted to OCD  PRIOR to lining trench.	· NO beg	OTIFY OCD 24 HOURS PRIOR to containing closure and 24 HOURS PRIOR obtaining samples. Samples are to be
Your certification and NMOCD approval of this application/closure does not otherwise endanger public health or the environment. Nor does it relieve to regulations.  Gerry Guye	obt my knowledge and belief. I turther certify obtes , a general permit , or an (attached) all subsets. Signature  Signature , of itability should the contents	ained from pit area and analyses omitted to OCD prior to back-filling.  of the pit or tank contaminate ground water or my other federal, state, or local laws and/or
Printed Name/Title Compliance Officer	Signature Olivery	Date: AUG 3 0 2007