ry.

AUG 1 4 2007

Form C-144

OCD-ARTESIA June 1, 2004

Energy Minerals and Natural Resources

District J 1625 N. French Dr., Hobbs, NM 88240 District II
1301 W. Grand Avenue, Artesia, NM 88210
District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

Oil Conservation Division 1220 South St. Francis Dr.

State of New Mexico

For drilling and production facilities, submit to appropriate NMOCD District Office. For downstream facilities, submit to Santa Fe office Santa Fe, NM 87505 Pit or Below-Grade Tank Registration or Closure

Is pit or below-grade tar Type of action: Registration of a pit	ik covered by a "general plan"? Yes [] No or below-grade tank [] Closure of a pit or below-gra	de tank M
		es: jlowery@eeronline.com
Address: 110 N. Marienfeld Suite 200 Midland, Tex	as 79701	ul me aue
Facility or well name: The Smith II #1 API#. County: Eddy Latitude	30-45-36303 U/Lor Qtr/Qtr M	Set 4 1115 R 348
	N32'49'48.1" Longitude W 10	NAD: 1927 [] 1983 PK
Surface Owner: Federal 🔲 State 🔀 Private 🗍 Indian 🗌		
Pit	Below-grade tank	
Type: Drilling Production Disposal		
Workover Emergency		
Lined 🗵 Unlined 🗌	Double-walled, with leak detection? Yes [] If no	t, explain why not.
Liner type: Synthetic Thickness 12 mil Clay		
Pit Volume: 11000 bbl		
Depth to ground water (vertical distance from bottom of pit to seasonal	Less than 50 feet	(20 points)
high water elevation of ground water.)	50 feet or more, but less than 100 feet	(10 points) XXX
Ings ween devalor of Fronting water.	100 feet or more	(0 points)
Wellhead protection area: (Less than 200 feet from a private domestic	Yes	(20 points)
water source, or less than 1000 feet from all other water sources.)	No	(0 points) XXX
WHICH BOULDES, OF ICES UISEL TOVO LESS MORE ALL MINES WAREL SOURCES,	Year than 200 Cart	(20 points)
Distance to surface water. (horizontal distance to all wetlands, playas,	Loss than 200 feet	
irrigation canals, ditches, and perennial and ephemeral watercourses.)	200 feet or more, but less than 1000 feet	(10 points)
	1000 feet or more	(0 points) XXX
	· · · · · · · · · · · · · · · · · · ·	
	Ranking Score (Total Points)	10 Points
your are burying in place) onsite 🔀 offsite 🔲 If offsite, name of facility_	s relationship to other equipment and tanks. (2) Indicates the control of the con	ate disposal location: (check the onsite box if
your are burying in place) onsite (2) offsite [] If offsite, name of facility_remediation start date and end date. (4) Groundwater encountered: No (2)	s relationship to other equipment and tanks. (2) Indicing the control of the cont	ate disposal location: (check the onsite box if
your are burying in place) onsite (2) offsite [] If offsite, name of facility_remediation start date and end date. (4) Groundwater encountered: No (2)	s relationship to other equipment and tanks. (2) Indicing the control of the cont	ate disposal location: (check the onsite box if escription of remedial setion taken including
your are burying in place) onsite (2) offsite [] If offsite, name of facility_remediation start date and end date. (4) Groundwater encountered: No (2)	s relationship to other equipment and tanks. (2) Indicates (3) Attach a general divisions.	ate disposal location: (check the onsite box if escription of remedial action taken includingft. and attach sample results.
your are burying in place) onsite (offsite If offsite, name of facility remediation start date and end date. (4) Groundwater encountered: No () Attach soil sample results and a diagram of sample locations and excava-	B relationship to other equipment and tanks. (2) Indicates the content of the contents will be mixed to stiffen the pit content.	ate disposal location: (check the onsite box if escription of remedial action taken includingft. and attach sample results.
your are burying in place) onsite. offsite I if offsite, name of facility remediation start date and end date. (4) Groundwater encountered: No in (5) Attach soil sample results and a diagram of sample locations and excavated Additional Comments: Work Plan for the closure of drilling pit. The drilling and lined with a 12 mil synthetic lines on former drilling pit site. Drilling at then be placed over the pit contents with a min of a 3" over lap of the under	s relationship to other equipment and tanks. (2) Indicates a general decrease of the second surface of the sec	ate disposal location: (check the onsite box if description of remedial action taken including fit and attach sample results. B. An encapsulation trench will be excavated on trench. A 20 mil synthetic liner will in be backfilled back to grade using a min of 3'
your are burying in place) onsite. offsite I If offsite, name of facility remediation start date and end date. (4) Groundwater encountered: No in the continuous start date and end date. (4) Groundwater encountered: No in the continuous start date and excavated Additional Comments: Work Plan for the closure of drilling pit. The drilling and lined with a 12 mil synthetic liner on former drilling pit site. Drilling pit then be placed over the pit contents with a min of a 3" over lap of the under of clean soil and like material. A one call and 48 hr notice will be provided.	s relationship to other equipment and tanks. (2) Indicates a general decrease of the part of the part content of contents will be mixed to stiffen the pit content of contents will then be emplaced into the encapsulation before pit closure as to the Oil Conservation Division before pit closure as	ate disposal location: (check the onsite box if description of remedial action taken including fit and attach sample results. B. An encapsulation trench will be excavated on trench. A 20 mil synthetic liner will in be backfilled back to grade using a min of 3'
your are burying in place) onsite. offsite I if offsite, name of facility remediation start date and end date. (4) Groundwater encountered: No in (5) Attach soil sample results and a diagram of sample locations and excavated Additional Comments: Work Plan for the closure of drilling pit. The drilling and lined with a 12 mil synthetic lines on former drilling pit site. Drilling at then be placed over the pit contents with a min of a 3" over lap of the under	is relationship to other equipment and tanks. (2) Indicated the content of the co	ate disposal location: (check the onsite box if description of remedial action taken including fit and attach sample results. B. An encapsulation trench will be excavated on trench. A 20 mil synthetic liner will in be backfilled back to grade using a min of 3'
your are burying in place) onsite. Offsite I If offsite, name of facility remediation start date and end date. (4) Groundwater encountered: No I (5) Attach soil sample results and a diagram of sample locations and excavate Additional Comments: Work Plan for the closure of drilling pit. The drilling and lined with a 12 mil synthetic liner on former drilling pit site. Drilling pit then be placed over the pit contents with a min of a 3" over lap of the under of clean soil and like material. A one call and 48 hr notice will be provided in pit area, samples are to be obtained and analyses submitted to OCD	B relationship to other equipment and tanks. (2) Indicated a general of the content of the contents will be mixed to stiffen the pit content of contents will then be emplaced into the encapsulation trench will then be emplaced into the encapsulation of the content of the contents will then be emplaced into the encapsulation of the contents will then be emplaced into the encapsulation of the contents will then be emplaced into the encapsulation of the contents will then be emplaced into the encapsulation of the contents o	ate disposal location: (check the onsite box if description of remedial action taken including fit and attach sample results. S. An encapsulation trench will be excavated on trench. A 20 mil synthetic liner will in be backfilled back to grade using a min of 3' extions begin. Pit closure actions will begin the above described pit or below-grade tank
your are burying in place) onsite. Offsite I if offsite, name of facility remediation start date and end date. (4) Groundwater encountered: No if (5) Attach soil sample results and a diagram of sample locations and excavate Additional Comments: Work Plan for the closure of drilling pit. The drilling and lined with a 12 mil synthetic liner on former drilling pit site. Drilling and lined with a 12 mil synthetic liner on former drilling pit site. Drilling and then be placed over the pit contents with a min of a 3" over lap of the under of clean soil and like material. A one call and 48 hr notice will be provided in pit area, samples are to be obtained and analyses submitted to OCD PRIOR to lining trench. I hereby certify that the information above is true and complete to the best	B relationship to other equipment and tanks. (2) Indicated a general of the content of the contents will be mixed to stiffen the pit content of contents will then be emplaced into the encapsulation trench will then be emplaced into the encapsulation of the content of the contents will then be emplaced into the encapsulation of the contents will then be emplaced into the encapsulation of the contents will then be emplaced into the encapsulation of the contents will then be emplaced into the encapsulation of the contents o	ate disposal location: (check the onsite box if description of remedial action taken including fit and attach sample results. S. An encapsulation trench will be excavated on trench. A 20 mil synthetic liner will in be backfilled back to grade using a min of 3' extions begin. Pit closure actions will begin the above described pit or below-grade tank
your are burying in place) onsite. Offsite I If offsite, name of facility remediation start date and end date. (4) Groundwater encountered: No I (5) Attach soil sample results and a diagram of sample locations and excavar Additional Comments: Work Plan for the closure of drilling pit. The drilling and lined with a 12 mil synthetic liner on former drilling pit site. Drilling pit then be placed over the pit contents with a min of a 3" over lap of the under of clean soil and like material. A one call and 48 hr notice will be provided in pit area, samples are to be obtained and analyses submitted to OCD PRIOR to lining trench. I hereby certify that the information above is true and complete to the best has been/will be constructed or closed according to NMOCD guidelines.	s relationship to other equipment and tanks. (2) Indicates a general decisions. (3) Attach a general decisions. (3) Attach a general decisions. (4) If yes, show depth below ground surface the pit content of the contents will be mixed to stiffen the pit content of the contents will then be emplaced into the encapsulation of the encapsulation trench will then the other of the contents will then be emplaced into the encapsulation of the encapsulation of the contents will then the other of the contents will be emplayed and analyses submitted to OCD prior to backfilling. (5) Indicate the contents will be mixed to stiffen the pit content of the contents will be emplaced into the encapsulation trench will then the other of the contents will be emplaced into the encapsulation of the contents will then be emplaced into the encapsulation trench will then the other of the contents will then the other of the contents will be emplaced into the encapsulation trench will then the other of the contents will be emplaced into the encapsulation trench will then the other of the contents will be emplaced into the encapsulation trench will then the other of the contents will be emplaced into the encapsulation trench will then the other of the contents will be emplaced into the encapsulation trench will then the other of the contents will be emplaced into the encapsulation trench will then the other of the contents will be emplaced into t	ate disposal location: (check the onsite box if description of remedial action taken including fit and attach sample results. S. An encapsulation trench will be excavated on trench. A 20 mil synthetic liner will in be backfilled back to grade using a min of 3' extions begin. Pit closure actions will begin the above described pit or below-grade tank
Additional Comments: Work Plan for the closure of drilling pit. The drilling and lined with a 12 mil synthetic liner on former drilling pit site. Drilling pit then be placed over the pit contents with a min of a 3" over lap of the under of clean soil and like material. A one call and 48 hr notice will be provided 1 week after permit approval. If burial trench is to be constructed in pit area, samples are to be obtained and analyses submitted to OCD PRIOR to lining trench. I hereby certify that the information above is true and complete to the best has been will be constructed or closed according to NMOCD guidelines.	B relationship to other equipment and tanks. (2) Indicated a general decisions. (3) Attach a general decision of hability shouls the contents of the contents will be mixed to stiffen the pit content of contents will then be emplaced into the energy ulation transh will then be emplaced into the energy ulation transh will then be offered into the energy ulation transh will then the Oil Conservation Division before pit closure and closure Samples are to be obtained from pit area and analyses submitted to OCD prior to backfilling. Signature Signature Signature for the operator of hability shouls the contents are the operator of hability shouls the contents.	ate disposal location: (check the onsite box if description of remedial section taken including fit and attach sample results. S. An encapsulation trench will be excavated on trench. A 20 mil synthetic liner will in be backfilled back to grade using a min of 3' extrons begin. Pit closure actions will begin the above-described pit or below-grade tank five OCD-approved plan.
your are burying in place) onsite. Offsite I if offsite, name of facility remediation start date and end date. (4) Groundwater encountered: No if (5) Attach soil sample results and a diagram of sample locations and excavariational Comments: Work Plan for the closure of drilling pit. The drilling and lined with a 12 mal synthetic liner on former drilling pit site. Drilling pit then be placed over the pit contents with a min of a 3" over large of the under of clean soil and like material. A one call and 48 hr notice will be provided in pit area, samples are to be obtained and analyses submitted to OCD PRIOR to lining trench. I hereby certify that the information above is true and complete to the best has been/will be constructed or closed according to NMOCD guideline. Printed Name/Title Colv. Cause Engineer Meyour certification and NMOCD approval of this application/closure does notherwise endanger public health or the environment. Nor does it relieve to regulations.	s relationship to other equipment and tanks. (2) Indicated a general of the content of the contents will be mixed to stiffen the pit content of contents will be mixed to stiffen the pit content of contents will then be emplaced into the energy-sulation of the contents will then be emplaced into the energy-sulation of the contents will then be emplaced into the energy-sulation of the contents will then be offered into the Oil Conservation Division before pit closure as and analyses submitted to OCD prior to backfilling. NOTIFY OCD 24 HOURS prior to sampling and closure and analyses submitted to OCD prior to backfilling. Of my knowledge and belief. I further certify that the contents of the co	ate disposal location: (check the onsite box if description of remedial action taken including fit and attach sample results. S. An encapsulation trench will be excavated on trench. A 20 mil synthetic liner will in be backfilled back to grade using a min of 3' etions begin. Pit closure actions will begin the above described pit or below-grade tank have OCD-approved plan . Of the pit or tank contaminate ground water or my other federal, state, or local laws and/or
your are burying in place) onsite. Offsite If offsite, name of facility remediation start date and end date. (4) Groundwater encountered: No If (5) Attach soil sample results and a diagram of sample locations and excavate Additional Comments: Work Plan for the closure of drilling pit. The drilling and lined with a 12 mil synthetic liner on former drilling pit site. Drilling pit then be placed over the pit contents with a min of a 3" over lap of the under of clean soil and like material. A one call and 48 hr notice will be provided in pit area, samples are to be obtained and analyses submitted to OCD PRIOR to lining trench. I hereby certify that the information above is true and complete to the best has been/will be constructed or closed according to NMOCD guideline. Date: Printed Name/Title Color approval of this application/closure does notherwise endanger public health or the environment. Nor does it relieve to	B relationship to other equipment and tanks. (2) Indicated a general decisions. (3) Attach a general decision of hability shouls the contents of the contents will be mixed to stiffen the pit content of contents will then be emplaced into the energy ulation transh will then be emplaced into the energy ulation transh will then be offered into the energy ulation transh will then the Oil Conservation Division before pit closure and closure Samples are to be obtained from pit area and analyses submitted to OCD prior to backfilling. Signature Signature Signature for the operator of hability shouls the contents are the operator of hability shouls the contents.	ate disposal location: (check the onsite box if description of remedial action taken including fit and attach sample results. S. An encapsulation trench will be excavated on trench. A 20 mil synthetic liner will in be backfilled back to grade using a mm of 3 retions begin. Pit closure actions will begin the above-described pit or below-grade tank five OCD-approved plan.