<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Avenue, Artesia, NM 88210 District III

1000 Rio Brazos Road, Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

submitted to OCD prior to back-filling.



## State of New Mexico **Energy Minerals and Natural Resources**

For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

Form C-144

June 1, 2004

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Pit or Belo	w-Grade	Tank R	egistration	or Closure

	rade tank covered by a "general plan"? Yes 1 a of a pit or below-grade tank 1 Closure of a pit or below			
Operator: MEWBOULNE Oil Company	OCD-ARTESIA			
Address: 701 S. CERIL HOLAS NIM 882UD				
Facility or well name: WESSON 33 PED #/	API#: 30-015-35366 U/L or Qtr/Qtr_	P Sec 33 T 195 R 29E		
County: END4	Latitude N32°36'44. 9 Longitude W	104°04'27.8' NAD: 1927 🗆 1983 🗆		
Surface Owner: Federal 🔀 State 🗌 Private 🔲 Indian 🗍	•			
Pit	Below-grade tank	Below-grade tank		
Type: Drilling 🔀 Production 🗌 Disposal 🗍	Volume:bbl Type of fluid:	Volume:bbl Type of fluid:		
Workover ☐ Emergency ☐	Construction material:	Construction material:		
Lined 🔀 Unlined 🗌	Double-walled, with leak detection? Yes	Double-walled, with leak detection? Yes If not, explain why not.		
Liner type: Synthetic 🔀 Thickness 12 mil Clay 🗌				
Pit Volume 5000 bbl				
	Less than 50 feet	(20 points) Horabale Dry 127		
Depth to ground water (vertical distance from bottom of pit to so	50 feet or more, but less than 100 feet	(10 points)		
high water elevation of ground water.)	100 feet or more	( 0 points) 50 +0 60		
	Yes	(20 points)		
Wellhead protection area: (Less than 200 feet from a private do	mestic No.	( 0 points)		
water source, or less than 1000 feet from all other water sources.	)			
Distance to surface water: (horizontal distance to all wetlands, p	Less than 200 feet	(20 points)		
irrigation canals, ditches, and perennial and ephemeral watercou	200 feet or more, but less than 1000 feet irses.)	(10 points)		
	1000 feet or more	( 0 points)		
	Ranking Score (Total Points)	10		
If this is a pit closure: (1) Attach a diagram of the facility showi	ng the pit's relationship to other equipment and tanks. (2)	Indicate disposal location: (check the onsite box if		
your are burying in place) onsite 🛛 offsite 🗌 If offsite, name of				
remediation start date and end date. (4) Groundwater encountered				
(5) Attach soil sample results and a diagram of sample locations a		it and attent surpre results.		
()*) () ()	be EXCAUATED from the Pit	Man Silvill be tedan		
	Emors further Remediation			
	E dug à Cines with A impereu			
	BE PLACED ON FOR AND ENCL	apsulated Pit Will		
THEN BE. BACKFILLED AND	contoured with 3'et so	IL CASABLE OF		
Supporting NATIVE Plant GA	powth AND PREJENT EROSION	v and fonding of PANWAGE		
I hereby certify that the information above is true and complete	to the best of my knowledge and belief. I further certify the	hat the above-described pit or below-grade tank		
has been/will be constructed or closed according to NMOCE	guidelines [], a general permit [], or an (attached) alt	ternative OCD-approved plan .		
Date: 10-19-07 _ 10 \ \		)		
Printed Name/Title JEFF CAINES / AGET	W Signature	/		
Your certification and NMOCD approval of this application/clo		tents of the nit or tank contaminate around water or		
otherwise endanger public health or the environment. Nor does regulations.				
	11			
NOTIEV OCD 14 HOURS DRYON	Signed By Mily B	KAMMER OCT 3 0 2007		
NOTIFY OCD 24 HOURS PRIOR to beginning closure and 24 HOURS PRIOR	Signature	Date:		
to obtaining samples. Samples are to be	urial trench is to be constructed it area, samples are to be obtained			
	analyses submitted to OCD			

PRIOR to lining trench.

## Mewbourne Oil Company PO Box 5270 Hobbs, NM 88240 (505) 393-5905

August 15, 2007

New Mexico OCD Attn: Mike Bratcher 1301 West Gande Ave. Artesia, NM 88210

Re: Wesson "33" Federal # 1

On August 13, 2007 a borehole was drilled on an offset location 10742' South and West of the above mentioned location to a depth of 72' (As per verbal agreement with Mike Bratcher this borehole was in sufficient proximity to prove to the NMOCD that ground water on the above mentioned location does or does not exist at 70'). No water was encountered during the drilling of the borehole. The depth of 72' was reached at 11:00 am 8/13/07. The borehole was then left exposed to atmospheric conditions for 24 hrs and tested with a bailer. No water was recovered with the bailer to a depth of 70'. Ron Harvey w/ NMOCD witnessed the testing of the borehole. Given this information Mewbourne Oil Company is requesting to deep bury the reserve contents on location. The deep bury pit would be no greater than 20' deep and would comply with all NMOCD rules and regulations.

Sincerely,

Robin Terrell