Form 3160-5 (September 2001)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

JAN 03 2008

FORM APPROVED OMB No 1004-0135

Expires January 31, 2004

SUNDRY NOTICES AND REPORTS ON WELLS OCD-ART COMA		5 Lease Serial No. LC-049945 (B)
abandoned well. Use Form 3160-3 (APD) for such p	proposals.	6 If Indian, Allottee or Tribe Name
SUBMIT IN TRIPLICATE - Other instruction  1 Type of Well	ns on reverse side	7 If Unit or CA/Agreement, Name and/or No.
X Oil Well Gas Well Other		8. Well Name and No
2 Name of Operator Yates Drilling Company		Parakeet 29 Federal #1
	ne No (include area code)	30-015-35140
105 S. 4th Str., Artesia, NM 88210	505-748-8663	10. Field and Pool, or Exploratory Area
4 Location of Well (Footage, Sec., T, R, M, OR Survey Description)		Wildcat San Andres  11 County or Parish, State
1535' FSL & 662' FEL Section 29-	-19S-27E	Eddy, NM
12. CHECK APPROPRIATE BOX(ES) TO INDIC	CATE NATURE OF NOTICE, R	EPORT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	
Notice of Intent    Subsequent Report   Casing Repair	Fracture Treat  New Construction  Plug and Abandon  Temporarily  Plug Back  estimated starting date of any proposed work and ations and measured and true vertical depths of all file with BLM/BIA Required subsequent reports sompletion or recompletion in a new interval, a For aquirements, including reclamation, have been con	Abandon  Perf, Acidize, Frac  approximate duration thereof pertinent markers and zones shall be filed within 30 days m 3160-4 shall be filed once
14 I hereby certify that the foregoing is true and correct Name (Printed/Typed) Karen J. Leishman  Signature  Karen J. Leishman	Title Operations Tech  Date 12/21/2007	
THIS SPACE FOR FEDERAL OR STATE OFFICE USE		
Approved by	Title	Date
Conditions of approval, if any, are attached Approval of this notice does not vicertry that the applicant holds legal or equitable title to those rights in the subwhich would entitle the applicant to condition operations thereon.	bject lease Office	
Title 18 U S.C. Section 1001 and Title 43 U.S.C Section 1212, make it a crime f	ior any person knowingly and willbully to ma	ke to any department or agency of the United

Accepted for record - NMOCD

1/1/108

Sundry Attachment Parakeet "29" Federal #1 1535' FSL & 662' FEL Section 29-19S-27E Eddy County, NM 30-015-35140

2-22-2007 2-23-2007	RIH and set RBP @ 1601'. Perforated .36", 3 SPF as follows: .1448', 1460', 1476', 1483', 1492', 1510', 1521', 1528', 1533', 1547', 1554', 1573', 1580', 1590' (total 42 holes). Set packer @1350'. Swabbed well. Acidized 1448' – 1590' with 5000 gals 10% HCL acid with 90 ball
3-2-2007	sealers. Frac'd with 12,012 gals Aqua Frac, 1000 for pad, 53,500 gals Aqua Frac, 1000 treating fluid, 30,000 gals cut brine water with 7123# LiteProp 125C 14/30, 9890# Siber Prop 16/30 sand, 45,000# 20/40 brown sand. Set RBP @ 1420'.Perforated .36", 3 SPF as follows: 1213', 1222', 1248', 1264', 1276', 1312', 1324', 1346', 1362', 1370', 1380', 1398', 1409' (total 39 holes). Acidized 1213'-1409' with 4500 gals 10% HCL acid. Frac'd 1213'-1409' with 12,020 gals Aqua Frac 1000 for pad, 53,500 gals Aqua Frac 1000 treating fluid and 30,000 gals cut brine. Used 8000# Lit Prop 125 14/30 53,000# 20/40 brown sand, 11,250# 16/30 Siber Prop. Flowed well back.
5-18-2007	Set CIBP at 1270'. RIH and set retainer at 1185'.
5-19-2007	Pumped 100 sxs Class "C" + 4/10% FL-52 + 1% CaCl2. Tailed in with 250 sxs Class "C" with loose CaCl2 (wt 14.8, yld 1.32).
5-23-2007 9-27-2007	Drilled cement to CIBP at 1270'. Tagged RBP at 1601'.  RIH and set 5 ½" composite plug at 1200'. Perforated .39" holes, as follows:  842' (1 SPF)  852' (1 SPF)  862' (1 SPF)  930' (1 SPF)  937' (4 SPF)  951' (1 SPF)  957' (1 SPF)  966' (2 SPF)  985' (1 SPF)  1003' (2 SPF)  1003' (2 SPF)  1053' (4 SPF)  1060' (1 SPF)  1076' (4 SPF)  1076' (4 SPF)  1076' (4 SPF)  1077' (1 SPF)
9-28-2007	Acidized perfs 842' – 1107' with 2500 gals 7.5% HCL acid with 50 ball sealers.
9-29-2007	Frac'd with 19,000# Lite Prop 125C 14/30 and 1000# 20/40 sand with
11-10-2007	79,715 gals treating fluid brine water. Set CIBP at 974' and set cement retainer at 814'. Pumped 100 sxs Class "H" cement with 2% CaCl (yld 1.06, wt 16.5). Tailed in with 200 sxs Class "C" Neat with 2% CaCl.
11-14-2007	Drilled cement and tagged CIBP at 974'. Drilled out CIBP and cleaned hole to 1200'. Tagged composite plug and drilled plug. Tagged PBTD at 1731'. Returned well to production.  Note: Perfs open from 985' – 1675', 121 holes, size .39".