

Submit 3 Copies To Appropriate District Office  
District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
1301 W. Grand Ave., Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
May 27, 2004

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

FEB 28 2008

OCD-ARTESIA



WELL API NO.

30-015-25044

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name  
ATOKA SAN ANDRES UNIT

8. Well Number

159

9. OGRID Number

6137

10. Pool name or Wildcat

ATOKA SAN ANDRES

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator

DEVON ENERGY PRODUCTION COMPANY, LP

3. Address of Operator

20 North Broadway, Ste 1500, Oklahoma City, OK 73102

405-552-4615

4. Well Location

Unit Letter C : 125' feet from the NORTH line and 1665' feet from the WEST line  
Section 14 Township 18S Range 26E NMPM County Eddy

11. Elevation (Show whether DR, RKB, RT, GR, etc.)  
3332' KB; 3320' GL

Pit or Below-grade Tank Application ☐ or Closure ☐

Pit type \_\_\_\_\_ Depth to Groundwater \_\_\_\_\_ Distance from nearest fresh water well \_\_\_\_\_ Distance from nearest surface water \_\_\_\_\_

Pit Liner Thickness: \_\_\_\_\_ mil Below-Grade Tank: Volume \_\_\_\_\_ bbls; Construction Material \_\_\_\_\_

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☒  
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

- 2/14/08--MIRU. TIH & circulated wellbore w/10 ppg mud.
- Spot 25 Sx cement (247') in 5-1/2" production casing on top of CIBP @ 1,574'.
- Spot 25 Sx cement (247') @ 1,043'. Tagged TOC @ 790'. (8-5/8" casing shoe @ 943').
- Circulated 25 Sx cement (247') for surface plug.
- 2/15/08--wellbore plugged out.
- 2/25/08--wellhead cut off. Dry hole marker set. Well plugged & abandoned.

Approved for plugging of well bore only.  
Liability under bond is retained pending receipt  
of C-103 (Subsequent Report of Well Plugging)  
which may be found at OCD Web Page under  
Forms. [www.emnrd.state.nm.us/oed](http://www.emnrd.state.nm.us/oed).

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE Ronnie Slack TITLE Engineering Technician DATE 2/25/08

Type or print name Ronnie Slack E-mail address: Ronnie.Slack@dvn.com Telephone No. 405-552-4615  
For State Use Only

APPROVED BY: [Signature] TITLE Comdr DATE 2/28/08  
Conditions of Approval (if any):

**DEVON ENERGY PRODUCTION COMPANY LP**

Well Name: ATOKA SAN ANDRES UNIT #159		Field: ATOKA SAN ANDRES	
Location: 125' FNL & 1665' FWL; SEC 14-T18S-R26E		County: EDDY	State: NM
Elevation: 3332' KB; 3320' GL		Spud Date: 1/18/85	Compl Date: 2/3/85
API#: 30-015-25044	Prepared by: Ronnie Slack	Date: 2/25/08	Rev:

**PLUGGED & ABANDONED**  
2/25/08

Cut wellhead off. Dry hole marker set. (2/25/08)  
Wellbore plugged out. (2/15/08)  
Circulated 25 Sx cement for surface plug

10 ppg mud

12-1/4" Hole  
8-5/8", 24#, K55, @ 943'  
Cmt'd w/650 Sx to surface

Tagged TOC at 790' (2/15/08)  
Spot 25 Sx cement @ 1,043'. (2/15/08)

8/8-8/15/88--Repaired casing leak between 1184' - 1470'.  
Sqzd w/100 Sx. Swab test w/no entry.  
12/30/88--tested casing to 1000 psi. Ok.  
4/28/05--MIT test-Ok.

10 ppg mud

MIRU for PA (2/14/08)  
Circulated hole w/10# mud (2/15/08)

Spot 25 Sx cement (247') on CIBP @ 1,574' (2/15/08)

**SAN ANDRES**

1,517' - 1,616' (added 8/7/97) sqzd 1517-1765 200 sx 8/19/97  
1,640' - 1,650' original perfs sqzd, reperfed 11/4/97 open  
1,643' - 1,650' (added 8/7/97) sqzd-8/19/97  
1,659' - 1,661' original perfs sqzd-8/19/97  
1,660' - 1,765' (added 8/7/97) sqzd-8/19/97  
8/11/97- fraced perfs 1517'-1765'

CIBP @ 1,574' (4/28/05)

Homco Casing Patch from 1638'-1668' (8/7/97)

CIBP @ 1,673' (11/4/97)

1835' PBDT

7-7/8" Hole  
5-1/2", 15.5#, K55, @ 1,879'  
Cmt'd w/330 Sx. Circulated to surface.

1,879' TD