Form 3160-5 (August 2007)

UNITED STATES DEPARTMENT OF THE INTERIOR

OCD-ARTESIA

FORM APPROVED OMB No 1004-0137

DL	Ex	tpites. July 31, 2010				
				5 Lease Serial No See attached		
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.				6 If Indian, Allottee or Tribe Name		
SUBMIT IN TRIPLICATE – Other Instructions on page 2.				7. If Unit of CA/Agreement, Name and/or No		
I. Type of Well Oil Well Gas V	Vell Other	.IIIN 2 4 2008		8 Well Name and No. See attached		
2 Name of Operator Marbob Energy Corporation			ž	9 API Well No See attached 3	0 015 36361	
3a. Address P O Box 227, Artesia, NM 88211-0227		3b. Phone No. (include area co 575-748-3303	ode)	10. Field and Pool or E See attached		
4 Location of Well (Footage, Sec, T, See attached	R ,M , or Survey Description,)		11 Country or Parish, See attached	State	
12 CHEC	CK THE APPROPRIATE BO	X(ES) TO INDICATE NATUR	E OF NOTIC	E, REPORT OR OTHE	ER DATA	
TYPE OF SUBMISSION	TYPE OF ACTION					
Notice of Intent	Acidize Alter Casing	Deepen Fracture Treat	_	uction (Start/Resume) amation	Water Shut-Off Well Integrity	
Subsequent Report	Casing Repair Change Plans	New Construction Plug and Abandon	_	mplete oorarily Abandon	Other Replacement Page	
Final Abandonment Notice	Convert to Injection	Plug Back	☐ Wate	r Dısposal		
13 Describe Proposed or Completed Of the proposal is to deepen directions. Attach the Bond under which the way following completion of the involvesting has been completed. Final determined that the site is ready for Marbob Energy respectfully request of cement does not circulate on surface 1" pipe will be fund.	ally or recomplete horizontally ork will be performed or proved operations. If the operation Abandonment Notices must be final inspection.	y, give subsurface locations and vide the Bond No. on file with I on results in a multiple completion filed only after all requirement statement to be added to the	measured an BLM/BIA. R on or recompl ts, including	nd true vertical depths of equired subsequent repoletion in a new interval, reclamation, have been ogram on the attacher	all pertinent markers and zones orts must be filed within 30 days a Form 3160-4 must be filed once completed and the operator has	

14 I hereby certify that the foregoing is true and correct Name (Printed/Typed)		
Nancy T. Agnew T _{1t}	le Land Department	
Signature Dancy T. Acnew Da	te 06/16/2008	APPROVED
THIS SPACE FOR FEDERA	L OR STATE OFFIC	E USE
Approved by	Title	JUN 21 aus
Conditions of approval, if any, are attached Approval of this notice does not warrant or certificate that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.	Office	WESLEY W. INGRAM PETROLEUM ENGINEER

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

Attachment for Marbob Sundry dated 6/16/08

Well Name and #	API#	Lease #	Location	Field and Pool
Loco Federal #6	30-015-36164	NMNM 106231	1800' FNL & 2310' FEL, Sec 21, T17S - R30E, Eddy County, NM	Loco Hills; Glorieta-Yeso
Birdie Federal #10	30-015-36371	NMNM 074936	1650' FNL & 530' FEL, Section 17, T17S - R30E, Eddy County, NM	Loco Hills; Glorieta-Yeso
Thunder Road Federal #8	30-015-36280	NMLC0029342E	1675' FNL & 2310' FEL, Sec 20, T17S - R30E, Eddy County, NM	Loco Hills; Glorieta-Yeso
Randy Federal #6	30-015-36361	NMLC 29020E	1750' FNL & 2310' FEL, Sec 22, T17S -R30E, Eddy County, NM	Loco Hills; Glorieta-Yeso
Randy Federal #7	30-015-36264	NMLC 29020E	1800' FNL & 990' FEL, Sec 22, T17S - R30, Eddy County, NM	Loco Hills; Glorieta-Yeso

1

.

Randy Federal #6 API 30-015-36361 June 21, 2008 Conditions of Approval

For the surface casing: If cement does not circulate to the surface, the appropriate BLM office shall be notified and a tag with 1" will be performed at four positions 90 degrees apart to verify cement depth. BLM Petroleum Engineer Technician to witness tags. If depth is greater than 100' or water is standing in the annulus, remedial cementing will be done. If no water and TOC tag is less than 100', when 100% excess cement of the annulus volume was run on the primary job, ready-mix can be used to bring cement to surface.

WWI 062108