

Submit 3 Copies to Appropriate District Office

State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103 Revised 1-1-89

DISTRICT I P.O. Box 1980, Hobbs, NM 88240

DISTRICT II P.O. Drawer DD, Artesia, NM 88210

DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION 2040 Pacheco St. Santa Fe, NM 87505

AUG 1 2008 OCD-ARTESIA

WELL API NO. 30-015-24748
Indicate Type of Lease STATE X FEE
State Oil & Gas Lease No. L-4861
Lease Name or Unit Agreement Name Avalon (Delaware) Unit
Well No. 464
Pool name or Wildcat Avalon Delaware 3715
Well Location: Unit Letter P : 660 Feet From The South Line and 660 Feet From The East Line
Section 36 Township 20S Range 27E NMPM Eddy County
Elevation (Show whether DF, RKB, RT, GR, etc.) 3326.7'

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

Type of Well: OIL WELL X GAS WELL OTHER

Name of Operator ExxonMobil Corporation Attn: Meadows, RM PO53 Tiffany Stebbins

Address of Operator Po Box 4358 Houston, Texas 77210-4358

Well Location: Unit Letter P : 660 Feet From The South Line and 660 Feet From The East Line
Section 36 Township 20S Range 27E NMPM Eddy County

Elevation (Show whether DF, RKB, RT, GR, etc.) 3326.7'

11 Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK [] PLUG AND ABANDON []
TEMPORARILY ABANDON [] CHANGE PLANS []
PULL OR ALTER CASING []
OTHER: []

REMEDIAL WORK [] ALTERING CASING []
COMMENCE DRILLING OPNS. [] PLUG AND ANBANDONMENT X
CASING TEST AND CEMENT JOB []
OTHER: []

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

06-17-08 MIRUWSU. NUBOP. NOTIFIED PHIL HAWKINS OF OCD OF RIG UP.
06-18-08 TAG CIBP AT 4282'. MIX 40 SKS SALT WATER CLAY WITH 100 BBL 10# BRINE. TESTED CSG TO 600 PSI. SPOT 25 SKS C NEAT CEMENT FROM 4282-4036. LD 8 JTS. STAND BACK 20 STANDS. WOC PLUG. TAG TOC AT 4084'. PUH TO 2715. SPOT 45 SKS C NEAT CEMENT FROM 2715-2271. PUH AND WOC PLUG OVER NIGHT.
06-19-08 TAG TOP OF CEMENT AT 2255'. PUH AND CIRCULATE WELL FROM 708' TO SURFACE WITH 80 SKS OF CLASS C NEAT CEMENT. L/D TBG. REFILL CSG. RDMOWSU.

Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms. www.emurd.state.nm.us/oed.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Chris Luther TITLE worker or Tech DATE 06-30-08
TYPE OR PRINT NAME Chris Luther TELEPHONE NO 804-215-0813

(This space for State Use)
APPROVED BY Garry Guye TITLE Compliance Officer DATE AUG 1 - 2008
CONDITIONS OF APPROVAL, IF ANY