

District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505



WELL API NO. 30-015-36384
5. Indicate Type of Lease STATE [X] FEE []
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name RDX "16"
8. Well Number 3
9. OGRID Number 246289
10. Pool name or Wildcat Brushy Draw - Delaware East
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3,082' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)
1. Type of Well: Oil Well [X] Gas Well [] Other []
2. Name of Operator RKI Exploration and Production, LLC.
3. Address of Operator 3817 NW Expressway, Suite 950, Oklahoma City, OK. 73112
4. Well Location Unit Letter : 990' feet from the South line and 990' feet from the East line
Section 16 Township 26S Range 30E NMPM Eddy County
Pit or Below-grade Tank Application [] or Closure []
Pit type Depth to Groundwater Distance from nearest fresh water well Distance from nearest surface water
Pit Liner Thickness: mil Below-Grade Tank: Volume bbls; Construction Material

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:
PERFORM REMEDIAL WORK [] PLUG AND ABANDON []
TEMPORARILY ABANDON [] CHANGE PLANS []
PULL OR ALTER CASING [] MULTIPLE COMPL []
OTHER: []
SUBSEQUENT REPORT OF:
REMEDIAL WORK [] ALTERING CASING []
COMMENCE DRILLING OPNS. [] P AND A []
CASING/CEMENT JOB [X]
OTHER: []

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

DRILLED 11" HOLE TO 3564'. RAN 8-5/8", 32#, J-55, ST&C, CASING. SHOE @ 3561'. FLOAT COLLAR @ 3516'. CIRCULATE CEMENT W/ SCHLUMBERGER, 20 BBL SPACER 1225 SX 35-65 POZ: CLASS "C" + 5% D44 (BWOW) + 6% D20 + 2 PPS D42 + 0.125 PPS D130 DENSITY 12.6, YIELD 2.05, TAIL 200 SX CLASS "C" + 1% S1 + 0.125 PPS D130. DENSITY 14.8, YIELD 1.33 DISPLACE W/ FRESH WATER. BUMP PLUG W/ 500 PSI OVER 1420, FLOAT HELD, CIRC 145 SX CEMENT TO SURFACE. WAIT ON CEMENT. CUT OFF 13 5/8" HEAD, WELD ON 11" 3M X 8 5/8" SOW HEAD AND TEST @ 1000 PSI. NIPPLE UP BOPE. TEST BOPS ANNULAR @ 1500 PSI. DRILL CEMENT AND FLOAT COLLAR TEST CASING @ 1000 PSI AND FINISH DRILLING CEMENT. DRILLED OUT SHOE 28.5 HOURS AFTER CEMENT IN PLACE.

ACCEPTED FOR RECORD

AUG 12 2008

I hereby certify that the information above is true and complete to the best of my knowledge and belief, and that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines [], a general permit [] or an attached approved plan [].

SIGNATURE Gene Simer TITLE SUPERINTENDENT DATE 8/11/08

Type or print name GENE SIMER E-mail address: gsimer@rkixp.com Telephone No. 505-885-1313

For State Use Only

APPROVED BY: TITLE DATE

Conditions of Approval (if any):