

S

OCD-ARTESIA

Form 3160-5
(June 1990)UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENTAUG 27 2008
OCD-ARTESIAFORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT-" for such proposals

SUBMIT IN TRIPLICATE

1 Type of Well

☐

Oil

Well

☐

Gas

Well

☐

Other

2 Name of Operator

CHI OPERATING, INC.

3 Address and Telephone No.

P.O. BOX 1799 MIDLAND, TEXAS 79702

4 Location of Well (Footage, T, R, M, or Survey Description)

SHL 2475' FNL & 2310' FWL, Sec.12-19S-30E
BHL 1980' FSL & 1980' FWL, Sec.12-19S-30E

12 CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☒

Notice of Intent

☐

Subsequent Report

☐

Final Abandonment Notice

TYPE OF ACTION

☐

Abandonment

☐

Recompletion

☒

Plugging Back

☐

Casing Repair

☐

Altering Casing

☐

Other

☐

Change of Plans

☐

New Construction

☐

Non-Routine Fracturing

☐

Water Shut-Off

☐

Conversion to Injection

☐

Dispose Water

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Chi Operating, is planning to Plugback to Yates Sand on this well. Plugback procedure is attached.

APPROVED

AUG 24 2008

JAMES A. AMOS
SUPERVISOR-EPG

14 I hereby certify that the foregoing is true and correct

Signed

ROBIN ASKEW

Title

REGULATORY CLERK

Date

8/07/08

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any

Title 18 U. S. C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

FOR RECORDS ONLY

Chi Operating, Inc.
Plugback to Yates Sand
Munchkin Federal #7
Eddy County, New Mexico
API # 30-015-33933

Location: SHL-2475' FNL & 2310' FWL, Section 12 -19S-30E
BHL-1980 FSL & 1980 FWL, Section 12-19S-30E

SUPERVISORY PERSONNEL:

	<u>Office</u>	<u>Home</u>	<u>Mobile</u>
Gary Womack	432-685-5001	432-682-5315	432-634-8958
Sonny Mann	432-365-2722	432-365-2722	432-634-7062

CURRENT WELLBORE:

KB	14'	
Surf Csg:	@ 526'	9-5/8", 36#, J-55 cmt surf
Intermediate	@ 5500'	5-1/2", 15.5# J55 cmt surf

Prod Tbg:	2 7/8"-6.5#-N-80 - 8rd.	ID: 2.441"	Drift: 2.347"
Capacity:	.0058 bbl/ft		
Capacity annulus:	.0152 bbl/ft		

Existing Perfs: **4993-5000' 2SPF-60 deg. Delaware**

Procedure: Plugback to Yates Sand

MIRU DDP. NUBOP (screw on -2000#.)

POOH w/production string.

RU WL. Set CIBP at 4975'. Dump 35' cement on top.

TIH w/4" gun . Correlate to Schlumberger *Measured Depth* log and perforate selected intervals:

Yates Sand : 2478-2486 4 SPF-60 deg. .

Spot 7.5% NEFE acid across perfs. Acidize w/750 gals pumped at 4-6 BPM dropping ballsealers for Recover load and test. Evaluate for further stimulation.