


30-015-05976

Form 8-580



LOCATE WELL CORRECTLY

RECEIVED

SEP 26 1963

SEP 26 1963

UNITED STATES

DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYBudget Bureau No. 42-03554
Approval expires 12-31-63

U. S. LAND OFFICE

SERIAL NUMBER LC - 661581

LEASE OR PERMIT TO PROSPECT

RECEIVED
SEP 23 1963
U. S. GEOLOGICAL SURVEY
ALBUQUERQUE, NEW MEXICO

LOG OF OIL OR GAS WELL

Company Gulf Oil Corporation Address P. O. Box 900, Kermit, Texas
 Lessor or Tract Federal Section 14 Field Brushy Draw State New Mexico
 Well No. 2 Sec. 14 T. 26S R. 23E Meridian 10N County El Paso
 Location 1900 ft. S. of 14 Line and 660 ft. E. of 14 Line of Section 14 Elevation 2904
 (Correct flow relative to sea level)
 The information given herewith is a complete and correct record of the well and all work done thereon
 so far as can be determined from all available records
 Signed W. W. WHITAKER
 Date September 23, 1963 Title Area Engineer

The summary on this page is for the condition of the well at above date
 Commenced drilling July 27, 1963. Finished drilling July 31, 1963.

OIL OR GAS SANDS OR ZONES

(Denote gas by G)

No. 1, from _____ to _____ No. 4, from _____ to _____
 No. 2, from _____ to _____ No. 5, from _____ to _____
 No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

No. 1, from _____ to _____ No. 3, from _____ to _____
 No. 2, from _____ to _____ No. 4, from _____ to _____

CASING RECORD

Size casing	Weight per foot	Threads per inch	Make	Amount	Kind of shoe	Cut and pulled from	Perforated		Purpose
							From	To	
2-5/8	35	8	1-55	360	ROCK	ROCK			
4-1/2	95	8	1-55	377	Leathin	380			

MUDDING AND CEMENTING RECORD

Size casing	Where set	Number sacks of cement	Method used	Mud gravity	Amount of mud used
2-5/8	380	150	PLP		
4-1/2	3190	140	PLP		

PLUGS AND ADAPTERS

Heaving plug—Material _____ Length _____ Depth set _____
 Adapters—Material _____ Size _____

SHOOTING RECORD

Size	BH&I used	Explosive used	Quantity	Date	Depth shot	Depth cleaned out

TOOLS USED

Rotary tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet
 Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet

DATES

Put to producing 100 September 22, 1963
 The production for the first 24 hours was _____ barrels of fluid of which _____ % was oil; _____ %
 emulsion; _____ % water; and _____ % sediment Gravity, °Bé. _____
 If gas well, cu. ft. per 24 hours _____ Gallons gasoline per 1,000 cu. ft. of gas _____
 Rock pressure, lbs. per sq. in. _____

EMPLOYEES

Driller _____ Driller _____
 Driller _____ Driller _____

FORMATION RECORD

FROM	TO	TOTAL FEET	FORMATION
0	14	14	Kelly Drive Boring
14	314	301	Surface Sand
315	1390	1075	Dolomite & Anhydrite
1390	3103	1713	Salt & Anhydrite
3103	3148	45	Black Lime and Shale
3148	3190	42	Sand
			Tape from Electric Log:
			Delaware Lime 3103
			Delaware Sand 3148
FROM	TO	TOTAL FEET	FORMATION

26-1

16-43094-2 U S GOVERNMENT PRINTING OFFICE

16-43094-2 U S GOVERNMENT PRINTING OFFICE

16-43094-2 U S GOVERNMENT PRINTING OFFICE

16-43094-2 U S GOVERNMENT PRINTING OFFICE

16-43094-2 U S GOVERNMENT PRINTING OFFICE

16-43094-2 U S GOVERNMENT PRINTING OFFICE