Form 3160-5 (February 2005)

## **UNITED STATES** DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

OCD-ARTESIA

FORM APPROVED OMB No 1004-0137

Expires March 31, 2007

	DOTAL OF BITTE WITH THE BITTE
S	SUNDRY NOTICES AND REPORTS ON WELLS
	not use this form for proposals to drill or to re-enter a
	andoned well. Use Form 3160-3 (APD) for such proposa

5 Lease Serial No NM-100558 20965 6 If Indian, Allottee or Tribe Name

a andoned well.	Use Form 3160-3 (A				
SUBM	IT IN TRIPLICATE Othe	7. If Unit of CA/Agre	7. If Unit of CA/Agreement, Name and/or No		
1. Type of Well  ☑ Oil Well ☐ Gas V	Well Other	OCT 06 2008		8 Well Name and No. RDX "17" # 1	
2 Name of Operator RKI Exploration	on & Production	ocd-ariesia	9. API Well No.	9. API Well No. 30-015-36504	
3a Address 3817 NW Express Oklahoma City, Ok		3b Phone No (include area code) 405-949-2221	i	10. Field and Pool or Exploratory Area Brushy Draw - Delaware	
	\$ 990' FEL Sec. 17 T26S - R30E		Eddy	11. Country or Parish, State Eddy Co. New Mexico	
TYPE OF SUBMISSION	CK THE APPROPRIATE B	OX(ES) TO INDICATE NATURE C	OF ACTION	HER DATA	
Notice of Intent	Acidize Alter Casing	Deepen Fracture Treat	Production (Start/Resume) Reclamation	☐ Water Shut-Off ☐ Well Integrity	
Subsequent Report	Casing Repair Change Plans	New Construction Plug and Abandon	Recomplete Temporarily Abandon	Other Spud & Set surface casing	
Final Abandonment Notice	Convert to Injection	Plug Back	Water Disposal		
the proposal is to deepen direction	nally or recomplete horizonta	ertinent details, including estimated stally, give subsurface locations and me	asured and true vertical depths		

following completion of the involved operations If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection )

RIG UP AND SPUD IN 9-11-2008. DRILLED 17-1/2" HOLE TO 775'. RAN 13-3/8", 68#, J-55, ST&C and 13-3/8", 68#, J55 LT&C CASING. LANDED CASING WITH SHOE @ 768', FLOAT COLLAR @ 725'. CEMENT W/ SCHLUMBERGER PUMPED 20 BBL GEL FLUSH, LEAD: 450 SX 35:65 POZ / C PLUS 6% D20 + 0.125 PPS D130 + 3% S1 + 3 PPS D42, DENSITY: 12.7, YIELD: 1.96, H2O 10.34 GAL/SX, TAIL: 200 SX CLASS "C" + 2% S1 + 0.125 PPS D130, DENSITY 14.8 YIELD 1.34 H20 6.29 GAL/SX, DISPLACED W/ 109.5 BBLS FW, BUMPED PLUG W/ 691 PSI, FLOAT HELD. CIRC 151 SX CEMENT TO SURFACE.

DRILLED OUT SHOE 23.25 HOURS AFTER CEMENT IN PLACE.

ACCEPTED FOR RECORD

OCT 7 2008

Gerry Guye, Deputy Field Inspector NMOCD-District II ARTESIA

14 I hereby certify that the foregoing is true and correct Name (Printed/Typed)  Gene Simer  Title		e Production Superintendent				
Signature Simu Date  THIS SPACE FOR FEDERAL			ACCEPTED FOR RECORD			
TINO OF AGE FOR FEBRUARE		TATE OF THE GOL			+	
Approved by	Title			SEP 3 0 2008		
Conditions of approval, if any, are attached Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon			PE	WESLEY W. INGRAM TROLEUM FNGINEE	J R	

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction