## Form 3160-5 (August 2007)...

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

OCT 072008

FORM APPROVED OMB NO. 1004-0135 Expires: July 31, 2010

y	
	5

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.

Lease Serial No.
NMLC064894A

6. If Indian, Allottee or Tribe Name

SUBMIT IN TRIPLICATE - Other instructions on reverse side.					7. If Unit or CA/Agreement, Name and/or No		
1. Type of Well ☐ Gas Well ☐ Other					8. Well Name and No. PLU PIERCE CANYON 17 FEDERAL 1		
Name of Operator Contact: LINDA GOOD     CHESAPEAKE OPERATING, INC. E-Mail: linda.good@chk.com					9. API Well No. 30-015-36635-00-X1		
3a. Address 3b. Phone No. (inc Ph: 405-767-42				)	10. Field and Pool, or I WILDCAT	Exploratory	
OKLAHOMA CITY, OK 73154-0496							
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)  Sec 17 T25S R30E SESE 350FSL 350FEL					11. County or Parish, and State EDDY COUNTY, NM		
12. CHECK APP	ROPRIATE BOX(ES) TO	) INDICATE	NATURE OF	NOTICE, R	EPORT, OR OTHER	R DATA	
TYPE OF SUBMISSION			Maria da Santa Angular ya manana				
☐ Notice of Intent	☐ Acidize	□ Dee	oen ACCEPTI	ED FOR BI	GGRan/Resume)	☐ Water Shut-Off	
Subsequent Report	☐ Alter Casing	_	ture Treat	□ Reclam		☐ Well Integrity	
Final Abandonment Notice	☐ Casing Repair☐ Change Plans	□ New	Construction and Abandon CT	8_ 72000	plete	Other Drilling Operations	
Titlal Abandonment Notice	Convert to Injection		and Abandor Temporarily Abandon Drilling Operati				
following completion of the involved testing has been completed. Final Al determined that the site is ready for f SPUD AND SET SURFACE OF 9/29/2008 SET CONDUCTO TOO'. WO HALLIBURTON CE 9/30/2008 CEMENT 13 3/8" 1.35 YIELD. WOC TO RUN TO SURVEY SHOWED TOP OF TAGGED @ 54'. PULLED 1" OUT OF HOLE 1" PLUGGED SAFETY MEETING. RAN 1" I 1.35 @ 2 BBL/MIN. CIRC 9 B	pandonment Notices shall be fil inal inspection.) CASING:  R @ 40'. SPUDDED @ 6 MENT TRUCK.  CSG, LEAD CMT 100 SX TEMP SURVEY 7 HRS. R CMT @ 240'. RD TEMP OUT OF HOLE. 1" PIPE F W/CMT. NOTIFIED BLM N THE HOLE. HOOKED I	S:00 AM. RUN S:00 AM. RUN SS 14.2 PPG RIGGED UP & SURVEY. PU PLUG W/CMT REP. KENT UP CEMENT	requiréments, inclu N 17 JTS 13 3/8 1.65 YIELD, TA RUN TEMP SL I/MU 1" HYDRIL T. RAN BACK II CAFFAL, GAVE ERS & PUMPEI	" 48# H-40 \$ IL IN W/725 JRVEY. TAO N THE HOLE THE OK TO D 21 BBL 87	STC CSG, SET @  SXS 14.8 PPG GGED @ 650'. TEM I 1" PIPE IN THE BA E. TAGGED @ 54'. P O DO TOP JOB. COI	and the operator has  P CKSIDE ULLED NDUCTED	
14 Thereby certify that the foregoing is	true and correct. Electronic Submission # For CHESAPEAI mmitted to AFMSS for proc	KE OPERATIN	G, INC., sent to	the Carlsbac	l <sup>*</sup>		
Name (Printed/Typed) LINDA GOOD			Title REGULATORY COMPLIANCE SPEC.				
Signature (Electronic Submission)			Date 10/02/2008				
	THIS SPACE FO	OR FEDERA	L OR STATE	OFFICE U	SE		
Approved By ACCEPTED			JAMES A TitleSUPERV			Date 10/05/20	
Conditions of approval, if any, are attached Approval of this notice does not warrant o certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.			Office Carlsba			2008	
Title 18 U.S.C. Section 1001 and Title 43 States any false, fictitious or fraudulent	U.S.C. Section 1212, make it a statements or representations as	a crime for any p s to any matter w	erson knowingly ar	nd willfully to n	nake to any department or	agency of the United	

## Additional data for EC transaction #63512 that would not fit on the form

## 32. Additional remarks, continued

CASING. WELD ON 13 3/8" 3000 PSI WELLHEAD.

10/1/2008 WELD ON 13 3/8" X 3000 PSI & TEST TO 500 PSI TEST OK. NIPPLE UP SPACER SPOOL, MUD CROSS, 2" & 4" VALVES, 13 3/8" X 3000 PSI HYDRIL, CHOKE MANIFOLD. TEST HYDRIL, MUD CROSS VALES, CHOKE MANIFOLD, TO 250 LOW & 2000 HI.
NIPPLE UP SPACER SPOOL, ROTATING HEAD BOWL & FLOWLINE. REMOVED CMT FROM FLOWLINE @ SHALE SHAKER MANIFOLD. PU/MU BHA. SERVICE RIG. TRIP IN THE HOLE W/ BIT #2 TAGGED CMT @ 637'. TEST CASING @ 1200 PSI FOR 30 MINUTES - TEST OK. DRILL CMT @ FLOAT EQUIPMENT. WOB 3-5 ROTARY RPM 40 MOTOR RPM 65 PP 650 @ 112 SPM 411 GPM. WOC 24+ HRS PRIOR TO DRILL OUT. 500 PSI IN 7 HOURS.

(CHK PN 621390)