

OCD-ARTESIA

ATS -09-12

EA-09-209

JAN 05 2009

OCD-ARTESIA

Form 3160-3
(April 2004)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

APPLICATION FOR PERMIT TO DRILL OR REENTER

FORM APPROVED
OMB No. 1004-0137
Expires March 31, 2007

5. Lease Serial No.

NM-97874

6. If Indian, Allottee or Tribe Name

7. If Unit or CA Agreement, Name and No.

Pending

8. Lease Name and Well No.

Conoco 22 Federal Com No. 4

9. API Well No

30-015- 36868

10. Field and Pool, or Exploratory

County Line Tank; Abo

11. Sec., T. R. M. or Blk. and Survey or Area

22-16S-29E

12. County or Parish

Eddy

13. State

NM

1a. Type of Work: ☒ DRILL☐ REENTER1b. Type of Well: ☒ Oil Well ☐ Gas Well ☐ Other☒ Single Zone ☐ Multiple Zone

2. Name of Operator

Cirtex Energy Co. of Colorado

3a. Address

PO Box 140907, Irving, TX 75014

3b. Phone No. (include area code)

972-401-3111

4. Location of Well (Report location clearly and in accordance with any State requirements. *)

At Surface 375 FNL & 330 FEL

At proposed prod. Zone 375 FNL & 330 FWL

Roswell Controlled Water Basin

Horizontal Abo test

14. Distance in miles and direction from nearest town or post office*

15. Distance from proposed*

location to nearest
property or lease line, ft
(Also to nearest drig. unit line if
any)

330'

16. No of acres in lease

E0-0134-0007 120 acres

NM-97874 1491.18 acres

17. Spacing Unit dedicated to this well

N2N2 160 acres

18. Distance from proposed location*

to nearest well, drilling, completed,
applied for, on this lease, ft.

N/A

19. Proposed Depth

Pilot Hole 7500'

MD 11718'

TVD 7260'

20. BLM/BIA Bond No. on File

NM-2575

21. Elevations (Show whether DF, KDB, RT, GL, etc.)

3684' GR

22. Approximate date work will start*

12.15.08

23. Estimated duration

25-35 days

24. Attachments

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, shall be attached to this form.

1. Well plat certified by a registered surveyor
2. A Drilling Plan
3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO shall be filed with the appropriate Forest Service Office).

4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above).
5. Operator Certification
6. Such other site specific information and/or plans as may be required by the authorized officer

25. Signature

Title

Regulatory Analyst

Name (Printed/Typed)

Natalie Krueger

Date

10.03.08

Approved By (Signature) /s/ Don Peterson

Name (Printed/Typed)

/s/ Don Peterson

Date

DEC 19 2008

Title

FIELD MANAGER

Office

CARLSBAD FIELD OFFICE

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious, or fraudulent statements or representations as to any matter within its jurisdiction.

* (Instructions on page 2)

SEE ATTACHED FOR
CONDITIONS OF APPROVAL

ENTERED
1-6-09

APPROVAL SUBJECT TO
GENERAL REQUIREMENTS
AND SPECIAL STIPULATIONS
ATTACHED

DISTRICT I
1625 N. French Dr., Hobbs, NM 88240
DISTRICT II
1301 W. Grand Avenue, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

DISTRICT IV
1220 S. St. Francis Dr., Santa Fe, NM 87506

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-102
Revised October 12, 2005

Submit to Appropriate District Office

State Lease - 4 Copies
Fee Lease - 3 Copies

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, New Mexico 87505

☐ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

| | | |
|-----------------------------------|--|---|
| API Number 30-015-36868 | Pool Code 97197 | Pool Name County Line Tank; Abo |
| Property Code 36783 | Property Name CONOCO "22" FEDERAL COM | Well Number 4 |
| OGRID No. 162683 | Operator Name CIMAREX ENERGY CO. OF COLORADO | Elevation 3684' |

Surface Location


| UL or lot No. | Section | Township | Range | Lot Idn | Feet from the | North/South line | Feet from the | East/West line | County |
|---------------|-----------|-------------|-------------|---------|---------------|------------------|---------------|----------------|-------------|
| A | 22 | 16 S | 29 E | | 375 | NORTH | 330 | EAST | EDDY |

Bottom Hole Location If Different From Surface



| UL or lot No. | Section | Township | Range | Lot Idn | Feet from the | North/South line | Feet from the | East/West line | County |
|---------------|-----------|-------------|-------------|---------|---------------|------------------|---------------|----------------|-------------|
| D | 22 | 16 S | 29 E | | 375 | NORTH | 330 | WEST | EDDY |

| | | | |
|-------------------------------|-----------------|--------------------------------|-----------|
| Dedicated Acres 160 | Joint or Infill | Consolidation Code P | Order No. |
|-------------------------------|-----------------|--------------------------------|-----------|

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED
OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

| | |
|--|--|
|  | <p>OPERATOR CERTIFICATION</p> <p>I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.</p> <p><i>Natalie Krueger</i> 10-03-08 Signature Date</p> <p>Natalie Krueger Printed Name</p> <p>SURVEYOR CERTIFICATION</p> <p>I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.</p> <p>JULY 19, 2008 Date Surveyed</p> <p><i>Gary L. Jones</i> Signature</p> <p><i>GARY L. JONES</i> Professional Surveyor</p> <p>Certificate No. Gary L. Jones 7977</p> <p>BASIN SURVEYS</p> |
|--|--|

SECTION 22, TOWNSHIP 16 SOUTH, RANGE 29 EAST, N.M.P.M.,
EDDY COUNTY, NEW MEXICO.



Directions to Location:

FROM THE JUNCTION OF HWY 82 AND BARNIVAL
DRAW, GO NORTH ON BARNIVAL DRAW FOR APPROX
6.5 MILES TO LEASE ROAD, ON LEASE ROAD GO NO
EASTERLY FOR 1.2 MILES TO LEASE ROAD, ON LEASE
ROAD GO SOUTHERLY TO PROPOSED LEASE ROAD.

CIMAREX ENERGY CO. OF COLORADO

REF: CONOCO "22" FEDERAL COM #4 / WELL PAD TOPO

THE CONOCO "22" FEDERAL COM #4 LOCATED 375'
FROM THE NORTH LINE AND 330' FROM THE EAST LINE OF
SECTION 22, TOWNSHIP 16 SOUTH, RANGE 29 EAST,
N.M.P.M., EDDY COUNTY, NEW MEXICO.

BASIN SURVEYS P.O. BOX 1786 - HOBBS, NEW MEXICO

W.O. Number: 20080


Drawn By: J. SMALL


Date: 07-21-2008

Disk: JMS 20080

Survey Date: 07-19-2008

Sheet 1 of 1 Sheets





CONOCO "22" FEDERAL COM #4
 Located 375' FNL and 330' FEL
 Section 22, Township 16 South, Range 29 East,
 N.M.P.M., Eddy County, New Mexico.

basin
surveys
 focused on excellence
 in the oilfield

P.O. Box 1786
 1120 N. West County Rd.
 Hobbs, New Mexico 88241
 (505) 393-7316 - Office
 (505) 392-3074 - Fax
 basinsurveys.com

W.O. Number: JMS 20080


Survey Date: 07-19-2008

Scale: 1" = 2 MILES

Date: 07-20-2008

CIMAREX
ENERGY CO.
OF COLORADO

Exhibit B



CONOCO "22" FEDERAL COM #4
 Located 375' FNL and 330' FEL
 Section 22, Township 16 South, Range 29 East,
 N.M.P.M., Eddy County, New Mexico.



focused on excellence
 in the oilfield

P.O. Box 1786
 1120 N. West County Rd.
 Hobbs, New Mexico 88241
 (505) 393-7316 - Office
 (505) 392-3074 - Fax
 basinsurveys.com

W.O. Number JMS 20080

Survey Date: 07-19-2008

Scale: 1" = 2000'

Date: 07-21-2008

CIMAREX
ENERGY CO.
OF COLORADO

Exhibit C

Application to Drill
Conoco 22 Federal Com No. 4
 Cimarex Energy Co. of Colorado
 Unit A, Section 22
 T16S-R29E, Eddy County, NM

In response to questions asked under Section II B of Bulletin NTL-6, the following information is provided for your consideration:

1. Location: SHL 375 FNL & 330 FEL
BHL 375 FNL & 330 FWL
2. Elevation above sea level: 3,684' GR
3. Geologic name of surface formation: Quaternary Alluvium Deposits
4. Drilling tools and associated equipment: Conventional rotary drilling rig using fluid as a circulating medium for solids removal.
5. Proposed drilling depth: Pilot Hole 7500' MD 11718' TVD 7260'
6. Estimated tops of geological markers:
 San Andres 1,820'
 Abo Shale 5,340'
 Lower Abo Dolomite 6,870'
 Wolfcamp LS 6,910'
7. Possible mineral bearing formation:
 Abo Oil

8. Proposed Mud Circulating System:

| Depth | | | Mud Wt | Visc | Fluid Loss | Type Mud |
|-----------|----|--------|-----------|-------|---------------|-------------|
| 0' | to | 430' | 8.4 - 8.6 | 28 | NC | FW |
| 430' | to | 2650' | 10.0 | 30-32 | NC | Brine water |
| 2650' | to | 7500' | 8.4 - 9.5 | 30-32 | NC | FW, brine |
| KOP 7000' | to | 7297' | 9.0 | 28-32 | May lose circ | 2% KCl |
| 7297' | to | 11718' | 9.0 | 28-32 | May lose circ | 2% KCl |

Sufficient mud materials will be kept on location at all times in order to combat lost circulation or unexpected kicks. In order to run DSTs, open hole logs, and casing, the viscosity and water loss may have to be adjusted in order to meet these needs.

Proposed drilling Plan

Drill 8¾" hole to 7500' (pilot hole) and cement (see page 2 - Application to Drill). Set whipstock plug @ 7010.' Mill window from 6995' to 7005.' Kick off 6½" lateral @ 7000.' Drill 6½" hole to MD 11718' and TVD 7260.' Install 4½" **Peak Completion Assembly.** Liner will be BTC from Liner Hanger @ 6893' to EOC @ 7297' and LTC from EOC @ 7297' to TD @ 11718.' Peak liner will not require cement, but seal will be tested. Lateral length: 4609.' Liner length: 4825.'

Application to Drill
Conoco 22 Federal Com No. 4
 Cimarex Energy Co. of Colorado
 Unit A, Section 22
 T16S-R29E, Eddy County, NM

9. Casing & Cementing Program:

see
CDA

| String | Hole Size | Depth | Type | Casing OD | Casing ID | Weight | Grade | Thread | Collar |
|--------------------------------------|-----------|-------------------|------|-----------|-----------|--------|-------|--------|--------|
| Surface | 17½" | 0 to 430' | New | 13⅝" | 12.715# | 48# | H-40 | 8-R | STC |
| Intermediate | 12¼" | 0 to 2,650' | New | 9⅝" | 8.835# | 40# | J-55 | 8-R | LTC |
| Pilot Hole | 8¾" | 0 to 7,500' | New | 7" | 6.276# | 26# | P-110 | 8-R | LTC |
| Lateral (liner hgr to EOC) | 6⅝" | 6,893' to 7,297' | New | 4½" | 4" | 11.6# | P-110 | 8-R | BTC |
| Lateral (EOC to TD) | 6⅝" | 7,297' to 11,718' | New | 4½" | 4" | 11.6# | P-110 | 8-R | LTC |

10. Cementing:

Surface Lead: 300 sx Thixotropic/Premium Plus + 10# Gilsontite + 10# Cal-Seal + 1% CaCl₂ + 0.125# Poly-e-flake (wt 14.2, yld 1.64)
Tail: 220 sk Premium Plus + 2% CaCl₂ (wt 14.8, yld 1.35)

TOC Surface

Intermediate Lead: 415 sx Interfill C + 0.125# Poly-e-flake (wt 11.9, yld 2.45)

Tail: 215 sx Premium Plus + 1% CaCl₂ (wt 14.8, yld 1.33)

TOC Surface

Pilot Hole Lead: 550 sx Interfill H SBM + 0.1% HR-7 + 1# Pheno-seal (wt 11.5, yld 2.77)

Tail: 475 sx Permian Basin Super H SBM + 0.5% Halad-344 + 0.25% D-AIR 3000 + 0.4% CFR-3 w/o defoamer + 1# Salt + 3# Pheno-seal + 0.35% HR-7 (wt 13.2, yld 1.62)

TOC 2450'

Lateral No cement needed. Peak completion assembly.

Fresh water zones will be protected by setting 13⅝" casing at 430' and cementing to surface. Hydrocarbon zones will be protected by setting 9⅝" casing at 2650' and cementing to surface, and by setting 7" casing at 7500' and cementing to 2450.'

| | | |
|------------------------|---------------------|-----------------------|
| <u>Collapse Factor</u> | <u>Burst Factor</u> | <u>Tension Factor</u> |
| 1.125 | 1.125 | 1.6 |

11. Pressure control Equipment:

Exhibit "E". A 13⅝" 5000 PSI working pressure B.O.P. consisting of one set of blind rams and one set of pipe rams and a 5000# annular type preventer. A choke manifold and 120 gallon accumulator with floor and remote operating stations and auxiliary power system. Rotating head below 6000.' A kelly cock will be installed and maintained in operable condition and a drill string safety valve in the open position will be available on the rig floor.

BOP unit will be hydraulically operated. BOP will be nipped up and operated at least once a day while drilling and the blind rams will be operated when out of hole during trips. No abnormal pressure or temperature is expected while drilling. From the base of the surface pipe through the running of production casing, the well will be equipped with a 5000 psi BOP system.

see
CDA

We are requesting a variance for testing the 13⅝" surface casing from Onshore Order No. 2, which states that all casing strings below the conductor shall be pressure tested to 0.22 psi per foot or 1500 psi, whichever is greater, but not to exceed 70% of the manufacturer's stated maximum internal yield. We are requesting to test the 13⅝" casing to 1000 psi using rig pumps. The BOP will be tested to 3000 psi by an independent service company.

Application to Drill
Conoco 22 Federal Com No. 4
Cimarex Energy Co. of Colorado
Unit A, Section 22
T16S-R29E, Eddy County, NM

12. Testing, Logging and Coring Program:

- A. Mud logging program: 2 man unit from 2650' to TD
- B. Electric logging program: CNL / LDT / CAL / GR, DLL / CAL / GR
- C. No DSTs or cores are planned at this time.

Abo well

13. Potential Hazards:

No abnormal pressures or temperatures are expected. In accordance with Onshore Order 6, Cimarex does not anticipate that there will be enough H₂S from the surface to the Strawn formations to meet the BLM's minimum requirements for the submission of an "H₂S Drilling Operation Plan" or "Public Protection Plan" for the drilling and completion of this well. Since we have an H₂S Safety package on all wells, attached is an "H₂S Drilling Operations Plan." Adequate flare lines will be installed off the mud / gas separator where gas may be flared safely. All personnel will be familiar with all aspects of safe operation of equipment being used.

Estimated BHP **2300 psi** Estimated BHT **110°**

14. Road and location construction will begin after BLM approval of APD. Anticipated spud date as soon as approved.

Drilling expected to take 25-35 days

If production casing is run an additional 30 days will be required to complete and construct surface facilities.

15. Other Facets of Operations:

After running casing, cased hole gamma ray neutron collar logs will be run from total depth over possible pay intervals.

Abo pay will be perforated and stimulated.

The proposed well will be tested and potentialized as **an oil well.**

Patterson Rig 80

Cimarex Energy Co. of Colorado




Exhibit D – Rig Layout
Conoco 22 Federal Com No. 4
Cimarex Energy Co. of Colorado
22-16S-29E
SHL 375 FNL & 330 FEL
BHL 375 FNL & 330 FWL
Eddy County, NM

SR & A




Exhibit E – 5000# BOP Diagram
Conoco 22 Federal Com No. 4
 Cimarex Energy Co. of Colorado
 22-16S-29E
 SHL 375 FNL & 330 FEL
 BHL 375 FNL & 330 FWL
 Eddy County, NM

**DRILLING OPERATIONS
CHOKE MANIFOLD
SM SERVICE**




Exhibit E-1 – Choke Manifold Diagram
Conoco 22 Federal Com No. 4
 Cimarex Energy Co. of Colorado
 22-16S-29E
 SHL 375 FNL & 330 FEL
 BHL 375 FNL & 330 FWL
 Eddy County, NM



Planned Wellpath Report

Preliminary

Page 1 of 4



INTEQ

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--------------------------------|----------|------------|
| Operator | Cimarex Energy Co. of Colorado | Slot | No. 4H SHL |
| Area | Eddy County, NM | Well | No. 4H |
| Field | (Conoco)Sec. 22 T16S R29E | Wellbore | No. 4H PWB |
| Facility | Conoco 22 Fed Com No. 4H | | |

REPORT SETUP INFORMATION

| | | | |
|---------------------|--|----------------------|---------------------------|
| Projection System | NAD83 / TM New Mexico State Planes, Eastern Zone (3001), US feet | Software System | WellArchitect® 2.0 |
| North Reference | Grid | User | Victor Hernandez |
| Scale | 0.999917 | Report Generated | 7/30/2008 at 10:21:46 AM |
| Convergence at slot | 0.15° East | Database/Source file | WA_Midland/No. 4H_PWB.xml |

WELLPATH LOCATION

| | Local coordinates | | Grid coordinates | | Geographic coordinates | |
|-----------------------|-------------------|----------|------------------|----------------|------------------------|-----------------|
| | North[ft] | East[ft] | Easting[USft] | Northing[USft] | Latitude | Longitude |
| Slot Location | 0.00 | 0.00 | 626703.70 | 696139.20 | 32°54'48.213"N | 104°03'18.559"W |
| Facility Reference Pt | | | 626703.70 | 696139.20 | 32°54'48.213"N | 104°03'18.559"W |
| Field Reference Pt | | | 626718.00 | 691891.00 | 32°54'06.177"N | 104°03'18.523"W |

WELLPATH DATUM

| | | | |
|--------------------------|------------------------|---|-------------------|
| Calculation method | Minimum curvature | Rig on No. 4H SHL (RT) to Facility Vertical Datum | 18.00ft |
| Horizontal Reference Pt | Facility Center | Rig on No. 4H SHL (RT) to Mean Sea Level | 3702.00ft |
| Vertical Reference Pt | Rig on No. 4H SHL (RT) | Facility Vertical Datum to Mud Line (Facility) | 0.00ft |
| MD Reference Pt | Rig on No. 4H SHL (RT) | Section Origin | N 0.00, E 0.00 ft |
| Field Vertical Reference | Mean Sea Level | Section Azimuth | 269.88° |



Planned Wellpath Report

Preliminary

Page 2 of 4



INTEQ

| REFERENCE WELLPATH IDENTIFICATION | | | |
|-----------------------------------|--------------------------------|----------|------------|
| Operator | Cimarex Energy Co. of Colorado | Slot | No. 4H SHL |
| Area | Eddy County, NM | Well | No. 4H |
| Field | (Conoco)Sec. 22 T16S R29E | Wellbore | No. 4H PWB |
| Facility | Conoco 22 Fed Com No. 4H | | |

| WELLPATH DATA (51 stations) † = interpolated/extrapolated station | | | | | | | | |
|---|--------------------|----------------|-------------|-------------------|---------------|--------------|------------------|----------|
| MD [ft] | Inclination [°] | Azimuth [°] | TVD [ft] | Vert Sect [ft] | North [ft] | East [ft] | DLS [°/100ft] | Comments |
| 0.00 | 0.000 | 269.875 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | Tie On |
| 7000.00 | 0.000 | 269.875 | 7000.00 | 0.00 | 0.00 | 0.00 | 0.00 | KOP |
| 7100.00† | 30.000 | 269.875 | 7095.49 | 25.59 | -0.06 | -25.59 | 30.00 | |
| 7200.00† | 60.000 | 269.875 | 7165.40 | 95.49 | -0.21 | -95.49 | 30.00 | |
| 7297.02† | 89.105 | 269.875 | 7190.96 | 188.00 | -0.41 | -188.00 | 30.00 | EOC |
| 7300.00† | 89.105 | 269.875 | 7191.01 | 190.99 | -0.42 | -190.99 | 0.00 | |
| 7400.00† | 89.105 | 269.875 | 7192.57 | 290.97 | -0.63 | -290.97 | 0.00 | |
| 7500.00† | 89.105 | 269.875 | 7194.13 | 390.96 | -0.85 | -390.96 | 0.00 | |
| 7600.00† | 89.105 | 269.875 | 7195.69 | 490.95 | -1.07 | -490.95 | 0.00 | |
| 7700.00† | 89.105 | 269.875 | 7197.26 | 590.94 | -1.29 | -590.94 | 0.00 | |
| 7800.00† | 89.105 | 269.875 | 7198.82 | 690.92 | -1.50 | -690.92 | 0.00 | |
| 7900.00† | 89.105 | 269.875 | 7200.38 | 790.91 | -1.72 | -790.91 | 0.00 | |
| 8000.00† | 89.105 | 269.875 | 7201.94 | 890.90 | -1.94 | -890.90 | 0.00 | |
| 8100.00† | 89.105 | 269.875 | 7203.50 | 990.89 | -2.16 | -990.89 | 0.00 | |
| 8200.00† | 89.105 | 269.875 | 7205.06 | 1090.88 | -2.37 | -1090.87 | 0.00 | |
| 8300.00† | 89.105 | 269.875 | 7206.62 | 1190.86 | -2.59 | -1190.86 | 0.00 | |
| 8400.00† | 89.105 | 269.875 | 7208.19 | 1290.85 | -2.81 | -1290.85 | 0.00 | |
| 8500.00† | 89.105 | 269.875 | 7209.75 | 1390.84 | -3.03 | -1390.84 | 0.00 | |
| 8600.00† | 89.105 | 269.875 | 7211.31 | 1490.83 | -3.24 | -1490.82 | 0.00 | |
| 8700.00† | 89.105 | 269.875 | 7212.87 | 1590.81 | -3.46 | -1590.81 | 0.00 | |
| 8800.00† | 89.105 | 269.875 | 7214.43 | 1690.80 | -3.68 | -1690.80 | 0.00 | |
| 8900.00† | 89.105 | 269.875 | 7215.99 | 1790.79 | -3.90 | -1790.79 | 0.00 | |
| 9000.00† | 89.105 | 269.875 | 7217.56 | 1890.78 | -4.11 | -1890.77 | 0.00 | |
| 9100.00† | 89.105 | 269.875 | 7219.12 | 1990.77 | -4.33 | -1990.76 | 0.00 | |
| 9200.00† | 89.105 | 269.875 | 7220.68 | 2090.75 | -4.55 | -2090.75 | 0.00 | |
| 9300.00† | 89.105 | 269.875 | 7222.24 | 2190.74 | -4.77 | -2190.74 | 0.00 | |
| 9400.00† | 89.105 | 269.875 | 7223.80 | 2290.73 | -4.98 | -2290.72 | 0.00 | |
| 9500.00† | 89.105 | 269.875 | 7225.36 | 2390.72 | -5.20 | -2390.71 | 0.00 | |
| 9600.00† | 89.105 | 269.875 | 7226.93 | 2490.71 | -5.42 | -2490.70 | 0.00 | |
| 9700.00† | 89.105 | 269.875 | 7228.49 | 2590.69 | -5.64 | -2590.69 | 0.00 | |



Planned Wellpath Report

Preliminary

Page 3 of 4



INTEQ

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--------------------------------|----------|------------|
| Operator | Cimarex Energy Co. of Colorado | Slot | No. 4H SHL |
| Area | Eddy County, NM | Well | No. 4H |
| Field | (Conoco)Sec. 22 T16S R29E | Wellbore | No. 4H PWB |
| Facility | Conoco 22 Fed Com No. 4H | | |

WELLPATH DATA (51 stations) † = interpolated/extrapolated station

| MD [ft] | Inclination [°] | Azimuth [°] | TVD [ft] | Vert Sect [ft] | North [ft] | East [ft] | DLS [°/100ft] | Comments |
|------------|--------------------|----------------|-------------|-------------------|---------------|--------------|------------------|------------|
| 9800.00† | 89.105 | 269.875 | 7230.05 | 2690.68 | -5.85 | -2690.67 | 0.00 | |
| 9900.00† | 89.105 | 269.875 | 7231.61 | 2790.67 | -6.07 | -2790.66 | 0.00 | |
| 10000.00† | 89.105 | 269.875 | 7233.17 | 2890.66 | -6.29 | -2890.65 | 0.00 | |
| 10100.00† | 89.105 | 269.875 | 7234.73 | 2990.64 | -6.51 | -2990.64 | 0.00 | |
| 10200.00† | 89.105 | 269.875 | 7236.29 | 3090.63 | -6.72 | -3090.62 | 0.00 | |
| 10300.00† | 89.105 | 269.875 | 7237.86 | 3190.62 | -6.94 | -3190.61 | 0.00 | |
| 10400.00† | 89.105 | 269.875 | 7239.42 | 3290.61 | -7.16 | -3290.60 | 0.00 | |
| 10500.00† | 89.105 | 269.875 | 7240.98 | 3390.60 | -7.38 | -3390.59 | 0.00 | |
| 10600.00† | 89.105 | 269.875 | 7242.54 | 3490.58 | -7.59 | -3490.58 | 0.00 | |
| 10700.00† | 89.105 | 269.875 | 7244.10 | 3590.57 | -7.81 | -3590.56 | 0.00 | |
| 10800.00† | 89.105 | 269.875 | 7245.66 | 3690.56 | -8.03 | -3690.55 | 0.00 | |
| 10900.00† | 89.105 | 269.875 | 7247.23 | 3790.55 | -8.25 | -3790.54 | 0.00 | |
| 11000.00† | 89.105 | 269.875 | 7248.79 | 3890.53 | -8.46 | -3890.53 | 0.00 | |
| 11100.00† | 89.105 | 269.875 | 7250.35 | 3990.52 | -8.68 | -3990.51 | 0.00 | |
| 11200.00† | 89.105 | 269.875 | 7251.91 | 4090.51 | -8.90 | -4090.50 | 0.00 | |
| 11300.00† | 89.105 | 269.875 | 7253.47 | 4190.50 | -9.12 | -4190.49 | 0.00 | |
| 11400.00† | 89.105 | 269.875 | 7255.03 | 4290.49 | -9.33 | -4290.48 | 0.00 | |
| 11500.00† | 89.105 | 269.875 | 7256.59 | 4390.47 | -9.55 | -4390.46 | 0.00 | |
| 11600.00† | 89.105 | 269.875 | 7258.16 | 4490.46 | -9.77 | -4490.45 | 0.00 | |
| 11700.00† | 89.105 | 269.875 | 7259.72 | 4590.45 | -9.99 | -4590.44 | 0.00 | |
| 11718.06 | 89.105 | 269.875 | 7260.00† | 4608.51 | -10.02 | -4608.50 | 0.00 | No. 4H BHL |



Planned Wellpath Report

Preliminary

Page 4 of 4



INTEQ

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--------------------------------|----------|------------|
| Operator | Cimarex Energy Co. of Colorado | Slot | No. 4H SHL |
| Area | Eddy County, NM | Well | No. 4H |
| Field | (Conoco)Sec. 22 T16S R29E | Wellbore | No. 4H PWB |
| Facility | Conoco 22 Fed Com No. 4H | | |

TARGETS

| Name | MD [ft] | TVD [ft] | North [ft] | East [ft] | Grid East [srv ft] | Grid North [srv ft] | Latitude | Longitude | Shape |
|---------------|------------|-------------|---------------|--------------|-----------------------|------------------------|----------------|-----------------|-------|
| 1) No. 4H BHL | 11718.06 | 7260.00 | -10.02 | -4608.50 | 622095.59 | 696129.18 | 32°54'48.231"N | 104°04'12.617"W | point |

SURVEY PROGRAM Ref Wellbore: No. 4H PWB Ref Wellpath: Preliminary

| Start MD [ft] | End MD [ft] | Positional Uncertainty Model | Log Name/Comment | Wellbore |
|------------------|----------------|------------------------------|------------------|------------|
| 18.00 | 11718.06 | NaviTrak (Standard) | | No. 4H PWB |



Cimarex Energy Co. of Colorado


Location: Eddy County, NM
Field: (Conoco) Sec. 22 T16S R29E
Facility: Conoco 22 Fed Com No. 4H

Slot: No. 4H SHL
Well: No. 4H
Wellbore: No. 4H PWB



Well Profile Data

| Design Comment | MD (ft) | Inc (°) | Az (°) | TVD (ft) | Local N (ft) | Local E (ft) | DLS (%/100ft) | VS (ft) |
|----------------|----------|---------|---------|----------|--------------|--------------|---------------|---------|
| Tie On | 0.00 | 0.000 | 269.875 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| KOP | 7000.00 | 0.000 | 269.875 | 7000.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| EOC | 7297.02 | 89.105 | 269.875 | 7190.96 | -0.41 | -188.00 | 30.00 | 188.00 |
| No. 4H BHL | 11718.06 | 89.105 | 269.875 | 7260.00 | -10.02 | -4608.50 | 0.00 | 4608.51 |



Hydrogen Sulfide Drilling Operations Plan

Conoco 22 Federal Com No. 4

Cimarex Energy Co. of Colorado

Unit A, Section 22

T16S-R29E, Eddy County, NM

- 1 All Company and Contract personnel admitted on location must be trained by a qualified H₂S safety instructor to the following:
 - A. Characteristics of H₂S
 - B. Physical effects and hazards
 - C. Proper use of safety equipment and life support systems.
 - D. Principle and operation of H₂S detectors, warning system and briefing areas.
 - E. Evacuation procedure, routes and first aid.
 - F. Proper use of 30 minute pressure demand air pack.
- 2 H₂S Detection and Alarm Systems:
 - A. H₂S detectors and audio alarm system to be located at bell nipple, end of flow line (mud pit) and on derrick floor or doghouse.
- 3 Windsock and/or wind streamers:
 - A. Windsock at mudpit area should be high enough to be visible.
 - B. Windsock at briefing area should be high enough to be visible.
- 4 Condition Flags and Signs:
 - A. Warning sign on access road to location.
 - B. Flags to be displayed on sign at entrance to location. Green flag indicates normal safe condition. Yellow flag indicates potential pressure and danger. Red flag indicates danger (H₂S present in dangerous concentration). Only emergency personnel admitted to location.
- 5 Well control equipment:
 - A. See exhibit "E"
- 6 Communication:
 - A. While working under masks chalkboards will be used for communication.
 - B. Hand signals will be used where chalk board is inappropriate.
 - C. Two way radio will be used to communicate off location in case of emergency help is required. In most cases cellular telephones will be available at most drilling foreman's trailer or living quarters.
- 7 Drillstem Testing:

No DSTs or cores are planned at this time.
- 8 Drilling contractor supervisor will be required to be familiar with the effects H₂S has on tubular goods and other mechanical equipment.
- 9 If H₂S is encountered, mud system will be altered if necessary to maintain control of formation. A mud gas separator will be brought into service along with H₂S scavengers if necessary.

H₂S Contingency Plan
Conoco 22 Federal Com No. 4
Cimarex Energy Co. of Colorado
Unit A, Section 22
T16S-R29E, Eddy County, NM

Emergency Procedures

In the event of a release of gas containing H₂S, the first responder(s) must:

- ★ Isolate the area and prevent entry by other persons into the 100 ppm ROE.
- ★ Evacuate any public places encompassed by the 100 ppm ROE.
- ★ Be equipped with H₂S monitors and air packs in order to control the release.
- ★ Use the "buddy system" to ensure no injuries occur during the response.
- ★ Take precautions to avoid personal injury during this operation.
- ★ Contact operator and/or local officials to aid in operation. See list of phone numbers attached.
- ★ Have received training in the:
 - ◆ Detection of H₂S; and
 - ◆ Measures for protection against the gas,
 - ◆ Equipment used for protection and emergency response.

Ignition of Gas Source

Should control of the well be considered lost and ignition considered, take care to protect against exposure to Sulfur Dioxide (SO₂). Intentional ignition must be coordinated with the NMOCD and local officials. Additionally, the NM State Police may become involved. NM State Police shall be the Incident Command on scene of any major release. Take care to protect downwind whenever there is an ignition of the gas.

Characteristics of H₂S and SO₂

| Common Name | Chemical Formula | Specific Gravity | Threshold Limit | Hazardous Limit | Lethal Concentration |
|------------------|------------------|------------------|-----------------|-----------------|----------------------|
| Hydrogen Sulfide | H ₂ S | 1.189 Air=1 | 10 ppm | 100 ppm/hr | 600 ppm |
| Sulfur Dioxide | SO ₂ | 2.21 Air=1 | 2 ppm | N/A | 1000 ppm |

Contacting Authorities

Cimarex Energy Co. of Colorado's personnel must liaise with local and state agencies to ensure a proper response to a major release. Additionally, the OCD must be notified of the release as soon as possible but no later than 4 hours. Agencies will ask for information such as type and volume of release, wind direction, location of release, etc. Be prepared with all information available including directions to site. The following call list of essential and potential responders has been prepared for use during a release. Cimarex Energy Co. of Colorado's response must be in coordination with the State of New Mexico's "Hazardous Materials Emergency Response Plan" (HMER).

H₂S Contingency Plan Emergency Contacts

Conoco 22 Federal Com No. 4

Cimarex Energy Co. of Colorado

Unit A, Section 22

T16S-R29E, Eddy County, NM

Company Office

Cimarex Energy Co. of Colorado
Co. Office and After-Hours Menu

800-969-4789

Key Personnel

| Name | Title | Office | Mobile |
|---------------|------------------|---------------|---------------|
| Doug Park | Drilling Manager | 972-443-6463 | 972-333-1407 |
| Dee Smith | Drilling Super | 972-443-6491 | 972-882-1010 |
| Jim Evans | Drilling Super | 972-443-6451 | 972-465-6564 |
| Dorsey Rogers | Field Super | | 575-200-6105 |
| Roy Shirley | Field Super | | 432-634-2136 |

Artesia

| | |
|--------------------------------------|---------------------|
| Ambulance | 911 |
| State Police | 575-746-2703 |
| City Police | 575-746-2703 |
| Sheriff's Office | 575-746-9888 |
| Fire Department | 575-746-2701 |
| Local Emergency Planning Committee | 575-746-2122 |
| New Mexico Oil Conservation Division | 575-748-1283 |

Carlsbad

| | |
|------------------------------------|---------------------|
| Ambulance | 911 |
| State Police | 575-885-3137 |
| City Police | 575-885-2111 |
| Sheriff's Office | 575-887-7551 |
| Fire Department | 575-887-3798 |
| Local Emergency Planning Committee | 575-887-6544 |
| US Bureau of Land Management | 575-887-6544 |

Santa Fe

| | |
|--|--------------|
| New Mexico Emergency Response Commission (Santa Fe) | 505-476-9600 |
| New Mexico Emergency Response Commission (Santa Fe) 24 Hrs | 505-827-9126 |
| New Mexico State Emergency Operations Center | 505-476-9635 |

National

| | |
|---|--------------|
| National Emergency Response Center (Washington, D.C.) | 800-424-8802 |
|---|--------------|

Medical

| | |
|---|--------------|
| Flight for Life - 4000 24th St.; Lubbock, TX | 806-743-9911 |
| Aerocare - R3, Box 49F; Lubbock, TX | 806-747-8923 |
| Med Flight Air Amb - 2301 Yale Blvd S.E., #D3; Albuquerque, NM | 505-842-4433 |
| SB Air Med Service - 2505 Clark Carr Loop S.E.; Albuquerque, NM | 505-842-4949 |

Other

| | | | |
|-----------------------|--------------|----|--------------|
| Boots & Coots IWC | 800-256-9688 | or | 281-931-8884 |
| Cudd Pressure Control | 432-699-0139 | or | 432-563-3356 |
| Halliburton | 575-746-2757 | | |
| B.J. Services | 575-746-3569 | | |

Surface Use Plan
Conoco 22 Federal Com No. 4
Cimarex Energy Co. of Colorado
Unit A, Section 22
T16S-R29E, Eddy County, NM

1. Existing Roads: Area maps, Exhibit "B" is a reproduction of Eddy Co. General Highway Map. Exhibit "C" is a reproduction of a USGS Topographic Map, showing existing roads and proposed roads. All existing roads will be maintained in a condition equal to or better than current conditions. Any new roads will be constructed to BLM specifications.
 - A. Exhibit "A" shows the proposed well site as staked.
 - B. From the junction of Hwy 82 and Barnival Draw, go North on Barnival Draw for approx 6.5 miles to lease road. On lease road go Northeasterly for 1.2 miles to lease road. On lease road go Southerly to proposed lease road.
2. Planned Access Roads: 65' of new on-lease access road is proposed.
3. Location of Existing Wells in a One-Mile Radius - Exhibit A
 - A. Water wells - None known
 - B. Disposal wells - None known
 - C. Drilling wells - None known
 - D. Producing wells - As shown on Exhibit "A"
 - E. Abandoned wells - As shown on Exhibit "A"
4. If on completion this well is a producer, Cimarex Energy Co. of Colorado will furnish maps and/or plats showing on site facilities or off site facilities if needed. This will be accompanied by a Sundry Notice.
5. Location and Type of Water Supply:

Water will be purchased locally from a commercial source and trucked over the access roads or piped in flexible lines laid on top of the ground.
6. Source of Construction Material:

If possible, construction will be obtained from the excavation of drill site. If additional material is needed, it will be purchased from a local source and transported over the access route as shown on Exhibit "C".
7. Methods of Handling Waste Material:
 - A. Drill cuttings will be seperated by a series of solids removal equipment and stored in steel containment pits and then hauled to a state-approved disposal facility.
 - B. All trash, junk and other waste material will be contained in trash cages or bins to prevent scattering. When the job is completed all contents will be removed and disposed of in an approved sanitary land fill.
 - C. Salts remaining after completion of well will be picked up by supplier including broken sacks.
 - D. Sewage from living quarters will drain into holding tanks and be cleaned out periodically. A Porta-John will be provided for the rig crews. This equipment will be properly maintained during the drilling operations and removed upon completion of the well.
 - E. Drilling fluids will be contained in steel pits in a closed circulating system. Fluids will be cleaned and reused. Water produced during testing will be contained in the steel pits and disposed of at a state approved disposal facility. Any oil or condensate produced will be stored in test tanks until sold and hauled from the site.

Surface Use Plan
Conoco 22 Federal Com No. 4
Cimarex Energy Co. of Colorado
Unit A, Section 22
T16S-R29E, Eddy County, NM

8. Ancillary Facilities:

- A. No camps or airstrips to be constructed.

9. Well Site Layout:

- A. Exhibit "D" shows location and rig layout.
- C. Mud pits in the closed circulating system will be steel pits and the cuttings will be stored in steel containment pits.
- D. Cuttings will be stored in steel pits until they are hauled to a state-approved disposal facility.
- E. If the well is a producer, those areas of the location not essential to production facilities will be reclaimed and seeded per BLM requirements.

10. Plans for Restoration of Surface:

Rehabilitation of the location will start in a timely manner after all drilling operations cease. The type of reclamation will depend on whether the well is a producer or a dry hole.

Drainage systems, if any, will be reshaped to the original configuration with provisions made to alleviate erosion. These may need to be modified in certain circumstances to prevent inundation of the location's pad and surface facilities. After the area has been shaped and contoured, topsoil from the spoil pile will be placed over the disturbed area to the extent possible. Revegetation procedures will comply with BLM standards.

If the well is a dry hole, the pad and road area will be recountoured to match the existing terrain. Topsoil will be spread to the extent possible. Revegetation will comply with BLM standards.

Should the well be a producer, the previously noted procedures will apply to those areas which are not required for production facilities.

11. Other Information

- A. Topography consists of a sloping plane with loose tan sands. Vegetation is mainly yucca, mesquite and shin oak.
- B. The wellsite is on surface owned by the Department of the Interior, Bureau of Land Management. The land is used mainly for farming, cattle ranching, recreational use, and oil and gas production.
- C. In lieu of performing an archaeological survey, Cimarex will use the Carlsbad Area Memorandum of Agreement and will use the site location information to plan projects to avoid known eligible archaeological sites by at least 100 feet. In this regard, per the MOA, Cimarex will make the appropriate contribution to the Permian Basin Cultural Resource mitigation fund.
- D. There are no known dwellings within 1½ miles of this location.

Operator Certification Statement
Conoco 22 Federal Com No. 4
Cimarex Energy Co. of Colorado
Unit A, Section 22
T16S-R29E, Eddy County, NM

Operator's Representative

Cimarex Energy Co. of Colorado
P.O. Box 140907
Irving, TX 75014
Office Phone: (972) 443-6489
Zeno Farris

CERTIFICATION: I hereby certify that the statements and plans made in this APD are, to the best of my knowledge, true and correct; and that the work associated with the operations proposed herein will be performed by Cimarex Energy Co. of Colorado and/or its contractors/subcontractors and is in conformity with this plan and the terms and conditions under which it is approved. This statement is subject to the provision of U.S.C. 1001 for the filing of a false statement.

NAME: Natalie Krueger
Natalie Krueger
DATE: October 3, 2008
TITLE: Regulatory Analyst

PECOS DISTRICT CONDITIONS OF APPROVAL

| | |
|-----------------------|-------------------------------------|
| OPERATOR'S NAME: | Cimarex Energy Co. of Colorado |
| LEASE NO.: | NM97874 |
| WELL NAME & NO.: | Conoco 22 Federal Com #4 |
| SURFACE HOLE FOOTAGE: | 375' FNL & 330' FEL |
| BOTTOM HOLE FOOTAGE: | 375' FNL & 330' FWL |
| LOCATION: | Section 22, T. 16 S., R 29 E., NMPM |
| COUNTY: | Eddy County, New Mexico |

TABLE OF CONTENTS

Standard Conditions of Approval (COA) apply to this APD. If any deviations to these standards exist or special COAs are required, the section with the deviation or requirement will be checked below.

- ☐ **General Provisions**
- ☐ **Permit Expiration**
- ☐ **Archaeology, Paleontology, and Historical Sites**
- ☐ **Noxious Weeds**
- ☐ **Special Requirements**
- ☒ **Construction**
 - Notification
 - Topsoil
 - Closed Loop System
 - Federal Mineral Material Pits
 - Well Pads
 - Roads
- ☒ **Road Section Diagram**
- ☒ **Drilling**
- ☐ **Production (Post Drilling)**
 - Well Structures & Facilities
 - Pipelines
 - Electric Lines
- ☒ **Reserve Pit Closure/Interim Reclamation**
- ☐ **Closed Loop System/Reclamation**

I. GENERAL PROVISIONS

The approval of the Application For Permit To Drill (APD) is in compliance with all applicable laws and regulations: 43 Code of Federal Regulations 3160, the lease terms, Onshore Oil and Gas Orders, Notices To Lessees, New Mexico Oil Conservation Division (NMOCD) Rules, National Historical Preservation Act As Amended, and instructions and orders of the Authorized Officer. Any request for a variance shall be submitted to the Authorized Officer on Form 3160-5, Sundry Notices and Report on Wells.

II. PERMIT EXPIRATION

If the permit terminates prior to drilling and drilling cannot be commenced within 60 days after expiration, an operator is required to submit Form 3160-5, Sundry Notices and Reports on Wells, requesting surface reclamation requirements for any surface disturbance. However, if the operator will be able to initiate drilling within 60 days after the expiration of the permit, the operator must have set the conductor pipe in order to allow for an extension of 60 days beyond the expiration date of the APD. (Filing of a Sundry Notice is required for this 60 day extension.)

III. ARCHAEOLOGICAL, PALEONTOLOGY & HISTORICAL SITES

Any cultural and/or paleontological resource discovered by the operator or by any person working on the operator's behalf shall immediately report such findings to the Authorized Officer. The operator is fully accountable for the actions of their contractors and subcontractors. The operator shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery shall be made by the Authorized Officer to determine the appropriate actions that shall be required to prevent the loss of significant cultural or scientific values of the discovery. The operator shall be held responsible for the cost of the proper mitigation measures that the Authorized Officer assesses after consultation with the operator on the evaluation and decisions of the discovery. Any unauthorized collection or disturbance of cultural or paleontological resources may result in a shutdown order by the Authorized Officer.

IV. NOXIOUS WEEDS

The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes the roads, pads, associated pipeline corridor, and adjacent land affected by the establishment of weeds due to this action. The operator shall consult with the Authorized Officer for acceptable weed control methods, which include following EPA and BLM requirements and policies.

V. SPECIAL REQUIREMENT(S)

VI. CONSTRUCTION

A. NOTIFICATION

The BLM shall administer compliance and monitor construction of the access road and well pad. Notify the Carlsbad Field Office at (575) 234-5972 at least 3 working days prior to commencing construction of the access road and/or well pad.

When construction operations are being conducted on this well, the operator shall have the approved APD and Conditions of Approval (COA) on the well site and they shall be made available upon request by the Authorized Officer.

B. TOPSOIL

The operator shall stockpile the topsoil of the well pad. The topsoil shall not be used to backfill the reserve pit and will be used for interim and final reclamation.

C. Closed Loop System

Conoco 22 Federal Com. # 4: Closed Loop System V-Door East

Tanks are required for drilling operations: No Pits.

The operator shall properly dispose of drilling contents at an authorized disposal site.

D. FEDERAL MINERAL MATERIALS PIT

If the operator elects to surface the access road and/or well pad, mineral materials extracted during construction of the reserve pit may be used for surfacing the well pad and access road and other facilities on the lease.

Payment shall be made to the BLM prior to removal of any additional federal mineral materials from any site other than the reserve pit. Call the Carlsbad Field Office at (575) 234-5972.

E. WELL PAD SURFACING

Surfacing of the well pad is not required.

If the operator elects to surface the well pad, the surfacing material may be required to be removed at the time of reclamation.

The well pad shall be constructed in a manner which creates the smallest possible surface disturbance, consistent with safety and operational needs.

F. ON LEASE ACCESS ROADS

Road Width

The access road shall have a driving surface that creates the smallest possible surface disturbance and does not exceed fourteen (14) feet in width. The maximum width of surface disturbance, when constructing the access road, shall not exceed thirty (30) feet.

Surfacing

Surfacing material is not required on the new access road driving surface. If the operator elects to surface the new access road or pad, the surfacing material may be required to be removed at the time of reclamation.

Where possible, no improvements should be made on the unsurfaced access road other than to remove vegetation as necessary, road irregularities, safety issues, or to fill low areas that may sustain standing water.

The Authorized Officer reserves the right to require surfacing of any portion of the access road at any time deemed necessary. Surfacing may be required in the event the road deteriorates, erodes, road traffic increases, or it is determined to be beneficial for future field development. The surfacing depth and type of material will be determined at the time of notification.

Crowning


Crowning shall be done on the access road driving surface. The road crown shall have a grade of approximately 2% (i.e., a 1" crown on a 14' wide road). The road shall conform to Figure 1; cross section and plans for typical road construction.

Ditching

Ditching shall be required on both sides of the road.

Turnouts

Vehicle turnouts shall be constructed on the road. Turnouts shall be intervisible with interval spacing distance less than 1000 feet. Turnouts shall be constructed on all blind curves. Turnouts shall conform to the following diagram:




Drainage

Drainage control systems shall be constructed on the entire length of road (e.g. ditches, sidehill outslowing and insloping, lead-off ditches, culvert installation, and low water crossings).

A typical lead-off ditch has a minimum depth of 1 foot below and a berm of 6 inches above natural ground level. The berm shall be on the down-slope side of the lead-off ditch.

Cross Section of a Typical Lead-off Ditch



All lead-off ditches shall be graded to drain water with a 1 percent minimum to 3 percent maximum ditch slope. The spacing interval are variable for lead-off ditches and shall be determined according to the formula for spacing intervals of lead-off ditches, but may be amended depending upon existing soil types and centerline road slope (in %);

Formula for Spacing Interval of Lead-off Ditches

Example - On a 4% road slope that is 400 feet long, the water flow shall drain water into a lead-off ditch. Spacing interval shall be determined by the following formula:

$$400 \text{ foot road with } 4\% \text{ road slope: } \frac{400'}{4\%} + 100' = 200' \text{ lead-off ditch interval}$$

Culvert Installations

Appropriately sized culvert(s) shall be installed at the deep waterway channel flow crossing.

Cattleguards

An appropriately sized cattleguard(s) sufficient to carry out the project shall be installed and maintained at fence crossing(s).

Any existing cattleguard(s) on the access road shall be repaired or replaced if they are damaged or have deteriorated beyond practical use. The operator shall be responsible for the condition of the existing cattleguard(s) that are in place and are utilized during lease operations.

A gate shall be constructed and fastened securely to H-braces.

Fence Requirement


Where entry is required across a fence line, the fence shall be braced and tied off on both sides of the passageway prior to cutting.

The operator shall notify the private surface landowner or the grazing allotment holder prior to crossing any fence(s).

Public Access

Public access on this road shall not be restricted by the operator without specific written approval granted by the Authorized Officer.

Figure 1 – Cross Sections and Plans For Typical Road Sections



VII. DRILLING

A. DRILLING OPERATIONS REQUIREMENTS

The BLM is to be notified a minimum of 4 hours in advance for a representative to witness:

- a. Spudding well
- b. Setting and/or Cementing of all casing strings
- c. BOPE tests

☒ **Eddy County**

Call the Carlsbad Field Office, 620 East Greene St., Carlsbad, NM 88220,
(575) 361-2822

1. **Although Hydrogen Sulfide has not been reported in this section, it is always a possible hazard. If Hydrogen Sulfide is encountered, please report measured amounts and formations to the BLM.**
2. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval.
3. Floor controls are required for 3M or Greater systems. These controls will be on the rig floor, unobstructed, readily accessible to the driller and will be operational at all times during drilling and/or completion activities. Rig floor is defined as the area immediately around the rotary table; the area immediately above the substructure on which the draw works are located, this does not include the dog house or stairway area.

B. CASING

Changes to the approved APD casing and cement program require submitting a sundry and receiving approval prior to work. Failure to obtain approval prior to work will result in an Incident of Non-Compliance being issued.

Centralizers required on surface casing per Onshore Order 2.III.B.1.f.

Wait on cement (WOC) time for a primary cement job will be a minimum 18 hours for a water basin, 24 hours in the potash area, or 500 pounds compressive strength, whichever is greater for all casing strings. Provide compressive strengths including hours to reach required 500 pounds compressive strength prior to cementing each casing string. See individual casing strings for details regarding lead cement slurry requirements.

No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.

Possible lost circulation in the Grayburg and San Andres formations.

Possible high pressure gas bursts from the Wolfcamp formation – applicable to pilot hole.

1. The 13-3/8 inch surface casing shall be set at approximately 430 feet (a minimum of 25 feet into the Rustler Anhydrite and above the salt) and cemented to the surface. If the salt is penetrated, set casing 25' above the salt. There is a structural high in this area and the Rustler could be as shallow as 80 feet.
 - a. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with a surface log readout will be used or a cement bond log shall be run to verify the top of the cement.
 - b. Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry.
 - c. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength, whichever is greater.
 - d. If cement falls back, a remedial cementing will be done prior to drilling out that string.

Brine mud to be used below surface casing to drill 12-1/4" hole.

2. The minimum required fill of cement behind the 9-5/8 inch intermediate casing is:

☒ Cement to surface. If cement does not circulate see B.1.a, c-d above.

Formation below the 9-5/8" shoe to be tested according to Onshore Order 2.III.B.1.i. Test to be done as a mud equivalency test using the mud weight necessary for the pore pressure of the formation below the shoe (not the mud weight required to prevent dissolving the salt formation) and the mud weight for the bottom of the hole. Report results to BLM office.

3. The minimum required fill of cement behind the 7 inch production casing is:

☒ Cement should tie-back at least 200 feet into previous casing string. Operator shall provide method of verification.

Tag cement at bottom of pilot hole and report on subsequent report. NOTE: Pilot hole will require proper plug when well is plugged.

Formation below the kick off point to be tested according to Onshore Order

2.III.B.1.i. Test to be done as a mud equivalency test using the mud weight necessary for the pore pressure of the formation below the shoe and the mud weight for the bottom of the hole. Report results to BLM office.

4. The minimum required fill of cement behind the 4-1/2 inch production liner is:

☒ Not required as operator is using Peak completion assembly.

5. If hardband drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.

C. PRESSURE CONTROL

1. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in Onshore Oil and Gas Order No. 2 and API RP 53 Sec. 17.

2. The appropriate BLM office shall be notified a minimum of 4 hours in advance for a representative to witness the tests.

a. The tests shall be done by an independent service company.

b. The results of the test shall be reported to the appropriate BLM office.

c. All tests are required to be recorded on a calibrated test chart. A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.

d. The BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes if test is done with a test plug and 30 minutes without a test plug.

e. **Effective November 1, 2008, no variances will be granted on reduced pressure tests on the surface casing and BOP/BOPE. Onshore Order 2 requirements will be in effect.**

D. DRILL STEM TEST

If drill stem tests are performed, Onshore Order 2.III.D shall be followed.

WWI 110608

VIII. PRODUCTION (POST DRILLING)

A. WELL STRUCTURES & FACILITIES

Placement of Production Facilities

Production facilities should be placed on the well pad to allow for maximum interim recontouring and revegetation of the well location.

Containment Structures

The containment structure shall be constructed to hold the capacity of the entire contents of the largest tank, plus 24 hour production, unless more stringent protective requirements are deemed necessary by the Authorized Officer.

Painting Requirement

All above-ground structures including meter housing that are not subject to safety requirements shall be painted a flat non-reflective paint color
Shale Green, Munsell Soil Color Chart # 5Y 4/2

B. PIPELINES

C. ELECTRIC LINES

IX. INTERIM RECLAMATION & RESERVE PIT CLOSURE

A. INTERIM RECLAMATION

If the well is a producer, interim reclamation shall be conducted on the well site in accordance with the orders of the Authorized Officer. The operator shall submit a Sundry Notices and Reports on Wells (Notice of Intent), Form 3160-5, prior to conducting interim reclamation.

During the life of the development, all disturbed areas not needed for active support of production operations should undergo interim reclamation in order to minimize the environmental impacts of development on other resources and uses.

The operators should work with BLM surface management specialists to devise the best strategies to reduce the size of the location. Any reductions should allow for remedial well operations, as well as safe and efficient removal of oil and gas.

During reclamation, the removal of caliche is important to increasing the success of revegetating the site. Removed caliche may be used for road repairs, fire walls or for building other roads and locations. In order to operate the well or complete workover operations, it may be necessary to drive, park and operate on restored interim vegetation within the previously disturbed area. Disturbing revegetated areas for production or workover operations will be allowed. If there is significant disturbance and loss of vegetation, the area will need to be revegetated. Communicate with the appropriate BLM office for any exceptions/exemptions if needed.

BLM SERIAL #:
COMPANY REFERENCE:
WELL # & NAME:

Seed Mixture 2, for Sandy Sites

The holder shall seed all disturbed areas with the seed mixture listed below. The seed mixture shall be planted in the amounts specified in pounds of pure live seed (PLS)* per acre. There shall be no primary or secondary noxious weeds in the seed mixture. Seed will be tested and the viability testing of seed will be done in accordance with State law (s) and within nine (9) months prior to purchase. Commercial seed will be either certified or registered seed. The seed container will be tagged in accordance with State law(s) and available for inspection by the authorized officer.

Seed will be planted using a drill equipped with a depth regulator to ensure proper depth of planting where drilling is possible. The seed mixture will be evenly and uniformly planted over the disturbed area (smaller/heavier seeds have a tendency to drop the bottom of the drill and are planted first). The holder shall take appropriate measures to ensure this does not occur. Where drilling is not possible, seed will be broadcast and the area shall be raked or chained to cover the seed. When broadcasting the seed, the pounds per acre are to be doubled. The seeding will be repeated until a satisfactory stand is established as determined by the authorized officer. Evaluation of growth will not be made before completion of at least one full growing season after seeding.

Species to be planted in pounds of pure live seed* per acre:

| <u>Species</u> | <u>lb/acre</u> |
|---|----------------|
| Sand dropseed (<i>Sporobolus cryptandrus</i>) | 1.0 |
| Sand love grass (<i>Eragrostis trichodes</i>) | 1.0 |
| Plains bristlegrass (<i>Setaria macrostachya</i>) | 2.0 |

*Pounds of pure live seed:

Pounds of seed x percent purity x percent germination = pounds pure live seed
(Insert Seed Mixture Here)

X. FINAL ABANDONMENT & REHABILITATION REQUIREMENTS

Upon abandonment of the well and/or when the access road is no longer in service the Authorized Officer shall issue instructions and/or orders for surface reclamation and restoration of all disturbed areas.

On private surface/federal mineral estate land the reclamation procedures on the road and well pad shall be accomplished in accordance with the private surface land owner agreement.