Form 3160-5 (September 2001)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

FORM APPROVED OMB No 1004-0135 Expires January 31, 2004



NMLC-028731-b

abandoned well. Use Form 3160-3 (APD) for such proposals.				6. If Indian, Allottee or Tribe Name		
SUBMITINTE	RIPLICATE - Other instru	ctions on reverse sid	e	7 If Unit or CA	/Agreement, Name as	ıd/or No.
1 Type of Well		JAN 05 70		9 W-II N and No		
Other				8 Well Name and No.		
Name of Operator Mewbourne Oil Company 14744		OCD-ARTESIA		Pacu 14 Federal Com #1: 9 API Well No.		
3a. Address		3b. Phone No. (include area code)		30-015-36416		
		,	,		10. Field and Pool, or Exploratory Area	
		575-393-5905		Grayburg Morrow		
4. Location of Well (Footage, Sec., T, R., M., or Survey Description)			11. County or Parish, State			
800' FNL & 990' FWL, Sec 14			Eddy County,			
12. CHECK AP	PROPRIATE BOX(ES) TO	INDICATE NATURE C	F NOTICE, RE			
TYPE OF SUBMISSION	TYPE OF ACTION					
Notice of Intent	Acidize [Deepen 🔲	Production (Start/	Resume)	Water Shut-Off	
	Alter Casing	Fracture Treat	Reclamation		Well Integrity	
Subsequent Report	Casing Repair	New Construction	Recomplete		Other	
Subsequent Report	Change Plans	Plug and Abandon	Temporarily Abar	ndon .	_	
Final Abandonment Notice	Convert to Injection	Plug Back	Water Disposal			
As per correspondence w/Wesley TD @ 10970'. Top of Morrow @ Salt section 440' to 900'. 13 3/8"	Ingram, with verbal approval gas 10577'. Top of Wolfcamp @ csg shoe @ 350'.	7390'. Top of Glorietta @ 3	9982'. 9 5/8" csg s		edure.	
1st plug - 450' Class H Neat (yield @ 1.18cuft/sk) f/10970' - 10520'. Must tag @ 10520' or shallower. 2nd plug - 180' Class H Neat (yield @ 1.18cuft/sk) f/8980' - 8800'. (Spacer plug not required to tag). 3rd plug - 175' Class H Neat (yield @ 1.18cuft/sk) f/7440' - 7265'. Must tag @ 7265' or shallower. 4th plug - 150' Class C Neat (yield @ 1.32cuft/sk) f/5265' -5115'. (Spacer plug not required to tag). 5th plug - 140' Class C Neat (yield @ 1.32cuft/sk) f/4032' - 3892'. Must tag @ 3892' or shallower. 6th plug - 130' Class C Neat (yield @ 1.32cuft/sk) f/3060' - 2930'. Must tag @ 2930' or shallower.			ACCEPTED FOR RECORD			
7th plug - 950' Class C Neat (yield @ 1.32cuft/sk) f/950' - surface.			JAN 6 2009			
A dry hole marker will be installed & location will be cleaned up as required in the Abandonment COA. If you have any questions please call.			Gerry Guye, Deputy Field Inspector NMOCD-District II ARTESIA			
14. 1 hereby certify that the foregoin						
Name (PrintedlTyped)	g is true and correct	Tist				
F.C. Lathan		11tte Drilling	Title Drilling Superintendent			
Signature La Lathe		Date 12/22/08	Date 12/22/08		APPROVED	
	THIS SPACE FO	R FEDERAL OR STATE	OFFICE USE			
Approved by (Signature)		Name (Printed/T)	ped)	D ##6	3 0 2008	
Conditions of approval, if any, are certify that the applicant holds legs which would entitle the applicant to o	al or equitable title to those rights	does not warrant or in the subject lease		WESLE	Date Y W. INGRAM	

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction